

# Resource request from Native Windows 8.1 Universal and Windows 10 UWP applications

## Overview

MobileFirst applications can access resources using the `WorklightResourceRequest` REST API. The REST API works with all adapters and external resources.

### Prerequisites:

- Ensure you have added the MobileFirst Platform SDK to your Native Windows 8.1 Universal ([../adding-the-mfpf-sdk/adding-the-mfpf-sdk-to-windows-8-applications](#)) or Windows 10 UWP ([../adding-the-mfpf-sdk/adding-the-mfpf-sdk-to-windows-10-applications](#)) project.
- Learn how to create adapters ([../adapters/adapters-overview/](#)).

## WLResourceRequest

The `WorklightResourceRequest` class handles resource requests to adapters or external resources.

Create a `WorklightResourceRequest` object and specify the path to the resource and the HTTP method. Available methods are: `GET`, `POST`, `PUT` and `DELETE`.

```
URI adapterPath = new URI("/adapters/RSSReader/getFeed",UriKind.Relative);
WorklightResourceRequest request = WorklightClient.ResourceRequest(adapterPath,"GET");
```

- For **JavaScript adapters**, use `/adapters/{AdapterName}/{procedureName}`
- For **Java adapters**, use `/adapters/{AdapterName}/{path}`. The `path` depends on how you defined your `@Path` annotations in your Java code. This would also include any `@PathParam` you used.
- To access resources outside of the project, use the full URL as per the requirements of the external server.
- **timeout**: Optional, request timeout in milliseconds
- **scope**: Optional, if you know which scope is protecting the resource - specifying this scope could make the request more efficient.

## Sending the request

Request the resource by using the `.send()` method.

```
WorklightResponse response = await request.send();
```

Use the `WorklightResponse response` object to get the data that is retrieved from the adapter.

The `response` object contains the response data and you can use its methods and properties to retrieve the required information. Commonly used properties are `ResponseText`, `ResponseJSON` (if the response is in JSON), `Success` (if the invoke was successful or failure) and `HTTPStatus` (the HTTP status of the response).

# Parameters

Before sending your request, you may want to add parameters as needed.

## Path parameters

As explained above, **path** parameters ( `/path/value1/value2` ) are set during the creation of the `WorklightResourceRequest` object:

```
URI adapterPath = new URI("/adapters/JavaAdapter/users/value1/value2", UriKind.Relative);
WorklightResourceRequest request = WorklightClient.createInstance(adapterPath, "GET");
```

## Query parameters

To send **query** parameters ( `/path?param1=value1...` ) use the `SetQueryParameter` method for each parameter:

```
request.SetQueryParameter("param1", "value1");
request.SetQueryParameter("param2", "value2");
```

## Form parameters

To send form parameters in the body, use `.Send(Dictionary<string, string> formParameters)` instead of `.Send()`:

```
Dictionary<string, string> formParams = new Dictionary<string, string>();
formParams.Add("height", height.getText().toString());
request.Send(formParams);
```

## Header parameters

To send a parameter as an HTTP header use `.AddHeader()` API:

```
request.AddHeader(System.Net.WebHeaderCollection header);
```

## Other custom body parameters

- `.Send(requestBody)` allows you to set an arbitrary String in the body.
- `.Send(JSONObject json)` allows you to set an arbitrary dictionary in the body.
- `.Send(byte[] data)` allows you to set an arbitrary byte array in the body.

## Javascript Adapters

JavaScript adapters use ordered nameless parameters. To pass parameters to a Javascript adapter, set an array of parameters with the name `params`:

```
request.SetQueryParameter("params", "[ 'param1', 'param2' ]");
```

## For more information

## Sample application

The ResourceRequestWin8 and ResourceRequestWin10 projects contain a native Windows 8 Universal/Windows 10 UWP application that makes a resource request using a Java adapter.

The adapter Maven project contains the Java adapter to be used during the resource request call.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/ResourceRequestWin8/tree/release80>) the Native project.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/ResourceRequestWin10/tree/release80>) the Native project.

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/Adapters/tree/release80>) the adapter Maven project.



The screenshot shows a mobile application titled "Resource Request". It features a form with the following fields and values:

Field	Value
Name	John
Middle Initial	M
Last Name	Smith
Age	44
Height	175
Date of Birth	1974-05-05

Below the form is a blue "Submit" button. After submission, the data is displayed in a text area:

Name = John M Smith  
Age = 44  
Height = 175  
Date = 1974-05-05

## Sample usage

1. From the command line, navigate to the Visual Studio project.
2. Ensure the sample is registered in the MobileFirst Server by running the command: `mfpdev app register`.
3. The sample uses the `JavaAdapter` contained in the Adapters Maven project. Use either Maven or MobileFirst Developer CLI to build and deploy the adapter (`../../adapters/creating-adapters/`).
4. import the project to Visual Studio, and run the sample by clicking the *\*Run* button.