

# Using Analytics Rest API

## Overview

MobileFirst Foundation Operational Analytics provides REST APIs to help developers with importing (POST) and exporting (GET) analytics data.

## Jump to:

- [Analytics REST API](#)
- [Try It Out on Swagger Docs](#)

## Analytics REST API

To use the analytics REST API:

### Base URL

```
/analytics-service/rest
```

### Example

```
https://example.com:9080/analytics-service/v3/applogs
```

REST API Method	Endpoint	Description
Application Logs (POST)	/v3/applogs	Creates a new application log.
Application Session (POST)	/v3/appsession	Creates an application session or updates an existing one when reporting with the same appSessionID.
Bulk (POST)	/v3/bulk	Reports events in bulk.
Custom Chart (GET)	/v3/customchart	Exports all custom chart definitions.
Custom Chart (POST)	/v3/customchart/import	Imports a list of custom charts.
Custom Data (POST)	/v3/customdata	Creates new custom data.
Device (POST)	/v3/device	Creates or updates a device.
Export Data (GET)	/v3/export	Exports data to the specified data format.
Network Transaction (POST)	/v3/networktransaction	Creates a new network transaction.
Server Log (POST)	/v3/serverlog	Creates a new server log.
User (POST)	/v3/user	Creates a new user.

## Try it out on Swagger docs

Try out the analytics REST API on Swagger Docs.

In a MobileFirst Server configuration with Analytics enabled, visit: `<ipaddress>:<port>/analytics-service`.

**WARNING:**

Do not use a production datastore name for "x-mfp-analytics-api-key", as it could interfere with production data.

**Application Session**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**Bulk**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**Client Logs**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**Custom Chart**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**Custom Data**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**Device**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**Export Data**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**Network Transaction**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**Server Log**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**User**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)

[ BASE URL: /analytics-service/rest ]

By clicking on **Expand Operations**, you can see the implementation notes, parameters, and response messages for each method.

Warning: Any data that you send by using **Try it out!** might interfere with data already in the data store. If you are not specifically trying to send data to your production environment, use a test name for the `x-mfp-analytics-api-key`.

**Client Logs**[Show/Hide](#) | [List Operations](#) | [Expand Operations](#)**POST**`/v3/clientlogs`[Creates a new Client Log](#)**Implementation Notes**

An Client Log is any debug log from the user's application

**Parameters**

Parameter	Value	Description	Parameter Type	Data Type
<b>body</b>	(required)		body	Model
	<div></div>			Example Value
				<pre>{   "logs": [     {       "timestamp": "2016-07-18T05:24:03.358Z",       "timezone": "60",       "file": "Main.swift",       "level": "ERROR",       "line": "234",       "message": "Something normal happened.",       "sourceClass": "string",       "method": "takePicture",       "locationName": "string"     }   ] }</pre>
<b>x-mfp-analytics-api-key</b>	TestIndex	Index name of the datastore.	header	string

**Response Messages**

HTTP Status Code	Reason	Response Model	Headers
202	Client Log created		
400	Invalid Client Log supplied	Model	Example Value