Java HTTP Adapter

fork and edit tutorial (https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/7.1/server-side-development/java-adapter/java-http-adapter.html) | report issue (https://github.ibm.com/MFPSamples/DevCenter/issues/new)

Overview

This tutorial is a continuation of Java Adapter (../../../server-side-development/java-adapter/) and assumes previous knowledge of the concepts described there.

Java adapters provide free reign over connectivity to your backend. It is therefore your responsibility to ensure best practices regarding performance and other implementation details.

This tutorial shows an example of a Java adapter that connects to an RSS feed by using a Java `HttpClient`.

Topics:

- RSSAdapterApplication
- RSSAdapterResource
- Results

RSSAdapterApplication

`RSSAdapterApplication` extends `MFPJAXRSApplication` and is a good place to trigger any initialization required by your application.

```
@Override
protected void init() throws Exception {
    RSSAdapterResource.init();
    logger.info("Adapter initialized!");
}
```

RSSAdapterResource

```
@Path("/")
public class RSSAdapterResource {
}
```

`RSSAdapterResource` is where we handle the requests to your adapter.

`@Path("/")` means that the resources will be available at the URL `http(s)://host:port/ProjectName/adapters/AdapterName/`.

HTTP Client

```
private static CloseableHttpClient client;
private static HttpHost host;
public static void init() {
   client = HttpClients.createDefault();
   host = new HttpHost("developer.ibm.com")
;
}
```

Because every request to your resource will create a new instance of `RSSAdapterResource`, it is important to reuse objects that may impact performance. In this example we made the Http client a `static` object and initialized it in a static `init()` method, which gets called by the `init()` of `RSSAdapterApplication` as described above.

Procedure resource

```
@GET
@Produces("application/json")
public void get(@Context HttpServletResponse response, @QueryParam("tag") String tag) throws Clie
ntProtocolException, IOException, IllegalStateException, SAXException {
   if(tag!=null &amp;amp;&amp;amp; !tag.isEmpty()){
    execute(new HttpGet("/mobilefirstplatform/tag/"+ tag +"/feed"), response);
   } else{
    execute(new HttpGet("/mobilefirstplatform/feed"), response);
   }
}
```

Our adapter exposes just one resource URL which allows to retrieve the RSS feed from the backend service.

- `@GET` means that this procedure only responds to `HTTP GET` requests.
- `@Produces("application/json")` specifies the Content Type of the response to send back. We chose to send the response as a `JSON` object to make it easier on the client-side.
- `@Context HttpServletResponse response` will be used to write to the response output stream. This enables us more granularity than returning a simple string.
- `@QueryParam("tag")` String tag enables the procedure to receive a parameter. The choice of `QueryParam` means the parameter is to be passed in the query (`/RSSAdapter/?tag=MobileFirst_Platform`). Other options include `@PathParam`, `@HeaderParam`, `@CookieParam`, `@FormParam`, etc.
- `throws ClientProtocolException, ...` means we are forwarding any exception back to the client. The client code is responsible for handling potential exceptions which will be received as `HTTP 500` errors. Another solution (more likely in production code) is to handle exceptions in your server Java code and decide what to send to the client based on the exact error.
- `execute(new HttpGet("/mobilefirstplatform/feed"), response)`. The actual HTTP request to the backend service is handled by another method defined later.

Depending if you pass a `tag` parameter, `execute` will retrieve a different build a different path and retrieve a different RSS file.

execute()

```
public void execute(HttpUriRequest req, HttpServletResponse resultResponse) throws ClientProtocolE
xception, IOException,
  IllegalStateException, SAXException {
    HttpResponse RSSResponse = client.execute(host, req);
    ServletOutputStream os = resultResponse.getOutputStream();

    if (RSSResponse.getStatusLine().getStatusCode() == HttpStatus.SC_OK){
        resultResponse.addHeader("Content-Type", "application/json");
        String json = XML.toJson(RSSResponse.getEntity().getContent());
        os.write(json.getBytes(Charset.forName("UTF-8")));</p>
    } else {
        resultResponse.setStatus(RSSResponse.getStatusLine().getStatusCode());
        RSSResponse.getEntity().getContent().close();
        os.write(RSSResponse.getStatusLine().getReasonPhrase().getBytes());
    }
    os.flush();
    os.close();
}
```

- `HttpResponse RSSResponse = client.execute(host, req)`. We use our static HTTP client to execute the HTTP request and store the response.
- `ServletOutputStream os = resultResponse.getOutputStream()`. This is the output stream to write a response to the client.
- `resultResponse.addHeader("Content-Type", "application/json")`. As mentioned before, we chose to send the response as JSON.
- `String json = XML.toJson(RSSResponse.getEntity().getContent())`. We used `org.apache.wink.json4j.utils.XML` to convert the XML RSS to a JSON string.
- `os.write(json.getBytes(Charset.forName("UTF-8")))` the resulting JSON string is written to the output stream.

The output stream is then `flush`ed and `close`d.

If `RSSResponse` is not `200 OK`, we write the status code and reason in the response instead.

Results

Use the testing techniques described in Java Adapter (../#testing) to test your work.

The adapter should return the RSS feed converted to JSON.


```
{
  "rss": {
    "channel": {
      "description": "Develop, test, manage, and secure your mobile web, native and hybrid apps",
      "generator": "http:\/\/wordpress.org\/?v=4.2.4",
      "item": [
        {
          "category": [
            "Mobile",
            "android",
            "Mobile Quality Assurance",
```

```
            "mobile_development",
            "mobilefirst",
            "xamarin"
          ],
          "commentRss": "https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/09\/01\/integrating-mqa
-into-xamarin-android-app\/feed\/",
          "comments": [
            "https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/09\/01\/integrating-mqa-into-xamarin-
android-app\/#comments",
            "0"
          ],
          "creator": "Vidyasagar MSC",
          "description": "<p>The post <a rel=\"nofollow\" href=\"https:\/\/developer.ibm.com\/mobilefirstpl
atform\/2015\/09\/01\/integrating-mqa-into-xamarin-android-app\/\">Integrating MQA into Xamarin.Android
app<\/a> appeared first on <a rel=\"nofollow\" href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\">IB
M MobileFirst Platform<\/a>.<\/p>",
          "encoded": "<p>It all startedÂ when I received an email seeking help on using MQA or to be m
ore precise integrating MQA into Xamarin based android app. Before jumping into addressing the proble
m, let&amp;#8217;s define MQA.<\/p>\n<h4>What is MQA?<\/h4>\n<p>MQA stands for &amp;#8220;Mo
bile Quality Assurance&amp;#8221; and is part of the IBM MobileFirst Platform.<\/p>\n<blockquote><p><
em><span style=\"line-height: 1.5\">IBM MQA provides line of business professionals and development t
eams with insightful and streamlined quality feedback and metrics from both pre-production and productio
n, enabling them to prioritize and take action to support a dynamic mobile app strategy.<\/span><\/em><\/
p><\/blockquote>\n<p>The Features of MQA are<\/p>\n<div style=\"width: 1058px\" class=\"wp-caption al
igncenter\"><a href=\"http:\/\/vidyasagarmsc.com\/wp-content\/uploads\/2015\/09\/MQA1.png\"><img clas
s=\"size-full wp-image-65\" src=\"http:\/\/vidyasagarmsc.com\/wp-content\/uploads\/2015\/09\/MQA1.png\"
alt=\"Features of Mobile Quality Assurance.\" width=\"1048\" height=\"350\" \/><\/a><p class=\"wp-caption
-text\">Features of Mobile Quality Assurance.<\/p><\/div>\n<p><em><strong>Note<\/strong><\/em>: To
understand more about MQA, visitÂ <a href=\"http:\/\/www-03.ibm.com\/software\/products\/en\/ibm-mobil
efirst-platform-quality-assurance\">IBM Mobile Quality Assurance<\/a><\/p>\n<p>So, by now we should b
e good with the first part of our blog title that is MQA. So, the next question is<\/p>\n<h4>What is Xamarin
.Android?<\/h4>\n<p>Xamarin is a platform to create nativeÂ iOS, Android, Mac and Windows apps in C#
.Â Xamarin.Android allows us to create native Android applications using the same UI controls we would i
n Java, except with the flexibility and elegance of a modern language (C#).<\/p>\n<p>As we are good wit
h the definitions, let&amp;#8217;s address the problem.<\/p>\n<p><strong>What&amp;#8217;s the probl
em in integrating MQA into Xamarin Android app?<\/strong><\/p>\n<p>At the time of this blog post, the av
ailable MQA SDKs are iOS native SDK, Android native SDK and Javascript Â SDK.<\/p>\n<p>So, we hav
e to find a workaround to address this use-case. The initial step is to download the Android MQA SDK an
d see what&amp;#8217;s provided. you can download it from <a href=\"http:\/\/www-01.ibm.com\/support\
/knowledgecenter\/#!\/SSJML5_6.0.0\/com.ibm.mqa.uau.saas.doc\/topics\/c_AndroidSDKsForDownload.h
tml\">here<\/a>. Once successfully downloaded and unzipped, we should see a jar file namely <strong><
em>MQA-Android-library-&amp;lt;version number&amp;gt;.jar<\/em>Â  <\/strong>under lib folder<strong
>.<\/strong><\/p>\n<div style=\"width: 634px\" class=\"wp-caption aligncenter\"><a href=\"http:\/\/vidyasag
armsc.com\/wp-content\/uploads\/2015\/09\/MQA2.png\"><img class=\"size-full wp-image-70\" src=\"http:\
/\/vidyasagarmsc.com\/wp-content\/uploads\/2015\/09\/MQA2.png\" alt=\"MQA Android SDK \" width=\"62
4\" height=\"440\" \/><\/a><p class=\"wp-caption-text\">MQA Android SDK<\/p><\/div>\n<p>As Xamarin is
C# based, What can we do with this jar file?<\/p>\n<p>We haveÂ <strong>Xamarin bindings<\/strong> to
our rescue, which helps using in consuming .JARs from C#.<\/p>\n<p><strong><em>Note<\/em>:<\/stro
ng> Steps to consume MQA Android JAR in a Xamarin.Android app is mentionedÂ <a href=\"https:\/\/dev
eloper.xamarin.com\/guides\/android\/advanced_topics\/java_integration_overview\/binding_a_java_librar
y_(.jar)\/\">here<\/a><\/p>\n<div style=\"width: 257px\" class=\"wp-caption aligncenter\"><a href=\"http:\/\/
vidyasagarmsc.com\/wp-content\/uploads\/2015\/09\/MQA31.png\"><img class=\"wp-image-72 size-full\"
src=\"http:\/\/vidyasagarmsc.com\/wp-content\/uploads\/2015\/09\/MQA31.png\" alt=\"\" width=\"247\" heig
ht=\"303\" \/><\/a><p class=\"wp-caption-text\">Xamarin binding project with MQA Android .JAR file<\/p>
<\/div>\n<p>The files of our interest here are <strong>MQA-Android-library-2.7.4.jar<\/strong> (Version n
umber may vary) and <strong>Metadata.xml.<\/strong><\/p>\n<ul>\n<li>MQA-Android-library-2.7.4.jar file
will have all the MQA related classes and methods required for us to start an Android MQA session.<\/li>\
```

ort trigger\n\t\t\t\t.WithDefaultUser("default_user@email.com") \/\/Sets a default user and user selection\n\t\t\t\t.Build();\n\n\t\t\t\/\/Starting MQA Android Session\n\t\t\tMQA.StartNewSession (this, configuration);\n\t\t\t\/\/ Set our view from the "main" layout resource\n\t\t\tSetContentView (Resource.Layout.Main);\n\n\t\t\t\/\/ Get our button from the layout resource,\n\t\t\t\/\/ and attach an event to it\n\t\t\tButton button = FindViewById<Button> (Resource.Id.myButton);\n\t\t\t\n\t\t\tbutton.Click += delegate {\n\t\t\t\tbutton.Text = string.Format ("{0} clicks!", count++);\n\t\t\t};\n\t\t}\n}\n\n\n\n<\/pre>\n<p>Now, MQA is integrated into Xamarin.Android app and we are good to go.<\/p>\n<p>What we have implemented above is just a drop in the Ocean of MQA, to know more about MQA and its features – VisitÂ <a href=\"http:\/\/www-01.ibm.com\/support\/knowledgecenter\/?lang=en#!\/SSJML5_6.0.0\/com.ibm.mqa.uau.saas.doc\/mqa600saas_welcome.html\" target=\"_blank\">MQA Knowledge Centre<\/a><\/p>\n<p>Happy Coding !!!<\/p>\n<p>The post <a rel=\"nofollow\" href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/09\/01\/integrating-mqa-into-xamarin-android-app\/\">Integrating MQA into Xamarin.Android app<\/a> appeared first on <a rel=\"nofollow\" href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\">IBM MobileFirst Platform<\/a>.<\/p>",
        "guid": {
          "content": "https:\/\/developer.ibm.com\/mobilefirstplatform\/?p=16964",
          "isPermaLink": "false"
        },
        "link": "https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/09\/01\/integrating-mqa-into-xamarin-android-app\/",
        "pubDate": "Tue, 01 Sep 2015 20:27:07 +0000",
        "title": "Integrating MQA into Xamarin.Android app"
      },
      {
        "category": [
          "Uncategorized",
          "MobileFirst_Platform"
        ],
        "commentRss": "https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/08\/19\/try-on-bluemix-and-buy-mfp\/feed\/",
        "comments": [
          "https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/08\/19\/try-on-bluemix-and-buy-mfp\/#comments",
          "0"
        ],
        "creator": "ChethanKumar",
        "description": "<p>The post <a rel=\"nofollow\" href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/08\/19\/try-on-bluemix-and-buy-mfp\/\">Try on Bluemix and migrate to on-prem MobileFirst Platform<\/a> appeared first on <a rel=\"nofollow\" href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\">IBM MobileFirst Platform<\/a>.<\/p>",
        "encoded": "<p>Contributed By : Chethan Kumar SN (chethankumar.sn@in.ibm.com) and Vittal Pai (vittalpai@in.ibm.com)<\/p>\n<p>With the release of MobileFirst Platform v7.1, one can now migrate any existing iOS app built for MobileServices on Bluemix to MobileFirst Platform with just a handful of simple steps.<\/p>\n<p>To elucidate the process, lets look at how to migrate a simple Bluemix iOS app.<\/p>\n<p>To migrate an existing iOS app built for MobileServices on Bluemix to run on MobileFirst Platform, follow the steps below.<\/p>\n<ul>\n<li><a href=\"#migrateexisting\">Existing Bluemix Server Application<\/a><\/li>\n<li><a href=\"#migrateblu\">Existing Bluemix Client Application<\/a><\/li>\n<li><a href=\"#configureclient\">Migration of Client Application<\/a><\/li>\n<li><a href=\"#migratemfp\">Migration of JAX-RS Application to JAVA Adapter<\/a><\/li>\n<li><a href=\"#configoauth\">Configuring Custom-OAuth<\/a><\/li>\n<li><a href=\"#configurepush\">Configuring Push Capability<\/a><\/li>\n<li><a href=\"#sample\">Sample and Source Code<\/a><\/li>\n<\/ul>\n<h2 id=\"migrateexisting\">Existing Bluemix Server Application<\/h2>\n<p>The Bluemix app has the following functionality:<\/p>\n<ul>\n<li>On the client side, the application stores a list of items and provides a way to add more items to the list. Each item can able to store Name, Store, Price and image of the product. The App’s are protected by Custom Authenticator via AMA security service provided by bluemix.<\/li>\n<li>On the server side, the App contains a JAX-RS class to store and manipulate the data. It also contains the server side AMA security implementation.<\/li>\n<\/ul>\n<p>On BlueMix we have application with the following configuration:<\/p>\n<ul>\n<li>Liberty Runti

me : which used to run JAX-RS application on Bluemix<\/li>\n<li>Advance Mobile Access service : which gives mobile application security and monitoring functionality<\/li>\n<li>Push Service for iOS 8 : which provides the capability to use iOS Push features<\/li>\n<\/ul>\n<h3> Liberty Runtime <\/h3>\n<ul>\n<li>Liberty contains two projects with JAX-RS service (i.e Custom-oauth-java for Custom Authentication and Local storeAdapter for storing items). The service include the protected resource and the custom identity provider code. The liberty server is configured with TAI.\n<\/li>\n<li>Trust Association Interface (TAI) is a service provider API that enables the integration of third-party security services with a Liberty profile server. For more info on TAI : <a href=\"http:\/\/www-01.ibm.com\/support\/knowledgecenter\/was_beta_liberty\/com.ibm.websphere.wlp.nd.multiplatform.doc\/ae\/twlp_dev_custom_tai.html\" target=\"_blank\">click here<\/a>\n<\/li>\n<li>The custom identity provider authenticates a user by sending challenges to the client. However, custom identity providers do not communicate directly with clients. They send challenges and receive responses to the challenges by means of the Advanced Mobile Access service. When a custom identity provider successfully authenticates the user, it provides the user identity information to Advanced Mobile Access. For more information on custom authentication refer bluemix documentation : <a href=\"https:\/\/www.ng.bluemix.net\/docs\/services\/mobileaccess\/security\/id_provs\/index-gentopic2.html#custom_id_prov\" target=\"_blank\">click here<\/a>\n<p>The custom identity provider code is defined by two http API:<\/p>\n<pre class=\"brush: plain; title: ; notranslate\">\/startAutorization<\/pre>\n<p> and\n<pre class=\"brush: plain; title: ; notranslate\">\/handleChallengeAnswer<\/pre>\n<pre class=\"brush: java; title: ; notranslate\"> @POST\n\t@Consumes ("application\/json")\n\t@Path("\/{tenantId}\/customAuthRealm_3\/startAuthorization")\n\t@Produces(MediaType.APPLICATION_JSON)\n\tpublic JSONObject startAuthorization(String payload,\n\t\t\t@PathParam("tenantId") String deviceId,\n\t\t\t@PathParam("realmName") String realmName) throws Exception {\n\t\tJSONObject returnJson = (JSONObject) JSON.parse(CHALLENGE_JSON);\n\t\treturn returnJson;\n\t}\n\t\n\t@POST\n\t@Consumes ("application\/json")\n\t@Path("\/{tenantId}\/customAuthRealm_3\/handleChallengeAnswer")\n\t@Produces(MediaType.APPLICATION_JSON)\n\tpublic JSONObject handleChllengeAnswer(String payload,\n\t\t\t@PathParam("tenantId") String deviceId,\n\t\t\t@PathParam("realmName") String realmName) throws Exception {\n\t\t\n\t\tJSONObject userStoreJson = (JSONObject) JSON.parse(USER_STORE_JSON);\n\t\tJSONObject failedResponseJson = (JSONObject) JSON.parse(FAILURE_JSON);\n\t\t\n\t\tif(payload == null || payload.isEmpty()) {\n\t\t\treturn failedResponseJson;\n\t\t}\n\t\tJSONObject payloadJson = (JSONObject) JSON.parse(payload);\n\t\tJSONObject challengeAnswer = (JSONObject) payloadJson.get("challengeAnswer");\n\t\t\n\t\tif (challengeAnswer == null) {\n\t\t\treturn failedResponseJson;\n\t\t}\n\t\t\n\t\tString userName = (String) challengeAnswer.get("userName");\n\t\tString password = (String) challengeAnswer.get("password");\n\t\t\n\t\tif (userName == null || userName.isEmpty() || password == null || password.isEmpty()) {\n\t\t\treturn failedResponseJson;\n\t\t}\n\t\t\n\t\tif (userStoreJson.containsKey(userName)) {\t\n\t\t\tJSONObject userInfoJson = (JSONObject) userStoreJson.get(userName);\n\t\t\tString userPassword = (String) userInfoJson.get("password");\n\t\t\tString userDisplayName = (String) userInfoJson.get("displayName");\n\t\t\t\n\t\t\tif (password.equals(userPassword)) {\n\t\t\t\tJSONObject returnJson = new JSONObject();\n\t\t\t\tJSONObject userIdentityJson = new JSONObject();\n\t\t\t\tuserIdentityJson.put("userName", userName);\n\t\t\t\tuserIdentityJson.put("displayName", userDisplayName);\n\t\t\t\t\n\t\t\t\treturnJson.put("status", "success");\n\t\t\t\treturnJson.put("userIdentity", userIdentityJson);\n\t\t\t\treturn returnJson;\n\t\t\t}\t\t\n\t\t}\n\t\t\n\t\treturn failedResponseJson;\n\t}\n<\/pre>\n<p>The Localstore adapter contains few http API’s to perform some basic operations like Add, Update, Create and Delete in client application.<\/p>\n<pre class=\"brush: java; title: ; notranslate\"> @GET\n\t@Path("\/getAllItems")\n\tpublic String getAllItems() throws IOException{\n\t\tinit();\n\t\tJsonArray jsonArray = new JsonArray();\n\t\tfor(Object key : props.keySet()){\n\t\t\tjsonArray.add(parser.parse(props.getProperty((String) key)).getAsJsonObject());\n\t\t}\n\t\treturn jsonArray.toString();\n\t}\n\n\t@PUT\n\t@Path("\/addItem")\n\tpublic void addItem(String itemJson) \n\t\t\tthrows IOException, URISyntaxException{\n\t\ttry{\n\t\t\tinit();\n\t\t\tint newKey = props.keySet().size()+1;\n\t\t\tprops.put(String.valueOf(newKey), itemJson);\n\t\t\tURL url = this.getClass().getClassLoader().getResource("data.properties"); \n\t\t\tFile file = new File(url.toURI().getPath());\n\t\t\tFileOutputStream foStream = new FileOutputStream(file);\n\t\t\tprops.store(foStream, "saving new item");\n\t\t\tfoStream.close();\n\n\t}catch(IOException ioe){\n\t\tioe.printStackTrace();\n\t}\n\n}\n\n\t@POST\n\t@Path("\/addAllItems")\n\tpublic String addAllItems(String itemsJson) \n\t\t\tthrows URISyntaxException, IOException{\n\t\ttry{\n\t\t\tinit();\n\t\t\tclearAllData();\n\t\t\tJsonArray jsonArr = parser.

parse(itemsJson).getAsJsonArray();\n\t\t\tfor(int i=0;i<jsonArr.size();i++){\n\t\t\t\tprops.put(String.valueOf(i+1), jsonArr.get(i).toString());\n\t\t\t}\n\t\t\tURL url = this.getClass().getClassLoader().getResource("data.properties"); \n\t\t\tFile file = new File(url.toURI().getPath());\n\t\t\tFileOutputStream foStream = new FileOutputStream(file);\n\t\t\tprops.store(foStream, "saving new item");\n\t\t\tfoStream.close();\n\t\t\treturn "true";\n\t\t}catch(IOException ioe){\n\t\t\tioe.printStackTrace();\n\t\t}\n\t\treturn "false";\n\t}\n\n\t@DELETE\n\t@Path("/clearAll")\n\tpublic String clearAllData() \n\t\t\tthrows MissingConfigurationOptionException, URISyntaxException, IOException{\n\t\t\tinit();\n\t\t\tprops.clear();\n\t\t\tSystem.out.println("Size : "+props.size());\n\t\t\tURL url = this.getClass().getClassLoader().getResource("data.properties"); \n\t\t\tFile file = new File(url.toURI().getPath());\n\t\t\tFileOutputStream foStream = new FileOutputStream(file);\n\t\t\tprops.store(foStream, "clearing all data");\n\t\t\tfoStream.close();\n\t\t\treturn "cleared";\n\t}\n</pre>\n</li>\n<li> Add TAI Extension in the following path of server directory server\/usr\/extensions
\nTAI Extension Link : Download the extension.zip from <a href=\"https:\/\/hub.jazz.net\/project\/chethan\/parkstore-bluemix-server\/overview\" target=\"_blank\">here</a>\n</li>\n<li> Add TAI Security constraint in web.xml file for both the projects.\n<pre class=\"brush: xml; title: ; notranslate\"><security-constraint>\n \t<web-resource-collection>\n \t <web-resource-name>LocalstoreApplication<\/web-resource-name>\n \t <url-pattern>\/apps\/*<\/url-pattern>\n \t<\/web-resource-collection>\n \t<auth-constraint>\n <role-name>TAIUserRole<\/role-name>\n \t<\/auth-constraint>\n<\/security-constraint>\n<security-role id="SecurityRole_TAIUserRole" >\n <role-name>TAIUserRole<\/role-name>\n<\/security-role><\/pre>\n</li>\n<li> Add OAuthTai feature in server.xml\n<pre class=\"brush: plain; title: ; notranslate\"><feature>usr:OAuthTai-1.0<\/feature><\/pre>\n</li>\n<li> Protect the Url’s using TAI by adding following code in server.xml\n<pre class=\"brush: xml; title: ; notranslate\"> <usr_OAuthTAI id="myOAuthTAI" realmName="imfRealm">\n\t\t<securityConstraint httpMethods="GET, POST" securedURLs="\/LocalstoreAdapter\/*"\/>\n\t\t<securityConstraint httpMethods="GET, POST" securedURLs="\/custom-oauth-java\/*"\/>\n\t<\/usr_OAuthTAI> \n\n <webApplication id="custom-oauth-java" location="custom-oauth-java.war" name="custom-oauth-java">\n <application-bnd>\n\t\t<security-role name="TAIUserRole">\n\t\t\t<special-subject type="ALL_AUTHENTICATED_USERS"\/>\n\t\t<\/security-role>\n\t<\/application-bnd> \n\t<\/webApplication> \n\t <webApplication id="LocalstoreAdapter" location="LocalstoreAdapter.war" name="LocalstoreAdapter">\n <application-bnd>\n\t\t<security-role name="TAIUserRole">\n\t\t\t<special-subject type="ALL_AUTHENTICATED_USERS"\/>\n\t\t<\/security-role>\n\t<\/application-bnd> \n\t<\/webApplication><\/pre>\n</li>\n<li> Specify the IMF Auth Url inside Server.env file in liberty.\n<pre class=\"brush: xml; title: ; notranslate\">imfServiceUrl=https:\/\/imf-authserver.ng.bluemix.net\/imf-authserver<\/pre>\n</li>\n<li> Create a server package which contains above two applications using following command.\n<pre class=\"brush: plain; title: ; notranslate\">.\/server package ${server_name} --include=usr<\/pre>\n</li>\n<li> Push the newly created server package to bluemix using following command.\n<pre class=\"brush: plain; title: ; notranslate\">cf push ${app_name} -p ${path_to_server_package_zip}<\/pre>\n</li>\n</ul>\n<h3>Advance Mobile Access service<\/h3>\n<ul>\n<li> Bind the pushed application to Advance Mobile Access Service.\n<p><a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-17-at-3.28.04-pm.png\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-17-at-3.28.04-pm-1024x346.png\" alt=\"Advance Mobile Access\" width=\"980\" height=\"331\" class=\"alignnone size-large wp-image-14882\" \/><\/a>\n</li>\n<li> Register your client application in AMA dashboard. For more info refer documentation : <a href=\"https:\/\/www.ng.bluemix.net\/docs\/services\/mobileaccess\/index.html\" target=\"_blank\">click here<\/a>\n<p><a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-17-at-3.42.32-pm.png\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-17-at-3.42.32-pm.png\" alt=\"AMA Client Registration\" width=\"935\" height=\"452\" class=\"alignnone size-full wp-image-14883\" \/><\/a>\n</li>\n<li> AMA provid

es Facebook, Google, or a custom identity provider to authenticate access to protected resources. Add C ustom identity provider feature as it can be migrated to MFPF and specify the corresponding jax-rs custo m authentication application url and realm name.<br \/>\n<a href=\"https:\/\/developer.ibm.com\/mobilefirs tplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-17-at-4.03.21-pm.png\"><img s rc=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Sh ot-2015-07-17-at-4.03.21-pm.png\" alt=\"Custom Auth AMA\" width=\"955\" height=\"375\" class=\"alignno ne size-full wp-image-14890\" \/><\/a>\n<\/li>\n<li> Add the following code inside didFinishLaunchingWith Options function in AppDelegate of client application which will register the realm and initialize connection with Bluemix Application.\n<pre class=\"brush: plain; title: ; notranslate\"> IMFClient.sharedInstance().regi sterAuthenticationDelegate(customAuthDelegate, forRealm: "customAuthRealm_3") \nIMFClient.sharedInstance().initializeWithBackendRoute("https:\/\/parkstore.mybluemix.net&a mp;quot;, backendGUID: "5e3ad88d-dd48-469d-b46f-2c4ad66b5345")<\/pre>\n<\/li >\n<li> The following is the sample code to invoke the Rest url’s in client application.\n<pre c lass=\"brush: plain; title: ; notranslate\">var request: IMFResourceRequest = IMFResourceRequest(path: "https:\/\/parkstore.mybluemix.net\/LocalstoreAdapter\/apps\/5e3ad88d-dd48-469d-b46f-2c4ad 66b5345\/localstore\/getAllItems", method: "GET")\n request.sendWi thCompletionHandler { (wlResponse:IMFResponse!, err:NSError!) -> Void in<\/pre>\n<\/li>\n<\/ul> \n<h3>Push Service for iOS 8<\/h3>\n<ul>\n<li> Bind the application with Push Service for iOS 8<br \/>\n <a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Scree n-Shot-2015-07-17-at-4.07.01-pm.png\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-c ontent\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-17-at-4.07.01-pm-1024x367.png\" alt=\"Push AMA\" width=\"980\" height=\"351\" class=\"alignnone size-large wp-image-14891\" \/><\/a>\n<\/li>\n<li> C onfigure Apple Push Notification service (APNs) which requires Apple Developer Account and Generate pl2 certificates. Documentation link : <a href=\"https:\/\/www.ng.bluemix.net\/docs\/services\/mobilepush\/i ndex.html#certificates\" target=\"_blank\">click here<\/a>\n<\/li>\n<li> Upload the generated pl2 certificate in Push service dashboard\n<p><a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/up loads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.47.14-pm.png\"><img src=\"https:\/\/developer.ib m.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.47.14- pm-1024x377.png\" alt=\"Push Service\" width=\"980\" height=\"361\" class=\"alignnone size-large wp-im age-14816\" \/><\/a>\n<\/li>\n<li>Add the following code inside didFinishLaunchingWithOptions function in AppDelegate of client application which will register notifications in client app.\n<pre class=\"brush: plain; title: ; notranslate\"> let notificationTypes: UIUserNotificationType = UIUserNotificationType.Badge | UIUs erNotificationType.Alert | UIUserNotificationType.Sound\n let notificationSettings: UIUserNotification Settings = UIUserNotificationSettings(forTypes: notificationTypes, categories: nil)\n \n applicatio n.registerUserNotificationSettings(notificationSettings)\n application.registerForRemoteNotifications() <\/pre>\n<\/li>\n<li>Add the following code inside didRegisterForRemoteNotificationsWithDeviceToken fu nction in AppDelegate of client application which will register pushclient and subscribe to tag in client app .\n<pre class=\"brush: plain; title: ; notranslate\">IMFPushClient.sharedInstance().registerDeviceToken(de viceToken, completionHandler: { (response, error) -> Void in\n if error != nil {\n println("Error during device registration \\(error.description)")\n }\n els e {\n println("Response during device registration json: \\(response.responseJson.de scription)")\n var tags = ["parkstore"]\n IMFPushClie nt.sharedInstance().subscribeToTags(tags, completionHandler: { (response:IMFResponse!, err:NSError!) -> Void in\n if err != nil {\n println("There was an error whil e subscribing to tag")\n }else{\n println("Successfully s ubscribe to tag parkstore")\n }\n })\n }<\/pre>\n<\/li>\n<li>Add th e following function inside Appdelegate which triggers when push notification arrived in client app.\n<pre class=\"brush: plain; title: ; notranslate\">func application(application: UIApplication, didReceiveRemoteN otification userInfo: [NSObject : AnyObject]) {\n println("Got remote Notification. Data : \\(u serInfo.description)")\n let info = userInfo as NSDictionary\n let data = info.objectFor Key("aps")?.objectForKey("alert") as! NSDictionary\n let u serData = data.objectForKey("body") as! String\n let alertView = UIAlertView(titl e: "WishList!", message: "\\(userData)", delegate: nil, cancelBu ttonTitle: "OK")\n alertView.show()\n }\n}<\/pre>\n<\/li>\n<\/ul>\n<h2 id=\"mi grateblu\">Existing Bluemix Client Application<\/h2>\n<p>Add the following Code snippets to the existing Bluemix Client Application and name the application with same name which you have registered in Advan ce Mobile Access Dashboard.<\/p>\n<ul>\n<li> Add the following code inside didFinishLaunchingWithOpt

ce Mobile Access Dashboard.<\/p>\n<ul>\n<li> Add the following code inside didFinishLaunchingWithOpt
ions function in AppDelegate of client application which will register the realm and initialize connection wit
h Bluemix Application.\n<pre class=\"brush: plain; title: ; notranslate\"> IMFClient.sharedInstance().registe
rAuthenticationDelegate(customAuthDelegate, forRealm: "customAuthRealm_3")\nI
MFClient.sharedInstance().initializeWithBackendRoute("https:\/\/parkstore.mybluemix.net&amp
;quot;, backendGUID: "5e3ad88d-dd48-469d-b46f-2c4ad66b5345")<\/pre>\n<\/li>\n
<li> The following is the sample code to invoke the Rest url’s in client application.\n<pre clas
s=\"brush: plain; title: ; notranslate\">var request: IMFResourceRequest = IMFResourceRequest(path: &a
mp;quot;https:\/\/parkstore.mybluemix.net\/LocalstoreAdapter\/apps\/5e3ad88d-dd48-469d-b46f-2c4ad66
b5345\/localstore\/getAllItems", method: "GET")\n request.sendWith
CompletionHandler { (wlResponse:IMFResponse!, err:NSError!) -> Void in<\/pre>\n<\/li>\n<li>Add
the following code inside didFinishLaunchingWithOptions function in AppDelegate of client application wh
ich will register notifications in client app.\n<pre class=\"brush: plain; title: ; notranslate\"> let notificationT
ypes: UIUserNotificationType = UIUserNotificationType.Badge | UIUserNotificationType.Alert | UIUserNoti
ficationType.Sound\n let notificationSettings: UIUserNotificationSettings = UIUserNotificationSettings
(forTypes: notificationTypes, categories: nil)\n \n application.registerUserNotificationSettings(not
ificationSettings)\n application.registerForRemoteNotifications()<\/pre>\n<\/li>\n<li>Add the following
code inside didRegisterForRemoteNotificationsWithDeviceToken function in AppDelegate of client applic
ation which will register pushclient and subscribe to tag in client app.\n<pre class=\"brush: plain; title: ; not
ranslate\">IMFPushClient.sharedInstance().registerDeviceToken(deviceToken, completionHandler: { (res
ponse, error) -> Void in\n if error != nil {\n println("Error during device
registration \\(error.description)")\n }\n else {\n println("Res
ponse during device registration json: \\(response.responseJson.description)")\n var
tags = ["parkstore"]\n IMFPushClient.sharedInstance().subscribeToTags(t
ags, completionHandler: { (response:IMFResponse!, err:NSError!) -> Void in\n if err !
= nil {\n println("There was an error while subscribing to tag")\n
}else{\n println("Successfully subscribe to tag parkstore")\n
}\n })\n }<\/pre>\n<\/li>\n<li>Add the following function inside Appdelegate which trigger
s when push notification arrived in client app.\n<pre class=\"brush: plain; title: ; notranslate\">func applica
tion(application: UIApplication, didReceiveRemoteNotification userInfo: [NSObject : AnyObject]) {\n p
rintln("Got remote Notification. Data : \\(userInfo.description)")\n let info = userI
nfo as NSDictionary\n let data = info.objectForKey("aps")?.objectForKey(&
quot;alert") as! NSDictionary\n let userData = data.objectForKey("body&q
uot;) as! String\n let alertView = UIAlertView(title: "WishList!", message: &
quot;\\(userData)", delegate: nil, cancelButtonTitle: "OK")\n alertView
.show()\n }\n}<\/pre>\n<\/li>\n<li>The following are the screenshots of client application.<br \/>\n<a hr
ef=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/IMG_0020.
jpg\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07
\/IMG_0020-169x300.jpg\" alt=\"IMG_0020\" width=\"169\" height=\"300\" class=\"alignnone size-medium
wp-image-14917\" \/><\/a><a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\
/sites\/32\/2015\/07\/IMG_00211.jpg\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-con
tent\/uploads\/sites\/32\/2015\/07\/IMG_00211-169x300.jpg\" alt=\"IMG_0021\" width=\"169\" height=\"300
\" class=\"alignnone size-medium wp-image-14918\" \/><\/a><a href=\"https:\/\/developer.ibm.com\/mobile
firstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/IMG_0025.jpg\"><img src=\"https:\/\/developer.ibm.
com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/IMG_0025-169x300.jpg\" alt=\"IMG_00
25\" width=\"169\" height=\"300\" class=\"alignnone size-medium wp-image-14920\" \/><\/a><a href=\"http
s:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/IMG_0024.jpg\"><i
mg src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/IMG_
0024-169x300.jpg\" alt=\"IMG_0024\" width=\"169\" height=\"300\" class=\"alignnone size-medium wp-im
age-14919\" \/><\/a><a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\
/32\/2015\/07\/IMG_0026.jpg\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/u
ploads\/sites\/32\/2015\/07\/IMG_0026-169x300.jpg\" alt=\"IMG_0026\" width=\"169\" height=\"300\" class
=\"alignnone size-medium wp-image-14921\" \/><\/a>\n<\/li>\n<\/ul>\n<h2>Migration to On-Prem<\/h2>\n
<h3 id=\"configureclient\">Migration of Client Application<\/h3>\n<p>Migration of Client Application includ
es following two steps<\/p>\n<li>Configuring Cocoapods<\/li>\n<li>Client App Migration<\/li>\n<h3 id=\"co
coapods\">Configuring Cocoapods<\/h3>\n<p>If CocoaPods has not been installed on a specific comput
er:<\/p>\n<ul>\n<li>Follow the “Getting Started” guide for CocoaPods installatio

n: http:\/\/guides.cocoapods.org\/using\/getting-started.html<\/li>\n<li>Open “Terminal” at the installation location and run the “pod init” command<\/li>\n<\/ul>\n<p>The following steps assume that the client application is working with CocoPods. If not, follow this “Using CocoaPods” documentation : <a href=\"http:\/\/guides.cocoapods.org\/using\/using-cocoapods.html\" target=\"_blank\">click here<\/a><\/p>\n<p>In both cases, the instructions below explain how to edit the “Podfile” file.<\/p>\n<ol>\n<li>Open the “Podfile” file located in the root of your XCode project in a favourite text editor.<\/li>\n<li>Comment out or remove the existing content.<\/li>\n<li>Add the following lines:\n<pre class=\"brush: plain; title: ; notranslate\">source 'https:\/\/github.rtp.raleigh.ibm.com\/imflocalsdks\/imf-client-sdk-specs.git'\npod 'IMFCompatibility'<\/pre>\n<\/li>\n<li>Open “Terminal” at the location of “Podfile”.<\/li>\n<li>Verify that the XCode project is closed.<\/li>\n<li>Run the “pod install” command.<\/li>\n<\/ol>\n<p>Open the [MyProject].xcworkspace file in XCode. This file is located side by side with [MyProject].xcodeproj.<br \/>\nAn usual CocoaPods-based project is managed as a workspace containing the application (the executable) and the library (all project dependencies brought by the CocoaPods manager).<\/p>\n<p>In Xcode’s Build Settings, search for “Other Linker Flags” and insert ${inherited} (if -ObjC is defined in this field, you can just delete it, since it is configured in the CocoaPod project).<\/p>\n<h3>Client App Migration<\/h3>\n<ol>\n<li>Search for bluemix dependency imports like\n<pre class=\"brush: plain; title: ; notranslate\">#import <IMFCore\/IMFCore.h>\n#import <IMFPush\/IMFPush.h><\/pre>\n<p>Replace the above imports with <\/p>\n<pre class=\"brush: plain; title: ; notranslate\">#import <IMFCompatibility\/IMFCompatibility.h><\/pre>\n<\/li>\n<li>Look for a call to the “initializeWithBackendRoute” method and replace the route URL with your on-premise server URL. For example:\n<pre class=\"brush: plain; title: ; notranslate\">IMFClient.sharedInstance().initializeWithBackendRoute("https:\/\/parkstore.mybluemix.net", backendGUID: "5e3ad88d-dd48-469d-b46f-2c4ad66b5345"<\/pre>\n<p>should be replaced with your on-premise MFP server URL<\/p>\n<pre class=\"brush: plain; title: ; notranslate\">IMFClient.sharedInstance().initializeWithBackendRoute("http:\/\/localhost:10080\/ParkStoreMFP", backendGUID: "5e3ad88d-dd48-469d-b46f-2c4ad66b5345"<\/pre>\n<p>Note, that backendGUID parameter is ignored and can be empty. Look for all instantiations of IMFResourceRequest class and update it<\/li>\n<li>Look for all instantiations of IMFResourceRequest class and update the request URL with absolute or relative path to the resource. For example:\n<pre class=\"brush: plain; title: ; notranslate\">var request: IMFResourceRequest = IMFResourceRequest(path: "https:\/\/parkstore.mybluemix.net\/LocalstoreAdapter\/apps\/5e3ad88d-dd48-469d-b46f-2c4ad66b5345\/localstore\/getAllItems", method: "GET")<\/pre>\n<p>should be replaced with<\/p>\n<pre class=\"brush: plain; title: ; notranslate\">var request: IMFResourceRequest = IMFResourceRequest(path: "http:\/\/localhost:10080\/ParkStoreMFP\/adapters\/LocalstoreAdapter\/localstore\/getAllItems", method: "GET")<\/pre>\n<\/li>\n<li>Add the following code inside didRegisterForRemoteNotificationsWithDeviceToken function in Appdelegate of Client application.\n<pre class=\"brush: plain; title: ; notranslate\"> WLPush.sharedInstance().tokenFromClient = deviceToken.description<\/pre>\n<\/li>\n<li>All on-premise applications require the “worklight.plist” file to be present in the application resources. In the <code>IBMMobileFirstPlatformFoundationNativeSDK<\/code> pod we supply a file named sample.worklight.plist<\/strong>.\n<ul>\n<li>Locate the “sample.worklight.plist” file in the â€˜IBMMobileFirstPlatformFoundationNativeSDKâ€™ pod.<\/li>\n<li>Copy this file to the parent (application) project and rename it to “worklight.plist”.<\/li>\n<li>Edit the “worklight.plist” file by setting the “application id” key to the name of your application deployed to the on-premise MFPF server<\/li>\n<\/ul>\n<\/li>\n<\/ol>\n<h3 id=\"migratemfp\">Migration of JAX-RS Application to JAVA Adapter<\/h3>\n<ol>\n<li>To migrate JAX-RS application to on-prem (MobileFirst Foundation) server we need to do the following steps for server:\n<p>Create MobileFirst Project –> Create native API app for iOS<br \/>\n â€‹â€‹<br \/>\n<a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.50.04-pm.png\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.50.04-pm.png\" alt=\"Screen Shot 2015-07-12 at 6.50.04 pm\" width=\"595\" height=\"596\" class=\"alignnone size-full wp-image-14817\" \/><\/a><\/p>\n<p><a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.51.13-pm.png\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.51.13-pm.png\" alt=\"Screen Shot 2015-07-12 at 6.51.13 pm\" width=\"598\" height=\"590\" class=\"alignnone size-full wp-image-

14818\" \/><\/a><\/p>\n<p><a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.52.28-pm.png\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.52.28-pm.png\" alt=\"Screen Shot 2015-07-12 at 6.52.28 pm\" width=\"717\" height=\"424\" class=\"alignnone size-full wp-image-14819\" \/><\/a><\/li>\n<li>Add two adapters for Custom Authentication and Localstore and migrate the JAX-RS code as shown in the following example.<\/li>\n<\/ol>\n<p>Copy the JAX-RS BlueMix code and paste it in the newly created Localstore Java adapter JAX-RS file.<\/p>\n<p>Add and remove the following changes in your adapter code.<\/p>\n<ul>\n<li> remove <code>\/{tenantId}\/<\/code><\/li>\n<li> remove the <code>@PathParam -> PathParam(\"tenantId\") String deviceId<\/code> and <code>@PathParam(\"realmName\") String realmName<\/code><\/li>\n<li> Add scope to the all http api resource <code>@OAuthSecurity (scope=\"customAuthRealm_3\")<\/code><\/li>\n<\/ul>\n<p>The code looks like the following<\/p>\n<pre class=\"brush: plain; title: ; notranslate\">\n\t@GET\n\t@OAuthSecurity (scope="customAuthRealm_3")\n\t@Path("\/getAllItems")\n\tpublic String getAllItems() throws MissingConfigurationOptionException{\n\t\tinit();\n\t\tJsonArray jsonArray = new JsonArray();\n\t\tfor(Object key : props.keySet()){\n\t\t\tjsonArray.add(parser.parse(props.getProperty((String) key)).getAsJsonObject());\n\t\t}\n\t\treturn jsonArray.toString();\n\t}\n\n\t@PUT\n\t@OAuthSecurity (scope="customAuthRealm_3")\n\t@Path("\/addItem")\n\tpublic void addItem(String itemJson) \n\t\t\tthrows MissingConfigurationOptionException, URISyntaxException, IOException{\n\t\ttry{\n\t\t\tinit();\n\t\t\tint newKey = props.keySet().size()+1;\n\t\t\tprops.put(String.valueOf(newKey), itemJson);\n\t\t\tURL url = this.getClass().getClassLoader().getResource("data.properties"); \n\t\t\tFile file = new File(url.toURI().getPath());\n\t\t\tFileOutputStream foStream = new FileOutputStream(file);\n\t\t\tprops.store(foStream, "saving new item");\n\t\t\tfoStream.close();\n\n\t}catch(IOException ioe){\n\t\tioe.printStackTrace();\n\t}\n\n\t}\n\n\t@POST\n\t@OAuthSecurity (scope="customAuthRealm_3")\n\t@Path("\/addAllItems")\n\tpublic String addAllItems(String itemsJson) \n\t\t\tthrows MissingConfigurationOptionException, URISyntaxException, IOException{\n\t\ttry{\n\t\t\tinit();\n\t\t\tclearAllData();\n\t\t\tJsonArray jsonArr = parser.parse(itemsJson).getAsJsonArray();\n\t\t\tfor(int i=0;i<jsonArr.size();i++){\n\t\t\t\tprops.put(String.valueOf(i+1), jsonArr.get(i).toString());\n\t\t\t}\n\t\t\tURL url = this.getClass().getClassLoader().getResource("data.properties"); \n\t\t\tFile file = new File(url.toURI().getPath());\n\t\t\tFileOutputStream foStream = new FileOutputStream(file);\n\t\t\tprops.store(foStream, "saving new item");\n\t\t\tfoStream.close();\n\t\t\treturn "true";\n\t}catch(IOException ioe){\n\t\tioe.printStackTrace();\n\t}\n\treturn "false";\n\t}\n\n@DELETE\n\t@OAuthSecurity(enabled=false)\n\t@Path("\/clearAll")\n\tpublic String clearAllData() \n\t\t\tthrows MissingConfigurationOptionException, URISyntaxException, IOException{\n\t\tinit();\n\t\tprops.clear();\n\t\tSystem.out.println("Size : "+props.size());\n\t\tURL url = this.getClass().getClassLoader().getResource("data.properties"); \n\t\tFile file = new File(url.toURI().getPath());\n\t\tFileOutputStream foStream = new FileOutputStream(file);\n\t\tprops.store(foStream, "clearing all data");\n\t\tfoStream.close();\n\t\treturn "cleared";\n\t}\n<\/pre>\n<h3 id=\"configoauth\">Configuring Custom-OAuth<\/h3>\n<ul>\n<li>Add realm with same name you had on BlueMix and login module to the authenticationConfig.xml.\n<pre class=\"brush: xml; title: ; notranslate\"><realm name="customAuthRealm_3" loginModule="customAuthLoginModule_3">\n<className>com.worklight.core.auth.ext.CustomIdentityAuthenticator<\/className>\t\n<parameter name="providerUrl" value="http:\/\/localhost:10080\/ParkStoreMFP\/adapters\/Customauth"\/>\n<\/realm>\n\n<loginModule name="customAuthLoginModule_3" expirationInSeconds="3600">\n<className>com.worklight.core.auth.ext.CustomIdentityLoginModule<\/className>\n<\/loginModule><\/pre>\n<\/li>\n<li>Add Custom-oauth Realm in userIdentityRealms in Application Descriptor file of iOS Native API\n<pre class=\"brush: xml; title: ; notranslate\"><userIdentityRealms>customAuthRealm_3<\/userIdentityRealms><\/pre>\n<\/li>\n<\/ul>\n<h3 id=\"configurepush\">Configuring Push Capability<\/h3>\n<ul>\n<li> Add apns p12 certificate which is generated from Apple Developer Account under iOS Native API Folder\n<p><a href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.58.03-pm.png\"><img src=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/wp-content\/uploads\/sites\/32\/2015\/07\/Screen-Shot-2015-07-12-at-6.58.03-pm.png\" alt=\"Screen Shot 2015-07-12 at 6.58.03 pm\" width=\"286\" height=\"171\" class=\"alignnone size-full wp-image-14820\" \/><\/a>\n<\/li>\n<li> Add Push configuration in Application Descriptor file of iOS Native API and include the pas

sword of added apns certificate.\n<pre class=\"brush: xml; title: ; notranslate\"><pushSender password="password"\/>\n<tags>\n <tag>\n   <name>parkstore<\/name>\n <\/tag>\n<\/tags><\/pre>\n<\/li>\n<li> Create HTTP Push Adapter with following function code which will send the user push notification to the devices which is subscribed to tag “parkstore”.\n<pre class=\"brush: xml; title: ; notranslate\">function sendTagNotification(notificationText) {\n   var notificationOptions = {};\n   notificationOptions.message = {};\n   notificationOptions.target = {};\n\n   notificationOptions.message.alert = notificationText;\n   notificationOptions.target.tagNames = ["parkstore"];\n\n   WL.Server.sendMessage("ParkStoreMFP", notificationOptions);\n\n   return {\n   result : "Notification sent to users subscribed to the tag parkstore."\n   };\n}<\/pre>\n<\/li>\n<\/ul>\n<p>By performing above steps one can easily run iOS app built for Bluemix on MobileFirst Platform and following are the links to samples.<\/p>\n<h3 id=\"sample\">Sample and Source Code<\/h3>\n<p>Bluemix Server : <a href=\"https:\/\/hub.jazz.net\/git\/chethan\/parkstore-bluemix-server\">Parkstore bluemix server<\/a><br \/>\nBluemix Client : <a href=\"https:\/\/hub.jazz.net\/git\/chethan\/parkstore-bluemix\">Parkstore bluemix<\/a><br \/>\nMFP Server   : <a href=\"https:\/\/hub.jazz.net\/git\/chethan\/parkstore-mfp-server\">Parkstore mfp server<\/a><br \/>\nMFP Client   : <a href=\"https:\/\/hub.jazz.net\/git\/chethan\/parkstore-mfp\">Parkstore mfp<\/a><\/p>\n<p>The post <a rel=\"nofollow\" href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/08\/19\/try-on-bluemix-and-buy-mfp\/\">Try on Bluemix and migrate to on-prem MobileFirst Platform<\/a> appeared first on <a rel=\"nofollow\" href=\"https:\/\/developer.ibm.com\/mobilefirstplatform\">IBM MobileFirst Platform<\/a>.<\/p>",
            "guid": {
              "content": "https:\/\/developer.ibm.com\/mobilefirstplatform\/?p=14769",
              "isPermaLink": "false"
            },
            "link": "https:\/\/developer.ibm.com\/mobilefirstplatform\/2015\/08\/19\/try-on-bluemix-and-buy-mfp\/",
            "pubDate": "Wed, 19 Aug 2015 10:36:51 +0000",
            "title": "Try on Bluemix and migrate to on-prem MobileFirst Platform"
          }
        ],
        "language": "en-US",
        "lastBuildDate": "Tue, 08 Sep 2015 09:22:53 +0000",
        "link": [
          {
            "href": "https:\/\/developer.ibm.com\/mobilefirstplatform\/feed\/",
            "rel": "self",
            "type": "application\/rss+xml"
          },
          "https:\/\/developer.ibm.com\/mobilefirstplatform"
        ],
        "title": "IBM MobileFirst Platform",
        "updateFrequency": "1",
        "updatePeriod": "hourly"
      },
      "version": "2.0"
    }
}

Sample

The attached sample (https://github.com/MobileFirst-Platform-Developer-Center/JavaAdapters/tree/release71) includes an adapter called `RSSAdapter` and a hybrid application called `RSSReader` to test the adapter inside an application.