

Event Source Notifications in Native Windows Phone 8 Applications

Relevant to:



Overview

Prerequisite: Make sure that you read the [Push notifications in native Windows Phone 8 applications](#) tutorial first.

Event source notifications are notification messages that are targeted to devices with a user subscription.

While the user subscription exists, MobileFirst Server can produce push notifications for the subscribed user. These notifications can be delivered by the adapter code to all or some of the devices from which the user subscribed.

To learn more about the architecture and terminology of event-source push notifications refer to the [Push notification overview](#) tutorial.

Implementation of the push notification API consists of the following main steps:

On the server side:

- *Creating an event source*
- *Sending notification*

On the client side:

- *Sending the token and initializing the WLPush class*
- *Registering the event source*
- *Subscribing to/unsubscribing from the event source*

Agenda

- [Notification API – Server-side](#)
- [Notification API – Client-side](#)
- [Sample application](#)

Notification API – Server-side

Creating an event source

To create an event source, you declare a notification event source in the adapter JavaScript code at a global level (outside any JavaScript function):

```
WL.Server.createEventSource({
  name: 'PushEventSource',
  onDeviceSubscribe: 'deviceSubscribeFunc',
  onDeviceUnsubscribe: 'deviceUnsubscribeFunc',
  securityTest: 'PushApplication-strong-mobile-securityTest'
});
```

- **name** – a name by which the event source is referenced.
- **onDeviceSubscribe** – an adapter function that is invoked when the user subscription request is received.
- **onDeviceUnsubscribe** – an adapter function that is invoked when the user unsubscription request is received.
- **securityTest** – a security test from the `authenticationConfig.xml` file, which is used to protect the event source.

An additional event source option:

```
poll: {
  interval: 3,
  onPoll: 'getNotificationsFromBackend'
}
```

- **poll** – a method that is used for notification retrieval.
The following parameters are required:
 - **interval** – the polling interval in seconds.
 - **onPoll** – the polling implementation. An adapter function to be invoked at specified intervals.

Sending a notification

As described previously, notifications can be either polled from the back-end system or pushed by one. In this example, a `submitNotifications()` adapter function is invoked by a back-end system as an external API to send notifications.

```
function submitNotification(userId, notificationText) {
  var userSubscription = WL.Server.getUserNotificationSubscription('PushAdapter.PushEventSource', userId);

  if (userSubscription === null) {
    return { result: "No subscription found for user :: " + userId };
  }

  var badgeDigit = 1;
  var notification = WL.Server.createDefaultNotification(notificationText, badgeDigit, {custom:"data"});
```

```
WL.Server.notifyAllDevices(userSubscription, notification);
```

```
    return {
        result: "Notification sent to user :: " + userId
    };
}
```

The `submitNotification` function receives the `userId` to send notification to and the `notificationText`.

```
function submitNotification(userId, notificationText) {
```

A user subscription object contains the information about all of the user's subscriptions. Each user subscription can have several device subscriptions. The object structure is as follows:

```
{
  userId: 'bjones',
  state: {
    customField: 3
  },
  getDeviceSubscriptions: function(){}
};
```

Next line:

```
var userSubscription = WL.Server.getUserNotificationSubscription('PushAdapter.PushEventSource', userId);
```

If the user has no subscriptions for the specified event source, a `null` object is returned.

```
if (userSubscription === null) {
    return { result: "No subscription found for user :: " + userId };
}
```

The `WL.Server.createDefaultNotification` API method creates and returns a default notification JSON block for the supplied values.

```
var badgeDigit = 1;
var notification = WL.Server.createDefaultNotification(notificationText, badgeDigit, {custom:"data"});
```

- **notificationText** – The text to be pushed to the device.
- **Badge** (number) – A number that is displayed on the application icon or tile (in environments that support it).
- **custom** – Custom, or Payload, is a JSON object that is transferred to the application and that can contain custom properties.

The `WL.Server.notifyAllDevices` API method sends notification to all the devices that are subscribed to the user.

```
WL.Server.notifyAllDevices(userSubscription, notification);
```

Several APIs exist for sending notifications:

- `WL.Server.notifyAllDevices(userSubscription, options)` – to send notification to all user's devices.
- `WL.Server.notifyDevice(userSubscription, device, options)` – to send notification to a specific device that belongs to a specific user subscription.
- `WL.Server.notifyDeviceSubscription(deviceSubscription, options)` – to send the notification to a specific device.

Notification API – Client-side

1. Create an instance of the `WLClient` class.

```
WLClient client = WLClient.getInstance();
```

2. Use the methods of the `WLPush` class.

`getPush` – This method retrieves an instance of the `WLPush` class from the `WLClient` instance.

```
WLPush push = client.getPush();
```

`onReadyToSubscribeListener` – When connecting to a MobileFirst Server instance, the application attempts to register itself with the MPNS server to receive push notifications.

```
push.onReadyToSubscribeListener = onReadyListener;
client.connect(connectListener);
```

`notificationListener` – Then the app receives the notification.

```
push.notificationListener = notificationListener;
client.connect(connectListener);
```

The `onReadyToSubscribe` method of `WLOnReadyToSubscribeListener` is called when registration is complete.

```
public void onReadyToSubscribe() { ..... }
```

3. To register an alias on a particular event source, use the `WLPush.registerEventSourceCallback` method. The API takes the following arguments:

`alias` – An alias name.

`Adaptername` – The adapter in which the event source is defined.

`EventSourceName` – The event source on which the alias is called.

Example:

```
WLCClient.getInstance().getPush().registerEventSourceCallback("newalias", "PushAdapter", "PushEventSource",
this);
```

Typically, this method is called in the `onReadyToSubscribe` callback function.

```
public void onReadyToSubscribe() {
    WLCClient.getInstance().getPush().registerEventSourceCallback("newalias", "PushAdapter", "PushEventSource", this)
}
```

Subscribing to push notifications

To set up subscription to push notifications, use the `WLPush.subscribe(alias, pushOptions, responseListener)` API.

The API takes the following arguments:

`alias` – The alias to which the device must subscribe.
`pushOptions` – An object of type `WLPushOptions`
`responseListener` – An object of type `WLResponseListener`, which is called when subscription completes.

Example:

```
WLCClient client = WLCClient.getInstance(); client.getPush().subscribe("newalias", new WLPushOptions(), new
MyListener());
```

`MyListener` implements `WLResponseListener` and provides the following callback functions:

`onSuccess` – Called when subscription succeeds.
`onFailure` – Called when subscription fails.

Unsubscribing from push notifications

To set up unsubscription from push notifications, use the `WLPush.unsubscribe(alias, responseListener)` API.

The API takes the following arguments:

`alias` – The alias to which the device has subscribed.
`responseListener` – An object of type `WLResponseListener`, which is called when unsubscription completes.

```
WLCClient client = WLCClient.getInstance(); client.getPush().unsubscribe("newalias", new MyListener());
```

`MyListener` implements `WLResponseListener` and provides the following callback functions:

`onSuccess` – Called when unsubscription succeeds.
`onFailure` – Called when unsubscription fails.

Additional client-side API methods:

`isSubscribed()` – Indicates whether the device is subscribed to push notifications.

```
WLCClient client = WLCClient.getInstance(); boolean bIsSubscribed = client.getPush().isSubscribed("newalias");
```

Receiving a push notification

When a push notification is received, the `onReceive` method is called on an `WLEventSourceListener` instance.

```
class MyListener : WLOnReadyToSubscribeListener , WLEventSourceListener
{
```

The `WLEventSourceListener` instance is registered during the `registerEventSourceCallback` callback.

```
WLCClient.getInstance().getPush().registerEventSourceCallback("newalias", "PushAdapter", "PushEventSource", this
);
```

The `onReceive` method displays the received notification on the screen.

```
public void onReceive(String props, String payload) {
    Deployment.Current.Dispatcher.BeginInvoke(() =>
    {
        MessageBox.Show("Push notification received " + payload);
    });
}
```

If the application is not running, the notification icon appears on the notification bar at the top of the screen.

Sample application

[Click to download](#) the MobileFirst project.

[Click to download](#) the Native project.

- The `EventSourceNotifications` project contains a MobileFirst native API that you can deploy to your MobileFirst server.
- The `EventSourceNotificationsWP8` project contains a native Windows Phone 8 application that uses a MobileFirst native API library to subscribe for push notifications and receive notifications from MPNS.
- Make sure to update the `wlclient.properties` file in the native project with the relevant server settings.

