

# JavaScript SQL Adapter

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/8.0/adapters/javascript-adapters/js-sql-adapter/index.md>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

## Overview

An IBM MobileFirst Platform Foundation SQL adapter is designed to communicate with any SQL data source. You can use plain SQL queries or stored procedures.

To connect to a database, JavaScript code needs a JDBC connector driver for the specific database type. You must download the JDBC connector driver for the specific database type separately and add it as a dependency in your project. For more information on how to add a dependency, see the Dependencies section in the Creating Java and JavaScript Adapters ([../creating-adapters/#dependencies](#)) tutorial.

In this tutorial and in the accompanying sample, you learn how to use a MobileFirst adapter to connect to a MySQL database.

**Prerequisite:** Make sure to read the JavaScript Adapters ([../](#)) tutorial first.

## The XML File

The XML file contains settings and metadata.

1. In the adapter XML file, declare the following parameters:
  - Driver Class
  - Database URL
  - Username
  - Password

```
<?xml version="1.0" encoding="UTF-8"?>
<mfp:adapter name="JavaScriptSQL"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xmlns:mfp="http://www.ibm.com/mfp/integration"
  xmlns:sql="http://www.ibm.com/mfp/integration/sql">

  <displayName>JavaScriptSQL</displayName>
  <description>JavaScriptSQL</description>
  <connectivity>
    <connectionPolicy xsi:type="sql:SQLConnectionPolicy">
      <dataSourceDefinition>
        <driverClass>com.mysql.jdbc.Driver</driverClass>
        <url>jdbc:mysql://localhost:3306/mobilefirst_training</url>
        <user>mobilefirst</user>
        <password>mobilefirst</password>
      </dataSourceDefinition>
    </connectionPolicy>
  </connectivity>

  <procedure name="getAccountTransactions1"/>
  <procedure name="getAccountTransactions2"/>
</mfp:adapter>
```

2. Declare a procedure in the adapter XML file.

```
<procedure name="getAccountTransactions1"/>
```

## JavaScript implementation

The adapter JavaScript file is used to implement the procedure logic.

There are two ways of running SQL statements:

- SQL statement query
- SQL stored procedure

1. Use the `WL.Server.createStatement` method to prepare a SQL query. This method must always be called outside the function.
2. Add more parameters, if necessary.

```
//Create SQL query  
var getAccountsTransactionsStatement = WL.Server.createStatement(  
    "SELECT transactionId, fromAccount, toAccount, transactionDate, transactionAmount, transactionT  
ype " +  
    "FROM accounttransactions " +  
    "WHERE accounttransactions.fromAccount = ? OR accounttransactions.toAccount = ? " +  
    "ORDER BY transactionDate DESC " +  
    "LIMIT 20;"  
);
```

3. Use the `WL.Server.invokeSQLStatement` method to call prepared queries.
4. Return the result to the application or to another procedure.

```
//Invoke prepared SQL query and return invocation result  
function getAccountTransactions1(accountId){  
    return WL.Server.invokeSQLStatement({  
        preparedStatement : getAccountsTransactionsStatement,  
        parameters : [accountId, accountId]  
    });  
}
```

5. To run a SQL stored procedure, use the `WL.Server.invokeSQLStoredProcedure` method. Specify a SQL stored procedure name as an invocation parameter.
6. Add more parameters, if necessary.
7. Return the invocation result to the application or to another procedure.

```
//Invoke stored SQL procedure and return invocation result  
function getAccountTransactions2(accountId){  
    return WL.Server.invokeSQLStoredProcedure({  
        procedure : "getAccountTransactions",  
        parameters : [accountId]  
    });  
}
```

## Invocation Results

The result is retrieved as a JSON object:

```
{
  "isSuccessful": true,
  "resultSet": [{
    "fromAccount": "12345",
    "toAccount": "54321",
    "transactionAmount": 180.00,
    "transactionDate": "2009-03-11T11:08:39.000Z",
    "transactionId": "W06091500863",
    "transactionType": "Funds Transfer"
  }, {
    "fromAccount": "12345",
    "toAccount": null,
    "transactionAmount": 130.00,
    "transactionDate": "2009-03-07T11:09:39.000Z",
    "transactionId": "W214122V5337",
    "transactionType": "ATM Withdrawal"
  }]
}
```

- The `isSuccessful` property defines whether the invocation was successful.
- The `resultSet` object is an array of returned records.
  - To access the `resultSet` object on the client-side: `result.invocationResult.resultSet`
  - To access the `resultSet` object on the server-side: `result.ResultSet`

## Sample adapter

Click to download (<https://github.com/MobileFirst-Platform-Developer-Center/Adapters>) the Adapters Maven project.

The Adapters Maven project includes the **JavaScriptSQL** adapter described above. Also included is an SQL script in the **Utils** folder.

## Sample usage

- Import the SQL script to a database.
- Make sure that the `mobilefirst@%` user has all access permissions assigned.
- Use either Maven or MobileFirst Developer CLI to build and deploy the JavaScriptSQL adapter (`../../creating-adapters/`).
- To test or debug an adapter, see the testing and debugging adapters (`../../testing-and-debugging-adapters`) tutorial.