

Managing Alerts

Overview

Alerts provide a proactive means to monitor the health of your mobile apps without having to check the MobileFirst Analytics Console regularly.

You can set reactive thresholds in the MobileFirst Analytics Console to trigger alerts when a specific criteria is met.

You can set thresholds at a broad level (a specific app) or at a granular level (a specific app instance or device). Alert notifications can be configured to display in the MobileFirst Analytics Console, and also be sent to a pre-configured REST endpoint or custom webhook.

Prerequisite: Ensure that the MobileFirst Analytics Server is started and ready to receive client logs.

Creating an alert

In the MobileFirst Analytics Console, click the **Alert Management** tab → **Create Alert**

Provide the following values: Alert Name, Message, Query Frequency, Event Type, Application Name, Application Version, Threshold Type and Operator.




Distribution Method tab

The alert is displayed in the Analytics Console. Additionally you can send a POST message with a JSON payload to a customized URL by selecting the **Analytics Console and Network Post** option.

The following fields are available if you choose this option:

- *required.* Network POST URL
- *optional.* Headers
- *required.* Authentication Type

The screenshot shows the MobileFirst Analytics Console interface. The top navigation bar includes 'MobileFirst Analytics Console', a notification bell, a settings gear, and a user profile 'admin'. The left sidebar has 'Dashboard', 'Apps', and 'Infrastructure' options. The main content area is titled 'Alert Management' and includes tabs for 'Overview', 'Custom Charts', 'Alert Log', and 'Alert Management' (which is active). A 'Create Alert' button is in the top right. Below is a table with columns: Name, Event Type, Property, Enabled, and Actions. The table contains one row: 'My alert', 'Application Crashes', 'Closed By', 'Enabled' (checked), and Actions (edit, delete, and a document icon).

Name ▾	Event Type ▾	Property ▾	Enabled ▾	Actions
My alert	Application Crashes	Closed By	<input checked="" type="checkbox"/>	  

Custom Webhook

You can set up a distribution method for an alert. For example: define a custom web hook to which a payload is sent to when an alert threshold is triggered.

Example payload:

```
{
  "timestamp": 1442848504431,
  "condition": {"value":5.0,"operator":"GTE"},
  "value": "CRASH",
  "offenders": [
    { "XXX 1.0": 5.0 },
    { "XXX 2.0": 1.0 }
  ],
  "property":"closedBy",
  "eventType":"MfpAppSession",
  "title":" Crash Count Alert for Application ABC",
  "message": "The crash count for a application ABC exceeded XYZ.
  View the Crash Summary table in the Crashes tab in the Apps
  section of the MobileFirst Analytics Console
  to see a detailed stacktrace of this crash instance."
}
```

The POST request includes the following attributes:

- **timestamp** - the time at which the alert notification was created.
- **condition** - the threshold that was set by the user (for example, greater than or equals 5).
- **eventType** - the eventType that was queried.
- **property** - the property of the eventType that was queried.
- **value** - the value of the property that was queried.
- **offenders** - a list of apps or devices that triggered the alert.
- **title** - the user-defined title.
- **message** - the user-defined message.

Viewing alert details

Alert details can be viewed from the **Alert Log** tab in the MobileFirst Operational Analytics console.

MobileFirst Analytics Console

Operations Console

1

admin

Dashboard

Apps

Infrastructure

Overview

Custom Charts

Alert Log

Alert Management

Alert Log

Refresh

Count	Date	Alert Name	Event Type	<input type="checkbox"/>
<div><div>+</div><div>1</div></div>	Jul 17, 2016	Network transaction spotted	Network Transactions	<input type="checkbox"/>

Dashboard

Apps

Infrastructure

Refresh



	Count	Date	Alert Name	Event Type	
	1	Jul 17, 2016	Network transaction spotted	Network Transactions	<input type="checkbox"/>

Alert Definition

Network transaction spotted

Event Type: Network Transactions

Query Frequency: 1 Minute

Type: All Adapter Requests

Property: Round Trip Time

Threshold Type: Average

Threshold: is greater than or equal to 0

Created 7/17/2016

Edit Alert

Alert Instances

Time Triggered	Trigger	Measured Value
Jul 17, 4:31 PM	http://9.148.225.87:9080/mfp/api/adapters/ResourceAdapter/transfer	0