

# Cordova end-to-end demonstration

## Overview

The purpose of this demonstration is to experience an end-to-end flow where an application & an adapter are created from the MobileFirst Operations Console, and application makes a resource request call using the MobileFirst Adapter to verify connectivity with the MobileFirst Server.

### Prerequisites:

- Configured Xcode for iOS, Android Studio for Android or Visual Studio 2013/2015 for Windows 8/10
- MobileFirst developer CLI (download  
(file:///home/travis/build/MFPSamples/DevCenter/\_site/downloads))
- *Optional* Stand-alone MobileFirst Server (download  
(file:///home/travis/build/MFPSamples/DevCenter/\_site/downloads))

## 1. Starting the MobileFirst Server

If a remote server was already set-up, skip this step.

From a **Command-line** window, navigate to the server's **scripts** folder and run the command: `./start.sh` in Mac and Linux or `start.cmd` in Windows.

## 2. Creating an application

In a browser window, open the MobileFirst Operations Console by loading the URL: `http://your-server-host:server-port/mfpconsole`. If running locally, use: `http://localhost:9080/mfpconsole` (`http://localhost:9080/mfpconsole`). The username/password are *admin/admin*.

1. Click on the "Create new" button next to **Applications** and select the desired *platform*, *identifier* and *version* values.



2. Click on the **Get Starter Code** tile and select to download the Cordova Starter Code.



### 3. Editing application logic

1. Open the Cordova project in your code editor of choice.
2. Select the `/config.xml` file and edit the `<mfp:server ... url=" " />` value with the IP address of the MobileFirst Server.
3. Select the `www/js/index.js` file and paste the following code snippet, replacing the existing `wlCommonInit()` function:

```
function wlCommonInit() {
    var resourceRequest = new WLResourceRequest(
        "/adapters/javaAdapter/users/world",
        WLResourceRequest.GET
    );

    resourceRequest.send().then(
        function(response) {
            // Will display "Hello world".
            alert("Success: " + response.responseText);
        },
        function(response) {
            alert ("Failure: " + response.errorMsg);
        }
    );
}
```

### 4. Creating an adapter

1. Click on the "Create new" button next to **Adapters** and download the **Java** adapter sample.

If Maven and the MobileFirst developer CLI are not installed, follow the on-screen **Setting up your environment** instructions to install.

The screenshot shows the 'MobileFirst Operations Console' interface. The left sidebar contains navigation links: Dashboard, Runtimes, mfp, Settings, Applications, Adapters, Devices, Client Logs, and Error Log. The main content area is titled 'Create a new Adapter' and includes a breadcrumb 'Home > mfp > Create a new Adapter'. It features a 'Deploy Adapter' button and a section titled 'Follow these steps to set up an adapter' with a 'Hide guide' link. The steps are: 1. Setting up your environment, 2. Start with a sample adapter (with sub-tabs for Console, CLI, and Maven), 3. In your IDE of choice, edit the adapter code - REST end points and adapter descriptor, 4. Build and package, and 5. Upload adapter. A console log snippet is visible under step 2.

The screenshot shows the 'MobileFirst Operations Console' interface for the 'Get Starter Code' page. The left sidebar is the same as the previous screenshot. The main content area has a breadcrumb 'Home > mfp > Get Starter Code' and a title 'Get Starter Code'. It includes tabs for 'Application' and 'Adapter'. Under 'Java Adapter Samples', there are buttons for 'Java' and 'Java-security check'. Under 'Javascript Adapter Samples', there are buttons for 'Javascript-SQL', 'Javascript-SAP', 'Javascript-JMS', and 'Javascript-HTTP'. A 'Next Step' section at the bottom features a diagram and a 'Go to Adapter Quickstart' button.

- From a **Command-line** window, navigate to the adapter's Maven project root folder and run the command:

```
mpfdev adapter build
```

- When the build finishes, run the command:

```
mpfdev adapter deploy
```

If using a remote MobileFirst Server, run the command:

```
mpfdev adapter deploy Replace-with-remote-server-name
```

## 5. Testing the application

1. From a **Command-line** window, navigate to the Cordova project root folder.
  2. Run the commands: `cordova prepare` followed by `cordova run`.
- If a device is connected, the application will be installed and launched in the device,
  - Otherwise the Simulator or Emulator will be used.

## Next steps

- Review the Client-side development tutorials ([../client-side-development/](#))
- Review the Server-side development tutorials ([../server-side-development/](#))
- Review the Authentication and security tutorials ([../authentication-and-security/](#))
- Review All Tutorials ([../all-tutorials](#))

