

Reports and analytics

fork and edit tutorial (<https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/>) | report issue (<https://github.com/MobileFirst-Platform-Developer-Center/DevCenter/issues/new>)

This tutorial covers the following topics:


- Introducing reports
- Comparison with IBM MobileFirst Platform Operational Analytics
- Introducing device reports
- Raw data
- Device usage reports

Introducing reports

IBM MobileFirst Platform Foundation provides an extensible mechanism for enterprises to use their own reporting tools to integrate with the IBM MobileFirst Platform and use the analytics data that is captured by the platform.

The figure to the right gives a high-level overview of the reports architecture.

Comparison with IBM MobileFirst Platform Operational Analytics



- IBM MobileFirst Platform Operational Analytics provides the capability to search for specific terms in

your mobile infrastructure, including MobileFirst Server logs and client-generated analytic data.

- The BIRT reports tool is deprecated in MobileFirst Platform 7.0. The recommended approach is to use the Operational Analytics console instead.
- You do not have to configure or administer a database for the specific purpose of managing accumulated analytics data in MobileFirst Operational Analytics.

Introducing device reports

Two reporting mechanisms are provided:


- **Raw data** - IBM MobileFirst Platform emits raw data that enables an OLAP system to extract the required information and present it through corporate reporting mechanisms.
- **Device usage** - Device Usage reports are default aggregations that are based on raw data and are provided for the benefit of organizations that do not have OLAP systems or choose not to integrate IBM MobileFirst Platform with an OLAP system.

To enable raw data collection, edit the `worklight.properties` file:

1. Uncomment the `reports.exportRawData` property and set its value to `true`.
2. Modify the `wl.reports.db` properties to contain your database settings.

Raw data

With raw data reports, you create collections of analytics information about the usage of your applications and adapters, such as: activity type, device info, or app version.



For more information about how to enable raw data reports, see the IBM MobileFirst Platform user documentation.

Device usage reports

To allow simpler and faster access to reports data, MobileFirst Server runs an analytics data processor task with a default 24-hour interval.

This task retrieves the raw entries for the specified time interval from the `app_activity_report` table, processes them, and fills the `fact_activities` table.

For more information about how to enable device usage reports, see the IBM MobileFirst Platform user documentation.

