

# iOS end-to-end demonstration

fork and edit tutorial (<https://github.ibm.com/MFPSamples/DevCenter/tree/master/tutorials/en/foundation/8.0/quick-start/ios/index.md>) | report issue (<https://github.ibm.com/MFPSamples/DevCenter/issues/new>)

## Overview

The purpose of this demonstration is to experience an end-to-end flow where an application and an adapter are registered using the MobileFirst Operations Console, an "skeleton" Xcode project is downloaded and edited to call the adapter, and the result is printed to the log - verifying a successful connection with the MobileFirst Server.

### Prerequisites:

- Xcode
- MobileFirst Developer CLI (download ([file:///home/travis/build/MFPSamples/DevCenter/\\_site/downloads](file:///home/travis/build/MFPSamples/DevCenter/_site/downloads)))
- *Optional.* Stand-alone MobileFirst Server (download ([file:///home/travis/build/MFPSamples/DevCenter/\\_site/downloads](file:///home/travis/build/MFPSamples/DevCenter/_site/downloads)))

## 1. Starting the MobileFirst Server

If a remote server was already set-up, skip this step.

From a **Command-line** window, navigate to the server's folder and run the command: `./run.sh`.

## 2. Creating an application

In a browser window, open the MobileFirst Operations Console by loading the URL: `http://your-server-host:server-port/mfpconsole`. If running locally, use: `http://localhost:9080/mfpconsole` (`http://localhost:9080/mfpconsole`). The username/password are `admin/admin`.

1. Click on the "New" button next to **Applications** and select the desired *platform*, *identifier* and *version* values.

The screenshot shows the MobileFirst Operations Console interface. On the left is a sidebar with navigation links: Dashboard, Runtimes, Applications (with a 'New' button), Adapters (with a 'New' button), Settings, Devices, and Error Log. The main content area is titled 'Register an Application' and contains the following fields: 'Application Name' (text input), 'Optional display name of the Application' (text input), 'Choose Platform' (radio buttons for Android, iOS (selected), and Windows), 'Bundle ID' (text input with a red asterisk, labeled 'Application Identifier; case sensitive'), and 'Version' (text input with a red asterisk, labeled 'Application Version'). At the bottom of the form is a blue 'Register application' button. The top of the console shows the title 'MobileFirst Operations Console', a user profile 'Hello, admin', and an 'Analytics Console' link.

2. Click on the **Get Starter Code** tile and select to download the iOS Starter Code.



### 3. Editing application logic

1. Open the Xcode project project by double-clicking the **.xcworkspace** file.
2. Select the **[project-root]/ViewController.m/swift** file and paste the following code snippet, replacing the existing `viewDidLoad()` function:

In Objective-C:

```
- (void)viewDidLoad {
    [super viewDidLoad];

    NSURL* url = [NSURL URLWithString:@"~/adapters/javaAdapter/users/world"];
    WLResourceRequest* request = [WLResourceRequest requestWithURL:url method:WLHttpMethodGet];

    [request sendWithCompletionHandler:^(WLResponse *response, NSError *error) {
        if (error != nil){
            NSLog(@"Failure: %@",error.description);
        }
        else if (response != nil){
            // Will print "Hello world" in the Xcode Console.
            NSLog(@"Success: %@",response.responseText);
        }
    }];
}
```

In Swift:

```
override func viewDidLoad() {
    super.viewDidLoad()

    let url = NSURL(string: "~/adapters/javaAdapter/users/world")
    let request = WLResourceRequest(URL: url, method: WLHttpMethodGet)

    request.sendWithCompletionHandler { (WLResponse response, NSError error) -> Void in
        if (error != nil){
            NSLog("Failure: " + error.description)
        }
        else if (response != nil){
            NSLog("Success: " + response.responseText)
        }
    }
}
```

### 4. Creating an adapter

1. Click on the "New" button next to **Adapters**
  - Select the **Actions** → **Download sample** option. Download the **Java** adapter sample.

- From a **Command-line** window, navigate to the adapter's Maven project root folder and run the command:

- When the build finishes, deploy it from the MobileFirst Operations Console using the **Actions** → **Deploy adapter** action. The adapter can be found in the **[adapter]/target** folder.
- Alternatively, download this prepared .adapter artifact and deploy it from the MobileFirst Operations Console using the **Actions** → **Deploy adapter** action.

## 5. Testing the application

- The adapter response is then printed in the Xcode Console.

```
Date = "Tue, 19 Jan 2016 06:14:40 GMT";
"Transfer-Encoding" = Identity;
"X-Powered-By" = "Servlet/3.1.1";
}

Response Data:
{"access_token": "eyJhbGciOiJSUzI1NiIsImtpZCI6YmVGeWljOjVFQ8f0isIn4ioJBTTEBZD2dQRkRnktgtdWMN3I4cUNMZEUtMkoya2s0NXpnNmREZF9xczhndmdSZ2xmPvcRvtYjRfmNoQT0dHOENWNUNLNDQF7XD3jd12MNDEwdWIJwms2AhhvVmVG0lTYU9LSXFvZSlsSkEwdvpIdz  
JyShGNVjNWxVkSI2SVGVldzJo99ZCtFOLWLRSztBznolzLnZWLFZvdHrU893QKjsMuVocUL3VKR3T2LLZJKUTdsMEVCYCbaZmtOkkstFSU8Bo1paSLuckSMelJAoElTHZMDLOTDVB63NMVTKECNXXZLq8twadJCxGLTBJTNjFuRhGIN2dmRW95BURUVeFKUlQ9wmLuSSoS8ZNJHW  
YZVVWVqZQ3JOVLVLS9nj2TVpekbekOpDUccZhZHJHUduKSRMLWDovJHNrvTKNEcdTh8bQMWHu4ia1wa3rsjoiUHEIziawja1kiyoJZvZ2mDuKuWakiOTTLlngh8MBDZITksZQHMTZEGRNLGHUBGT03in19_eyp3c3k0IAJjbZ8wbMdzImncISinnYil16tmm  
SEntakYjRLdHMkylSi5FIzGIZtmhv5SpvmdubuzZiwiJ2xviioQUdNZGShjqpCYALCjiZY29zc3IEti39_r96Ad4UhuyQ5FY_67CX7d3XP7NP_psgmLVmkcuIJ_Y_BxidecditJqgnKm8idB3KL8BFHNFdy03vb_wqb9sqIoqymPaIXZ  
ITrcxyVWQno30YmlVj1eqseLMkdCuiprnFalIPbj20h=LR48ZXPE4B6KqdYMGDS1Q6TsdJCglCPzOsnnQg+3pgvCUkv5X3QG0ZfyabbbKFNS_6VEAME4Y8rJD8m1VcfTSZgb3sbdb2E4Z1LDW6KiuxYTynGDh6JKQKKXkjYmj30LiDNdcZ_u_  
_4vkypjr7mXLrx6zxHG84gyBM8YG2Ba7jFPnLKdd3g","token_type": "Bearer", "expires_in": 3599, "scope": ""};
Status code=200
2016-01-19 08:14:40 .410 MyApplication[93738:36590517] +[OCLogger printMessage:withMetadata:andLevelTag:andPackage:] [Line 1005] [DEBUG] [WL_AFHTTPSessionManagerWrapper_PACKAGE] --[WLAFHTTPSessionManagerWrapper start]  
in WLAFHTTPSessionManagerWrapper.m:372 : Starting the request with URL http://:9808/mfp/api/adapters/javaAdapter/users/world  
2016-01-19 08:14:40 .440 MyApplication[93738:36590517] +[OCLogger printMessage:withMetadata:andLevelTag:andPackage:] [Line 1005] [DEBUG] [WL_AFHTTPSessionManagerWrapper_PACKAGE] --[WLAFHTTPSessionManagerWrapper  
requestFinished:responseObject:] in WLAFHTTPSessionManagerWrapper.m:388 : Request Success  
2016-01-19 08:14:40 .448 MyApplication[93738:36590517] +[OCLogger printMessage:withMetadata:andLevelTag:andPackage:] [Line 1005] [DEBUG] [WL_AFHTTPSessionManagerWrapper_PACKAGE] --[WLAFHTTPSessionManagerWrapper  
requestFinished:responseObject:] in WLAFHTTPSessionManagerWrapper.m:391 : Response Status Code 200  
2016-01-19 08:14:40 .448 MyApplication[93738:36590517] -[WLAFHTTPSessionManagerWrapper requestFinished:responseObject:] [Line 393] Response Content : Hello world  
2016-01-19 08:14:40 .441 MyApplication[93738:36590517] Adapter invocation response: Hello world
```

All Output ↕

**Note:** Xcode 7 enables Application Transport Security (ATS)

([https://developer.apple.com/library/ios/releasenotes/General/WhatsNewIniOS/Articles/iOS9.html#//apple\\_ref/doc/uid/TP40016198-SW14](https://developer.apple.com/library/ios/releasenotes/General/WhatsNewIniOS/Articles/iOS9.html#//apple_ref/doc/uid/TP40016198-SW14)) by default.

To complete the tutorial, disable ATS (<http://iosdevtips.co/post/121756573323/ios-9-xcode-7-http-connect-server-error>).

1. In Xcode, right-click the **[project]/info.plist** file → **Open As** → **Source Code**
2. Paste the following:

```
<key>NSAppTransportSecurity</key>
<dict>
  <key>NSAllowsArbitraryLoads</key>
  <true/>
</dict>
```

3. Press the **Play** button.

## Next steps

Learn more on using adapters in applications, and how to integrate additional services such as Push Notifications, using the MobileFirst security framework and more:

- Review the Server-side development tutorials ([../adapters/](#))
- Review the Authentication and security tutorials ([../authentication-and-security/](#))
- Review the Notifications tutorials ([../notifications/](#))
- Review All Tutorials ([../all-tutorials](#))