





Quantity	Comment	LibRef	Designator	Description	Footprint	Layer
1 100		RES_ACUR T	R105	Resistance	RESC1608X06N	Bottom
1 1uF		100F[/I][J]060 3[/\][J]1	C63	Capacitor	RESC1608X06L	Bottom
1 6.2		RES	R38	120	RESC1608X06L	Bottom
1 815-ABLS-8-B2		HC49/4H_3 MX	Y1	Surface Mount Quartz Crystal 8Mhz	HC49/4H_SMX	Bottom
1 AP7331-33WG-7		AP7331	U26	300mA, Low Quiescent Current, Fast Transient LDO	SOT95P285X100-5N	Bottom
1 MCP6L04T-E/ST		MCP6L04T- E/ST	U4	1 MHz, 85 µA Quad Op Amp, 14-Pin TSSOP, Extended Temperature Range, Tape and Reel	TSSOP-ST14_N	Bottom
12 4.7K		4.7K[/I][J]06 03[/\][J]1	R1, R2, R57, R59, R61, R63, R64, R65, R111, R112, R113, R114	Resistor	RESC1608X06L	Bottom
15 100nF		100nF[/I][J]06 603[/\][J]1	C5, C7, C8, C9, C14, C22, C25, C26, C28, C30, C55, C68, C69, C70, C71	Capacitor	RESC1608X06L	Bottom
18 BC817-40		BC817-40	Q1, Q2, Q3, Q4, Q7, Q12, Q19, Q20, Q21, Q22, Q23, Q24, Q25, Q26, Q27, Q28, Q29, Q30	NPN General-purpose Transistor	SOT23_N	Bottom
2 18pF		100pF[/I][J]06 03[/\][J]3	C41, C42		RESC1608X06L	Bottom
2 2.7K		RES	R4, R6	Resistor	RESC1608X06L	Bottom
2 4.7uF		4.70F[/I][J]06 603[/\][J]1	C40, C43	Capacitor	RESC1608X06L	Bottom
2 BT5050RGBCT-180		LED RGB SMD 2	D2, D6	\$0.027/ 2000k	LED5MD5	Bottom
2 ITR9909		ITR9909	U2, U3	Everlight Opto Interrupter	ITR9909_LONG	Bottom
2 WP7104SRC/D		LED	D19, D20	Red led 2V@20ma 57mcd	Led_TH_3mm_20mm	Bottom
3 10uF		4.70F[/I][J]06 603[/\][J]1, 10uF[/I][J]06 03[/\][J]1	C51, C52, C72	Capacitor	RESC1608X06L	Bottom
3 MC74HC595ADTR2		MC74HC59 5ADTR2	U13, U15, U17	8-Bit Serial-Input/Serial or Parallel Output Shift Register with Latched 3-State Outputs	948F-01_N	Bottom
4 1.5K		RES	R17, R18, R19, R20	120	RESC1608X06L	Bottom
4 1K		RES	R21, R22, R23, R24	120	RESC1608X06L	Bottom
4 22K		RES	R7, R8, R9, R10	120	RESC1608X06L	Bottom
4 DMG1012T		DMG1012T	T5, T6, T7, T8	Transistor MOSFET 1.5V N, Pining : 1=G, 2=S, 3=D	SOT50P160X80-3N	Bottom
4 DMG1013T		DMG1013T	T1, T2, T3, T4	Transistor MOSFET 1.5V P Pining : 1=G, 2=S, 3=D	SOT50P160X80-3N	Bottom
6 100K		100K[/I][J]06 03[/\][J]1	R119, R120, R121, R122, R123, R124	Resistor	RESC1608X06L	Bottom
6 56		68K[/I][J]060 3[/\][J]1	R74, R75, R76, R77, R90, R91	Resistor	RESC1608X06L	Bottom
7 4.7nF		CAP-NP	C15, C16, C17, C18, C19, C20, C21	Capacitor	CAPC1608N	Bottom
8 10K		10K[/I][J]060 3[/\][J]2, RES	R27, R28, R29, R30, R31, R50, R51, R136	120, Resistor	RESC1608X06L	Bottom
8 2.2K		2.2K[/I][J]06 03[/\][J]1, RES	R12, R13, R14, R15, R16, R33, R44, R45	120, Resistor	RESC1608X06L	Bottom
8 33		RES	R3, R5, R68, R69, R70, R71, R72, R73	120, Resistor	RESC1608X06L	Bottom
8 39		68K[/I][J]060 3[/\][J]1	R82, R83, R84, R85, R95, R96, R97, R133	Resistor	RESC1608X06L	Bottom
9 27-21SURC/SS30-A3		LED	D9, D10, D11, D12, D17, D18, D25, D26, D35	SMD Red led right angle mount 2V @20ma 57mcd	27-21 Everlight	Bottom
1 1.5nF		100pF[/I][J]06 03[/\][J]1	C57	Capacitor	RESC1608X06L	Top
1 100		RES_ACUR T	R106	Resistance	RESC1608X06N	Top
1 10uF X5R		100F[/I][J]06 03[/\][J]1	C34	Capacitor	RESC1608X06L	Top
1 270K		270K[/I][J]06 03[/\][J]2	R140	Resistor	RESC1608X06L	Top
1 47K		22K[/I][J]060 3[/\][J]1	R132	Resistor	RESC1608X06L	Top
1 51pF		100pF[/I][J]06 03[/\][J]1	C64	Capacitor	RESC1608X06L	Top
1 6.8K		10K[/I][J]060 3[/\][J]1	R127	Resistor	RESC1608X06L	Top
1 680K		470K[/I][J]06 03[/\][J]1	R125	Resistor	RESC1608X06L	Top
1 820		22K[/I][J]060 3[/\][J]1	R131	Resistor	RESC1608X06L	Top
1 Alstron R3190005-021-R		USB_MINIA B	X3	USB connector Micro B	Astron 3190005-x21-r	Top
1 Battery		Battery	BT1	Multicell Battery	BAT-2	Top
1 Con1x6		Con1x6	X2	1 x 6 pins connector	MHDR1X6	Top
1 FAN3988		FAN3988	U23	User Charger and Over voltage Detection Device	MLP 1.45x1mm	Top
1 IRM-3636T		TSOP32236	U20	IR Receiver Module (36 kHz) for Remote Control Systems	IR-receiver	Top
1 LM4819M		LM4819M	U25	350mW Audio Power Amplifier with Shutdown Mode	M08A_N	Top
1 MCP6L04T-E/ST		MCP6L04T- E/ST	U5	1 MHz, 85 µA Quad Op Amp, 14-Pin TSSOP, Extended Temperature Range, Tape and Reel	TSSOP-ST14_N	Top
1 MCP73871-2AAI/ML		MCP73871- 2AAI/ML	U21	Stand-Alone System Load Sharing and Li-Ion/ Li-Polymer Battery Charge Management Controller, 4.2V, 20-Pin QFN, Industrial Temperature	QFN-ML20_N	Top

1	MCP6L04T-E/ST	Microcontroller E/ST	U5			Standard-Axine system Load Sharing and Li-Ion/ Li-Polymer Battery Charge Management Controller, 4.2V, 20-Pin QFN, Industrial Temperature	QFN-ST14_N	Top
1	MCP73871-2AAI/ML	MCP73871- 2AAI/ML	U21				QFN-ML20_N	Top
1	MicroSD-Astron 5190008-XA4-R	SD Card- Micro- ASL-TRON 5190008- XA4-R	S1			MicroSD Card connector 5190008-XA4-R	Astron 5190008-XA4-R	Top
1	MMA7660FC	MMA7660F C	U1			MMA7660FC: XYZ-AXIS ACCELEROMETER ±1.5 g	DFN50P300X300X100-12N	Top
1	NCP15XH103F03RC	Res Thermal	RT1			Thermistors - NTC 10K OHM 1% 0402	RESC1005X04L	Top
1	PIC24FJ128GB106-I/PT	PIC24FJ128 GB106-I/PT	U19			General Purpose 16-Bit Flash Microcontroller with USB On- The-Go, 128KB Flash, 16KB SRAM, 64-Pin TQFP, Industrial Temperature	TQFP-PT64_N	Top
1	Speaker	Speaker	LS1			Loudspeaker	PIN2	Top
1	SW-PB	SW-PB	S2			Switch	FSMRA2JH	Top
1	TD4015BPN	Micro1	MC1			Omnidirectional Back Electret Condenser Microphone	MICRO_PANASONIC_WM- 64PN	Top
10	4.7K	4.7K[[\]]06 03[[\]]1	R67, R92, R93, R94, R103, R104, R142, R144, R145, R146			Resistor	RESC1608X06L	Top
2	180	180K[[\]]06 03[[\]]1	R107, R137			Resistor	RESC1608X06L	Top
2	1nF	100nF[[\]]0 603[[\]]1	C53, C54			Capacitor	RESC1608X06L	Top
2	1uF	10uF[[\]]060 3[[\]]1, 4.7uF[[\]]0 603[[\]]1	C56, C61			Capacitor	RESC1608X06L	Top
2	5.6K	2.2K[[\]]06 03[[\]]1	R115, R116			Resistor	RESC1608X06L	Top
2	BAT54S	BAT54S	D33, D34			Schottky Barrier Double Diode	SOT23_N	Top
2	BT5050RGBC-T180	LED RGB SMD 2	D27, D38			\$0.027/ 2000k	LEDSDMS	Top
2	MC74HC595ADTR2	MC74HC59 5ADTR2	U14, U16			8-Bit Serial Input/Serial or Parallel Output Shift Register with Latched 3-State Outputs	948F-01_N	Top
2	Motor	Motor	B1, B2			Motor, General Kind	RB5-10.5	Top
21	100nF	100nF[[\]]0 603[[\]]1	C1, C3, C6, C10, C11, C12, C13, C23, C24, C27, C29, C33, C35, C36, C37, C38, C39, C62, C65, C66, C67			Capacitor	RESC1608X06L	Top
28	BC817-40	BC817-40	Q5, Q6, Q8, Q9, Q10, Q11, Q13, Q14, Q15, Q16, Q17, Q18, Q31, Q32, Q33, Q34, Q35, Q36, Q37, Q38, Q39, Q40, Q41, Q42, Q43, Q44, Q45, Q46			NPN General-purpose Transistor	SOT23_N	Top
3	1.5K	RES	R26, R46, R47			120	RESC1608X06L	Top
3	27-21/ BHC-AN1P2/ 3C	LED	D8, D31, D37			SMD Blue led right angle mount 3.3V @ 20ma 28mcd	27-21 Everlight Blue	Top
3	27-21/SURC/ S530-A3	LED	D7, D32, D36			SMD Red led right angle mount 2V @ 20ma 57mcd	27-21 Everlight	Top
3	47nF	10nF[[\]]06 03[[\]]1, 470nF[[\]]0 603[[\]]1	C58, C59, C60			Capacitor	RESC1608X06L	Top
3	AP7331-33WG-7	AP7331	U18, U22, U24			300ma, Low Quiescent Current, Fast Transient LDO	SOT95P285X100-5N	Top
3	APTD1608CGCK	LED	D28, D29, D30			LED standard - CMS Helios SMD Green 570nm 230mcd	DIOC1608X08N	Top
4	100K	100K[[\]]060 3[[\]]1, 100K[[\]]06 03[[\]]1	R138, R139, R141, R143			Resistor	RESC1608X06L	Top
4	10uF	4.7uF[[\]]06 603[[\]]1, 10uF[[\]]06 03[[\]]1	C2, C4, C32, C46			Capacitor	RESC1608X06L	Top
4	19-21/SURC/ S530- A3/ TR8	LED	D1, D3, D4, D5			SMD Red 0603 2V @ 20ma 58 mcd	DIOC1608X08N	Top
4	1K	1K[[\]]0603 [[\]]1, RES	R25, R48, R49, R108			120, Resistor	RESC1608X06L	Top
4	22K	22K[[\]]060 3[[\]]1, RES	R11, R42, R43, R130			120, Resistor	RESC1608X06L	Top
6	39	68K[[\]]060 3[[\]]1	R66, R86, R87, R88, R89, R134			Resistor	RESC1608X06L	Top
6	5.2	RES	R36, R37, R39, R40, R54, R55			120	RESC1608X06L	Top
7	2.2K	2.2K[[\]]06 03[[\]]1	R32, R34, R35, R41, R52, R53, R126			Resistor	RESC1608X06L	Top
7	4.7uF	4.7uF[[\]]06 603[[\]]1	C31, C44, C45, C47, C48, C49, C50			Capacitor	RESC1608X06L	Top
7	1TR9909	1TR9909	U6, U7, U8, U9, U10, U11, U12			Everlight Opto Interrupter	1TR9909_EDGE	Top
8	10K	8.2K[[\]]06 03[[\]]2, 10K[[\]]060 3[[\]]1, 10K[[\]]060 3[[\]]2	R101, R102, R109, R110, R117, R118, R128, R129			Resistor	RESC1608X06L	Top
8	33	68K[[\]]060 3[[\]]1, RES	R98, R99, R100, R135, R147, R148, R149, R150			120, Resistor	RESC1608X06L	Top
8	56	68K[[\]]060 3[[\]]1	R56, R58, R60, R62, R78, R79, R80, R81			Resistor	RESC1608X06L	Top
8	APTD1608SYCK	LED	D13, D14, D15, D16, D21, D22, D23, D24			LED standard - CMS Helios SMD	DIOC1608X08N	Top



