

F@ctory Express Product Catalogue

Oilkey Corporation — TEL +81-72-284-1711 / FAX +81-72-298-7790 / oilkey@oilkey.co.jp

Issued: 2026-07-08

The E-price is the unit price (JPY) for an order of one; discounted pricing applies to orders in units of ten. Prices and lead times are subject to change without notice.

01 Greases — 32 products

Product	Features	Service temp. (°C)*1 Drop point	NLGI grade*2 Colour Composition	DN value dm × n	Base oil viscosity @40°C (mm²/s)	Weld load (N) / wear scar (mm)	Sizes*4	E-price*5	Dispatch*6
OKS 400 MoS2 Multi-Purpose High-Performance Grease	MoS2-fortified grease that keeps protecting even if the oil film fails. Allows extended relubrication intervals.	-30 to +130 drop pt. +195	2 black lithium soap / mineral oil	350,000	100	3,600 1.9	100g 400ml 1kg	900 3,500 6,600	On request On request 80ml
OKS 402 Ball Bearing High-Performance Grease	General-purpose bearing grease. Usable in a wide range of applications, allowing plants to standardise on one grease.	-30 to +120 drop pt. +195	2 light brown lithium soap / mineral oil	400,000	100	2,000 1.9	400ml 1kg	3,020 6,800	On request
OKS 403 Marine Grease German Army TL 9150-0066 NATO spec. G-460	Water-resistant grease with outstanding underwater rust protection. Proven in humid plants and in coastal and offshore locations exposed to seawater.	-25 to +80 drop pt. +115	1-2 light brown special calcium soap / mineral oil	350,000	100	5,200 1.2	1kg 400ml	9,500 5,850	On request 400ml
OKS 404 High-Performance High-Temp Grease	New-generation semi-synthetic grease for long-term lubrication of medium-speed, medium-load bearings. Heat resistant.	-30 to +150 drop pt. >+260	2 light brown lithium complex soap / mineral oil / polyalphaolefin	350,000	100	2,800 0.8	1kg	8,400	On request
OKS 410 MoS2 High-Pressure Long-Life Grease Mox-Active*3	Outstanding adhesion, impact-load capacity, and wear resistance from the synergy of multiple additives. Ideal for construction machinery subject to repeated impact loads.	-20 to +120 drop pt. +190	2 black MoS2 / lithium soap / mineral oil	250,000	185	4,200 0.4	400ml 1kg	4,700 9,200	On request 400ml
OKS 4100 MoS2 Extreme-Pressure Grease	For low speeds, high loads, and impact loads. Extreme-pressure grease with added corrosion protection. The high-viscosity base oil keeps it in place under impact.	-20 to +120 drop pt. +185	2 dark grey MoS2 / lithium-calcium soap	50,000	1,020	4,800 1.0 @1,000 N	400ml	6,600	On request
OKS 416 Low-Temp & High-Speed Grease	For high-speed rotation; also usable at polar low temperatures. For conveyors, cold stores, spindle bearings, machine tools, and control equipment.	-55 to +120 drop pt. +195	2 light brown lithium soap / ester	1,000,000	15	3,000 0.4	1kg	20,900	On request
OKS 418 High-Temp Grease	No-drop-point grease that does not drip even at high temperature. Fewer regreasing cycles cut maintenance costs. Ideal for drying ovens, mixers, hot-air blowers, and rubber production.	-20 to +150 no drop pt.	2 black MoS2 / inorganic thickener / mineral oil	200,000	220	1,700 0.7	1kg	12,200	On request
OKS 420 High-Temp Multi-Purpose Grease Mox-Active	High load capacity, shock absorption, adhesion, and sealing. Reduces noise. Also usable on slow, heavily loaded open gears.	-10 to +160 drop pt. +240	1-2 light brown organic thickener / mineral oil	300,000	460	3,200 0.3	1kg	15,300	On request

Product	Features	Service temp. (°C)*1 Drop point	NLGI grade*2 Colour Composition	DN value dm × n	Base oil viscosity @40°C (mm²/s)	Weld load (N) / wear scar (mm)	Sizes*4	E-price*5	Dispatch*6
OKS 422 Universal Long-Life Grease	High-performance grease for versatility, long life, high loads, high temperature, high speed, and water exposure. A synthetic grease that meets every requirement to a high standard.	-40 to +180 drop pt. +230	2 light brown barium complex soap / polyalphaolefin	800,000	50	4,000 0.6	400ml 1kg	13,800 33,600	On request
OKS 424 Synthetic High-Temp Grease	Synthetic heat- and impact-resistant grease, ideal where heat resistance and impact resistance are required at the same time.	-30 to +200 drop pt. +240	1-2 light brown organic thickener / polyalphaolefin	200,000	410	1,300 2.0	400g 1kg	12,700 26,700	On request 400ml
OKS 428 Fluid Grease for Gears	Long life, oxidation resistant. For high-speed, high-load gears. Semi-fluid, yet does not leak from unsealed vertical shafts.	-40 to +120 drop pt. +155	00 light brown lithium soap / polyglycol	600,000	120	2,000 0.6	1kg	7,800	On request
OKS 4200 Synthetic High-Temp Bearing Grease with MoS2 Mox-Active	Synthetic molybdenum grease for fans, autoclaves, drying ovens, metallurgical plants, and steelworks.	-10 to +180 no drop pt.	2 black MoS2 / inorganic thickener / polyalphaolefin	400,000	220	2,600 0.7	400ml	9,200	On request 400ml
OKS 4220 Extreme-Temp Bearing Grease NSF-H1*8	Long life. Extremely high temperatures. High loads. Chemical resistant. Top-performance grease, insoluble in everything except perfluorinated solvents. Fluorine-based (PTFE/Teflon*) grease that does not drip even when ambient temperature exceeds the service range. Used mainly in precision equipment such as cameras, copiers, and printers, in drying ovens, and in food machinery. PFPE (perfluoropolyether) base oil with PTFE (polytetrafluoroethylene) thickener. CH4 compatible. (An O2-compatible grease, OKS 4225, is available as a special order.)	-20 to +280 to +300 without oxygen no drop pt.	2 white PTFE / organic polymer / perfluoropolyether	300,000	500	9,000 0.6	40ml 500g 1kg	29,700 122,000 222,000	On request 40ml
OKS 432 High-Melting-Point Grease	Long life, oxidation resistant. Slightly firm synthetic grease.	-25 to +190 drop pt. +250	2-3 light brown aluminium complex soap / mineral oil	200,000	230	2,600 0.7	1kg	9,500	On request
OKS 450 Chain & Wire Rope Lubricant transparent synthetic Mox-Active	Synthetic high-performance lubricant with polyisobutylene. Wear resistant, rust protective, highly adhesive, penetrating. Transparent type that keeps machinery clean. Reduces noise. Lubrication and rust protection last at least two months.	-30 to +200 drop pt. N/A	N/A translucent light brown tackifier / polyisobutylene	N/A	300	2,400 0.4	1L	12,300	On request
OKS 451 Chain & Wire Rope Lubricant transparent synthetic Mox-Active spray can	Synthetic high-performance lubricant with polyisobutylene. Wear resistant, rust protective, highly adhesive, penetrating. Transparent type that keeps machinery clean. Reduces noise. Lubrication and rust protection last at least two months. OKS 450 filled into a spray can.	-30 to +200 drop pt. N/A	N/A translucent light brown tackifier / polyisobutylene	N/A	300	2,400 0.4	500ml	7,900	On request 400ml
OKS 469 Plastic & Elastomer Grease NSF-H1*8	Highly adhesive, colourless, transparent grease that does not attack plastics or elastomers. Suitable for cleanliness-critical areas and food machinery.	-25 to +150 no drop pt.	2 clear inorganic thickener / polyalphaolefin	N/A	400	N/A	1kg	13,900	On request

Product	Features	Service temp. (°C)*1 Drop point	NLGI grade*2 Colour Composition	DN value dm × n	Base oil viscosity @40°C (mm²/s)	Weld load (N) / wear scar (mm)	Sizes*4	E-price*5	Dispatch*6
OKS 470 White Universal High-Performance Grease	White grease that keeps lubrication points clean. Also for the textile, paper, and precision industries.	-30 to +120 drop pt. +195	2 white white solid lubricants / lithium soap / mineral oil	300,000	108	3,800 0.3	80ml 400ml 1kg	2,440 4,580 9,700	On request 80ml 400ml
OKS 471 White Universal High-Performance Grease spray can	Safe white grease that keeps lubrication points clean. Also for the textile, paper, and precision industries. OKS 470 filled into a spray can.	-30 to +120 drop pt. +195	2 light brown white solid lubricants / lithium soap / mineral oil	300,000	108	3,800 0.3	400ml	5,520	On request
OKS 475 High-Performance Grease	Synthetic grease for high speeds and low temperatures. Also usable in filling and packaging machinery. Contains fluoropolymer (PTFE/Teflon*).	-50 to +140 drop pt. +200	2 light brown PTFE / lithium soap / polyalphaolefin	1,000,000	35	1,700 1.7	1kg	21,900	On request
OKS 476 Multi-Purpose Grease food industry USDA-H1*8	All-round food-machinery grease with the widest range of uses in food processing, beverage filling, and pharmaceutical plants. Resists alkaline and acidic sterilising and cleaning agents.	-20 to +120 drop pt. +250	2 white aluminium complex soap / white oil	400,000	67	2,200 1.8	400ml 1kg 25kg	6,500 13,900 277,500	On request On request On request
OKS 477 Valve Grease NSF-H1*8	Tasteless, odourless valve grease. Resists sterilising and cleaning agents.	-10 to +160 no drop pt.	3 light brown inorganic thickener / polyalphaolefin	N/A	1,200	N/A	100g	5,340	On request 80ml
OKS 479 High-Temp Grease food industry NSF-H1*8	Heat resistant, with long life even at high temperature. Also for parts exposed to cold or hot water and for rubber and elastomer parts. Chemically resistant — withstands alkaline and acidic sterilising and cleaning agents.	-25 to +160 drop pt. +200	1 light brown aluminium complex soap / polyalphaolefin	350,000	400	2,200 0.7	400ml 1kg	10,260 21,400	On request On request
OKS 490 Open Gear Grease sprayable	For large, heavily loaded gears. Open-gear grease free of asphalt and solvents.	-25 to +180 drop pt. +250	0-00 black solid lubricants / aluminium complex soap / mineral oil	N/A	850	8,200 N/A	1kg	8,100	On request
OKS 491 Open Gear Spray dry type spray can	Highly adhesive, with penetration that reaches fine clearances. After the solvent evaporates it forms a dry film, so it stays tack-free and does not pick up dust or sand.	-30 to +150 drop pt. N/A	N/A black solid lubricants / natural & synthetic resins / mineral oil	N/A	N/A	N/A	500ml	7,410	On request 400ml
OKS 495 High-Adhesion Lubricant	For running in heavily loaded gears.	-25 to +180 drop pt. +250	2 black solid lubricants / aluminium complex soap / mineral oil	N/A	300	5,500 N/A	1kg	8,800	On request

Product	Features	Service temp. (°C)*1 Drop point	NLGI grade*2 Colour Composition	DN value dm × n	Base oil viscosity @40°C (mm²/s)	Weld load (N) / wear scar (mm)	Sizes*4	E-price*5	Dispatch*6
OKS 1110 Multi-Silicone Grease NSF-H1	Highly adhesive multi-purpose silicone grease that bonds well to virtually any material. Excellent sealing, lubricity, and load capacity. No drying, softening, or oil separation across a wide temperature range. Chemically resistant — withstands acetone, ethanol, ethylene, glycol, glycerine, and methanol. The only NLGI No. 3 silicone grease — the firmest available.	-40 to +200 no drop pt.	3 transparent inorganic thickener / polydi methylsiloxane	N/A	9,500	N/A	10ml 80ml 500g	1,120 8,950 37,000	On request On request On request
OKS 1133 Low-Temp Silicone Grease	Silicone grease for low temperatures. Also ideal for plastic-on-plastic and plastic-on-metal lubrication. Excellent oxidation resistance, low oil separation, low evaporation.	-70 to +160 drop pt. +215	2 light brown lithium soap / poly phenylmethylsilox ane	350,000	55	1,200 2.6	100g 500g	9,390 31,000	On request On request 80g
OKS 1140 Extreme-Temp Silicone Grease	The silicone grease with the highest service temperature, for high-temperature, low-speed rotation. Low evaporation even at high temperature.	-20 to +290 no drop pt.	2 black special carbon black / polyphenyl methylsiloxane	75,000	100	2,100 1.2	500g	30,200	On request
OKS 1144 Multi-Purpose Silicone Grease	Multi-purpose silicone grease for a wide temperature range. Also ideal for plastic-on-plastic and plastic-on-metal lubrication. Excellent oxidation resistance, low oil separation.	-40 to +200 drop pt. +205	2 light brown lithium soap / poly phenylmethylsilox ane	500,000	75	1,300 3.3	500g	33,000	On request
OKS 1155 Silicone Grease high adhesion	Highly adhesive silicone grease with excellent sealing at low speeds. Ideal for lubricating like or unlike materials — metal, plastic, elastomer. Low oil separation even at high temperature.	-60 to +180 drop pt. +210	2 light brown lithium soap / poly phenylmethylsilox ane / ester	N/A	60	N/A	500g	28,000	On request

*1 Service temperature — the temperature at which the product can be used under continuous conditions; the drop point is higher still, and short-term use up to the drop point is possible.

*2 NLGI grade (consistency) — centred on No. 2; higher numbers are firmer, lower numbers are softer.

*3 Mox-Active — a proprietary OKS additive combining organic molybdenum with several solid lubricants. It smooths the lubricated surface and reduces friction and wear.

*4 Sizes — 400 g items come as cylindrical cartridges (10 per box). A dedicated grease gun (sold separately) is required for use; see the Related Products section.

*5 E-price — the price for an order quantity of one (JPY). Discounted prices apply to orders in units of ten; please enquire using the fax quote request form.

*6 Dispatch — "On request": please contact us. Dispatch dates are updated according to stock.

*7 SOS express — items eligible for our emergency delivery service. Request SOS delivery when ordering; service-area restrictions apply. Contact us for details.

*8 USDA-H1/NSF-H1 — certified by public bodies as lubricants usable where incidental contact with food is possible.

*9 BIOlogic — the OKS range of biodegradable lubricants built on new technology.

02 Pastes — 16 products

Product	Features	Colour Composition	Service temp. (°C)*1	Press-fit test [μ]	Four-ball weld load [N]*2	Sizes	E-price*4	Dispatch*5	Remarks
OKS 200 MoS2 Assembly Paste universal standard Mox-Active*3 German Rail No. 07606	Double-molybdenum type combining MoS2 with organic molybdenum. Prevents seizure, wear, and stick-slip. For press-fitting parts, lubricating sliding surfaces, running-in, and preventing galling in press forming. Also used for pressing railway wheels onto axles. Resistant to water, oil, chemicals, and hydraulic fluids.	black MoS2 / organic molybdenum / other solid lubricants / synthetic oil	-35 to +450 (+630)	0.12	2,400	50g	3,460	On request	Tube *40ml
OKS 220 MoS2 Rapid Paste Mox-Active	Double-molybdenum type combining MoS2 with organic molybdenum. Fast acting — no rubbing-in required. The most versatile molybdenum paste. Prevents seizure, wear, and stick-slip under extreme pressure. For press-fitting parts, sliding surfaces, running-in, and preventing galling in press forming. Resistant to water, oil, chemicals, and hydraulic fluids.	black MoS2 / organic molybdenum / other solid lubricants / synthetic oil	-35 to +450 (+630)	0.05	4,200	50g	9,000	On request	Tube *250g
OKS 221 MoS2 Rapid Paste Mox-Active spray can	Double-molybdenum type combining MoS2 with organic molybdenum. Fast acting — no rubbing-in required. The most versatile molybdenum paste. Prevents seizure, wear, and stick-slip under extreme pressure. For press-fitting parts, sliding surfaces, running-in, and preventing galling in press forming. Resistant to water, oil, chemicals, and hydraulic fluids. OKS 220 filled into a spray can.	black MoS2 / organic molybdenum / other solid lubricants / synthetic oil	-35 to +450 (+630)	0.05	4,200	400ml	8,060	On request	
OKS 230 MoS2 High-Temp Paste	Lubricating paste that forms a dry lubricant film after the base oil evaporates at 180°C; particularly effective from +200 to +450°C. For bearings, sliding surfaces, chains, rollers, and other moving parts in metallurgical plants, hot-forming plants, and drying processes; for kilns, casting ladles, blowers, and other equipment above 200°C. Also ideal for furnace-trolley bearings. Synthetic-oil base, so it does not attack plastics or rubber. Resistant to water, oil, chemicals, and hydraulic fluids. Can be used together with OKS 310.	black MoS2 / synthetic oil	+450 (+630)	N/A	3,200	250g	11,600	On request	Tube
OKS 235 Aluminium Paste Anti-Seize	Heavy-metal-free aluminium paste for lubrication and separation. Prevents seizure of bolts on pipe flanges that run hot. Also used for sliding-surface lubrication in chemical and petrochemical plants, ships, offshore, power stations, glassworks, and foundries.	metallic silver aluminium powder / other solid lubricants / synthetic oil	-40 to +1100	N/A	N/A	250g	23,000	On request	With brush
OKS 240 Copper Paste Anti-Seize MIL-A-907E	Copper-based anti-seize paste usable up to 1,100°C. Ideal for protecting bolt threads exposed to high temperature around engines and exhaust pipes. Also used on bolts of gas- and oil-fired furnaces.	metallic brown copper powder / other solid lubricants / synthetic oil	+1100	N/A	2,800	8ml 75ml 1kg	1,700 4,600 26,000	On request On request On request	Tube Tube *8ml *75ml
OKS 241 Copper Paste Anti-Seize spray can	Copper-based anti-seize paste usable up to 1,100°C. Ideal for protecting bolt threads exposed to high temperature around exhausts and engines. Also used on bolts of gas- and oil-fired furnaces. OKS 240 filled into a spray can.	metallic brown copper powder / other solid lubricants / synthetic oil	+1100	N/A	2,800	400ml	9,550	On request	
OKS 245 Copper Paste high corrosion protection Mox-Active	Prevents thread corrosion and seizure even after long service. Highly adhesive; corrosion protective. Protects bolt threads exposed to heat and water around the engines and exhaust pipes of off-road motorcycles and vehicles.	brown copper powder / organic molybdenum / semi-synthetic oil	-30 to +1100	N/A	2,500	250g	4,800	On request	With brush *250ml

Product	Features	Colour Composition	Service temp. (°C)*1	Press-fit test [μ]	Four-ball weld load [N]*2	Sizes	E-price*4	Dispatch*5	Remarks
OKS 250 White Allround Paste metal-free Mox-Active NSF-H2	White multi-purpose heat-resistant paste for a wide temperature range. For low-speed, high-load lubrication; also ideal where subject to repeated vibration. Prevents seizure, corrosion, cold fretting, and stick-slip. Prevents seizure of both ferrous and non-ferrous threads; ideal for stainless bolts and for protecting mould and die bolt threads. Also used in refineries, steelworks, cement plants, shipping, offshore, and agricultural machinery. Metal-free formulation with the environment in mind. Corrosion protective; resists seawater, acids, and alkalis. Also suited to cleanliness-critical areas. Strong against vibration, corrosion, and heat, so ideal for preventing disc-brake squeal too. The one product that covers most emergencies on site.	white white solid lubricants / organic molybdenum / synthetic oil	-40 to +1400	0.08	4,000	8ml 80ml	2,030 4,700	On request On request	Tube Tube
OKS 2501 White Allround Paste metal-free Mox-Active spray can	White multi-purpose heat-resistant paste for a wide temperature range. For low-speed, high-load lubrication; also ideal where subject to repeated vibration. Prevents seizure, corrosion, cold fretting, and stick-slip. Prevents seizure of both ferrous and non-ferrous threads; ideal for stainless bolts and for protecting mould and die bolt threads. Also used in refineries, steelworks, cement plants, shipping, offshore, and agricultural machinery. Metal-free formulation with the environment in mind. Corrosion protective; resists seawater, acids, and alkalis. Also suited to cleanliness-critical areas. Strong against vibration, corrosion, and heat, so ideal for preventing disc-brake squeal too. OKS 250 filled into a spray can.	white white solid lubricants / organic molybdenum / synthetic oil	-40 to +1400	0.08	4,000	400ml	7,930	On request	
OKS 252 White High-Temp Paste food industry NSF-H1	High-temperature, highly adhesive paste for the food industry. For low-speed, high-load lubrication; also ideal where subject to repeated vibration. Prevents seizure, corrosion, cold fretting, and stick-slip on both ferrous and non-ferrous threads. Metal-free formulation with the environment in mind.	light grey white solid lubricants / polyglycol / silicate	-30 to +1200	0.12	2,500	250g 200g	8,400 7,500	On request On request	With brush
OKS 260 White Assembly Paste	White assembly paste that keeps machinery clean. For paper, packaging, plastic-moulding, textile, and printing machinery and office equipment. Lubrication under vibration or in high humidity. Also highly effective against fretting corrosion. Water resistant.	white white solid lubricants / lithium grease / white oil	-25 to +150	0.09	2,600	250g	7,400	On request	*250g
OKS 265 Chuck-Jaw Paste high adhesion	For lubricating machine-tool chucks. Ideal for lubrication under impact loads and vibration. High-tack formulation that is not washed off by water-soluble cutting fluids.	light brown white solid lubricants / tackifier / mineral oil	-25 to +150	0.10	3,600	1kg	15,800	On request	
OKS 270 White Grease Paste	For any machinery under high load where cleanliness and long-term lubrication are required. For precision, paper, textile, and packaging machinery.	white white solid lubricants / lithium grease / white oil	-25 to +125	0.14	5,000	250g	7,300	On request	1kg
OKS 2771 High-Load Lubricating Paste with PTFE spray can	Adhesive white paste with excellent plastic compatibility. For long-term lubrication of heavily loaded parts. Fluoropolymer (PTFE/Teflon*) fortified.	white PTFE / special ester / additives	-20 to +150	0.11	2,600	400ml	12,960	On request	
OKS 280 White High-Temp Paste	For hot forming of ferrous and non-ferrous metals: drop forging, hot drawing, hot rolling, hot bending. Small quantities separate and lubricate, extending tool life. Contains no graphite, which would carburise tools or workpieces.	white white solid lubricants / mineral oil	+1150	N/A	2,400	1kg	18,900	On request	

- *1 Service temperature — the temperature at which the product can be used under continuous conditions. Figures in parentheses apply when contact with air is restricted.
- *2 Weld load — higher values indicate greater load-carrying capacity.
- *3 Mox-Active — a proprietary OKS additive combining organic molybdenum with several solid lubricants. It smooths the lubricated surface and reduces friction and wear.
- *4 E-price — the price for an order quantity of one (JPY). Discounted prices apply to orders in units of ten; please enquire using the fax quote request form.
- *5 Dispatch — "On request": please contact us. Dispatch dates are updated according to stock.
- *6 SOS express — items eligible for our emergency delivery service. Request SOS delivery when ordering; service-area restrictions apply. Contact us for details.

03 Dry Lubricants — 13 products

Product	Features	Service temp. (°C)*1	Flash point (°C)	Sizes	E-price*2	Dispatch*3	Remarks
OKS 100 MoS2 Powder high purity	Reduces friction and wear over a wide temperature range. Can also be blended into plastics, joints, and seal materials.	-185 to +450	N/A	1kg	35,800	On request	
OKS 110 MoS2 Powder micro-size	Reduces friction and wear over a wide temperature range. Particularly suited to lubricating precision-finished surfaces.	-185 to +450	N/A	1kg	46,500	On request	
OKS 510 MoS2 Bonded Coating fast-drying	Usable over a wider temperature range than OKS 500. Vacuum compatible. Dries at room temperature. Can be recoated.	-180 to +450	-30			Transferred	
OKS 511 MoS2 Bonded Coating fast-drying spray can	Usable over a wider temperature range than OKS 500. Vacuum compatible. Dries at room temperature. Can be recoated. OKS 510 filled into a spray can.	-180 to +450	-30			Transferred	
OKS 530 MoS2 Bonded Coating water-based air-drying	For low speed, high load, and intermittent operation. Film thickness adjustable by dilution with water.	-35 to +450	+37			Transferred	
OKS 536 Graphite Bonded Coating water-based air-drying	For high temperature and extreme pressure. Graphite dry film; water-dilutable.	-35 to +600	N/A	5kg	72,000	On request	
OKS 570 PTFE Bonded Coating	Colourless PTFE coating that keeps lubricated surfaces clean. Forms a lubricating and separating film with anti-stick effect at low speeds and low loads. For all kinds of metal, plastic, ceramic, and wood. Also usable as a release agent for resin moulding.	-180 to +260	+4			Transferred	
OKS 571 PTFE Bonded Coating spray can	Colourless PTFE coating that keeps lubricated surfaces clean. Forms a lubricating and separating film with anti-stick effect at low speeds and low loads. For all kinds of metal, plastic, ceramic, and wood. Also usable as a release agent for resin moulding. OKS 570 filled into a spray can.	-180 to +260	+4			Transferred	
OKS 1300 Sliding Film colourless	Dry film with UV indicator. Eliminates scatter in screw friction coefficients. Prevents fretting in thread rolling and stainless-screw fabrication. Colourless; for screws of any material. Improves the sliding of glass, ceramics, wood, and metal. Proven for lubricating shutters, blinds, and sunshades.	-60 to +100	+68			Transferred	
OKS 1301 Sliding Film colourless spray can	Dry film. Eliminates scatter in screw friction coefficients. Prevents fretting in thread rolling and stainless-screw fabrication. Colourless; for screws of any material. Improves the sliding of glass, ceramics, wood, and metal. Proven for lubricating shutters, blinds, and sunshades. OKS 1300 filled into a spray can; without the UV indicator.	-60 to +100	+68			Transferred	
OKS 1710 Sliding Film for screws water-based concentrate	Dry-film lubricant with UV indicator. Prevents cold welding. Ideal for friction control on assembly lines using galvanised or stainless screws. Dilutable with water up to 1:5 to suit the required friction coefficient (standard dilution 1:2). After drying, an anti-corrosion additive prevents rust. The water-soluble components are biodegradable; the non-soluble components are environmentally harmless.	+60	N/A			Transferred	
OKS 1750 Sliding Film for wood screws water-based concentrate	Dry-film lubricant with UV indicator. Non-tacky. Prevents cold welding of austenitic steels. Ideal for friction control on assembly lines using galvanised screws, e.g. for chipboard. Dilutable with water up to 1:5 to suit the required friction coefficient (standard dilution 1:2). An anti-corrosion additive prevents rust.	+70	N/A			Transferred	

Product	Features	Service temp. (°C)*1	Flash point (°C)	Sizes	E-price*2	Dispatch*3	Remarks
OKS 1765 Sliding Film for thread rolling water-based concentrate	Dry-film lubricant with UV indicator. Non-tacky. For pre-coating before thread rolling. Dilutable with water up to 1:5 to suit the required friction coefficient (standard dilution 1:2).	+70	N/A			Transferred	

*1 Service temperature — the temperature at which the product can be used under continuous conditions.
*2 E-price — the price for an order quantity of one (JPY). Discounted prices apply to orders in units of ten; please enquire using the fax quote request form.
*3 Dispatch — "On request"; please contact us. Dispatch dates are updated according to stock.
*4 SOS express — items eligible for our emergency delivery service. Request SOS delivery when ordering; service-area restrictions apply. Contact us for details.

04 Oils — 21 products

Product	Features	Service temp. (°C)*1	Viscosity ISO VG	Sizes	E-price*3	Dispatch*4	Remarks
OKS 300 MoS2 Mineral Oil Concentrate Mox-Active*2	MoS2 additive for blending into standard industrial oils. Reduces friction, temperature, wear, and noise; smooths and conditions metal surfaces; maintains lubrication even if the oil film fails. Does not settle out; passes through filters without clogging; unaffected by magnetic filters.	Temperature range of the oil it is added to	68	5L	87,000	On request	
OKS 350 MoS2 High-Temp Chain Oil synthetic Mox-Active*2	For emergency lubrication when temperatures rise above normal or oiling intervals are extended.	-30 to +250	220	5L	60,000	On request	
OKS 352 High-Temp Oil synthetic Mox-Active*2	Keeps machinery clean. Low evaporation; no residue after evaporation. Drip resistant. Steam resistant.	-40 to +250	320	5L	60,000	On request	
OKS 3521 High-Temp Oil synthetic Mox-Active*2 spray can	Keeps machinery clean. Low evaporation; no residue after evaporation. Drip resistant. Steam resistant. OKS 352 filled into a spray can.	-40 to +250	320	500ml	7,650	On request	*400ml
OKS 360 High-Performance Corrosion Protection Oil	Adhesive anti-rust and anti-corrosion oil for harsh climatic conditions. Excellent lubricity. For indoor and outdoor use.	-40 to +80	15	5L 25L	59,500 262,500	On request	Transferred
OKS 361 High-Performance Corrosion Protection Oil spray can	Adhesive anti-rust and anti-corrosion oil for harsh climatic conditions. Excellent lubricity. For indoor and outdoor use. OKS 360 filled into a spray can.	-40 to +80	15	400ml	9,070	On request	
OKS 371 Multi-Purpose Oil food industry NSF-H1*6 spray can	High-performance lubricating oil with strong penetration. Colourless, tasteless, odourless.	-10 to +180	15	400ml	6,300	On request	
OKS 3720 Gear Oil food industry NSF-H1*6	Excellent wear resistance. Long life thanks to high-temperature stability and oxidation resistance. Tasteless, odourless. Chemically resistant — withstands steam, alkalis, acids, and other sterilising and cleaning agents.	0 to +160	220	5L 25L	46,000 202,000	On request	
OKS 3730 Gear Oil food industry NSF-H1*6	Excellent wear resistance. Long life thanks to high-temperature stability and oxidation resistance. Tasteless, odourless. Chemically resistant — withstands steam, alkalis, acids, and other sterilising and cleaning agents.	0 to +160	460	5L 25L	50,000 222,000	On request	
OKS 3751 High-Adhesion Oil with PTFE food industry NSF-H1*6 spray can	Tasteless, odourless. Highly adhesive with excellent load-carrying capacity. Fluoropolymer (PTFE/Teflon*) fortified. Chemically resistant — withstands steam, alkalis, acids, and other sterilising and cleaning agents. PAO based.	-35 to +135	100	500ml	7,000	On request	*400ml
OKS 3760 Multi-Purpose Oil food industry NSF-H1*6	Versatile long-term lubricant with excellent lubricity and strong adhesion. Tasteless, odourless.	-10 to +180	100	5L 25L	53,000 240,000	On request	

Product	Features	Service temp. (°C)*1	Viscosity ISO VG	Sizes	E-price*3	Dispatch*4	Remarks
OKS 3770 Hydraulic Oil food industry NSF-H1*6	Long life. Excellent wear resistance. Tasteless, odourless.	-15 to +200	46	5L 25L	44,850 201,750	On request	
OKS 3790 Sugar-Dissolving Oil fully synthetic food industry NSF-H1*6	Tasteless, odourless emulsion. Wear resistant and corrosion protective. Excellent lubricity — and dissolves and washes away sugar at the same time.	0 to +80	15	5L	46,000	On request	
OKS 390 Cutting Oil for all metals Mox-Active*2	Cutting oil for machining a wide range of metals. Free of chlorine and phosphorus, so there is no strong odour and little impact on people or the environment.	N/A	22	250ml	2,750	On request	
OKS 391 Cutting Oil for all metals Mox-Active*2 spray can	Cutting oil for machining a wide range of metals. Free of chlorine and phosphorus, so there is no strong odour and little impact on people or the environment. OKS 390 filled into a spray can.	N/A	22	400ml	5,470	On request	
OKS 600 Multi Oil	Multi-purpose lubricant: rust removal, screw loosening, moisture displacement, lubrication, cleaning, restoring electrical contacts, and rust protection.	-30 to +60	7	5L	17,250	On request	
OKS 601 Multi Oil spray can	Multi-purpose lubricant: rust removal, screw loosening, moisture displacement, lubrication, cleaning, restoring electrical contacts, and rust protection. OKS 600 filled into a spray can.	-30 to +60	7	300ml	2,300	On request	*400ml
OKS 670 High-Performance Oil with white solid lubricants Mox-Active*2	All-round lubricant that keeps machinery clean. Strong penetration reaches the finest clearances. Excellent extreme-pressure performance from white solid lubricants. Also ideal for lubricating machinery without central lubrication.	-30 to +80	46	5L	26,250	On request	
OKS 671 High-Performance Oil with white solid lubricants Mox-Active*2 spray can	All-round lubricant that keeps machinery clean. Strong penetration reaches the finest clearances. Excellent extreme-pressure performance from white solid lubricants. Also ideal for lubricating machinery without central lubrication. OKS 670 filled into a spray can.	-30 to +80	46	300ml	3,870	On request	*400ml
OKS 700 Synthetic Oil	Synthetic oil for cleaning, lubrication, and rust protection. A transparent protective film guards metal surfaces.	-50 to +100	7	5L	39,000	On request	
OKS 701 Synthetic Oil non-gas spray container	Synthetic oil for cleaning, lubrication, and rust protection. A transparent protective film guards metal surfaces. OKS 700 filled into a non-gas pump-spray container.	-50 to +100	7	100ml	2,600	On request	

*1 Service temperature — the temperature at which the product can be used under continuous conditions.

*2 Mox-Active — a proprietary OKS additive combining organic molybdenum with several solid lubricants. It smooths the lubricated surface and reduces friction and wear.

*3 E-price — the price for an order quantity of one (JPY). Discounted prices apply to orders in units of ten; please enquire using the fax quote request form.

*4 Dispatch — "On request": please contact us. Dispatch dates are updated according to stock.

*5 SOS express — items eligible for our emergency delivery service. Request SOS delivery when ordering; service-area restrictions apply. Contact us for details.

*6 USDA-H1/NSF-H1 — certified by public bodies as lubricants usable where incidental contact with food is possible.

*7 BIOlogic — the OKS range of biodegradable lubricants built on new technology.

05 Corrosion Protection — 14 products

Product	Features	Service temp. (°C)*1	Salt spray test (h)	Sizes*2	E-price*3	Dispatch*4	Remarks
OKS 2100 Protective Film for metals MIL-C-16173 grade 1	Non-tacky rust preventive usable under all climatic conditions. Unlike ordinary lubricating oils, the protective film does not need to be removed before operation. US military specification item, used where equipment and fittings at sea need maximum protection from salt water.	-40 to +70	640	5L	27,000	On request	
OKS 2101 Protective Film for metals spray can MIL-C-16173 grade 1	Non-tacky rust preventive usable under all climatic conditions. Unlike ordinary lubricating oils, the protective film does not need to be removed before operation. US military specification item, used where equipment and fittings at sea need maximum protection from salt water. OKS 2100 filled into a spray container.	-40 to +70	640	500ml	4,690	On request	*400ml
OKS 2301 Mould Protector for moulds and dies spray can	Highly water-repellent, non-tacky rust preventive for moulds and dies. Green colour makes it easy to confirm a uniform coating.	-40 to +70	>1000	400ml	5,020	On request	
OKS 2511 Zinc Coating spray can TÜV certified	For heavy-duty corrosion protection; passes the DIN 53167 salt spray test. Heat resistant to +490°C. Spot-weldable. For steel structures, bridges, ships, offshore structures, plant, and vehicles. Also ideal for repairing axle undercoating and as a primer before painting. Dries in 5 minutes at room temperature; a scratch-resistant protective film forms in 2 hours; paintable after 6 hours. The aerosol can uses a self-cleaning valve to prevent clogging.	+490	480	500ml	6,300	On request	Transferred
OKS 2521 Gloss Zinc spray can	Drying rust preventive with a bright metallic finish. Weldable and paintable. Protects against scratches. Same drying times as OKS 2511.	+490	480	500ml	6,650	On request	Transferred
OKS 2531 Alu-Metallic	Drying rust preventive with a matt aluminium finish. Usable on all metals. Electrically conductive. Ideal for maintaining hot pipework and flues; also used on car exhaust pipes. Same drying times as OKS 2511.	-70 to +800	480	500ml	5,950	On request	Transferred
OKS 2541 Stainless Steel spray can	Rust preventive for stainless steel in high-humidity environments. Contains stainless steel powder. Resists impact and peeling.	to +100	72	500ml	7,250	On request	Transferred
OKS 360 High-Performance Corrosion Protection Oil	For rust protection under severe conditions. Adhesive. Usable indoors and outdoors. Also ideal for export packing of machinery and parts.	-40 to +80	340			On request	Transferred
OKS 361 High-Performance Corrosion Protection Oil spray can	For rust protection under severe conditions. Adhesive. Usable indoors and outdoors. Also ideal for export packing of machinery and parts. OKS 360 filled into a spray can.	-40 to +80	340	400ml	9,070	On request	
OKS 403 Marine Grease German Army TL 9150-0066 NATO spec. G-460	Special grease with outstanding corrosion protection even under water. Proven in humid workplaces and coastal areas.	-25 to +80 drop pt. +115	>700	400ml 1kg	5,850 9,500	On request On request	*400ml
OKS 600 Multi Oil	Short-term rust protection combined with lubrication. A maintenance essential with countless uses.	-30 to +60	—	5L	17,250	On request	
OKS 601 Multi Oil spray can	Short-term rust protection combined with lubrication. A maintenance essential with countless uses. OKS 600 filled into a spray can.	-30 to +60	—	400ml	2,500	On request	*400ml
OKS 700 Synthetic Oil	Long-lasting rust protection from a thin film. Economical — a small amount protects a large area. For precision equipment such as measuring instruments.	-50 to +100	—	5L	39,000	On request	

Product	Features	Service temp. (°C)*1	Salt spray test (h)	Sizes*2	E-price*3	Dispatch*4	Remarks
OKS 701 Synthetic Oil non-gas spray container	Long-lasting rust protection from a thin film. Economical — a small amount protects a large area. OKS 700 filled into a non-gas spray container. For precision equipment such as measuring instruments.	-50 to +100	—	100ml	2,600	On request	

*1 Service temperature — the temperature at which the product can be used under continuous conditions; the drop point is higher still, and short-term use up to the drop point is possible.

*2 Sizes — 400 g items come as cylindrical cartridges (10 per box). A dedicated grease gun is required for use; sold separately at 10,000 JPY.

*3 E-price — the price for an order quantity of one (JPY). Discounted prices apply to orders in units of ten; please enquire using the fax quote request form.

*4 Dispatch — "On request": please contact us. Dispatch dates are updated according to stock.

*5 SOS express — items eligible for our emergency delivery service. Request SOS delivery when ordering; service-area restrictions apply. Contact us for details.

06 Maintenance Chemicals — 13 products

Product	Features	Service temp. (°C)*1	Colour	Sizes	E-price*2	Dispatch*3	Remarks
OKS 611 Rust Remover with MoS2 spray can	Powerful penetration. Contains MoS2. Removes rust from metal surfaces and frees seized screws. Water repellent. Short-term rust protection.	-30 to +50	grey	400ml	3,000	On request	
OKS 1103 Heat-Sink Paste	Heat-dissipating paste that protects electronic components — CPUs, sensors, probes, diodes, transistors, thyristors — from heat. High thermal conductivity. Does not attack materials.	-40 to +200 no drop pt.	white	40ml	3,000	On request	40ml
OKS 1360 Silicone Release Agent	Highly effective release lubricant with an antistatic additive. Chemically neutral. Solvent-free.	-60 to +200	colourless	5L	59,000	On request	
OKS 1361 Silicone Release Agent NSF-H1*5 spray can	Highly effective release lubricant with an antistatic additive. Chemically neutral. Solvent-free. OKS 1360 filled into a spray can.	-60 to +200	colourless	500ml	3,720	On request	Spray can *400ml
OKS 1511 Release Agent silicone-free spray can	Makes painting, printing, bonding, and plating of moulded plastic surfaces easier. Non-tacky. Silicone-free.		colourless	500ml	2,550	On request	Spray can *400ml
OKS 1600 Spatter Release water-based concentrate	Prevents weld spatter from sticking to workpieces and welding nozzles. Dilute with water for use.		colourless	5L	26,000	On request	
OKS 1601 Spatter Release water-based concentrate spray can	Prevents weld spatter from sticking to workpieces and welding nozzles. OKS 1600 filled into a spray can. Water-dilutable type.		colourless	400ml	2,560	On request	Spray can *400ml
OKS 2611 Universal Cleaner spray can	Powerful degreaser. Quickly removes grease, oil, and other soiling. Fast drying — evaporates rapidly without residue. VCI additive provides short-term rust protection. OKS 2610 filled into a spray can.		colourless	500ml	3,700	On request	Spray can
OKS 2621 Contact Cleaner spray can	Electrical contact cleaner that quickly penetrates and cleans the finest gaps. Removes dirt and oxides without dripping. Restores contacts; prevents stray currents. CFC-free!		colourless	400ml	9,500	On request	
OKS 2800 Leak Detector	Foam instantly reveals even the slightest gas leak.	+80	colourless	5L	11,950	On request	
OKS 2801 Leak Detector spray can	Foam instantly reveals even the slightest gas leak. OKS 2800 filled into a spray can.	+80	colourless	400ml	2,230	On request	
OKS 2731 Compressed-Air Spray spray can	Blows dust and debris off electronic components and precision equipment. Oil-free, dry-air type. CFC-free!		colourless	400ml	5,000	On request	Spray can
OKS 2901 Belt Tuner spray can	Increases belt tension by 50% and improves power transmission. Highly adhesive; prevents slip. Keeps belts from drying out, extending their life. Usable on V-belts, round belts, flat belts, and many other belt types.	+80	colourless	400ml	5,670	On request	Spray can

*1 Service temperature — the temperature at which the product can be used under continuous conditions. Figures in parentheses apply when contact with air is restricted.

*2 E-price — the price for an order quantity of one (JPY). Discounted prices apply to orders in units of ten; please enquire using the fax quote request form.

*3 Dispatch — "On request": please contact us. Dispatch dates are updated according to stock.

*4 SOS express — items eligible for our emergency delivery service. Request SOS delivery when ordering; service-area restrictions apply. Contact us for details.

*5 USDA-H1/NSF-H1 — certified by public bodies as lubricants usable where incidental contact with food is possible.

*6 BIOlogic — the OKS range of biodegradable lubricants built on new technology.

07 Related Products — 2 products

Item no.	Product	Features	Type	E-price*1	Dispatch*2	Remarks
2118	High-Pressure Grease Gun LS-600E	For 400 g cartridge greases	Manual	8,000	Same day	Lever type, with grip.
—	Grease Nipples*3	Types A, B, C; pin type; button head	Inch & metric	Quote	On request	JIS and overseas standards in all sizes. Dust caps sold separately.

*1 E-price — the price for an order quantity of one (JPY). Discounted prices apply to orders of ten or more; please enquire using the fax quote request form.

*2 Dispatch — "On request": please contact us. Dispatch dates are updated according to stock.

*3 Grease nipples — please specify the thread standard and material when ordering. Contact us for details.