

AM-400 Air Grease Gun

360° rotating, continuous-discharge air grease gun with silencer.



Features

- A special air-bleed valve quickly eliminates the air pockets that commonly form in air grease guns.
- The grip body rotates 360°, so the angle can be adjusted to suit the job. Continuous grease discharge makes it ideal for grease-up work.
- Dual-use design: 400 g bellows cartridge or 600 g hand-fill.
- The silencer suppresses operating noise.
- The grip body and gun head separate, making cleaning easy.

Specifications

Model	AM-400
Included accessory	No. 4 nozzle, 180 mm
Discharge pressure (MPa)	min. 16.5 / max. 41.2
Air pressure (MPa)	min. 0.41 / max. 1.03
Recommended working pressure	0.62 MPa
Grease	Bellows cartridge (400 g) or hand-fill (600 g)
Type	360° rotating, continuous discharge, with silencer

Preparation before use

1. Remove the barrel from the gun head (turn it counter-clockwise).
2. Pull the ring and draw the barrel chain all the way out toward you, then hook the chain into the notch in the bottom cap.
3. Unscrew the cap of the bellows grease cartridge and attach the cartridge to the threaded section inside the gun head.
4. Screw the barrel back onto the gun head and release the chain from the notch.
5. Turn the wing lock 1–2 turns counter-clockwise.
6. Rotate the grip body to set a comfortable working angle.
7. Tighten the wing lock fully.
8. Before connecting air, add a few drops of oil through the air vent.
9. After connecting air, pull the trigger to start greasing.



Air-bleed valve: if an air pocket forms during use and grease stops discharging, the air can be purged easily.

OILKEY CORPORATION

Head Office: 4-4-18 Makitsukadai, Minami-ku, Sakai, Osaka 590-0114, Japan
TEL +81-72-284-1711 FAX +81-72-298-7790 <http://www.oilkey.co.jp>

Sakai Sales Office: 617 Taiheiji (2F), Nishi-ku, Sakai, Osaka 593-8314, Japan
English edition, translated from the original Japanese document.



1. Pull the trigger, then stop.
2. Pressing the top of the valve easily eliminates the air pocket.
3. Repeat this procedure until grease comes out.
4. Pull the trigger (greasing restarts).

Applications

Construction machinery, agricultural machinery, vehicles, ships, general industrial machinery and more.

Options

Code	Product	Model	Overall length
1203	Jet Hose	No. 3	350 mm
1209	Jet Hose	No. 3	430 mm
3145	Jet Hose	No. 3	1000 mm
1201	Hybrid Hose	HB-No. 3	350 mm
1205	Jet Nozzle	No. 4	180 mm
1245	Jet Nozzle	No. 4	300 mm
1207	Jet Nozzle	No. 4	430 mm
1208	Jet Nozzle	No. 5	120 mm
1210	Jet Nozzle	No. 5	250 mm
1212	Jet Nozzle	No. 5	450 mm

Patented cartridge grease — usable to the very last, leaving no grease behind

Code	Product	Model	Content	Per case	Grease type	Dropping point (°C)
1315	Jet Grease	GT-400LG	400 g	20	Lithium grease	190
1317	Jet Grease	GT-400M	400 g	20	Molybdenum complex grease	260

OILKEY CORPORATION

Head Office: 4-4-18 Makitsukadai, Minami-ku, Sakai, Osaka 590-0114, Japan Sakai Sales Office: 617 Taiheiji (2F), Nishi-ku, Sakai, Osaka 593-8314, Japan
 TEL +81-72-284-1711 FAX +81-72-298-7790 <http://www.oilkey.co.jp> English edition, translated from the original Japanese document.