



Product Data Sheet

OILKEY JET-GREASE GT-400M

Molybdenum grease

GT-400M is a grease based on carefully selected, high-flash-point refined mineral oil with a lithium thickener and molybdenum disulfide as a solid lubricant, giving it excellent load-carrying capacity and wear resistance.

Features

1. Excellent high-temperature oxidation stability

A highly refined base oil and carefully selected additives give a grease that withstands long-term use with little oxidative degradation even at high temperatures.

2. Excellent load-carrying capacity and wear resistance

The synergy of molybdenum disulfide and extreme-pressure additives provides excellent load-carrying capacity and wear resistance.

Applications

Sliding surfaces of ball joints; construction machinery.

Operating temperature range

−20 °C to +130 °C

Typical properties

Test method	Property	Typical value
—	NLGI grade	2
Visual	Appearance	Grey-black, buttery
JIS K 2220 7	Worked penetration, 25 °C	273
JIS K 2220 8	Dropping point, °C	190
JIS K 2220 9	Copper corrosion (100 °C, 24 h)	Pass
JIS K 2220 11	Oil separation (100 °C, 24 h), mass %	2.3
JIS K 2220 12	Oxidation stability (99 °C, 100 h), kPa	30
JIS K 2220 21	Worked stability	Trace
ASTM D2596	High-speed four-ball test, weld load, N	3,090
ASTM D2266	High-speed four-ball test, wear scar, mm	0.45
—	Thickener	Lithium soap

Contents: 400 g cartridges, 20 per case.

OILKEY CORPORATION

Head Office: 4-4-18 Makitsukadai, Minami-ku, Sakai, Osaka 590-0114, Japan Sakai Sales Office: 617 Taiheiji (2F), Nishi-ku, Sakai, Osaka 593-8314, Japan
 TEL +81-72-284-1711 FAX +81-72-298-7790 <http://www.oilkey.co.jp> English edition, translated from the original Japanese document.