



OILKEY 8000

Odorless penetrating spray — penetrates, lubricates and prevents rust.



Features

- Contains the ultra-fine fluorine compound FLO® for extra penetrating and lubricating power.
- A well-balanced formulation of water-displacing, penetrating rust preventives protects metal surfaces from rust.
- Odorless, so it can be used anywhere, regardless of location.

Applications

- Loosening seized bolts, nuts and other threaded parts.
- Rust prevention and lubrication for automobiles, construction machinery, agricultural machinery and more.

How to use

- To loosen threads: spray the seized threads generously and remove after about 5 minutes.
- For lubrication: spray evenly over the sliding surfaces.
- For moisture-proofing and rust prevention: spray evenly over the metal surface.
- To remove rust: spray, wait 5–10 minutes, then polish with steel wool, a cloth or similar.

Cautions — keep away from open flame and high temperatures

This product uses high-pressure flammable gas (LPG) as a propellant and is a flammable product. Observe the following: do not use near open flames or in closed rooms with poor ventilation; do not spray large amounts near fire sources; do not place the can where temperatures exceed 40 °C, in direct sunlight, near fire or in cars in hot weather; heating the can above high temperature may cause it to burst. Do not throw the can into fire. Use up the contents completely before disposal; when discarding, release the remaining gas outdoors away from flame with the button pressed. Keep out of reach of children. If sprayed in the eyes, flush with running water for at least 15 minutes and see a doctor if any abnormality persists. In case of skin irritation or if swallowed, seek medical advice immediately. Inhalation of vapour is harmful — use protective gloves, mask and goggles, and work in a well-ventilated place.

Classification	Class 3 petroleum, hazard grade III (68 ml); labelled under Article 57 of the Industrial Safety and Health Act (mineral oil)
Contents	NET 420 ml
Propellant	High-pressure gas: LPG (i-butane / n-butane)

OILKEY CORPORATION

Head Office: 4-4-18 Makitsukadai, Minami-ku, Sakai, Osaka 590-0114, Japan Sakai Sales Office: 617 Taiheiji (2F), Nishi-ku, Sakai, Osaka 593-8314, Japan
 TEL +81-72-284-1711 FAX +81-72-298-7790 <http://www.oilkey.co.jp> English edition, translated from the original Japanese document.