

## SBML Model Report

# Model name: “Wodarz2007 - Basic Model of Cytomegalovirus Infection”



May 17, 2018

## 1 General Overview

This is a document in SBML Level 2 Version 4 format. This model was created by the following two authors: Matthew Grant Roberts<sup>1</sup> and Catherine Lloyd<sup>2</sup> at June 25<sup>th</sup> 2010 at 1:41 p.m. and last time modified at March ninth 2018 at 4:21 p.m. Table 1 provides an overview of the quantities of all components of this model.

Table 1: Number of components in this model, which are described in the following sections.

Element	Quantity	Element	Quantity
compartment types	0	compartments	1
species types	0	species	0
events	0	constraints	0
reactions	0	function definitions	0
global parameters	16	unit definitions	3
rules	6	initial assignments	0

## Model Notes

This a model from the article:

**Dynamics of killer T cell inflation in viral infections.**

Wodarz D, Sierro S, Klenerman P. J R Soc Interface 2007 Jun 22;4(14):533-43 [17251133](#) ,

**Abstract:**

<sup>1</sup>EMBL-EBI, [mroberts@embl.ac.uk](mailto:mroberts@embl.ac.uk)

<sup>2</sup>University of Auckland, [c.lloyd@auckland.ac.nz](mailto:c.lloyd@auckland.ac.nz)

Upon acute viral infection, a typical cytotoxic T lymphocyte (CTL) response is characterized by a phase of expansion and contraction after which it settles at a relatively stable memory level. Recently, experimental data from mice infected with murine cytomegalovirus (MCMV) showed different and unusual dynamics. After acute infection had resolved, some antigen specific CTL started to expand overtime despite the fact that no replicative virus was detectable. This phenomenon has been termed as „CTL memory inflation,. In order to examine the dynamics of this system further, we developed a mathematical model analysing the impact of innate and adaptive immune responses. According to this model, a potentially important contributor to CTL inflation is competition between the specific CTL response and an innate natural killer (NK) cell response. Inflation occurs most readily if the NK cell response is more efficient than the CTL at reducing virus load during acute infection, but thereafter maintains a chronic virus load which is sufficient to induce CTL proliferation. The model further suggests that weaker NK cell mediated protection can correlate with more pronounced CTL inflation dynamics over time. We present experimental data from mice infected with MCMV which are consistent with the theoretical predictions. This model provides valuable information and may help to explain the inflation of CMV specific CD8+T cells seen in humans as they age.

This model was taken from the [CellML repository](#) and automatically converted to SBML.

The original model was: [Wodarz D, Siero S, Klennerman P. \(2007\) - version=1.0](#)

The original CellML model was created by:

**Catherine Lloyd**

c.lloyd@auckland.ac.nz

The University of Auckland

This model originates from BioModels Database: A Database of Annotated Published Models (<http://www.ebi.ac.uk/biomodels/>). It is copyright (c) 2005-2011 The BioModels.net Team.

To the extent possible under law, all copyright and related or neighbouring rights to this encoded model have been dedicated to the public domain worldwide. Please refer to [CC0 Public Domain Dedication](#) for more information.

In summary, you are entitled to use this encoded model in absolutely any manner you deem suitable, verbatim, or with modification, alone or embedded it in a larger context, redistribute it, commercially or not, in a restricted way or not..

To cite BioModels Database, please use: [Li C, Donizelli M, Rodriguez N, Dharuri H, Endler L, Chelliah V, Li L, He E, Henry A, Stefan MI, Snoep JL, Hucka M, Le Novre N, Laibe C \(2010\) BioModels Database: An enhanced, curated and annotated resource for published quantitative kinetic models. BMC Syst Biol., 4:92.](#)

## 2 Unit Definitions

This is an overview of seven unit definitions of which four are predefined by SBML and not mentioned in the model.

## 2.1 Unit `time`

**Name** `time`

**Definition** 3600 s

## 2.2 Unit `unit_0`

**Name** 1

**Definition** dimensionless<sup>0</sup>

## 2.3 Unit `unit_1`

**Name**  $1/(0.277778 \cdot \text{ms})$

**Definition**  $(0.277778 \text{ ms})^{-1}$

## 2.4 Unit `substance`

**Notes** Mole is the predefined SBML unit for substance.

**Definition** mol

## 2.5 Unit `volume`

**Notes** Litre is the predefined SBML unit for volume.

**Definition** l

## 2.6 Unit `area`

**Notes** Square metre is the predefined SBML unit for area since SBML Level 2 Version 1.

**Definition** m<sup>2</sup>

## 2.7 Unit `length`

**Notes** Metre is the predefined SBML unit for length since SBML Level 2 Version 1.

**Definition** m

# 3 Compartment

This model contains one compartment.

Table 2: Properties of all compartments.

Id	Name	SBO	Spatial Dimensions	Size	Unit	Constant	Outside
COMpartment	Mouse		3	1	litre	<input checked="" type="checkbox"/>	

### 3.1 Compartment COMpartment

This is a three dimensional compartment with a constant size of one litre.

**Name** Mouse

## 4 Parameters

This model contains 16 global parameters.

Table 3: Properties of each parameter.

Id	Name	SBO	Value	Unit	Constant
x	x		1.000	dimensionless <sup>0</sup>	<input type="checkbox"/>
y0	y0		0.000	dimensionless <sup>0</sup>	<input type="checkbox"/>
y1	y1		0.000	dimensionless <sup>0</sup>	<input type="checkbox"/>
L	L		0.000	dimensionless <sup>0</sup>	<input type="checkbox"/>
v	v		1.000	dimensionless <sup>0</sup>	<input type="checkbox"/>
R0	R0		15.909	dimensionless <sup>0</sup>	<input type="checkbox"/>
a0	a0		0.100	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
a1	a1		0.200	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
k	k		1.000	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
u	u		1.000	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
lambda	lambda		10.000	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
d	d		0.100	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
beta	beta		0.100	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
gamma	gamma		0.500	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
phi	phi		0.100	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>
eta	eta		0.010	(0.277778 ms) <sup>-1</sup>	<input checked="" type="checkbox"/>

## 5 Rules

This is an overview of six rules.

### 5.1 Rule R0

Rule R0 is an assignment rule for parameter R0:

$$R0 = \frac{\lambda \cdot \eta}{d \cdot a1 \cdot (a0 + \eta)} \cdot \left( \beta + \frac{\gamma \cdot \phi}{\phi + d} \right) \quad (1)$$

**Derived unit** dimensionless

### 5.2 Rule x

Rule x is a rate rule for parameter x:

$$\frac{d}{dt}x = \lambda - (d \cdot x + \beta \cdot x \cdot v + \gamma \cdot x \cdot v) \quad (2)$$

**Derived unit**  $(0.277778 \text{ ms})^{-1}$

### 5.3 Rule y0

Rule y0 is a rate rule for parameter y0:

$$\frac{d}{dt}y0 = \beta \cdot x \cdot v - (a0 \cdot y0 + \eta \cdot y0) + \phi \cdot L \quad (3)$$

**Derived unit**  $(0.277778 \text{ ms})^{-1}$

### 5.4 Rule y1

Rule y1 is a rate rule for parameter y1:

$$\frac{d}{dt}y1 = \eta \cdot y0 - a1 \cdot y1 \quad (4)$$

**Derived unit**  $(0.277778 \text{ ms})^{-1}$

### 5.5 Rule L

Rule L is a rate rule for parameter L:

$$\frac{d}{dt}L = \gamma \cdot x \cdot v - (\phi \cdot L + d \cdot L) \quad (5)$$

**Derived unit**  $(0.277778 \text{ ms})^{-1}$

### 5.6 Rule v

Rule v is a rate rule for parameter v:

$$\frac{d}{dt}v = k \cdot y1 - u \cdot v \quad (6)$$

**Derived unit**  $(0.277778 \text{ ms})^{-1}$

SBML<sup>2</sup>TeX was developed by Andreas Dräger<sup>a</sup>, Hannes Planatscher<sup>a</sup>, Dieudonné M Wouamba<sup>a</sup>, Adrian Schröder<sup>a</sup>, Michael Hucka<sup>b</sup>, Lukas Endler<sup>c</sup>, Martin Golebiewski<sup>d</sup> and Andreas Zell<sup>a</sup>. Please see <http://www.ra.cs.uni-tuebingen.de/software/SBML2LaTeX> for more information.

<sup>a</sup>Center for Bioinformatics Tübingen (ZBIT), Germany

<sup>b</sup>California Institute of Technology, Beckman Institute BNMC, Pasadena, United States

<sup>c</sup>European Bioinformatics Institute, Wellcome Trust Genome Campus, Hinxton, United Kingdom

<sup>d</sup>EML Research gGmbH, Heidelberg, Germany