

## Front end feed

## 8. UtiligramFeedView.jsx

Purpose: Lets users post proof-of-good (via IPFS/Arweave), view ranked feed, and track tips.

## Jsx

```
import React, { useEffect, useState }
from "react";
import { Card, CardContent } from
"@/components/ui/card";
import { Input } from "@/components/ui
/input";
import { Button } from "@/components
/ui/button";
import { ethers } from "ethers";
import { toast } from "react-hot-toast";

const FEED_ABI = [/* compiled
UtiligramFeed ABI here */];
const FEED_ADDRESS = "0x..."; //
Replace with deployed address

export default function
UtiligramFeedView() {
  const [provider, setProvider] =
useState(null);
  const [contract, setContract] =
useState(null);
  const [posts, setPosts] = useState([]);
  const [newPost, setNewPost] =
useState("");

  useEffect(() => {
    const setup = async () => {
      if (window.ethereum) {
        const p = new ethers.BrowserProvi
der(window.ethereum);
        const s = await p.getSigner();
        const c = new
ethers.Contract(FEED_ADDRESS,
FEED_ABI, s);
        setProvider(p);
        setContract(c);
        fetchPosts(c);
      }
    };
    setup();
  }, []);

  const fetchPosts = async (c) => {
    const count = await c.totalPosts();
    const data = [];
    for (let i = count; i > 0 && i > count -
20; i--) {
      const post = await c.getPost(i);
      data.push(post);
    }
    setPosts(data);
  };

  const submitPost = async () => {
    if (!newPost) return toast.error("Post
link is required");
    const tx = await
contract.submitPost(newPost,
"community contribution");
    await tx.wait();
    toast.success("Posted to Utiligram");
    setNewPost("");
    fetchPosts(contract);
  };

  return (
    <div className="space-y-6">
      <div className="flex gap-2">
        <Input
          value={newPost}
          onChange={(e) =>
setNewPost(e.target.value)}
          placeholder="IPFS or Arweave link
to proof of action"
        />
        <Button onClick={submitPost}>Post</Button>
      </div>

      <div className="grid gap-4">
        {posts.map((p) => (
          <Card key={p.id}
className="border shadow-sm">
            <CardContent className="p-4">
              <p className="text-sm
text-muted-foreground">Post #{p.id}</p>
              <a
                href={`https://ipfs.io/ipfs/${p
.contentHash}`}
                className="text-blue-600
underline"
                target="_blank"
                rel="noopener noreferrer"
              >
                View Proof
              </a>
              <p className="mt-2
text-gray-800">
                Tipped:
                {ethers.formatUnits(p.totalTips || 0n,
18)} EUT
              </p>
            </CardContent>
          </Card>
        ))}
      </div>
    </div>
  );
}
```

