

45

79



Performance

Accessibility

Best Practices

SEO



Progressive Web App

0-49

50-89

90-100



Performance

Metrics



7.3 s

- First Contentful Paint
 First Contentful Paint marks
 the time at which the first
 text or image is painted.

 Learn more.
- 1.5 s Time to Interactive

 Time to interactive is the amount of time it takes for the page to become fully interactive. Learn more.

Speed Index
Speed Index shows how
quickly the contents of a
page are visibly populated.
Learn more.

- 5.2 s
- ▲ Total Blocking Time 1,530 ms

 Sum of all time periods between

 FCP and Time to Interactive,

 when task length exceeded

 50ms, expressed in

 milliseconds. Learn more.

- Largest Contentful Paint
- 2.7 s
- Cumulative Layout Shift

Largest Contentful Paint marks the time at which the largest text or image is painted. <u>Learn More</u> Cumulative Layout Shift measures the movement of visible elements within the viewport. Learn more.

Values are estimated and may vary. The <u>performance score is calculated</u> directly from these metrics. See calculator.



Opportunities — These suggestions can help your page load faster. They don't <u>directly</u> <u>affect</u> the Performance score.

Opportunity Estimated Savings

Serve images in next-gen formats

Image formats like JPEG 2000, JPEG XR, and WebP often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. Learn more.

Defer offscreen images

Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. <u>Learn more</u>.

Show 3rd-party resources (4)

0.6s ^

0.45 s ^

	URL	Resource Size	Potential Savings	
Ĵ. ≙	img/spritelist_71904c7.png (gss0.bdstatic.c	com) 27.7 KiB	27.7 KiB	
	img/default_icon_02f13d8.png (gss0.bdsta	tic.com) 23.8 KiB	23.8 KiB	
d	iphone/logo.png (m.baidu.com)	13.4 KiB	13.4 KiB	
	iphone/tab_loadingbg_logo.png (m.baid	lu.com) 8.0 KiB	8.0 KiB	
=/	img/fankui_cc44349.png (gss0.bdstatic.con	n) 2.6 KiB	2.6 KiB	
	img/shoucang_5ef89d6.png (gss0.bdstatic	.com) 2.3 KiB	2.3 KiB	
Effici	ently encode images	_	0.24 s ^	
Optir	nized images load faster and consume less cel	lular data. <u>Learn more</u> .		
		Show 3rd-party reso	ources (1)	
	URL	Resource Size	Potential Savings	
2	/e2c291bjpg (search-operate.cdn.bcebos.cc	om) 69.2 KiB	32.4 KiB	
Rem	ove unused JavaScript	_	0.18 s ^	
	Remove unused JavaScript to reduce bytes consumed by network activity. <u>Learn</u> more.			
		Show 3rd-party reso	ources (1)	
URL		Transfer Size		
pa	ckage/newsActivity_f9b101c.js (sm.bdimg.com)	35.9 KiB	34.7 KiB	
Prop	erly size images	_	0.15 s ^	
	e images that are appropriately-sized to save continued to save co	ellular data and improve	load	

Show 3rd-party resources (1)

URL	Resource Size	Potential Savings
img/default_icon_02f13d8.png (gss0.bdstatic.com)	23.8 KiB	9.0 KiB
logo/plus_logo_web_white_2.png (www.baidu.com)	15.4 KiB	4.2 KiB

Diagnostics — More information about the performance of your application. These numbers don't <u>directly affect</u> the Performance score.

▲ Ensure text remains visible during webfont load

Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. <u>Learn more</u>.

onow ord party resources (e)
Potential
Savings

fonts/n-icons_/bcbf44.woff (sm.bdimg.com)	3,000 ms
iconfont/iconfont_fcd5aba.woff (gss0.bdstatic.com)	1,180 ms

...fonts/n-icons_d083fee.ttf (sm.bdimg.com) 690 ms

▲ Minimize main-thread work — 6.0 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>

Category	Time Spent
Style & Layout	2,099 ms
Script Evaluation	1,824 ms
Other	1,017 ms
Parse HTML & CSS	437 ms
Rendering	335 ms
Script Parsing & Compilation	278 ms
Garbage Collection	26 ms

A long cache lifetime can speed up repeat visits to your page. Learn more.

✓ Show 3rd-party resources (46)

URL	Cache TTL	Transfer Size
fonts/n-icons_d083fee.ttf (sm.bdimg.com)	None	42 KiB
iconfont/iconfont_fcd5aba.woff (gss0.bdstatic.com)	None	29 KiB
wise/feedlist?sid= (feed.baidu.com)	None	28 KiB
tab/gettabinfo?pd= (feed.baidu.com)	None	3 KiB
/tc?tcreq4log= (m.baidu.com)	None	0 KiB
/v.gif?tid= (hpd.baidu.com)	None	0 KiB
openjs/openBox.js?_v=2021-02-12-18 (s.bdstatic.com)	1 h	12 KiB
/e2c291bjpg (search-operate.cdn.bcebos.com)	1 d 13 h 24 m 15 s	70 KiB
img/report.png (b.bdstatic.com)	2 d 6 h 30 m 15 s	2 KiB
it/u=315,171&fm=173&app=49&f=JPEG?w= (ss0.baidu.com)	21 d 6 h 40 m 26 s	12 KiB
it/u=273,135&fm=173&app=49&f=JPEG?w= (ss0.baidu.com)	23 d 18 h 27 m 11 s	16 KiB
it/u=359,357&fm=173&app=49&f=JPEG?w= (ss0.baidu.com)	23 d 18 h 27 m 11 s	13 KiB

URL	Cache TTL	Transfer Size
it/u=190,117&fm=173&app=49&f=JPEG?w= (ss2.baidu.com)	23 d 18 h 27 m 11 s	11 KiB
it/u=240,212&fm=173&app=49&f=JPEG?w= (ss0.baidu.com)	26 d 3 h 23 m 43 s	20 KiB
it/u=175,285&fm=173&app=49&f=JPEG?w= (ss0.baidu.com)	26 d 3 h 23 m 43 s	17 KiB
it/u=182,186&fm=173&app=49&f=JPEG?w= (ss0.baidu.com)	26 d 3 h 23 m 43 s	15 KiB
it/u=186,662&fm=173&app=49&f=JPEG?w= (ss2.baidu.com)	27 d 17 h 23 m 28 s	8 KiB
it/u=178,385&fm=173&app=49&f=JPEG?w= (ss0.baidu.com)	27 d 17 h 23 m 28 s	7 KiB
package/newsActivity_f9b101c.js (sm.bdimg.com)	30 d	36 KiB
img/spritelist_71904c7.png (gss0.bdstatic.com)	30 d	28 KiB
img/default_icon_02f13d8.png (gss0.bdstatic.com)	30 d	24 KiB
lib/atomWrapper_6fc442d.js (sm.bdimg.com)	30 d	23 KiB
@baidu/invoke-box_3410134.js (sm.bdimg.com)	30 d	15 KiB
@baidu/wise-invoke-prompt_3cade39.js (sm.bdimg.com)	30 d	10 KiB
@baidu/wise-invoke-panel_3e86ac0.js (sm.bdimg.com)	30 d	9 KiB
@baidu/invoke-box-search_9c4e6d4.js (sm.bdimg.com)	30 d	6 KiB
component/btmBanner_f91323e.js (sm.bdimg.com)	30 d	5 KiB

URL	Cache TTL	Transfer Size
plugin/safariicon_6bd009a.js (sm.bdimg.com)	30 d	4 KiB
personalcenter/pack_dd25317.js (gss0.bdstatic.com)	30 d	4 KiB
dist/index_f95793e.js (gss0.bdstatic.com)	30 d	3 KiB
package/superframe_5b7bdae.js (sm.bdimg.com)	30 d	3 KiB
a4/carousel_59baff7.js (sm.bdimg.com)	30 d	3 KiB
img/fankui_cc44349.png (gss0.bdstatic.com)	30 d	3 KiB
img/shoucang_5ef89d6.png (gss0.bdstatic.com)	30 d	3 KiB
common/Carousel_76e2bc0.js (sm.bdimg.com)	30 d	3 KiB
channelMgr/index_c70dc69.js (gss0.bdstatic.com)	30 d	3 KiB
invoke/invokeSecr_13c5fec.js (sm.bdimg.com)	30 d	2 KiB
img/guanzhu_0edf6fe.png (gss0.bdstatic.com)	30 d	2 KiB
img/personal-center-white_e77b2dd.png (gss0.bdstatic.com)	30 d	2 KiB
img/pifu_eef387c.png (gss0.bdstatic.com)	30 d	2 KiB
component/fullscreen_bb2defb.js (sm.bdimg.com)	30 d	2 KiB
@baidu/wise-invoke-popup_fa02b72.js (sm.bdimg.com)	30 d	2 KiB
invoke/fnProvider_9833c78.js (sm.bdimg.com)	30 d	2 KiB
img/fetch_ing_8_0.png (gss0.bdstatic.com)	30 d	1 KiB
common/Core_426be15.js (sm.bdimg.com)	30 d	1 KiB
@searchfe/user-agent_24ce52d.js (sm.bdimg.com)	30 d	1 KiB
img/fetch_ing_8_0.png (sm.bdimg.com)	30 d	1 KiB
common/ivkBox_d19bab7.js (sm.bdimg.com)	30 d	1 KiB
common/ShieldMonitor_b61052e.js (sm.bdimg.com)	30 d	1 KiB
common/DataProcess_deb477f.js (sm.bdimg.com)	30 d	1 KiB
invoke/invokeCookie_31fef6f.js (sm.bdimg.com)	30 d	1 KiB

URL	Cache TTL	Transfer Size
common/StrategyDjs (sm.bdimg.com)	30 d	1 KiB
invoke/invokeBox_12354c1.js (sm.bdimg.com)	30 d	1 KiB
invoke/setFullScjs (sm.bdimg.com)	30 d	1 KiB
invoke/log_8406fdd.js (sm.bdimg.com)	30 d	1 KiB
common/bannerConfig_eaabf68.js (sm.bdimg.com)	30 d	1 KiB
invoke/serverDatjs (sm.bdimg.com)	30 d	1 KiB
img/hanbaobao_04adf60.png (gss0.bdstatic.com)	30 d	1 KiB
invoke/setlvkCK_bb46616.js (sm.bdimg.com)	30 d	0 KiB

■ Reduce JavaScript execution time — 1.9 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. <u>Learn more</u>.

	Show 3rd-party	resources (0)
Total CPU Time	Script Evaluation	Script Parse
3,904 ms	913 ms	31 ms
825 ms	562 ms	152 ms
749 ms	6 ms	1 ms
307 ms	256 ms	6 ms
	CPU Time 3,904 ms 825 ms 749 ms	Total CPU Script Evaluation Time 3,904 ms 913 ms 825 ms 562 ms 749 ms 6 ms

■ Avoid chaining critical requests — 3 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn more.

Maximum critical path latency: 10,830 ms

Initial Navigation

https://www.baidu.com

...iconfont/iconfont_fcd5aba.woff (gss0.bdstatic.com) - 1,180 ms, 29.14 KiB

...fonts/n-icons_d083fee.ttf (sm.bdimg.com) - 690 ms, 42.23 KiB

...fonts/n-icons_7bcbf44.woff (sm.bdimg.com) - 9,890 ms, 0.00 KiB

■ Keep request counts low and transfer sizes small — 81 requests • 828 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. Learn more.

Resource Type	Requests	Transfer Size
Total	81	827.5 KiB
Script	43	357.7 KiB
Image	32	309.1 KiB
Document	1	89.0 KiB
Font	3	71.4 KiB
Other	2	0.4 KiB
Stylesheet	0	0.0 KiB
Media	0	0.0 KiB
Third-party	55	377.9 KiB

■ Largest Contentful Paint element — 1 element found

This is the largest contentful element painted within the viewport. Learn More

Element

div

<div class="skin-container" id="skin-container" style="backgroundcolor:#f1f1f1;background-image: url(https://search-operate.cdn...">

■ Avoid large layout shifts — 2 elements found

These DOM elements contribute most to the CLS of the page.

CLS Contribution

CLS Contribution

inline;">

用户反馈 使用百度前必读 Baidu 京ICP证030173号 京公网安备	
11000002000001号	0.153
<div id="bottom"></div>	
span	
<pre></pre>	

Avoid long main-thread tasks — 16 long tasks found

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. Learn more

✓ Show 3rd-party resources (2) Start **URL** Duration Time /?action=... (www.baidu.com) 7,890 ms 409 ms https://www.baidu.com 2,275 ms 368 ms ...wise/feedlist?sid=... (feed.baidu.com) 4,292 ms 347 ms ...tab/gettabinfo?pd=... (feed.baidu.com) 2,643 ms 274 ms https://www.baidu.com 1,343 ms 209 ms https://www.baidu.com 2,076 ms 156 ms https://www.baidu.com 1,928 ms 148 ms Unattributable 134 ms 1,794 ms ...package/newsActivity_f9b101c.js (sm.bdimg.com) 4,950 ms 125 ms https://www.baidu.com 1,691 ms 103 ms https://www.baidu.com 1,552 ms 95 ms ...personalcenter/pack_dd25317.js (gss0.bdstatic.com) 6,450 ms 87 ms /hm.js?12423ec... (hm.baidu.com) 6,632 ms 77 ms https://www.baidu.com 6,721 ms 75 ms https://www.baidu.com 2,940 ms 58 ms

Text-based resources should be served with compression (gzip, deflate or brotli) to

minimize total network bytes. Learn more.

Start

	Show 3rd-party resources (0)
URL	Transfer Potential Size Savings
tab/gettabinfo?pd= (feed.baidu.com)	2.9 KiB 2.6 KiB
Preconnect to required origins	^
Consider adding `preconnect` or `dns-prefetch` resoconnections to important third-party origins. Learn m	·
 Initial server response time was short — Root docu 	ment took 190 ms ^
Keep the server response time for the main docume requests depend on it. <u>Learn more</u> .	ent short because all other
	☐ Show 3rd-party resources (0)
URL	Time Spent
https://www.baidu.com	190 ms
Avoid multiple page redirects	^
Redirects introduce additional delays before the pag	je can be loaded. <u>Learn more</u> .
Preload key requests	^
Consider using ` <link rel="preload"/> ` to prioritize fetch requested later in page load. Learn more.	ning resources that are currently
Use video formats for animated content	^
Large GIFs are inefficient for delivering animated co MPEG4/WebM videos for animations and PNG/Web GIF to save network bytes. Learn more	· ·
Remove duplicate modules in JavaScript bundles	^
Remove large, duplicate JavaScript modules from b bytes consumed by network activity.	undles to reduce unnecessary

Avoid serving legacy JavaScript to modern browsers — Potential savings of 0 KiB

Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. Learn More

	☐ Show 3rd-party resources (0)
URL	Potential Savings
https://www.baidu.com	0.2 KiB
https://www.baidu.com:2:2570	<pre>@babel/plugin-transform- classes</pre>
/?action= (www.baidu.com)	0.1 KiB
/? action=:1:304876 (www.baidu. com)	<pre>@babel/plugin-transform- classes</pre>

Avoids enormous network payloads — Total size was 828 KiB

Large network payloads cost users real money and are highly correlated with long load times. <u>Learn more</u>.

	Show 3rd-party resources (7)
URL	Transfer Size
/?action= (www.baidu.com)	153.4 KiB
https://www.baidu.com	89.0 KiB
/e2c291bjpg (search-operate.cdn.bcebos.com)	69.9 KiB
fonts/n-icons_d083fee.ttf (sm.bdimg.com)	42.2 KiB
package/newsActivity_f9b101c.js (sm.bdimg.com)	35.9 KiB
iconfont/iconfont_fcd5aba.woff (gss0.bdstatic.com	29.1 KiB
img/spritelist_71904c7.png (gss0.bdstatic.com)	28.1 KiB
wise/feedlist?sid= (feed.baidu.com)	27.7 KiB

Uses passive listeners to improve scrolling performance

Consider marking your touch and wheel event listeners as `passive` to improve your page's scroll performance. Learn more.

Avoids document.write()

For users on slow connections, external scripts dynamically injected via `document.write()` can delay page load by tens of seconds. <u>Learn more</u>.

Avoid non-composited animations

Animations which are not composited can be janky and increase CLS. Learn more

Avoids large JavaScript libraries with smaller alternatives — 0 large libraries found ^
 Large JavaScript libraries can lead to poor performance. Prefer smaller, functionally equivalent libraries to reduce your bundle size. <u>Learn more</u>.



Accessibility

These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

Navigation — These are opportunities to improve keyboard navigation in your application.

▲ The page does not contain a heading, skip link, or landmark region

Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. <u>Learn more</u>.

```
Failing Elements
```

```
html
```

```
<html class="">
```

Contrast — These are opportunities to improve the legibility of your content.

▲ Background and foreground colors do not have a sufficient contrast ratio.

Low-contrast text is difficult or impossible for many users to read. Learn more.

Failing Elements

百度一下

```
<button id="index-bn" class="se-bn " type="submit">百度一下
```

置顶

```
<span class="rn-icon-hot">置顶</span>
```

人民日报

人民日报

置顶

```
<span class="rn-icon-hot">置顶</span>
```

人民日报

人民日报

中国青年报

中国青年报

全球精彩影评

全球精彩影评

小璐妈妈育儿

小璐妈妈育儿

大国将令

大国将令

另类电影魂

另类电影魂

秘数

秘数

Internationalization and localization — These are opportunities to improve the interpretation of your content by users in different locales.

▲ <html> element does not have a [lang] attribute

If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more.

Failing Elements

html

<html class="">

Names and labels — These are opportunities to improve the semantics of the controls in your application. This may enhance the experience for users of assistive technology, like a screen reader.

▲ Image elements do not have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u>.

Failing Elements

imq

<img src="https://ss0.bdstatic.com/9bA1vGfa2gU2pMbfm9GUKT-w/timg?
searchbox_feed&size=f218_146&quality=80&wh_rate=0&imgtype
=0&ref=http%3A%2F%2Fwww.baidu.com&sec=0&di=aae9386720c6c3a5fe
b2ea5cb501a6a3&src=http%3A%2F%2Ftukuimg.bdstatic.com%2Fprocessed%2F99
c6761ff86967edeba3536ddded503a.jpeg">

```
img
<img
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhnq/it/u=2739061647,1358898488&
amp;fm=173&amp;app=49&amp;f=JPEG?
w=312&amp;h=208&amp;s=EE145085101749D2069C7EB10300D084">
```

```
img
```

<ima

```
src="https://ss2.baidu.com/60NYsjip0QIZ8tyhnq/it/u=1905567401,1176013176&
amp;fm=173&app=49&f=JPEG?
w=312&h=208&s=E62B9247186B6F1D0A97C4A70300F01B">
```

```
img
<img
src="https://ss0.baidu.com/60NWsjip00IZ8tyhnq/it/u=3593144091,3571119686&
amp; fm=173& app=49& f=JPEG?
w=312& h=208& s=128869A4329B25D0018D19B20300D042">
img
<ima
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhnq/it/u=1821970710,1863820120&
amp;fm=173&app=49&f=JPEG?
w=312\& h=208\& s=FC5AE90BDE621C96FAB4100B0100E0C1">
img
<img
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhnq/it/u=1754727720,2852109151&
amp; fm=173& app=49& f=JPEG?
w=312&h=208&s=18934FD97E1B28C468AD002303008052">
img
<img
src="https://ss0.baidu.com/60NWsjip00IZ8tyhnq/it/u=2403482739,2129830554&
amp; fm=173& app=49& f=JPEG?
w=312\& h=208\& s=0080D95F4CFBE0DC0CA05C0A0100A0C1">
img
<imq src="https://ss0.bdstatic.com/9bA1vGfa2gU2pMbfm9GUKT-w/timg?</pre>
searchbox_feed&size=f218_146&quality=80&wh_rate=0&imgtype
=0& ref=http%3A%2F%2Fwww.baidu.com& sec=0& di=38fbfd849da2eee8b2
23b30fa1c7debb&src=http%3A%2F%2Ftukuimg.bdstatic.com%2Fprocessed%2F33
35d68403e971debb34cfe6252d37f0.jpeg">
img
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhnq/it/u=315546849,1717031941&a
mp;fm=173&app=49&f=JPEG?
w=312\& h=208\& s=671A1CC7567321980480C4A30300F043">
img
src="https://ss2.baidu.com/60NYsjip0QIZ8tyhnq/it/u=1864175015,662404045&a
mp; fm=173& app=49& f=JPEG?
w=312\& h=208\& s=7F91A844AE8322C6A68D789E0100C090">
img
<img
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhng/it/u=1785244956,385101573&a
mp; fm=173& app=49& f=JPEG?
w=312& h=208& s=AEC1E05CD4B6BF9A4E711B4F0300E0E6">
```

Form elements do not have associated labels

Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more.

Failing Elements

input

<input type="search" autocomplete="off" autocorrect="off" maxlength="64"
id="index-kw" name="word" class="se-input adjust-input is-beforecallicon" data-sa="" data-sug="1">

Links do not have a discernible name

Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn more.

Failing Elements

```
a
<a class="square-enterance " data-tclog=""
href="https://m.baidu.com/l=1/tc?
logid=3694530742&amp;from=844b&amp;ref=index_iphone&amp;nsrc=IlPT2AEptyoA
_yixCF0xCGZb8c3JV3T5ABfPNy6R2iv5nk_qva02FMNsUiH5Nn_KJoCa9m3BdMZ0bmGcWyNnn</pre>
```

Best practices — These items highlight common accessibility best practices.

[user-scalable="no"] is used in the <meta name="viewport"> element or the [maximum-scale] attribute is less than 5.

1E2e_& bdenc=1& ct=10& cst=2& logFrom=navs_square">

Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. <u>Learn more</u>.

Failing Elements

meta

<meta name="viewport" content="width=device-width,minimumscale=1.0,maximum-scale=1.0,user-scalable=no">

automated testing tool cannot cover. Learn more in our guide on <u>conducting an accessibility review</u>.

The page has a logical tab order	^
Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more</u> .	at
Interactive controls are keyboard focusable	^
Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn more</u> .	
Interactive elements indicate their purpose and state	^
Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn more</u> .	
The user's focus is directed to new content added to the page	^
If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn more</u> .)
User focus is not accidentally trapped in a region	^
A user can tab into and out of any control or region without accidentally trapping the focus. <u>Learn more</u> .	ir
Custom controls have associated labels	^
Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more</u> .	
Custom controls have ARIA roles	^
Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
Visual order on the page follows DOM order	^
DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	
Offscreen content is hidden from assistive technology	^
Offscreen content is hidden with display: none or aria-hidden=true. Learn more.	
HTML5 landmark elements are used to improve navigation	^

Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology. <u>Learn more</u>.

Passed audits (7) [aria-hidden="true"] is not present on the document <body> Assistive technologies, like screen readers, work inconsistently when `ariahidden="true" is set on the document `<body>'. Learn more. Buttons have an accessible name When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. Learn more. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. [id] attributes on active, focusable elements are unique All focusable elements must have a unique `id` to ensure that they're visible to assistive technologies. Learn more. Lists contain only <1i> elements and script supporting elements (<script> and <template>). Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more. List items () are contained within or parent elements Screen readers require list items (`') to be contained within a parent ` `or

`` to be announced properly. Learn more.

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u>.

Not applicable (27)

[accesskey] values are unique

Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. <u>Learn more</u>.

[aria-*] attributes match their roles

Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. <u>Learn more</u>.

[aria-hidden="true"] elements do not contain focusable descendents

Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn more.

ARIA input fields have accessible names

When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

[role]s have all required [aria-*] attributes

Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more.

Elements with an ARIA [role] that require children to contain a specific [role] have all required children.

Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. <u>Learn more</u>.

[role]s are contained by their required parent element

Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more.

[role] values are valid

ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more.

ARIA toggle fields have accessible names

When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u>.

[aria-*] attributes have valid values

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. <u>Learn more</u>.

[aria-*] attributes are valid and not misspelled

Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. <u>Learn more</u>.

<dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template>
or <div> elements.

When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. <u>Learn more</u>.

Definition list items are wrapped in <dl> elements

Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. <u>Learn more</u>.

ARIA IDs are unique

The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn more.

No form fields have multiple labels

Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn more.

Screen reader users rely on frame titles to describe the contents of frames. <u>Learn</u> more.

Heading elements appear in a sequentially-descending order

Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. <u>Learn more</u>.

<html> element has a valid value for its [lang] attribute

Specifying a valid <u>BCP 47 language</u> helps screen readers announce text properly. Learn more.

<input type="image"> elements have [alt] text

When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. Learn more.

Presentational elements avoid using , <caption> or the [summary] attribute.

A table being used for layout purposes should not include data elements, such as the thor caption elements or the summary attribute, because this can create a confusing experience for screen reader users. <u>Learn more</u>.

The document does not use <meta http-equiv="refresh">

Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u>.

<object> elements have [alt] text

Screen readers cannot translate non-text content. Adding alt text to `<object>` elements helps screen readers convey meaning to users. <u>Learn more</u>.

Cells in a element that use the [headers] attribute refer to table cells within the same table.

Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. <u>Learn more</u>.

elements and elements with [role="columnheader"/"rowheader"] have data
cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more.

[lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn more</u>.

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.

Audio descriptions provide relevant information for videos that dialogue cannot, such as facial expressions and scenes. <u>Learn more</u>.



Best Practices

Trust and Safety

▲ Links to cross-origin destinations are unsafe

Add `rel="noopener"` or `rel="noreferrer"` to any external links to improve performance and prevent security vulnerabilities. <u>Learn more</u>.

Failing Anchors

```
京公网安备11000002000001号
```

<a class="recordcode"
href="http://www.beian.gov.cn/portal/registerSystemInfo?
recordcode=11000002000001" target="_blank">

General

Registers an unload listener The 'unload' event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Consider using the 'pagehide' or `visibilitychange` events instead. Learn More □ Show 3rd-party resources (0) **URL** (unknown) /hm.js?12423ec...:53:40 (hm.baidu.com) Browser errors were logged to the console Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more Show 3rd-party resources (4) URL Description /elog/glog?productId=... Failed to load resource: (als.baidu.com) net::ERR_BLOCKED_BY_CLIENT.Inspector /?data=fCMxlzsjM... Failed to load resource: %2BPiMtIzM...%2B (127.0.0.1) net::ERR CONNECTION FAILED /a27e7df71036d80c.js (hectorstatic Failed to load resource: .baidu.com) net::ERR TIMED OUT ...fonts/n-Failed to load resource: icons_7bcbf44.woff (sm.bdimg.com net::ERR TIMED OUT Failed to load resource: amd_modules/ralltiir_6ae1e84.js (net::ERR TIMED OUT sm.bdimg.com) ...@baidu/get-app-Failed to load resource: info_2747ad8.js (sm.bdimg.com) net::ERR TIMED OUT

Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <u>mixed content</u>, where some resources are loaded over HTTP despite the initial request being servedover HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more.

Avoids requesting the geolocation permission on page load

Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. <u>Learn more</u>.

Avoids requesting the notification permission on page load

Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. <u>Learn more</u>.

Avoids front-end JavaScript libraries with known security vulnerabilities

Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. <u>Learn more</u>.

Allows users to paste into password fields

Preventing password pasting undermines good security policy. Learn more.

Displays images with correct aspect ratio

Image display dimensions should match natural aspect ratio. Learn more.

Serves images with appropriate resolution

Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. <u>Learn more</u>.

Page has the HTML doctype

	more.		
•	Properly defines charset		^
	A character encoding declaration is require first 1024 bytes of the HTML or in the Conmore.	· ·	
•	Avoids Application Cache		^
	Application Cache is deprecated. Learn m	ore.	
•	Detected JavaScript libraries		^
	All front-end JavaScript libraries detected	on the page. <u>Learn more</u> .	
	Name	Version	
	Zepto.js		
	Vue		
•	Avoids deprecated APIs		^
	Deprecated APIs will eventually be remove	ed from the browser. <u>Learn more</u> .	
•	Page has valid source maps		^
	Source maps translate minified code to the developers debug in production. In additio insights. Consider deploying source maps more.	n, Lighthouse is able to provide further	<u>rn</u>
No	t applicable (1)		^
	Fonts with font-display: optional are p	reloaded	^
	Preload `optional` fonts so first-time visitor	s may use them. <u>Learn More</u>	

Specifying a doctype prevents the browser from switching to quirks-mode. <u>Learn</u>



These checks ensure that your page is optimized for search engine results ranking. There are additional factors Lighthouse does not check that may affect your search ranking. <u>Learn more</u>.

Crawling and Indexing — To appear in search results, crawlers need access to your app.

▲ Links are not crawlable

Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. Learn More

Uncrawlable Link

举报/反馈

Page is blocked from indexing

Search engines are unable to include your pages in search results if they don't have permission to crawl them. <u>Learn more</u>.

Blocking Directive Source

/robots.txt:165:0 (www.baidu.com)

Content Best Practices — Format your HTML in a way that enables crawlers to better understand your app's content.

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more.

Failing Elements

```
img
```

```
<img src="https://ss0.bdstatic.com/9bA1vGfa2gU2pMbfm9GUKT-w/timg?
searchbox_feed&amp;size=f218_146&amp;quality=80&amp;wh_rate=0&amp;imgtype
=0&amp;ref=http%3A%2F%2Fwww.baidu.com&amp;sec=0&amp;di=aae9386720c6c3a5fe
b2ea5cb501a6a3&amp;src=http%3A%2F%2Ftukuimg.bdstatic.com%2Fprocessed%2F99
c6761ff86967edeba3536ddded503a.jpeg">
```

```
img
<img
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhnq/it/u=2739061647,1358898488&
amp;fm=173&amp;app=49&amp;f=JPEG?
w=312&amp;h=208&amp;s=EE145085101749D2069C7EB10300D084">
```

img

```
<img
src="https://ss2.baidu.com/60NYsjip0QIZ8tyhnq/it/u=1905567401,1176013176&
amp;fm=173&amp;app=49&amp;f=JPEG?
w=312&amp;h=208&amp;s=E62B9247186B6F1D0A97C4A70300F01B">
```

img

img

```
<img
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhnq/it/u=1821970710,1863820120&
amp;fm=173&amp;app=49&amp;f=JPEG?
w=312&amp;h=208&amp;s=FC5AE90BDE621C96FAB4100B0100E0C1">
```

```
img
<img
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhnq/it/u=1754727720,2852109151&
amp;fm=173&amp;app=49&amp;f=JPEG?
w=312&amp;h=208&amp;s=18934FD97E1B28C468AD002303008052">
```

img

```
<img
src="https://ss0.baidu.com/60NWsjip0QIZ8tyhnq/it/u=2403482739,2129830554&
amp;fm=173&amp;app=49&amp;f=JPEG?
w=312&amp;h=208&amp;s=0080D95F4CFBE0DC0CA05C0A0100A0C1">
```

Failing Elements

imq <img src="https://ss0.bdstatic.com/9bA1vGfa2gU2pMbfm9GUKT-w/timg?</pre> searchbox feed&size=f218 146&quality=80&wh rate=0&imgtype =0& ref=http%3A%2F%2Fwww.baidu.com& sec=0& di=38fbfd849da2eee8b2 23b30fa1c7debb&src=http%3A%2F%2Ftukuimg.bdstatic.com%2Fprocessed%2F33 35d68403e971debb34cfe6252d37f0.jpeg"> imq img img

Mobile Friendly — Make sure your pages are mobile friendly so users don't have to pinch or zoom in order to read the content pages. <u>Learn more</u>.

■ Tap targets are not sized appropriately — 93% appropriately sized tap targets

Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. Learn more.

Tap Target Size Overlapping Target

Tap Target	Size	Overlapping Target
使用百度前必读 Baidu 京ICP证030173号 <a ;pageid='6"' =false&bw="44FA5F3AF2" ?="" data-="" f4bd2c497dbfaf41665f2a&a="" href="https://m.baidu.com/sf? pd=sd_privacy_terms&ms=1&ms=1 &word=%E5%85%8D%E8%B4%A3%E5%A3%B0 %E6%98%8E&title=%E5%85%8D%E8%B4%A 3%E5%A3%B0%E6%98%8E&openapi=1& ;from_sf=1&resource_id=37483& dsp=iphone&tn=wisexmlnew&ext= %7B%22pid%22%3A%22mianze</td><td>304x26</td><td>用户反馈 <i class="icon- feedback"></i>用户反馈 		
使用百度前必读 Baidu 京ICP证030173号 <i></i>京公网安备 11000002000001号		

Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices.

Structured data is valid

Run the <u>Structured Data Testing Tool</u> and the <u>Structured Data Linter</u> to validate structured data. Learn more.

Passed audits (9)

	more.				
•	Document has	a <title> element</th><th></th><th></th><th>^</th></tr><tr><th></th><th>•</th><th>screen reader users an overview
heavily to determine if a page is</th><th></th><th></th><th>•</th></tr><tr><th>•</th><th>Document has</th><th>a meta description</th><th></th><th></th><th>^</th></tr><tr><th></th><th>Meta description content. <u>Learn</u></th><th>ons may be included in search remore.</th><th>sults t</th><th>o concisely summariz</th><th>e page</th></tr><tr><th>•</th><th>Page has succ</th><th>essful HTTP status code</th><th></th><th></th><th>^</th></tr><tr><th></th><th>Pages with uns</th><th>successful HTTP status codes m</th><th>ay not</th><th>be indexed properly.</th><th><u>Learn</u></th></tr><tr><th>•</th><th>Links have des</th><th>scriptive text</th><th></th><th></th><th>^</th></tr><tr><th></th><th>Descriptive link</th><th>text helps search engines unde</th><th>rstand</th><th>your content. <u>Learn r</u></th><th>more.</th></tr><tr><th>•</th><th colspan=3>robots.txt is valid</th><th>^</th></tr><tr><th></th><th>-</th><th>xt file is malformed, crawlers ma
site to be crawled or indexed. <u>Le</u></th><th></th><th></th><th>how you</th></tr><tr><th>•</th><th>Document has</th><th>a valid hreflang</th><th></th><th></th><th>^</th></tr><tr><th></th><th>· ·</th><th>ell search engines what version
ven language or region. <u>Learn m</u></th><th>•</th><th>age they should list in</th><th>search</th></tr><tr><th>•</th><th>Document uses</th><th>s legible font sizes — 94.3% leg</th><th>jible te</th><th>ext</th><th>^</th></tr><tr><th></th><th colspan=2>Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. <u>Learn</u> more.</th><th></th></tr><tr><th></th><th></th><th></th><th></th><th>Show 3rd-party res</th><th>sources (0)</th></tr><tr><th></th><th>Source</th><th>Selector</th><th></th><th>% of Page
Text</th><th>Font Size</th></tr><tr><th></th><th>dynamic</th><th>.readme[data-a-1163fdae]</th><th></th><th>3.28%</th><th>10.8px</th></tr></tbody></table></title>			

Add a `<meta name="viewport">` tag to optimize your app for mobile screens. Learn

Source	Selector	% of Page Text	Font Size
dynamic	<pre>.rn-typeSmallVideo .rn-wise-icon- pics</pre>	2.07%	10px
dynamic	.setter-text[data-a-1163fdae]	0.35%	10.8px
Legible		94.30%	≥ 12px

Document avoids plugins

Search engines can't index plugin content, and many devices restrict plugins or don't support them. <u>Learn more</u>.

Not applicable (1)

Document has a valid rel=canonical

Canonical links suggest which URL to show in search results. Learn more.



Progressive Web App

These checks validate the aspects of a Progressive Web App. <u>Learn more</u>.

Fast and reliable

Page load is fast enough on mobile networks

A fast page load over a cellular network ensures a good mobile user experience. Learn more.

Current page does not respond with a 200 when offline

If you're building a Progressive Web App, consider using a service worker so that your app can work offline. <u>Learn more</u>.

start_url does not respond with a 200 when offline

No usable web app manifest found on page.

A service worker enables your web app to be reliable in unpredictable network conditions. Learn more.

Installable

Uses HTTPS

All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding <u>mixed content</u>, where some resources are loaded over HTTP despite the initial request being servedover HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more.

▲ Does not register a service worker that controls page and start_url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

Web app manifest does not meet the installability requirements

Failures: No manifest was fetched.

Browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u>.

PWA Optimized

▲ Does not redirect HTTP traffic to HTTPS

If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <u>Learn more</u>.

Is not configured for a custom splash screen Failures: No manifest was fetched. A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. Learn more. Does not set a theme color for the address bar. Failures: No manifest was fetched, No `<meta name="theme-color">` tag found. The browser address bar can be themed to match your site. Learn more. Content is sized correctly for the viewport If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. Learn more. ● Has a <meta name="viewport"> tag with width or initial-scale Add a `<meta name="viewport">` tag to optimize your app for mobile screens. Learn more. Contains some content when JavaScript is not available Your app should display some content when JavaScript is disabled, even if it's just a warning to the user that JavaScript is required to use the app. Learn more. Provides a valid apple-touch-icon Warnings: `apple-touch-icon-precomposed` is out of date; `apple-touch-icon` is preferred. For ideal appearance on iOS when users add a progressive web app to the home screen, define an 'apple-touch-icon'. It must point to a non-transparent 192px (or 180px) square PNG. Learn More. Manifest doesn't have a maskable icon No manifest was fetched A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. Learn more. Additional items to manually check (3) — These checks are required by the baseline ^ PWA Checklist but are not automatically checked by Lighthouse. They do not affect your

score but it's important that you verify them manually.

Site works cross-browser

To reach the most number of users, sites should work across every major browser. Learn more.

Page transitions don't feel like they block on the network

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. <u>Learn more</u>.

Each page has a URL

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. <u>Learn more</u>.

Runtime Settings

URL	https://www.baidu.com/
Fetch Time	Feb 13, 2021, 10:35 AM GMT+8
Device	Emulated Moto G4
Network throttling	Unknown
CPU throttling	Unknown
Channel	Ir
User agent (host)	Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) HeadlessChrome/85.0.4183.140 Safari/537.36
User agent (network)	Mozilla/5.0 (Linux; Android 7.0; Moto G (4)) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/84.0.4143.7 Mobile Safari/537.36 Chrome- Lighthouse
CPU/Memory Power	788