


Lecture 1: Introduction

Hossein Asadi (asadi@sharif.edu)

Rasool Jalili (jalili@sharif.edu)



Fall 2024



Today's Topics

- Course Introduction
- Class Policy
- Course Syllabus & Objective
- Introduction to Operating System





Course Introduction

■ Instructor: Hossein Asadi

■ Classes

- Sun. & Tuesday: 10:30 ~ 12:00

- ▶ Attend class on time

- We may use vclass: <https://vc.sharif.ir/jalili>

■ Office Hours

- Can be reached by email or stop by my office

- Emails: jalili@sharif.edu

- ▶ Sat. through Wed.: 9AM ~ 6PM

■ TA Classes

- TBD





Course Introduction (cont.)

■ Course Webpage on CW

- Check this webpage on regular basis
 - ▶ At least on Sun, Tue, Thur
 - ▶ Q&A only using CW forums
- Everything will be posted on CW
 - ▶ Announcements, handouts, assignments, grades, quiz and exam notices, tutorials, simulators, ...
- Handouts
 - ▶ Will be posted a day before class
 - Print it & bring it to class
 - ▶ But I may update it after class
 - Check out submission date of handouts





Few Notes on Assignments

- Post All your Questions on CW Forums
 - Check forum history before posting any question
- Be Respectful to your Classmates and TAs
- Harsh Cheating Penalty





Teaching Assistants





Textbook

- Operating System Concepts, 8th (or 9th) Edition, Wiley publishing
 - By A. Silberschatz, P. Galvin, & G. Gagne
- Other References:
 - Operating systems: design & implementation, by A. Tanenbaum and A. Woodhull, 3rd edition, 2006.
 - Operating systems: internals and design principles, by W. Stallings, 5th edition, 2005.





Syllabus

■ Introduction to Operating Systems

- OS basic concepts
 - ▶ Multi-programming, interrupt-driven OS
 - ▶ Dual-mode, process hugging
- OS structure & operations

■ System Structure

- OS services
- System calls
- OS design & implementation
- Virtual machines





Syllabus (cont.)

■ Process Management

- Process concept
- Interprocess communication
- Multithread models
- Threading libraries & issues
- Process scheduling
- Scheduling criteria & algorithms
- Threading scheduling
- Synchronization (HW & SW solutions)
- Semaphores
- Deadlocks (prevention, avoidance, detection, & recovery)





Syllabus (cont.)

■ Memory Management

- Swapping
- Memory allocation
- Paging
- Page table
- Segmentation





Syllabus (cont.)

■ Virtual-Memory Management

- Demand paging
- Copy-on-write
- Page replacement
- Allocation of frames
- Trashing
- Allocating kernel memory
- OS examples





Syllabus (cont.)

■ Storage Management

- Structure of SSDs and HDDs
- File system
- Implementing file systems
- I/O systems





Syllabus (cont.)

- Real-Time OSs
 - Real-time scheduling
 - Real-time kernels
- Protection & Security





Class Policy

- Ask Questions Anytime
 - Don't hesitate to ask even stupid questions!!!
- Cell Phones off or on Silent
- Absence
 - Three sessions allowed
- Food No, Water yes!
- Feel Free to Pass Me Your Feedbacks
 - Anything related to this course





Class Policy (cont.)

■ Assignments

- Three late assignments will be accepted!
 - ▶ Only two days late!
 - ▶ Fourth late assignment (two-day late)
 - HW will be graded out of 50%
 - ▶ Fifth and next late assignments will not be accepted!
- Discussions encouraged!
- But do your own handwriting!
- Zero score for copied assignments!
 - ▶ Second time zero score for 30% share!





Objective

- Understand Major Components of OSs
- Describe Various Ways of Structuring an OS
- Describe Various Features & Operations of Processes including Scheduling, Creation, Termination, & Communication
- Understand Thread and its Issues
- Describe Various CPU-Scheduling Algorithms
- Good Understanding of Evaluation Criteria to Select a CPU-Scheduling Algorithm for a System
- Learn Concept of Atomic Transaction
- Learn How to Ensure Consistency of Shared Data





Objective (cont.)

- Learn How to Prevent Deadlocks in a OS
- Learn Various Ways of Organizing Memory
- Understand Various Memory Management Techniques
- Learn Virtual-Management Techniques
- Understand Functions and Interface of File Systems
- Be Able to Explain Structure of an OS I/O Subsystem





Grading

- Midterm Exam: 25%
 - Ordibehesht 1404, 7th.
- Final Exam: 35% (as posted in EDU)
- Random (Unscheduled) Quizzes:
- Assignments & Project:
 - Bonus points for outstanding projects
- Exams Covers Topics of Lecture Classes and TA Classes





Copyright Notice

- Slides Mainly Adopted from Suggested Slides of Main Textbook.





Lecture 1: Introduction

■ Quick Overview and Review

- What operating systems do
- Computer-system organization
- Computer-system architecture
- Operating-system structure
- Operating-system operations
- Process management
- Memory management
- Storage management
- Protection and security
- Open-source operating systems





Objectives of this Lecture


- To Describe Basic **Organization** of **Computer systems**
- To Elaborate Basic Concepts
 - Multi-programming
 - Dual-mode
- To Provide a Grand Tour of **Major Components** of Operating Systems
- To Review **Open-Source** Operating Systems





General Picture

■ Computer Abstraction Levels



**Almost
Nearest SW
Layer to ISA**





What is an Operating System?

- A Program that Acts as an Intermediary between a **User** of a Computer and **Computer HW**
 - Acts as a **governor**
- Operating System Goals:

Execute user **programs** and make solving user problems easier

Allow **multiple programs** to simultaneously be executed in a **shared HW**

Use computer **HW** in an **efficient** manner

Make computer system **convenient** to use





OS: Mandatory or Optional?

■ Important Question:

- Can a computer run without an operating system?

■ Answer:

- Yes, earliest computers didn't have any OS

■ Another Question:

- What does a **computer without an OS** look like?

■ Answer:

- Machines tasked with one program at a time
 - ▶ Cannot look at a doc and keep a clock running on your desktop
- Each program has a lot of work to do
 - ▶ Where to load a program
 - ▶ IO access





Computer System Structure



- **HW**

- ▶ Provides basic computing resources
- ▶ CPU, memory, storage, and I/O devices

- **OS**

- ▶ Controls and coordinates use of HW among various applications and users

- **Application & System Programs**

- ▶ Define ways in which system resources used to solve computing problems of users
- ▶ Word processors, compilers, web browsers, database systems, video games


- **Users**

- ▶ People, machines, other computers





Components of a Computer System





The Role of Operating Systems

- Let's Start Designing & Implementing an Operating System
- Important Question:
 - Major parameters in which we would like to optimize OS towards to?
- To Answer this Question:
 - We need to take a look at the role of OS from two perspectives





The Role of Operating Systems (cont.)



- **Depends on the Point of View**
 - Users view or system view
- Users want Convenience, **Ease of Use**
 - **Throughput** not important
 - **Latency** is, however, of importance
 - **Don't care** about **resource utilization**
- Shared Computer such as **Mainframe** or **Minicomputer** must keep all users happy
 - Resource utilization
 - Fair share between all users





The Role of Operating Systems (cont.)



■ Also Depends on Type of System Usage

- Embedded, desktop, high-performance computing
 - ▶ Objectives: power, performance, ease of use, utilization, real-time, reliability, etc
- Users of dedicated systems such as **workstations** have **dedicated** resources but frequently use **shared resources** from **servers**
➔ **Compromise** between individual usability & resource utilization
- **Handheld** computers are resource poor, optimized for **usability** and **battery life**
- Some have **Little** or **No User Interface**
 - ▶ E.g. embedded computers in devices & automobiles





The Role of OS: System View



■ OS is a **Resource Allocator**

- Possible **resources** include CPU time, memory space, file-storage space, I/O devices, etc.
- Manages all resources
- **How, when, and for how long** allocate resources to programs and users
- Decides between **conflicting** requests for efficient and fair resource use

■ OS is a **Control Program**

- Controls execution of programs to **prevent errors and improper use** of computer





Operating System Story

- **Fundamental Goal** of a Computer System
 - Execute user programs and to make solving user problems easier
- ➔ **Computer HW Constructed**
 - HW alone **not easy** to use
 - ➔ Application programs developed
 - Application programs require certain **common operations** such as those controlling I/O devices
- **Finally:**
 - Common functions of controlling and allocating resources **brought** together into **one piece** ➔ called **OS**





Operating System Definition



- No Universally Accepted Definition
- “Everything a **Vendor Ships** when you Order an OS” is a Good Approximation
 - But varies wildly (from **1MB** to **GBs**)
- “The one Program Running at All Times on the computer” is **Kernel**.
- Everything else is either:
 - A **system** program (ships with OS)
 - ▶ File management programs, loader, linker, compiler
 - An **application** program





Computer Startup

■ Question:

- Can we think of any SW layer lower than OS?

■ Another Question:

- OS resides in disk. How it can be executed?
- Remember **stored program** concept





Computer Startup (cont.)



■ Bootstrap Program


- Loaded at Power-Up/Reboot
- Typically stored in ROM or EPROM, generally known as **firmware**
- **Initializes** all aspects of a system
 - ▶ Such as CPU registers, device controllers
- **Loads** OS kernel and starts execution
- OS then **starts executing** first process





Computer Startup (cont.)

■ Bootstrap Program (Linux Example)



© <https://www.geeksforgeeks.org/how-linux-kernel-boots/>







Baseboard Management Controller (BMC)

■ BMC Role

- Small computer that sits on every server MB
- Typically ARM-based SoC with GUI and built-in logic




© <https://www.servethehome.com>

management-controller-or-bmc-in




Baseboard Management Controller (BMC)

BLOCK DIAGRAM





BIOS to OS Initialization





The Rest of This Lecture

■ An Overview on Computer Structure

- Computer system organization
- Interrupt
- Storage structure
- Caching
- DMA
- BMC
- Computer system architecture
 - ▶ Multi-processors






Computer System Organization

■ Computer-System Operation

- One or more CPUs, device controllers connect through common bus providing access to shared memory
- **Concurrent execution** of CPUs and devices competing for memory cycles





Computer-System Operation

- Each Device Controller is in Charge of a Particular Device Type (e.g., disk drives, audio devices)
- Each Device Controller has a Local Buffer
- I/O: Device \longleftrightarrow Local Buffer of Controller
- Device Controller Informs CPU
 - That it has finished its operation by causing an interrupt
- CPU Moves Data
 - Main memory \longleftrightarrow Local buffers






I/O & Device Driver

■ Device Driver

- Alleviates complexity of I/O devices from Kernel
- For each device controller to manage I/O
- Provides uniform interface (controller ↔ kernel)
- Device ↔ Device controller (local buffer)
- Device controller ↔ Device driver
 - Device driver is informed by an interrupt
- Device driver ↔ Kernel





Common Functions of Interrupts



- Interrupt Transfers Control to Interrupt Service Routine
 - Generally, through **interrupt vector**, which contains addresses of all service routines
- Must Save Address of Interrupted Instruction
- A **Trap** or **Exception**
 - A SW-generated interrupt caused either by an **error** or a User Request (aka, **system call**)






Interrupt Handling

- OS Preserves State of CPU by Storing Registers and Program Counter (PC)
- Determines which Type of Interrupt has Occurred
- Different Segments of Code Determine what Action Should be Taken for Each Type of Interrupt





Interrupt Timeline





Storage Structure

- **Main Memory** – **only** large storage media that CPU can access **directly**
 - **Random access** and typically **volatile**
 - **Exception: Intel Optane DIMMs (also called, NVDIMMs)**
- **Secondary Storage**
 - Extension of main memory that provides large **nonvolatile** storage capacity
 - Hard Disk Drives (HDDs)
 - **Solid-State Drives (SSD)**
 - Faster than HDDs, non-volatile
- **Tertiary Storage**
 - Optical disk
 - Magnetic tape





Storage Hierarchy

- Storage Systems Organized in Hierarchy
 - Ideal storage → inexpensive, fast, non-volatile
 - Ranked based on Speed, cost, & volatility
- Caching
 - Information in use copied from slower to faster storage temporarily
 - Performed at various levels: HW, OS, & application
 - Example: main memory as a cache for secondary storage

Application
OS
HW






Caching

- Faster Storage (cache) Checked First
 - To determine if information is there
 - **If it is**, information used directly from cache (fast)
 - **If not**, data copied to cache and used there
- Cache is Smaller than Storage being Cached → Issues?
 - Cache **management** important design problem
 - Cache **size** and **replacement** policy





Storage-Device Hierarchy





Direct Memory Access Structure




- Used for High-Speed I/O Devices
 - Able to transmit info at close to memory speeds
- Device Controller Transfers Data Blocks
 - From buffer storage directly to main memory without CPU intervention
- Only one Interrupt is Generated per Block
 - Rather than one interrupt per byte





How a Modern Computer Works



A von Neumann architecture





Computer-System Architecture



■ Single General-Purpose Processor

- Commonly used in **embedded** and **thin clients**
- Most systems have special-purpose processors as well

■ Multiprocessors Systems

- Growing in use and importance
- Mainly used in **server-class** systems
- A.k.a **parallel systems, tightly-coupled systems**
- Advantages include:
 1. **Increased throughput**
 2. **Economy of scale**
 3. **Increased reliability** – graceful degradation or fault tolerance





Computer-System Architecture (cont.)


■ Multiprocessors Systems

- **Asymmetric Multiprocessing**
 - Each processor is assigned a specific task
 - Master/slave model
 - Master: schedules and allocates work to slave processors
- **Symmetric Multiprocessing (SMP)**
 - Each processor performs all tasks
 - All processors are peers
 - No Master-slave relationship





Symmetric Multiprocessing Architecture




- N CPUs → N concurrent processes
- Share physical memory





A Dual-Core Design

- **Multi-chip vs. Multicore**
- **Early Trend: Multi-Chip Processors**
- **Current Trend: Multicore**
 - **Faster communications between cores**
 - **More energy efficiency**
 - **No difference from OS perspective**





Back to OS Concepts

- Multi-Programming vs. Multi-Tasking
- Interrupt Driven OS
- Dual Mode in OS
- Process Hogging (Infinite Loop)





Operating System Structure



■ Multiprogramming (Batch system)

- Aimed at improving system efficiency
- Single user cannot keep CPU and I/O devices busy at all times
- Multiprogramming organizes jobs (code and data) so CPU always has one to execute
- Job pool: all jobs waiting to be executed reside either in disk or memory
 - A subset of total jobs in system is kept in memory
- When it has to wait (for I/O, e.g.), OS switches to another job
 - Non-multiprogrammed system → CPU sits idle





■ Multiprogrammed System

- Provides environment to effectively utilize resources
- Does not provide user interaction

■ Timesharing (Multitasking)

- Logical extension of multi-programmed
- CPU switches jobs so frequently that users can interact with each job → creating **interactive** computing
- **Response time** should be < 1 second
 - ▶ Each user is given impression that entire computer system is dedicated to his/her use





■ Timesharing (Multitasking)

- **Process:** A program loaded into memory and executing
 - ▶ A process executes for only a short time before it either finishes or needs to perform I/O

■ Fact:

- Time sharing and multiprogramming requires several jobs be kept in main memory
- **Job scheduling:** Decides which job to be brought to memory (Lec. 6)
- **CPU scheduling:** Decides which job to be executed (Lec. 5)





■ Timesharing (Multitasking)


- If processes don't fit in memory, **swapping** moves them in and out to run (Lec. 6)
- **Virtual memory** allows execution of processes not completely in memory (Lec. 7)
 - ▶ Separates **logical memory** (as viewed by users) from **physical memory**






Multiprogramming vs. Multitasking vs. Multiprocessing


Single Processing Non-Multi-programmed



Multiprocessing




Single Processing Multi-Programming



Single Processing Multi-Tasking




Multi-Processing Multi-Tasking





Memory Layout for Multiprogrammed System





Operating-System Operations



■ Modern OS are **Interrupt Driven**

- No process to execute → No I/O devices to service and no users to whom to respond → OS will sit **idle** and wait for sth to happen, i.e., **interrupt**
- Events are signaled by occurrence of an interrupt

■ **Interrupts**

- Hardware driven
- Software driven





Operating-System Operations (cont.)



- Hardware Interrupt by One of Devices
 - Disk drive, NIC, printer, and others
- Software Interrupt (**Exception** or **Trap**)
 - Software error
 - ▶ Division by zero
 - ▶ Invalid memory access
 - ▶ Access to kernel address space
 - Request for OS service from a user program
 - Other process problems
 - ▶ Infinite loop
 - ▶ Processes modifying each other or OS






Operating-System Operations (cont.)



- OS Needs to Manage All System Resources
 - It needs some kind of **privileged instructions only** executable by OS
- How **Privileged** vs. **Non-Privileged** Instructions could be distinguished by CPU?
 - HW Technique (?)
 - SW Technique (?)





Operating-System Operations (cont.)

■ **Dual-Mode** Operation Allows OS to **Protect** itself and Other System Components

- **User mode** and **kernel mode**

- **Kernel mode: aka, supervisor, system, privileged mode**

■ **Mode Bit**

- Provided by HW: kernel (0) or user (1)
- Ability to **distinguish** when code running in **user** or **kernel**

■ **System call**

- Changes mode to kernel, return from call resets to user
- At system boot time: HW starts in kernel mode

■ **3 Types of events to change from **user** to **kernel****

- a) System call, b) exception, c) interrupt





Operating-System Operations (cont.)

■ Main Aim of Dual-Mode Operation

- Protecting OS from errant users
- Some instructions may cause harm → designate such instructions as privileged instructions
 - Only executable in kernel mode
- Privileged instructions cannot be executed in user mode
 - Treated as illegal and traps it to OS interrupts
- Examples of privileged instructions
 - ❑ Switching to kernel mode
 - ❑ I/O control
 - ❑ Setting the timer
 - ❑ Interrupt management
 - ❑ Clearing memory
 - ❑ Remove process from memory





Operating-System Operations (cont.)




■ Flow of a System Call

- Treated as a SW interrupt
- → Control passes through interrupt vector to a service routing in the OS
- → Mode bit = 0 (kernel mode)
- → Kernel examines interrupting instruction to determine type of interrupt
- → Additional information may be found in RF or stack
- → Kernel verifies passed parameters
- → System call is executed
- → Control passed to instruction following system call
- → Mode bit =1 (user mode)





Operating-System Operations (cont.)



■ Two Important Questions:

- Is a system call instruction to switch to kernel mode a privileged or non-privileged instruction?
- Is a direct instruction to switch to kernel mode a privileged or non-privileged instruction?

(c) <https://www.codingninjas.com/codestudio/library/privileged-and-non-privileged-instructions>





Operating-System Operations (cont.)

■ Lack of HW-Supported Mode

- → Can cause serious shortcomings in OS
- MS-DOS written for 8088 both has no mode bit and no dual mode

■ Possible Scenarios in Absence of Dual-Mode

- User program can wipe out OS
- Multiple programs can write to a device at same time

■ Recent CPUs and OSs Support Dual-Mode

- Linux, Unix, Solaris, Win-XP, Win-Vista


■ Increasingly CPUs Support Multi-Mode Operations

- **Virtual Machine Manager (VMM)** mode for guest VMS






User/Kernel (Privileged) Mode



Kubiatowicz CS162@ UCB 2023





- Timer to Prevent Infinite Loop / Process Hogging Resources
 - Timer is set to interrupt computer after some time period
 - Keep a counter that is decremented by physical clock
 - OS sets counter (privileged instruction)
 - Counter = 0 → Generates an interrupt
 - Set up timer before scheduling process to regain control or terminate program that exceeds allotted time





A Quick Preview of Concepts

- Process Management
- Memory Management
- Storage Management
- Protection & Security
- Open Source OSes





Process Management

- A Process is a Program in Execution
 - Unit of work within a system
 - **Active entity** vs. program which is **passive entity**
- Process Needs Resources to Accomplish its Task
 - CPU, memory, I/O, files
 - Initialization data
- Process **Termination** Requires **Reclaiming** any Reusable Resources





Process Management Activities



■ OS Responsible for following Activities

- Creating and deleting both user and system processes
- Suspending and resuming processes
- Providing mechanisms for process synchronization
- Providing mechanisms for process communication
- Providing mechanisms for deadlock handling





Memory Management

■ Main Memory

- Repository of quickly accessible data shared by CPU and I/O devices
- The only large storage device that CPU is able to **address** and **access directly**

■ To Execute a Program

- All (or part) of **Instructions** must be in Memory
- All (or part) of **Data** needed by program must be in memory

■ To Improve Utilization of CPU

- Several programs must be kept in memory → needs memory management





Memory Management (cont.)



■ Memory Management

- Determines what is in memory and when
- Optimizing CPU utilization and computer response to users

■ Management Activities

- Keeping track of which parts of memory are currently being used and by whom
- Deciding which processes (or parts thereof) and data to move into and out of memory
- Allocating and deallocating memory space as needed





Storage Management

- OS Provides Uniform, Logical View of Information Storage
 - To make computer system **convenient** for users
 - **Abstracts physical properties** to logical storage unit, aka, **file**
 - Each **medium** is controlled by a device driver (i.e., disk drive, tape drive)
 - ▶ **Varying properties** include access speed, capacity, data-transfer rate, access method (sequential or random)





Mass-Storage Management

■ Why Mass Storage Needed?

- Main memory too small to accommodate all data/programs
- Main memory is volatile → data will be lost upon power outage

■ Disks usually Used to Store Data

- That does not fit in main memory or data that must be kept for a “long” period of time

■ Proper Management is of Central Importance

■ **Entire Speed** of Computer Operation Hinges on **Disk Subsystem** and its Algorithms





Mass-Storage Management (cont.)



■ OS Activities

- Free-space management
- Storage allocation
- Disk scheduling

■ Some Storage Need Not be Fast

- Tertiary storage includes optical storage, magnetic tape
- Still must be managed – by OS or applications
- Varies between WORM (write-once, read-many-times) and RW (read-write)





Performance of Various Levels of Storage

Level	1	2	3	4	5
Name	registers	cache	main memory	solid state disk	magnetic disk
Typical size	< 1 KB	< 16MB	< 64GB	< 1 TB	< 10 TB
Implementation technology	custom memory with multiple ports CMOS	on-chip or off-chip CMOS SRAM	CMOS-SRAM — DRAM	flash memory	magnetic disk
Access time (ns)	0.25 - 0.5	0.5 - 25	80 - 250	25,000 - 50,000	5,000,000
Bandwidth (MB/sec)	20,000 - 100,000	5,000 - 10,000	1,000 - 5,000	500	20 - 150
Managed by	compiler	hardware	operating system	operating system	operating system
Backed by	cache	main memory	disk	disk	disk or tape


Movement between levels of storage hierarchy can be explicit or implicit





Migration of data “A” from Disk to Register

- Multitasking environments must be careful to use **most recent value**, no matter where it is stored in storage hierarchy



- Multiprocessor environment must provide **cache coherency** in HW such that all CPUs have the most recent value in their cache
- Distributed environment situation even more complex → Need **OS-level data coherency**
 - Several copies of a datum can exist
 - Various solutions exist





■ Close-Source OS

- Available as compiled binary code
- Example include **Microsoft Windows**
- **Very hard to update** or extend by users
 - ▶ **Needs reverse engineering** which is **illegal** in many countries
 - ▶ Reverse engineering is a **lot of work**
 - ▶ **Comments** and **structure** of SW would not be available by reverse engineering
- Typically more **prone to bugs**
 - ▶ Limited number of code reviewers





■ Open-Source OS

- Available in **source-code** format
- A user can **modify**, **compile**, and **run** updated code
- **Large community** of interested programmers who contribute to code (debug/analyze/changes)
- **More secure** than close-source code as many more eyes reviewing the code
- **Revenue** achieved by **support** contracts and sale of **HW**
 - ▶ Red-Hat, SUSE, Sun





Open-Source vs. Closed-Source OS (cont.)



■ Open-Source OS

- Counter to **copy protection** and **Digital Rights Management (DRM)** movement
- Started by **Free Software Foundation (FSF)**, which has “copyleft” **GNU Public License (GPL)**
 - ▶ By Richard Stallman, 1983
 - ▶ **GPL** requires any changes made to source code must be released under the same GPL license
- Examples include **GNU/Linux** and **BSD UNIX** (including core of **Mac OS X**), and many more





Sample Open-Source OS



■ Linux

- Initiated by a student in Finland
- Updates released once a week
- Different distributions vary in function, utility, installed applications, HW support, user interface, and purpose
 - ▶ RedHat enterprise: large commercial use
 - ▶ PCLinuxOS: can be booted from a CD
 - ▶ Other distributions: Fedora, Debian, SUSE, Slackware, and Ubuntu





Sample Open-Source OS (cont.)



■ BSD UNIX

- Started in 1978 as a derivative of AT&T UNIX
- Fully functional, open-source released in 1994
- Different distributions
 - ▶ FreeBSD, NetBSD, OpenBSD, DragonflyBSD


■ Solaris

- Commercial UNIX-based OS
- Partially open-source OS
 - ▶ Since some part of the code is still owned by AT&T






OS Shares by Market Segments



End of Lecture 1





Storage Management (cont.)



■ File

- A collection of related info defined by its creator

■ File-System Management

- Files usually **organized** into **directories**
- **Access control** on most systems to determine who can access what
- OS **activities** include
 - ▶ Creating and deleting files and directories
 - ▶ Primitives to manipulate files and directories
 - ▶ Mapping files onto secondary storage
 - ▶ Backup files onto stable (non-volatile) storage media





Process Management (cont.)



■ Single-Threaded Process

- Only one **program counter** specifying location of next instruction to execute
- Process executes instructions sequentially, one at a time, until completion

■ Multi-Threaded Process

- One program counter per thread

■ Typically System has Many Processes

- User processes (running user code) + OS processes (running system code)
- Concurrency by multiplexing CPUs among processes / threads





I/O Subsystem

- One Purpose of OS is to Hide Peculiarities of HW Devices from Users
- I/O Subsystem Responsible for:
 - Memory management of I/O
 - ▶ Buffering
 - ▶ Caching
 - ▶ Spooling
 - General device-driver interface
 - Drivers for specific HW devices





■ Protection

- Mechanisms to ensure files, memory segments, CPU, and other resources can **be operated** on by only **authorized processes**
- Any mechanism for controlling access of processes or users to resources defined by OS
- Example
 - ▶ A process access only within its own address space
 - ▶ A timer ensures that no process can gain control of CPU without eventually relinquishing control
 - ▶ Device-control registers not accessible by users
 - To protect integrity of various peripheral devices





Protection and Security (cont.)



■ Fact

- A system can have enough protection but still prone to failure and allow inappropriate access

■ **Security** – defense of system against internal and external attacks

■ Examples

- Denial-of-service, worms
- Viruses
- Identity theft
- Theft of service





Protection and Security (cont.)



- Systems generally first distinguish among users to determine who can do what
 - User identities (**user IDs**, security IDs) include name and associated number, one per user
 - User ID then associated with all files, processes of that user to determine access control
 - Group identifier (**group ID**) allows set of users to be defined and controls managed, then also associated with each process, file
 - **Privilege escalation** allows user to change to effective ID with more rights
 - ▶ E.g, access a device that is normally restricted






Clustered Systems

- Like Multiprocessor Systems, but Multiple Systems Working Together
 - Usually sharing storage via a **Storage-Area Network (SAN)**
 - Provides a **high-availability** service which survives failures
 - **Asymmetric clustering** has one machine in hot-standby mode
 - **Symmetric clustering** has multiple nodes running applications, monitoring each other
 - Some clusters intended for **high-performance computing (HPC)**
 - Applications must be written to use **parallelization**
 - Some have **distributed lock manager (DLM)** to avoid conflicting operations (in order to access shared data)





Clustered Systems





Objective (cont.)

- By end of semester, you should be able to answer these questions:
 - Services an OS Provides to Users & Processes?
 - Fundamental components of an OS?
 - ??
 - ??





Objective (cont.)

■ By end of semester, you should be able to answer these questions:

● ??

● ??







Kernel Data Structures

- Many Similar to Standard Programming Data Structures


- ***Singly linked list***



- ***Doubly linked list***



- ***Circular linked list***






Kernel Data Structures (cont.)

■ Binary Search Tree

left \leq right


- Search performance is $O(n)$
- **Balanced** binary search tree is $O(\lg n)$





Kernel Data Structures (cont.)

- Hash function can create a hash map



- **Bitmap** – string of n binary digits representing the status of n items
- Linux data structures defined in ***include*** files `<linux/list.h>`, `<linux/kfifo.h>`, `<linux/rbtree.h>`





Storage Definitions and Notation Review

The basic unit of computer storage is the **bit**. A bit can contain one of two values, 0 and 1. All other storage in a computer is based on collections of bits. Given enough bits, it is amazing how many things a computer can represent: numbers, letters, images, movies, sounds, documents, and programs, to name a few. A **byte** is 8 bits, and on most computers it is the smallest convenient chunk of storage. For example, most computers don't have an instruction to move a bit but do have one to move a byte. A less common term is **word**, which is a given computer architecture's native unit of data. A word is made up of one or more bytes. For example, a computer that has 64-bit registers and 64-bit memory addressing typically has 64-bit (8-byte) words. A computer executes many operations in its native word size rather than a byte at a time.

Computer storage, along with most computer throughput, is generally measured and manipulated in bytes and collections of bytes.

A Kilobyte, or KB, is 1,024 bytes

A Megabyte, or MB, is $1,024^2$ bytes

A Gigabyte, or GB, is $1,024^3$ bytes

A Terabyte, or TB, is $1,024^4$ bytes

A Petabyte, or PB, is $1,024^5$ bytes

Computer manufacturers often round off these numbers and say that a megabyte is 1 million bytes and a gigabyte is 1 billion bytes. Networking measurements are an exception to this general rule; they are given in bits (because networks move data a bit at a time).





I/O Structure

- After I/O starts, control returns to user program only upon I/O completion
 - Wait instruction idles CPU until the next interrupt
 - Wait loop (contention for memory access)
 - At most one I/O request is outstanding at a time, no simultaneous I/O processing
- After I/O starts, control returns to user program without waiting for I/O completion
 - **System call** – request to the OS to allow user to wait for I/O completion
 - **Device-status table** contains entry for each I/O device indicating its type, address, and state
 - OS indexes into I/O device table to determine device status and to modify table entry to include interrupt





Computing Environments: Traditional



- Stand-Alone General Purpose Machines
- But Blurred as most Systems Interconnect with Others (i.e., the Internet)
- **Portals** Provide Web Access to Internal Systems
- **Network Computers (Thin Clients)** are like Web Terminals
- Mobile Computers Interconnect via **Wireless Networks**
- Networking becoming Ubiquitous – even home systems use **Firewalls** to protect home computers from Internet attacks





Computing Environments: Real-Time Embedded Systems



- Real-Time Embedded Systems Most Prevalent Form of Computers
 - Typically have **little or no user interface**
 - Mostly monitoring and managing HW devices such as automobile engines and robotic arms
 - Vary considerably: special purpose, limited purpose OS, **real-time OS**
 - Some have OSes, some perform tasks without an OS
- Real-Time OS has Well-Defined Fixed Time Constraints
 - Processing **must** be done within Constraint
 - Correct operation only if constraints met





Computing Environments: Mobile



- Handheld smartphones, tablets, etc
- What is the functional difference between them and a “traditional” laptop?
- Extra feature – more OS features (GPS, gyroscope)
- Allows new types of apps like *augmented reality*
- Use IEEE 802.11 wireless, or cellular data networks for connectivity
- Leaders are **Apple iOS** and **Google Android**





Computing Environments: Distributed

■ Distributed Computing

- Collection of separate, possibly heterogeneous, systems networked together
 - ▶ **Network**: a communications path, **TCP/IP** most common
 - Local Area Network (LAN)
 - Wide Area Network (WAN)
 - Metropolitan Area Network (MAN)
 - Personal Area Network (PAN)
- **Network Operating System** provides features between systems across network
 - ▶ Communication scheme allows systems to exchange messages
 - ▶ Illusion of a single system






Computing Environments: Client-Server



■ Client-Server Computing


- Dumb terminals supplanted by smart PCs
- Many systems now **servers**, responding to requests generated by **clients**
 - ▶ **Compute-server system** provides an interface to client to request services (i.e., database)
 - ▶ **File-server system** provides interface for clients to store and retrieve files





Computing Environments: Peer-to-Peer

- Another model of distributed system
- P2P does not distinguish clients and servers
 - Instead all nodes are considered peers
 - May each act as client, server or both
 - Node must join P2P network
 - ▶ Registers its service with central lookup service on network, or
 - ▶ Broadcast request for service and respond to requests for service via **discovery protocol**
 - Examples include Napster and Gnutella, **Voice over IP (VoIP)** such as Skype



Computing Environments: Cloud Computing



- Delivers computing, storage, even apps as a service across a network
- Logical extension of virtualization because it uses virtualization as the base for its functionality.
 - Amazon **EC2** has thousands of servers, millions of virtual machines, petabytes of storage available across the Internet, pay based on usage





Computing Environments:

Types of Cloud Computing

- **Public cloud** – available via Internet to anyone willing to pay
- **Private cloud** – run by a company for the company's own use
- **Hybrid cloud** – includes both public and private cloud components
- **Software as a Service (SaaS)** – one or more applications available via the Internet (i.e., word processor)
- **Platform as a Service (PaaS)** – software stack ready for application use via the Internet (i.e., a database server)
- **Infrastructure as a Service (IaaS)** – servers or storage available over Internet (i.e., storage available for backup use)





Computing Environments: Cloud Computing



- Cloud computing environments composed of traditional OSes, plus VMMs, plus cloud management tools
 - Internet connectivity requires security like firewalls
 - Load balancers spread traffic across multiple applications

