




Computer Networks

Amir Mahdi Sadeghzadeh, Ph.D.

Chapter 2

Application Layer



Computer Networking: A Top-Down Approach

8th edition

Jim Kurose, Keith Ross

Pearson, 2020

Application Layer: Overview

- Principles of network applications
- Web and HTTP
- E-mail, SMTP, IMAP
- The Domain Name System DNS
- P2P applications
- video streaming and content distribution networks
- socket programming with UDP and TCP



DNS: Domain Name System

people: many identifiers:

- SSN, name, passport #

Internet hosts, routers:

- IP address (32 bit) - used for addressing datagrams
- “name”, e.g., cs.umass.edu - used by humans

Q: how to map between IP address and name, and vice versa ?

Domain Name System (DNS):

- *distributed database* implemented in hierarchy of many *name servers*
- *application-layer protocol*: hosts, DNS servers communicate to *resolve* names (address/name translation)
 - *note*: core Internet function, implemented as application-layer protocol
 - complexity at network’s “edge”

DNS: services, structure

DNS services:

- hostname-to-IP-address translation
- host aliasing
 - canonical, alias names
- mail server aliasing
- load distribution
 - replicated Web servers: many IP addresses correspond to one name


Q: Why not centralize DNS?

- single point of failure
- traffic volume
- distant centralized database
- maintenance

A: doesn't scale!

- Comcast DNS servers alone: 600B DNS queries/day
- Akamai DNS servers alone: 2.2T DNS queries/day

DNS: a distributed, hierarchical database



Client wants IP address for `www.amazon.com`; 1st approximation:

- client queries root server to find `.com` DNS server
- client queries `.com` DNS server to get `amazon.com` DNS server
- client queries `amazon.com` DNS server to get IP address for `www.amazon.com`

Local DNS name servers


- when host makes DNS query, it is sent to its *local* DNS server
 - Local DNS server returns reply, answering:
 - from its local cache of recent name-to-address translation pairs (possibly out of date!)
 - forwarding request into DNS hierarchy for resolution
 - each ISP has local DNS name server; to find yours:
 - MacOS: `% scutil --dns`
 - Windows: `>ipconfig /all`
- local DNS server doesn't strictly belong to hierarchy

DNS name resolution: iterated query

Example: host at `engineering.nyu.edu` wants IP address for `gaia.cs.umass.edu`

Iterated query:

- contacted server replies with name of server to contact
- “I don’t know this name, but ask this server”



Caching DNS Information

- once (any) name server learns mapping, it *caches* mapping, and *immediately* returns a cached mapping in response to a query
 - caching improves response time
 - cache entries timeout (disappear) after some time (TTL)
 - TLD servers typically cached in local name servers
- cached entries may be *out-of-date*
 - if named host changes IP address, may not be known Internet-wide until all TTLs expire!
 - *best-effort name-to-address translation!*

DNS records

DNS: distributed database storing resource records (RR)

RR format: (name, value, type, ttl)

type=A

- name is hostname
- value is IP address

type=NS

- name is domain (e.g., foo.com)
- value is hostname of authoritative name server for this domain

type=CNAME


- name is alias name for some “canonical” (the real) name
- www.ibm.com is really servereast.backup2.ibm.com
- value is canonical name

type=MX

- value is name of SMTP mail server associated with name


DNS

- Imagine that you are trying to visit `www.enterprise.com`, but you don't remember the IP address the web-server is running on.



DNS

- Imagine that you are trying to visit `www.enterprise.com`, but you don't remember the IP address the web-server is running on.
 - Assume the following records are on the TLD DNS server:
(`www.enterprise.com`, `dns.enterprise.com`, NS)
(`dns.enterprise.com`, `146.54.181.144`, A)



DNS

- Imagine that you are trying to visit `www.enterprise.com`, but you don't remember the IP address the web-server is running on.

- Assume the following records are on the TLD DNS server:

(`www.enterprise.com`, `dns.enterprise.com`, NS)

(`dns.enterprise.com`, `146.54.181.144`, A)


- Assume the following records are on the `enterprise.com` DNS server:

(`www.enterprise.com`, `west5.enterprise.com`, CNAME)

(`west5.enterprise.com`, `142.81.17.206`, A)

(`enterprise.com`, `mail.enterprise.com`, MX)

(`mail.enterprise.com`, `247.29.232.23`, A)




DNS protocol messages

DNS *query* and *reply* messages, both have same *format*:


message header:

- **identification**: 16 bit # for query, reply to query uses same #
- **flags**:
 - query or reply
 - recursion desired
 - recursion available
 - reply is authoritative



DNS protocol messages

DNS *query* and *reply* messages, both have same *format*:



Getting your info into the DNS

example: new startup “Network Utopia”

- register name networkutopia.com at *DNS registrar* (e.g., Network Solutions)
 - provide names, IP addresses of authoritative name server (primary and secondary)
 - registrar inserts NS, A RRs into .com TLD server:
`(networkutopia.com, dns1.networkutopia.com, NS)`
`(dns1.networkutopia.com, 212.212.212.1, A)`
- create authoritative server locally with IP address `212.212.212.1`
 - type A record for `www.networkutopia.com`
 - type MX record for `networkutopia.com`

DNS security

DDoS attacks

- bombard root servers with traffic
 - not successful to date
 - traffic filtering
 - local DNS servers cache IPs of TLD servers, allowing root server bypass
- bombard TLD servers
 - potentially more dangerous

Spoofing attacks

- intercept DNS queries, returning bogus replies
 - DNS cache poisoning
 - RFC 4033: DNSSEC authentication services