

Curve and surface modeling

– a CAGD approach based on OpenGL and C++ –

Ágoston Róth

Department of Mathematics and Computer Science, Babeş-Bolyai University, Cluj-Napoca, Romania

(agoston.roth@gmail.com)

Seminar 2 | March 7 & March 16, 2022



Notations

Used colors

Color styles

- keywords, built-in types, enumerations, constants and namespaces of C++
- keywords, built-in types, enumerations, constants and functions of OpenGL
- our types, constants, enumerations and namespaces
- comments



Descartes coordinates

Class **DCoordinate3**

Description

- Class **DCoordinate3** forms the most elementary building block/data structure of all other classes.
- By means of Descartes coordinates we can represent curve points, tangent and acceleration vectors (i.e. higher order derivatives) of curves, surface points, higher order (mixed) partial derivatives of surfaces, normal vectors associated with surface points, control polygons, control nets, etc.
- Using operator overloading we can easily implement mathematical formulas that describe either curves or surfaces.



Descartes coordinates – header file, part I

DCoordinates3.h

```
1 #pragma once

2 #include <cmath>
3 #include <GL/glew.h>
4 #include <iostream>

5 namespace cagd
6 {
7     // _____
8     // class DCoordinate3
9     // _____
10    class DCoordinate3
11    {
12    private:
13        GLdouble _data[3];

14    public:

15        // default constructor
16        DCoordinate3();

17        // special constructor
18        DCoordinate3(GLdouble x, GLdouble y, GLdouble z = 0.0);

19        // get components by value
20        const GLdouble operator [] (GLuint index) const;
21        const GLdouble x() const;
22        const GLdouble y() const;
23        const GLdouble z() const;

24        // get components by reference
25        GLdouble& operator [] (GLuint index);
26        GLdouble& x();
27        GLdouble& y();
```



Descartes coordinates – header file, part II

DCoordinates3.h

```
28     GLdouble& z();
29
29     // change sign
30     const DCoordinate3 operator +() const;
31     const DCoordinate3 operator -() const;
32
32     // add
33     const DCoordinate3 operator +(const DCoordinate3& rhs) const;
34
34     // add to *this
35     DCoordinate3& operator +=(const DCoordinate3& rhs);
36
36     // subtract
37     const DCoordinate3 operator -(const DCoordinate3& rhs) const;
38
38     // subtract from *this
39     DCoordinate3& operator -=(const DCoordinate3& rhs);
40
40     // cross product
41     const DCoordinate3 operator ^(const DCoordinate3& rhs) const;
42
42     // cross product, result is stored by *this
43     DCoordinate3& operator ^=(const DCoordinate3& rhs);
44
44     // dot product
45     const GLdouble operator *(const DCoordinate3& rhs) const;
46
46     // scale
47     const DCoordinate3 operator *(const GLdouble& rhs) const;
48     const DCoordinate3 operator /(const GLdouble& rhs) const;
49
49     // scale *this
50     DCoordinate3& operator *=(const GLdouble& rhs);
51     DCoordinate3& operator /=(const GLdouble& rhs);
```



Descartes coordinates – header file, part III

DCoordinates3.h

```
52     // length
53     const GLdouble length() const;

54     // normalize
55     DCoordinate3& normalize();
56 };

57 //-----
58 // implementation of class DCoordinate3
59 //-----

60 // default constructor
61 inline DCoordinate3::DCoordinate3()
62 {
63     _data[0] = _data[1] = _data[2] = 0.0;
64 }

65 // special constructor
66 inline DCoordinate3::DCoordinate3(GLdouble x, GLdouble y, GLdouble z)
67 {
68     _data[0] = x;
69     _data[1] = y;
70     _data[2] = z;
71 }

72 // get components by value
73 inline const GLdouble DCoordinate3::operator [] (GLuint index) const
74 {
75     return _data[index];
76 }

77 inline const GLdouble DCoordinate3::x() const
78 {
79     return _data[0];
80 }
```



Descartes coordinates – header file, part IV

DCoordinates3.h

```
81     inline const GLdouble DCoordinate3::y() const
82     {
83         // homework
84     }
85
86     inline const GLdouble DCoordinate3::z() const
87     {
88         // homework
89     }
90
91     // get components by reference
92     inline GLdouble& DCoordinate3::operator [] (GLuint index)
93     {
94         return _data[index];
95     }
96
97     inline GLdouble& DCoordinate3::x()
98     {
99         return _data[0];
100     }
101
102     inline GLdouble& DCoordinate3::y()
103     {
104         // homework
105     }
106
107     inline GLdouble& DCoordinate3::z()
108     {
109         // homework
110     }
111
112     // change sign
113     inline const DCoordinate3 DCoordinate3::operator +() const
114     {
115         DCoordinate3 result;
116         for (int i = 0; i < 3; i++)
117             result._data[i] = -_data[i];
118         return result;
119     }
```



Descartes coordinates – header file, part V

DCoordinates3.h

```
109     return DCoordinate3(_data[0], _data[1], _data[2]);
110 }

111 inline const DCoordinate3 DCoordinate3::operator -() const
112 {
113     return DCoordinate3(-_data[0], -_data[1], -_data[2]);
114 }

115 // add
116 inline const DCoordinate3 DCoordinate3::operator +(const DCoordinate3& rhs) const
117 {
118     return DCoordinate3(_data[0] + rhs._data[0], _data[1] + rhs._data[1], _data[2] + rhs._data[2]);
119 }

120 // add to *this
121 inline DCoordinate3& DCoordinate3::operator +=(const DCoordinate3& rhs)
122 {
123     _data[0] += rhs._data[0];
124     _data[1] += rhs._data[1];
125     _data[2] += rhs._data[2];
126     return *this;
127 }

128 // subtract
129 inline const DCoordinate3 DCoordinate3::operator -(const DCoordinate3& rhs) const
130 {
131     // homework
132 }

133 // subtract from *this
134 inline DCoordinate3& DCoordinate3::operator -=(const DCoordinate3& rhs)
135 {
136     //homework
137 }
```



Descartes coordinates – header file, part VI

DCoordinates3.h

```
138 // cross product
139 inline const DCoordinate3 DCoordinate3::operator ^(const DCoordinate3& rhs) const
140 {
141     return DCoordinate3(
142         _data[1] * rhs._data[2] - _data[2] * rhs._data[1],
143         _data[2] * rhs._data[0] - _data[0] * rhs._data[2],
144         _data[0] * rhs._data[1] - _data[1] * rhs._data[0]);
145 }
146
147 // cross product, result is stored by *this
148 inline DCoordinate3& DCoordinate3::operator ^=(const DCoordinate3& rhs)
149 {
150     // homework
151 }
152
153 // dot product
154 inline const GLdouble DCoordinate3::operator *(const DCoordinate3& rhs) const
155 {
156     return _data[0] * rhs._data[0] + _data[1] * rhs._data[1] + _data[2] * rhs._data[2];
157 }
158
159 // scale
160 inline const DCoordinate3 DCoordinate3::operator *(const GLdouble& rhs) const
161 {
162     return DCoordinate3(_data[0] * rhs, _data[1] * rhs, _data[2] * rhs);
163 }
164
165 inline const DCoordinate3 operator *(const GLdouble& lhs, const DCoordinate3& rhs)
166 {
167     // homework
168 }
```



Descartes coordinates – header file, part VII

DCoordinates3.h

```
168     }

169     // scale *this
170     inline DCoordinate3& DCoordinate3::operator *=(const GLdouble& rhs)
171     {
172         _data[0] *= rhs;
173         _data[1] *= rhs;
174         _data[2] *= rhs;

175         return *this;
176     }

177     inline DCoordinate3& DCoordinate3::operator /=(const GLdouble& rhs)
178     {
179         // homework
180     }

181     // length
182     inline const GLdouble DCoordinate3::length() const
183     {
184         return std::sqrt((*this) * (*this));
185     }

186     // normalize
187     inline DCoordinate3& DCoordinate3::normalize()
188     {
189         GLdouble l = length();

190         if (l && l != 1.0)
191             *this /= l;

192         return *this;
193     }
```



Descartes coordinates – header file, part VIII

DCoordinates3.h

```
194 // _____
195 // definitions of overloaded input/output from/to stream operators
196 // _____
197
198 // output to stream
199 inline std::ostream& operator <<(std::ostream& lhs, const DCoordinate3& rhs)
200 {
201     return lhs << rhs[0] << " " << rhs[1] << " " << rhs[2];
202 }
203
204 // input from stream
205 inline std::istream& operator >>(std::istream& lhs, DCoordinate3& rhs)
206 {
207     // homework
208 }
```



Descartes coordinates – source file

DCoordinates3.cpp

Homework

Implement all operators and methods of class **DCoordinate3**! Notice that for efficiency reasons all operators, methods must be inlined.



A simple template for matrices

Template class **Matrix**

Description

- By means of the template class **Matrix** we can represent collocation matrices, control polygons, control nets, grouped spline or patch information.



A simple template for matrices – header file, part I

Matrices.h

```
1 #pragma once
2 #include <iostream>
3 #include <vector>
4 #include <GL/glew.h>
5 namespace cagd
6 {
7     // forward declaration of template class Matrix
8     template <typename T>
9     class Matrix;
10
11     // forward declaration of template class RowMatrix
12     template <typename T>
13     class RowMatrix;
14
15     // forward declaration of template class ColumnMatrix
16     template <typename T>
17     class ColumnMatrix;
18
19     // forward declaration of template class TriangularMatrix
20     template <typename T>
21     class TriangularMatrix;
22
23     // forward declarations of overloaded and templated input/output from/to stream operators
24     template <typename T>
25     std::ostream& operator << (std::ostream& lhs, const Matrix<T>& rhs);
26
27     template <typename T>
28     std::istream& operator >>(std::istream& lhs, Matrix<T>& rhs);
29
30     template <typename T>
31     std::istream& operator >>(std::istream& lhs, TriangularMatrix<T>& rhs);
32
33 }
```



A simple template for matrices – header file, part II

Matrices.h

```
27 template <typename T>
28 std::ostream& operator << (std::ostream& lhs, const TriangularMatrix<T>& rhs);

29 // =====
30 // template class Matrix
31 // =====
32 template <typename T>
33 class Matrix
34 {
35     friend std::ostream& operator << <T>(std::ostream&, const Matrix<T>& rhs);
36     friend std::istream& operator >> <T>(std::istream&, Matrix<T>& rhs);

37 protected:
38     GLuint                               _row_count;
39     GLuint                               _column_count;
40     std::vector< std::vector<T> >       _data;
41 public:
42     // special constructor (can also be used as a default constructor)
43     Matrix(GLuint row_count = 1, GLuint column_count = 1);

44     // copy constructor
45     Matrix(const Matrix& m);

46     // assignment operator
47     Matrix& operator =(const Matrix& m);

48     // get element by reference
49     T& operator ()(GLuint row, GLuint column);

50     // get copy of an element
51     T operator ()(GLuint row, GLuint column) const;

52     // get dimensions
53     GLuint GetRowCount() const;
54     GLuint GetColumnCount() const;
```



A simple template for matrices – header file, part III

Matrices.h

```
55 // set dimensions
56 virtual GLboolean ResizeRows(GLuint row_count);
57 virtual GLboolean ResizeColumns(GLuint column_count);

58 // update
59 GLboolean SetRow(GLuint index, const RowMatrix<T>& row);
60 GLboolean SetColumn(GLuint index, const ColumnMatrix<T>& column);

61 // destructor
62 virtual ~Matrix();
63 };

64 //-----
65 // template class RowMatrix
66 //-----
67 template <typename T>
68 class RowMatrix: public Matrix<T>
69 {
70 public:
71 // special constructor (can also be used as a default constructor)
72 RowMatrix(GLuint column_count = 1);

73 // get element by reference
74 T& operator ()(GLuint column);
75 T& operator [] (GLuint column);

76 // get copy of an element
77 T operator ()(GLuint column) const;
78 T operator [] (GLuint column) const;

79 // a row matrix consists of a single row
80 GLboolean ResizeRows(GLuint row_count);
81 };
```



A simple template for matrices – header file, part IV

Matrices.h

```
82 // _____
83 // template class ColumnMatrix
84 // _____
85 template <typename T>
86 class ColumnMatrix: public Matrix<T>
87 {
88 public:
89     // special constructor (can also be used as a default constructor)
90     ColumnMatrix(GLuint row_count = 1);
91
92     // get element by reference
93     T& operator ()(GLuint row);
94     T& operator [] (GLuint row);
95
96     // get copy of an element
97     T operator ()(GLuint row) const;
98     T operator [] (GLuint row) const;
99
100     // a column matrix consists of a single column
101     GLboolean ResizeColumns(GLuint column_count);
102 };
103
104 // _____
105 // template class TriangularMatrix
106 // _____
107 template <typename T>
108 class TriangularMatrix
109 {
110     friend std::istream& operator >> <T>(std::istream&, TriangularMatrix<T>& rhs);
111     friend std::ostream& operator << <T>(std::ostream&, const TriangularMatrix<T>& rhs);
112
113 protected:
114     GLuint _row_count;
115     std::vector< std::vector<T> > _data;
```



A simple template for matrices – header file, part V

Matrices.h

```
111 public:
112     // special constructor (can also be used as a default constructor)
113     TriangularMatrix(GLuint row_count = 1);
114
115     // get element by reference
116     T& operator()(GLuint row, GLuint column);
117
118     // get copy of an element
119     T operator()(GLuint row, GLuint column) const;
120
121     // get dimension
122     GLuint GetRowCount() const;
123
124     // set dimension
125     GLboolean ResizeRows(GLuint row_count);
126 };
127
128 // _____
129 // homework: implementation of template class Matrix
130 // _____
131
132 // _____
133 // homework: implementation of template class RowMatrix
134 // _____
135
136 // _____
137 // homework: implementation of template class ColumnMatrix
138 // _____
139
140 // _____
141 // homework: implementation of template class TriangularMatrix
142 // _____
```



A simple template for matrices – header file, part VI

Matrices.h

```
135 //
136 // definitions of Matrix-related overloaded and templated input/output from/to stream operators
137 //
138
139 // output to stream
140 template <typename T>
141 std::ostream& operator <<(std::ostream& lhs, const Matrix<T>& rhs)
142 {
143     lhs << rhs._row_count << " " << rhs._column_count << std::endl;
144     for (typename std::vector< std::vector<T> >::const_iterator row = rhs._data.begin();
145          row != rhs._data.end(); ++row)
146     {
147         for (typename std::vector<T>::const_iterator column = row->begin();
148              column != row->end(); ++column)
149             lhs << *column << " ";
150     }
151     return lhs;
152 }
153
154 // input from stream
155 template <typename T>
156 std::istream& operator >>(std::istream& lhs, Matrix<T>& rhs)
157 {
158     // homework
159 }
160
161 // definitions of TringularMatrix-related overloaded and templated input/output from/to
162 // stream operators
163
164 // homework
165 }
```



A simple template for matrices – source file

⚡ Matrices.cpp

Homework

Implement all operators, methods and friend functions of the template classes **Matrix**, **RowMatrix**, and **ColumnMatrix**! The implementation must be done in the header file **Matrices.h**.



Real square matrices

Derived class **RealSquareMatrix**

Description

- **Matrix<GLdouble>** is the base class of the class **RealSquareMatrix**.
- Some numerical methods (e.g. data point interpolation, degree elevation, LU-decomposition, solutions of linear systems) require real square matrices.



Real square matrices – header file, part I

RealSquareMatrices.h

```
1 #pragma once

2 #include "DCoordinates3.h"
3 #include <GL/glew.h>
4 #include <limits>
5 #include "Matrices.h"

6 namespace cagd
7 {
8     class RealSquareMatrix: public Matrix<GLdouble>
9     {
10     private:
11         GLboolean _lu_decomposition_is_done;
12         std::vector<GLuint> _row_permutation;

13     public:
14         // special constructor
15         RealSquareMatrix(GLuint size);

16         // homework: copy constructor
17         RealSquareMatrix(const RealSquareMatrix& m);

18         // homework: assignment operator
19         RealSquareMatrix& operator =(const RealSquareMatrix& rhs);

20         // homework: square matrices have the same number of rows and columns!
21         GLboolean ResizeRows(GLuint row_count);
22         GLboolean ResizeColumns(GLuint row_count);

23         // tries to determine the LU decomposition of this square matrix
24         GLboolean PerformLUdecomposition();

25         // Solves linear systems of type  $A \star x = b$ , where A is a regular square matrix,
26         // while b and x are row or column matrices with elements of type T.
27         // Here matrix A corresponds to  $\star$ this.
```



Real square matrices – header file, part II

RealSquareMatrices.h

```
28 // Advantage: T can be either GLdouble or DCoordinate,
29 // or any other type which has similar mathematical operators.
30 template <class T>
31 GLboolean SolveLinearSystem(const Matrix<T>& b, Matrix<T>& x,
32                             GLboolean represent_solutions_as_columns = GL_TRUE);
33 };
34
35 template <class T>
36 GLboolean RealSquareMatrix::SolveLinearSystem(const Matrix<T>& b, Matrix<T>& x,
37                                                GLboolean represent_solutions_as_columns)
38 {
39     if (! _lu_decomposition_is_done)
40         if (! PerformLUdecomposition())
41             return GL_FALSE;
42
43     if (represent_solutions_as_columns)
44     {
45         GLint size = static_cast<GLint>(GetColumnCount());
46         if (static_cast<GLint>(b.GetRowCount()) != size)
47             return GL_FALSE;
48
49         x = b;
50
51         for (GLuint k = 0; k < b.GetColumnCount(); ++k)
52         {
53             GLint ii = 0;
54             for (GLint i = 0; i < size; ++i)
55             {
56                 GLuint ip = _row_permutation[i];
57                 T sum = x(ip, k);
58                 x(ip, k) = x(i, k);
59                 if (ii != 0)
60                     for (GLint j = ii - 1; j < i; ++j)
61                         sum -= _data[i][j] * x(j, k);
62                 else
63                     sum = x(i, k);
64             }
65             x(ii, k) = sum;
66         }
67     }
68 }
```



Real square matrices – header file, part III

RealSquareMatrices.h

```
59         if (sum != 0.0)
60             ii = i + 1;
61         x(i, k) = sum;
62     }
63
64     for (GLint i = size - 1; i >= 0; --i)
65     {
66         T sum = x(i, k);
67         for (GLint j = i + 1; j < size; ++j)
68             sum -= _data[i][j] * x(j, k);
69         x(i, k) = sum / _data[i][i];
70     }
71 }
72 else
73 {
74     GLint size = static_cast<GLint>(GetRowCount());
75     if (static_cast<GLint>(b.GetColumnCount()) != size)
76         return GL_FALSE;
77
78     x = b;
79
80     for (GLuint k = 0; k < b.GetRowCount(); ++k)
81     {
82         GLint ii = 0;
83         for (GLint i = 0; i < size; ++i)
84         {
85             GLuint ip = _row_permutation[i];
86             T sum = x(k, ip);
87             x(k, ip) = x(k, i);
88             if (ii != 0)
89                 for (GLint j = ii - 1; j < i; ++j)
90                     sum -= _data[i][j] * x(k, j);
91             else
92                 if (sum != 0.0)
```



Real square matrices – header file, part IV

RealSquareMatrices.h

```
91         ii = i + 1;
92         x(k, i) = sum;
93     }
94     for (GLint i = size - 1; i >= 0; --i)
95     {
96         T sum = x(k, i);
97         for (GLint j = i + 1; j < size; ++j)
98             sum -= _data[i][j] * x(k, j);
99         x(k, i) = sum /= _data[i][i];
100     }
101 }
102
103 return GL_TRUE;
104 }
105 }
```



Real square matrices – source file, part I

RealSquareMatrix.cpp

```
1 #include "RealSquareMatrices.h"

2 using namespace cagd;
3 using namespace std;

4 RealSquareMatrix::RealSquareMatrix(GLuint size):
5     Matrix<GLdouble>(size, size),
6     _lu_decomposition_is_done(GL_FALSE)
7 {
8 }

9 GLboolean RealSquareMatrix::PerformLUdecomposition()
10 {
11     if (_lu_decomposition_is_done)
12         return GL_TRUE;

13     if (_row_count <= 1)
14         return GL_FALSE;

15     const GLdouble tiny = numeric_limits<GLdouble>::min();

16     GLuint size = static_cast<GLuint>(_data.size());
17     vector<GLdouble> implicit_scaling_of_each_row(size);

18     _row_permutation.resize(size);

19     GLdouble row_interchanges = 1.0;

20     // _____
21     // loop over rows to get the implicit scaling information
22     // _____
23     vector<GLdouble>::iterator its = implicit_scaling_of_each_row.begin();
24     for (vector<vector<GLdouble>>::const_iterator itr = _data.begin(); itr < _data.end(); ++itr)
25     {
26         GLdouble big = 0.0;
```



Real square matrices – source file, part II

RealSquareMatrix.cpp

```
27     for (vector<GLdouble>::const_iterator itc = itr->begin(); itc < itr->end(); ++itc)
28     {
29         GLdouble temp = abs(*itc);
30         if (temp > big)
31             big = temp;
32     }
33
34     if (big == 0.0)
35     {
36         // the matrix is singular
37         return GL_FALSE;
38     }
39     *its = 1.0 / big;
40     ++its;
41
42     // -----
43     // search for the largest pivot element
44     // -----
45     for (GLuint k = 0; k < size; ++k)
46     {
47         GLuint imax = k;
48         GLdouble big = 0.0;
49         for (GLuint i = k; i < size; ++i)
50         {
51             GLdouble temp = implicit_scaling_of_each_row[i] * abs(_data[i][k]);
52             if (temp > big)
53             {
54                 big = temp;
55                 imax = i;
56             }
57         }
58
59         // do we need to interchange rows?
60         if (k != imax)
```



Real square matrices – source file, part III

RealSquareMatrix.cpp

```
59     {
60         for (GLuint j = 0; j < size; ++j)
61         {
62             GLdouble temp = _data[imax][j];
63             _data[imax][j] = _data[k][j];
64             _data[k][j] = temp;
65         }
66         // change the parity of row-interchanges
67         row_interchanges = -row_interchanges;
68         // also interchange the scale factor
69         implicit_scaling_of_each_row[imax] = implicit_scaling_of_each_row[k];
70     }
71
72     _row_permutation[k] = imax;
73     if (_data[k][k] == 0.0)
74         _data[k][k] = tiny;
75
76     for (GLuint i = k + 1; i < size; ++i)
77     {
78         // divide by pivot element
79         GLdouble temp = _data[i][k] /= _data[k][k];
80
81         // reduce remaining submatrix
82         for (GLuint j = k + 1; j < size; ++j)
83             _data[i][j] -= temp * _data[k][j];
84     }
85 }
```

```
59     _lu_decomposition_is_done = GL_TRUE;
60
61     return GL_TRUE;
62 }
```



Real square matrices – source file, part IV

RealSquareMatrix.cpp

Homework

Implement all unfinished methods and operators of the class **RealSquareMatrix**!



Generic curves

Class `GenericCurve3`

Description

- Class `GenericCurve3` can also be used as a base class for any type of curve.
- This class provides methods only for rendering and updating (i.e. does not implement coordinate or blending functions).
- When using inheritance, the coordinates of the curve points, first and second order derivatives must be set either by one of the methods (e.g. constructor) of the derived class, or via the inherited methods

```
DCoordinate3& operator ()(GLuint order, GLuint index);
```

```
GLboolean SetDerivative(GLuint order, GLuint index, GLdouble x, GLdouble y, GLdouble z = 0.0);  
GLboolean SetDerivative(GLuint order, GLuint index, const DCoordinate3 &d);
```

- The rendering is based on vertex buffer objects. Notice that, for efficiency reasons all double coordinates are truncated to float numbers when creating/loading the data of vertex buffer objects.



Generic curves – header file, part I

GenericCurves3.h

```
1 #pragma once

2 #include "DCoordinates3.h"
3 #include <GL/glew.h>
4 #include "Matrices.h"
5 #include <iostream>

6 namespace cagd
7 {
8     // _____
9     // class GenericCurve3
10    // _____
11    class GenericCurve3
12    {
13        // _____
14        // input/output from/to stream
15        // _____
16        friend std::ostream& operator <<(std::ostream& lhs, const GenericCurve3& rhs);
17        friend std::istream& operator >>(std::istream& lhs, GenericCurve3& rhs);

18    protected:
19        GLenum _usage_flag;
20        RowMatrix<GLuint> _vbo_derivative;
21        Matrix<DCoordinate3> _derivative;

22    public:
23        // default and special constructor
24        GenericCurve3(
25            GLuint maximum_order_of_derivatives = 2,
26            GLuint point_count = 0,
27            GLenum usage_flag = GL_STATIC_DRAW);

28        // special constructor
29        GenericCurve3(const Matrix<DCoordinate3>& derivative, GLenum usage_flag = GL_STATIC_DRAW);
```



Generic curves – header file, part II

GenericCurves3.h

```
30 // copy constructor
31 GenericCurve3(const GenericCurve3& curve);

32 // assignment operator
33 GenericCurve3& operator =(const GenericCurve3& rhs);

34 // vertex buffer object handling methods
35 GLvoid DeleteVertexBufferObjects();
36 GLboolean RenderDerivatives(GLuint order, GLenum render_mode) const;
37 GLboolean UpdateVertexBufferObjects(GLenum usage_flag = GL_STATIC_DRAW);

38 GLfloat* MapDerivatives(GLuint order, GLenum access_mode = GL_READ_ONLY) const;
39 GLboolean UnmapDerivatives(GLuint order) const;

40 // get derivative by value
41 DCoordinate3 operator()(GLuint order, GLuint index) const;

42 // get derivative by reference
43 DCoordinate3& operator()(GLuint order, GLuint index);

44 // other update and query methods
45 GLboolean SetDerivative(GLuint order, GLuint index, GLdouble x, GLdouble y, GLdouble z = 0.0);
46 GLboolean SetDerivative(GLuint order, GLuint index, const DCoordinate3& d);
47 GLboolean GetDerivative(GLuint order, GLuint index, GLdouble& x, GLdouble& y, GLdouble& z) const;
48 GLboolean GetDerivative(GLuint order, GLuint index, DCoordinate3& d) const;

49 GLuint GetMaximumOrderOfDerivatives() const;
50 GLuint GetPointCount() const;
51 GLenum GetUsageFlag() const;

52 // destructor
53 virtual ~GenericCurve3();
54 };
55 }
```



Generic curves – source file, part I

GenericCurves3.cpp

```
1 #include "GenericCurves3.h"

2 using namespace cagd;
3 using namespace std;

4 //
5 // implementation of class GenericCurve3
6 //

7 // default and special constructor
8 GenericCurve3::GenericCurve3(GLuint maximum_order_of_derivatives, GLint point_count, GLenum usage_flag):
9     _usage_flag(usage_flag),
10     _vbo_derivative(maximum_order_of_derivatives + 1),
11     _derivative(maximum_order_of_derivatives + 1, point_count)
12 {
13 }

14 // special constructor
15 GenericCurve3::GenericCurve3(const Matrix<DCoordinate3>& derivative, GLenum usage_flag):
16     _usage_flag(usage_flag),
17     _vbo_derivative(RowMatrix<GLuint>(derivative.GetRowCount())),
18     _derivative(derivative)
19 {
20 }

21 // copy constructor
22 GenericCurve3::GenericCurve3(const GenericCurve3& curve):
23     _usage_flag(curve._usage_flag),
24     _vbo_derivative(RowMatrix<GLuint>(curve._vbo_derivative.GetColumnCount())),
25     _derivative(curve._derivative)
26 {
27     GLboolean vbo_update_is_possible = GL_TRUE;
28     for (GLuint i = 0; i < curve._vbo_derivative.GetColumnCount(); ++i)
29         vbo_update_is_possible &= curve._vbo_derivative(i);
```



Generic curves – source file, part II

GenericCurves3.cpp

```
30     if (vbo_update_is_possible)
31         UpdateVertexBufferObjects(_usage_flag);
32 }

33 // assignment operator
34 GenericCurve3& GenericCurve3::operator =(const GenericCurve3& rhs)
35 {
36     if (this != &rhs)
37     {
38         DeleteVertexBufferObjects();

39         _usage_flag = rhs._usage_flag;
40         _derivative = rhs._derivative;

41         GLboolean vbo_update_is_possible = GL_TRUE;
42         for (GLuint i = 0; i < rhs._vbo_derivative.GetColumnCount(); ++i)
43             vbo_update_is_possible &= rhs._vbo_derivative(i);

44         if (vbo_update_is_possible)
45             UpdateVertexBufferObjects(_usage_flag);
46     }
47     return *this;
48 }

49 // vertex buffer object handling methods
50 GLvoid GenericCurve3::DeleteVertexBufferObjects()
51 {
52     for (GLuint i = 0; i < _vbo_derivative.GetColumnCount(); ++i)
53     {
54         if (_vbo_derivative(i))
55         {
56             glDeleteBuffers(1, &_vbo_derivative(i));
57             _vbo_derivative(i) = 0;
58         }
59     }
```



Generic curves – source file, part III

GenericCurves3.cpp

```
60 }

61 GLboolean GenericCurve3::RenderDerivatives(GLuint order, GLenum render_mode) const
62 {
63     GLuint max_order = _derivative.GetRowCount();
64     if (order >= max_order || !_vbo_derivative(order))
65         return GL_FALSE;

66     GLuint point_count = _derivative.GetColumnCount();

67     glEnableClientState(GL_VERTEX_ARRAY);
68     glBindBuffer(GL_ARRAY_BUFFER, _vbo_derivative(order));
69     glVertexPointer(3, GL_FLOAT, 0, (const GLvoid *)0);

70     if (!order)
71     {
72         if (render_mode != GL_LINE_STRIP &&
73             render_mode != GL_LINE_LOOP &&
74             render_mode != GL_POINTS)
75         {
76             glBindBuffer(GL_ARRAY_BUFFER, 0);
77             glDisableClientState(GL_VERTEX_ARRAY);
78             return GL_FALSE;
79         }

80         glDrawArrays(render_mode, 0, point_count);
81     }
82     else
83     {
84         if (render_mode != GL_LINES && render_mode != GL_POINTS)
85         {
86             glBindBuffer(GL_ARRAY_BUFFER, 0);
87             glDisableClientState(GL_VERTEX_ARRAY);
88             return GL_FALSE;
89         }
90     }
```



Generic curves – source file, part IV

GenericCurves3.cpp

```
90         glDrawArrays(render_mode, 0, 2 * point_count);
91     }

92     glBindBuffer(GL_ARRAY_BUFFER, 0);
93     glDisableClientState(GL_VERTEX_ARRAY);

94     return GL_TRUE;
95 }

96 GLboolean GenericCurve3::UpdateVertexBufferObjects(GLenum usage_flag)
97 {
98     if (usage_flag != GL_STREAM_DRAW && usage_flag != GL_STREAM_READ &&
99         usage_flag != GL_STREAM_COPY &&
100         usage_flag != GL_DYNAMIC_DRAW && usage_flag != GL_DYNAMIC_READ &&
101         usage_flag != GL_DYNAMIC_COPY &&
102         usage_flag != GL_STATIC_DRAW && usage_flag != GL_STATIC_READ &&
103         usage_flag != GL_STATIC_COPY)
104         return GL_FALSE;

105     DeleteVertexBufferObjects();

106     _usage_flag = usage_flag;

107     for(GLuint d = 0; d < _vbo_derivative.GetColumnCount(); ++d)
108     {
109         glGenBuffers(1, &_vbo_derivative(d));

110         if (!_vbo_derivative(d))
111         {
112             for (GLuint i = 0; i < d; ++i)
113             {
114                 glDeleteBuffers(1, &_vbo_derivative(i));
115                 _vbo_derivative(i) = 0;
116             }
117         }
118     }
119 }
```



Generic curves – source file, part V

GenericCurves3.cpp

```
117         return GL_FALSE;
118     }
119 }

120 GLuint curve_point_count = _derivative.GetColumnCount();

121 GLfloat *coordinate = 0;

122 // curve points
123 GLuint curve_point_byte_size = 3 * curve_point_count * sizeof(GLfloat);

124 glBindBuffer(GL_ARRAY_BUFFER, _vbo.derivative(0));
125 glBufferData(GL_ARRAY_BUFFER, curve_point_byte_size, 0, _usage_flag);

126 coordinate = (GLfloat*)glMapBuffer(GL_ARRAY_BUFFER, GL_WRITE_ONLY);

127 if (!coordinate)
128 {
129     glBindBuffer(GL_ARRAY_BUFFER, 0);
130     DeleteVertexBufferObjects();
131     return GL_FALSE;
132 }

133 for (GLuint i = 0; i < curve_point_count; ++i)
134 {
135     for (GLuint j = 0; j < 3; ++j)
136     {
137         *coordinate = (GLfloat)_derivative(0,i)[j];
138         ++coordinate;
139     }
140 }

141 if (!glUnmapBuffer(GL_ARRAY_BUFFER))
142 {
```



Generic curves – source file, part VI

GenericCurves3.cpp

```
143     glBindBuffer(GL_ARRAY_BUFFER, 0);
144     DeleteVertexBufferObjects();
145     return GL_FALSE;
146 }
147
148 // higher order derivatives
149 GLuint higher_order_derivative_byte_size = 2 * curve_point_byte_size;
150
151 for (GLuint d = 1; d < _derivative.GetRowCount(); ++d)
152 {
153     glBindBuffer(GL_ARRAY_BUFFER, _vbo_derivative(d));
154     glBufferData(GL_ARRAY_BUFFER, higher_order_derivative_byte_size, 0, _usage_flag);
155
156     coordinate = (GLfloat*)glMapBuffer(GL_ARRAY_BUFFER, GL_WRITE_ONLY);
157
158     if (!coordinate)
159     {
160         glBindBuffer(GL_ARRAY_BUFFER, 0);
161         DeleteVertexBufferObjects();
162         return GL_FALSE;
163     }
164
165     for (GLuint i = 0; i < curve_point_count; ++i)
166     {
167         DCoordinate3 sum = _derivative(0, i);
168         sum += _derivative(d, i);
169
170         for (GLint j = 0; j < 3; ++j)
171         {
172             *coordinate = (GLfloat)_derivative(0, i)[j];
173             *(coordinate + 3) = (GLfloat)sum[j];
174             ++coordinate;
175         }
176
177         coordinate += 3;
178     }
179 }
```



Generic curves – source file, part VII

GenericCurves3.cpp

```
171     }
172     if (!glUnmapBuffer(GL_ARRAY_BUFFER))
173     {
174         glBindBuffer(GL_ARRAY_BUFFER, 0);
175         DeleteVertexBufferObjects();
176         return GL_FALSE;
177     }
178 }
179
180 glBindBuffer(GL_ARRAY_BUFFER, 0);
181
182 return GL_TRUE;
183 }
184
185 GLfloat* GenericCurve3::MapDerivatives(GLuint order, GLenum access_mode) const
186 {
187     if (order >= _derivative.GetRowCount())
188         return 0;
189
190     if (access_mode != GL_READ_ONLY && access_mode != GL_WRITE_ONLY && access_mode != GL_READ_WRITE)
191         return 0;
192
193     glBindBuffer(GL_ARRAY_BUFFER, _vbo_derivative(order));
194
195     return (GLfloat*)glMapBuffer(GL_ARRAY_BUFFER, access_mode);
196 }
197
198 GLboolean GenericCurve3::UnmapDerivatives(GLuint order) const
199 {
200     if (order >= _derivative.GetRowCount())
201         return GL_FALSE;
202
203     glBindBuffer(GL_ARRAY_BUFFER, _vbo_derivative(order));
```



Generic curves – source file, part VIII

GenericCurves3.cpp

```
196     return glUnmapBuffer(GL_ARRAY_BUFFER);
197 }

198 // get derivative by value
199 DCoordinate3 GenericCurve3::operator()(GLuint order, GLuint index) const
200 {
201     return _derivative(order, index);
202 }

203 // get derivative by reference
204 DCoordinate3& GenericCurve3::operator()(GLuint order, GLuint index)
205 {
206     return _derivative(order, index);
207 }

208 // other update and query methods
209 GLboolean GenericCurve3::SetDerivative(GLuint order, GLuint index, GLdouble x, GLdouble y, GLdouble z)
210 {
211     if (order >= _derivative.GetRowCount() || index >= _derivative.GetColumnCount())
212         return GL_FALSE;

213     _derivative(order, index)[0] = x;
214     _derivative(order, index)[1] = y;
215     _derivative(order, index)[2] = z;

216     return GL_TRUE;
217 }

218 GLboolean GenericCurve3::SetDerivative(GLuint order, GLuint index, const DCoordinate3& d)
219 {
220     if (order >= _derivative.GetRowCount() || index >= _derivative.GetColumnCount())
221         return GL_FALSE;

222     _derivative(order, index) = d;
```



Generic curves – source file, part IX

GenericCurves3.cpp

```
223     return GL_TRUE;
224 }

225 GLboolean GenericCurve3::GetDerivative(GLuint order, GLuint index, GLdouble& x, GLdouble& y, GLdouble& z)
226 {
227     if (order >= _derivative.GetRowCount() || index >= _derivative.GetColumnCount())
228         return GL_FALSE;

229     x = _derivative(order, index)[0];
230     y = _derivative(order, index)[1];
231     z = _derivative(order, index)[2];

232     return GL_TRUE;
233 }

234 GLboolean GenericCurve3::GetDerivative(GLuint order, GLuint index, DCoordinate3& d) const
235 {
236     if (order >= _derivative.GetRowCount() || index >= _derivative.GetColumnCount())
237         return GL_FALSE;

238     d = _derivative(order, index);

239     return GL_TRUE;
240 }

241 GLuint GenericCurve3::GetMaximumOrderOfDerivatives() const
242 {
243     return _derivative.GetRowCount() - 1;
244 }

245 GLuint GenericCurve3::GetPointCount() const
246 {
247     return _derivative.GetColumnCount();
248 }
```



Generic curves – source file, part X

GenericCurves3.cpp

```
249 GLenum GenericCurve3::GetUsageFlag() const
250 {
251     return _usage_flag;
252 }
253 // destructor
254 GenericCurve3::~GenericCurve3()
255 {
256     DeleteVertexBufferObjects();
257 }
258 // -----
259 // input/output from/to stream
260 // -----
261 ostream& cagd::operator <<(ostream& lhs, const GenericCurve3& rhs)
262 {
263     return lhs << rhs._usage_flag << "_" << rhs._derivative << endl;
264 }
265 std::istream& cagd::operator >>(std::istream& lhs, GenericCurve3& rhs)
266 {
267     rhs.DeleteVertexBufferObjects();
268     return lhs >> rhs._usage_flag >> rhs._derivative;
269 }
```



Parametric curves

Class `ParametricCurve3`

Description

- Class `ParametricCurve3` is based on classes `DCoordinate3`, `Matrix`, and `GenericCurve3`, and provides methods for creating and rendering smooth parametric curves of the form

$$\mathbf{c}(u) = \begin{bmatrix} x(u) \\ y(u) \\ z(u) \end{bmatrix}, u \in [u_{\min}, u_{\max}].$$

- Create a new folder `Parametric` aside of your project file. Copy the files `ParametricCurves3.h` and `ParametricCurves3.cpp` into this folder and finish their implementation.



Parametric curves – header file, part I

ParametricCurves3.h

```
1 #pragma once

2 #include "../Core/DCoordinates3.h"
3 #include "../Core/GenericCurves3.h"
4 #include "../Core/Matrices.h"

5 namespace cagd
6 {
7     // _____
8     // class ParametricCurve3
9     // _____
10    class ParametricCurve3
11    {
12    public:
13        typedef DCoordinate3 (*Derivative)(GLdouble);

14    private:
15        // definition domain
16        GLdouble _u_min, _u_max;

17        // derivatives of coordinate functions
18        RowMatrix<Derivative> _derivatives;

19    public:
20        // special constructor
21        ParametricCurve3(const RowMatrix<Derivative>& derivatives, GLdouble u_min, GLdouble u_max);

22        // calculate derivative at the parameter value u
23        DCoordinate3 operator()(GLuint order, GLdouble u) const;

24        // generate image/arc
25        GenericCurve3* GenerateImage(GLuint div_point_count, GLenum usage_flag = GL_STATIC_DRAW) const;

26        // set/get definition domain
27        GLvoid SetDefinitionDomain(GLdouble u_min, GLdouble u_max);
```



Parametric curves – header file, part II

ParametricCurves3.h

```
28     GLvoid GetDefinitionDomain(GLdouble& u_min, GLdouble& u_max) const;  
29     // set derivatives  
30     GLvoid SetDerivatives(const RowMatrix<Derivative>& derivatives);  
31 };  
32 }
```



Parametric curves – source file, part I

ParametricCurves3.cpp

```
1 #include "ParametricCurves3.h"

2 using namespace cagd;
3 using namespace std;

4 //
5 // implementation of class ParametricCurve3
6 //

7 // special constructor
8 ParametricCurve3::ParametricCurve3(
9     const RowMatrix<Derivative>& derivatives ,
10     GLdouble u_min, GLdouble u_max):
11     _u_min(u_min), _u_max(u_max),
12     _derivatives(derivatives)
13 {
14 }

15 // calculate derivative at parameter u:
16 // 0th order derivative corresponds to the curve point at parameter u
17 // 1st order derivative corresponds to the tangent vector at parameter u
18 // 2nd order derivative corresponds to the acceleration vector at parameter u
19 // etc.
20 DCoordinate3 ParametricCurve3::operator()(GLuint order, GLdouble u) const
21 {
22     return _derivatives(order)(u);
23 }

24 // generate image of the parametric curve
25 GenericCurve3* ParametricCurve3::GenerateImage(GLuint div_point_count, GLenum usage_flag) const
26 {
27     GenericCurve3* result = nullptr;
28     result = new (nothrow) GenericCurve3(_derivatives.GetColumnCount() - 1, div_point_count, usage_flag);
```



Parametric curves – source file, part II

ParametricCurves3.cpp

```
29     if (!result)
30     {
31         return nullptr;
32     }

33     // set derivatives at the endpoints of the parametric curve
34     for (GLuint order = 0; order < _derivatives.GetColumnCount(); ++order)
35     {
36         (*result)(order, 0) = _derivatives(order)(_u_min);
37         (*result)(order, div_point_count - 1) = _derivatives(order)(_u_max);
38     }

39     // calculate derivatives at inner curve points
40     GLdouble u_step = (_u_max - _u_min) / (div_point_count - 1);
41     GLdouble u = _u_min;

42     for (GLuint i = 1; i < div_point_count - 1; ++i)
43     {
44         u += u_step;

45         for (GLuint order = 0; order < _derivatives.GetColumnCount(); ++order)
46         {
47             (*result)(order, i) = _derivatives(order)(u);
48         }
49     }

50     return result;
51 }

52 // set/get definition domain
53 GLvoid ParametricCurve3::SetDefinitionDomain(GLdouble u_min, GLdouble u_max)
54 {
55     // homework
56 }
57
```



Parametric curves – source file, part III

ParametricCurves3.cpp

```
58 GLvoid ParametricCurve3::GetDefinitionDomain(GLdouble& u_min, GLdouble& u_max) const
59 {
60     // homework
61 }

62 // set derivatives
63 GLvoid ParametricCurve3::SetDerivatives(const RowMatrix<Derivative> &derivatives)
64 {
65     // homework
66 }
```



Testing parametric curves

Class ParametricCurve3

Testing parametric curves

- Create a new folder **Test** aside of your project file. Copy the files **TestFunctions.h** and **TestFunctions.cpp** into this folder.
- Modify the files **GLWidget.h** and **GLWidget.cpp** accordingly to the next slides.



Testing parametric curves – declaring/defining test functions

TestFunctions.h/cpp

• TestFunctions.h

```
1 #pragma once
2 #include " ../Core/DCoordinates3.h"
3 namespace cagd
4 {
5     namespace spiral_on_cone
6     {
7         extern GLdouble u_min, u_max;
8
9         DCoordinate3 d0(GLdouble);
10        DCoordinate3 d1(GLdouble);
11        DCoordinate3 d2(GLdouble);
12    }
13
14    namespace ...
15    {
16        extern GLdouble u_min, u_max;
17
18        DCoordinate3 d0(GLdouble);
19        DCoordinate3 d1(GLdouble);
20        DCoordinate3 d2(GLdouble);
21        DCoordinate3 d3(GLdouble);
22    }
23 }
```

• TestFunctions.cpp

```
1 #include <cmath>
2 #include "TestFunctions.h"
3 using namespace cagd;
4 using namespace std;
5 GLdouble spiral_on_cone::u_min = -6.2831;
6 GLdouble spiral_on_cone::u_max = +6.2831;
7 DCoordinate3 spiral_on_cone::d0(GLdouble u)
8 {
9     return DCoordinate3(
10         u * cos(u),
11         u * sin(u),
12         u);
13 }
14 DCoordinate3 spiral_on_cone::d1(GLdouble u)
15 {
16     return DCoordinate3(
17         cos(u) - u * sin(u),
18         sin(u) + u * cos(u),
19         1.0);
20 }
21 DCoordinate3 spiral_on_cone::d2(GLdouble u)
22 {
23     return DCoordinate3(
24         -2.0 * sin(u) - u * cos(u),
25         2.0 * cos(u) - u * sin(u),
26         0);
27 }
```



Testing parametric curves – modifying GLWidget.h

GLWidget.h

```
1 #pragma once
2 #include <GL/glew.h>
3 #include <QOpenGLWidget>
4 #include "../Parametric/ParametricCurves3.h"
5 namespace cagd
6 {
7     class GLWidget: public QOpenGLWidget
8     {
9         Q_OBJECT
10     private:
11         ...
12         ParametricCurve3* _pc;
13         GenericCurve3* _image_of_pc;
14     public:
15         ...
16         virtual ~GLWidget();
17     public slots:
18         ...
19 };
20 }
```



Testing parametric curves – modifying GLWidget.cpp, part I

GLWidget.cpp

```
1 #include "GLWidget.h"
2 #include <iostream>
3 #include "../Core/Matrices.h"
4 #include "../Test/TestFunctions.h"

5 using namespace cagd;
6 using namespace std;

7 ...

8 GLWidget::~GLWidget()
9 {
10     if (_pc)
11         delete _pc, _pc= nullptr;

12     if (_image_of_pc)
13         delete _image_of_pc, _image_of_pc = nullptr;
14 }

15 void GLWidget::initializeGL()
16 {
17     ...

18     try
19     {
20         // initializing the OpenGL Extension Wrangler library
21         GLenum error = glewInit();

22         if (error != GLEW_OK)
23         {
24             throw Exception("Could not initialize the OpenGL Extension Wrangler Library!");
25         }
26     }
```



Testing parametric curves – modifying GLWidget.cpp,

part II

GLWidget.cpp

```
26 if (!glewIsSupported("GL_VERSION_2_0"))
27 {
28     throw Exception("Your graphics card is not compatible with OpenGL 2.0+!"
29                     "Try to update your driver or buy a new graphics adapter!");
30 }
31
32 // create and store your geometry in display lists or vertex buffer objects
33 // ...
34 RowMatrix<ParametricCurve3::Derivative> derivative(3);
35 derivative[0] = spiral_on_cone::d0;
36 derivative[1] = spiral_on_cone::d1;
37 derivative[2] = spiral_on_cone::d2;
38
39 _pc = nullptr;
40 _pc = new (nothrow) ParametricCurve3(derivative, spiral_on_cone::u_min, spiral_on_cone::u_max);
41
42 if (!_pc)
43 {
44     // error: either close the application, or handle this exception
45 }
46
47 GLint div_point_count = 200;
48 GLenum usage_flag = GL_STATIC_DRAW;
49
50 _image_of_pc = nullptr;
51 _image_of_pc = _pc->GenerateImage(div_point_count, usage_flag);
52
53 if (!_image_of_pc)
54 {
55     throw Exception("Could not generate the image of the parametric curve!");
56 }
```



Testing parametric curves – modifying GLWidget.cpp, part III

GLWidget.cpp

```
52     if (! _image_of_pc->UpdateVertexBufferObjects( usage_flag ))
53     {
54         throw Exception(" Could_not_create_the_vertex_buffer_object_of_the_parametric_curve!");
55     }

56     glEnable(GL_POINT_SMOOTH);
57     glHint(GL_POINT_SMOOTH_HINT, GL_NICEST);

58     glEnable(GL_LINE_SMOOTH);
59     glHint(GL_LINE_SMOOTH_HINT, GL_NICEST);

60     glEnable(GL_POLYGON_SMOOTH);
61     glHint(GL_POLYGON_SMOOTH_HINT, GL_NICEST);

62     glHint(GL_PERSPECTIVE_CORRECTION_HINT, GL_NICEST);

63     glEnable(GL_DEPTH_TEST);
64 }
65 catch (Exception &e)
66 {
67     cout << e << endl;
68 }
69 }

70 void GLWidget::paintGL()
71 {
72     glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);

73     // saving the current modelview matrix
74     glPushMatrix();

75     // transformations
```



Testing parametric curves – modifying GLWidget.cpp, part IV

GLWidget.cpp

```
76     ...
77     if (_image_of_pc)
78     {
79         glColor3f(1.0f, 0.0f, 0.0f);
80         _image_of_pc->RenderDerivatives(0, GL_LINE_STRIP);
81
82         glPointSize(5.0f);
83
84         glColor3f(0.0f, 0.5f, 0.0f);
85         _image_of_pc->RenderDerivatives(1, GL_LINES);
86         _image_of_pc->RenderDerivatives(1, GL_POINTS);
87
88         glColor3f(0.1f, 0.5f, 0.9f);
89         _image_of_pc->RenderDerivatives(2, GL_LINES);
90         _image_of_pc->RenderDerivatives(2, GL_POINTS);
91
92         glPointSize(1.0f);
93     }
94
95     // restoring the former modelview matrix
96     glPopMatrix();
97 }
```



Testing parametric curves – results

A spiral on a cone

A spiral on a cone

$$\begin{cases} x(u) &= u \cos(u), \\ y(u) &= u \sin(u), \\ z(u) &= u, \end{cases}$$

$$u \in [-2\pi, 2\pi].$$

Fig. 1: A spiral lying on the surface of a perpendicular cone. The green and blue vectors represent the first (i.e., the tangent vectors) and second order derivatives (i.e., acceleration vectors), respectively.



Testing parametric curves – results

A torus knot

A torus knot

$$\begin{cases} x(u) &= (2 + \cos(\frac{2u}{3})) \cos(u), \\ y(u) &= (2 + \cos(\frac{2u}{3})) \sin(u), \\ z(u) &= \sin(\frac{2u}{3}), \end{cases}$$
$$u \in [0, 6\pi].$$



Homework

- Append the files `TestFunctions.h` and `TestFunctions.cpp` with at least 6 new parametric curve declarations and definitions.
- At least 2 of these new parametric curves should lie on smooth parametric surfaces (e.g., on spheres, ellipsoids, tori, cylinders, hyperboloids, Dupin cyclides), but you may also define other 2- and 3-dimensional continuous/smooth open or closed parametric curves (such as circles, ellipses, cycloids, epi- and hypocycloids, epi- and hypotrochoids, Lissajous-curves, foliums, rose and butterfly curves, witch of Agnesi, helices, Viviani curves, etc.).
- Declare/define/render at least 6 different smooth parametric curves!
- Update the GUI of the application (you should be able to interactively switch between different parametric curves, to show/hide/scale their first- and second-order derivatives, and to increase/decrease the number of subdivision points of the definition domain)!

