

Vertex and fragment/pixel shaders

Part 2

– a CAGD approach based on OpenGL and C++ –

Ágoston Róth

Department of Mathematics and Computer Science, Babeş-Bolyai University, Cluj-Napoca, Romania

(agoston.roth@gmail.com)

Lecture 8 – April 25, 2022



© Ágoston Róth, 2022

Data types in GLSL

- Simple data types:

```
float  
bool  
int
```

- Vectors with 2, 3, or 4 components are also available for each of the simple data types:

```
vec{2,3,4} // a vector of 2, 3, or 4 floats  
bvec{2,3,4} // bool vector  
ivec{2,3,4} // vector of integers
```

- Square matrices of size 2×2 , 3×3 , and 4×4 are also provided:

```
mat2  
mat3  
mat4
```

- The data types for texture sampling are:

```
sampler1D // for 1D textures  
sampler2D // for 2D textures  
sampler3D // for 3D textures  
samplerCube // for cube map textures  
sampler1DShadow // for shadow maps  
sampler2DShadow // for shadow maps
```

- Arrays can be declared using the same syntax as in C. However, arrays cannot be initialized when declared. Accessing elements of an array is done as in C.



Data types in GLSL

- Simple data types:

```
float  
bool  
int
```

- Vectors with 2, 3, or 4 components are also available for each of the simple data types:

```
vec{2,3,4} // a vector of 2, 3, or 4 floats  
bvec{2,3,4} // bool vector  
ivec{2,3,4} // vector of integers
```

- Square matrices of size 2×2 , 3×3 , and 4×4 are also provided:

```
mat2  
mat3  
mat4
```

- The data types for texture sampling are:

```
sampler1D // for 1D textures  
sampler2D // for 2D textures  
sampler3D // for 3D textures  
samplerCube // for cube map textures  
sampler1DShadow // for shadow maps  
sampler2DShadow // for shadow maps
```

- Arrays can be declared using the same syntax as in C. However, arrays cannot be initialized when declared. Accessing elements of an array is done as in C.



Data types in GLSL

- Simple data types:

```
float  
bool  
int
```

- Vectors with 2, 3, or 4 components are also available for each of the simple data types:

```
vec{2,3,4} // a vector of 2, 3, or 4 floats  
bvec{2,3,4} // bool vector  
ivec{2,3,4} // vector of integers
```

- Square matrices of size 2×2 , 3×3 , and 4×4 are also provided:

```
mat2  
mat3  
mat4
```

- The data types for texture sampling are:

```
sampler1D // for 1D textures  
sampler2D // for 2D textures  
sampler3D // for 3D textures  
samplerCube // for cube map textures  
sampler1DShadow // for shadow maps  
sampler2DShadow // for shadow maps
```

- Arrays can be declared using the same syntax as in C. However, arrays cannot be initialized when declared. Accessing elements of an array is done as in C.



Data types in GLSL

- Simple data types:

```
float  
bool  
int
```

- Vectors with 2, 3, or 4 components are also available for each of the simple data types:

```
vec{2,3,4} // a vector of 2, 3, or 4 floats  
bvec{2,3,4} // bool vector  
ivec{2,3,4} // vector of integers
```

- Square matrices of size 2×2 , 3×3 , and 4×4 are also provided:

```
mat2  
mat3  
mat4
```

- The data types for texture sampling are:

```
sampler1D // for 1D textures  
sampler2D // for 2D textures  
sampler3D // for 3D textures  
samplerCube // for cube map textures  
sampler1DShadow // for shadow maps  
sampler2DShadow // for shadow maps
```

- Arrays can be declared using the same syntax as in C. However, arrays cannot be initialized when declared. Accessing elements of an array is done as in C.



Data types in GLSL

- Simple data types:

```
float  
bool  
int
```

- Vectors with 2, 3, or 4 components are also available for each of the simple data types:

```
vec {2,3,4} // a vector of 2, 3, or 4 floats  
bvec {2,3,4} // bool vector  
ivec {2,3,4} // vector of integers
```

- Square matrices of size 2×2 , 3×3 , and 4×4 are also provided:

```
mat2  
mat3  
mat4
```

- The data types for texture sampling are:

```
sampler1D // for 1D textures  
sampler2D // for 2D textures  
sampler3D // for 3D textures  
samplerCube // for cube map textures  
sampler1DShadow // for shadow maps  
sampler2DShadow // for shadow maps
```

- Arrays can be declared using the same syntax as in C. However, arrays cannot be initialized when declared. Accessing elements of an array is done as in C.



Data types in GLSL

- Structures are also allowed in GLSL. The syntax is the same as C.

```
struct DirectionalLight
{
    vec4 position;
    vec3 ambient, diffuse, specular;
};
```



Variables in GLSL, part I

/*
Declaring a simple variable is pretty much the same as in C,
you can even initialize a variable when declaring it.
*/

```
vec3 a, b;           // two 3D vectors  
int c = 2;           // c is initialized with 2  
bool d = true;       // d is true
```

/*
Declaring the other types of variables follows the same pattern,
but there are differences between GLSL and C regarding initialization.
GLSL relies heavily on constructor for initialization and type casting.
*/

```
float e = 2;          // incorrect, there is no automatic type casting  
float f = (float)2;   // incorrect, requires constructors for type casting  
  
int g = 2;  
float h = float(g);   // correct  
  
vec3 v = vec3(1.0, 0.0, 0.0); // declaring and initializing v
```

/*
GLSL is pretty flexible when initializing variables using other variables.
All that it requires is that you provide the necessary number of components.
*/

```
vec2 x = vec2(1.0, 2.0);  
vec2 y = vec2(3.0, 4.0);  
  
vec4 z = vec4(x, y)           // z = vec4(1.0, 2.0, 3.0, 4.0);  
  
vec2 w = vec2(1.0, 2.0);  
float p = 3.0;  
  
vec3 q = vec3(w, p);          // q = vec3(1.0, 2.0, 3.0);
```



Variables in GLSL, part II

/* Matrices also follow this pattern. You have a wide variety of constructors for matrices. For instance the following constructors for initializing a matrix are available:

```
*/  
  
mat4 M = mat4(1.0)           // initializing the diagonal of the matrix with 1.0  
  
vec2 x = vec2(1.0, 2.0);  
vec2 y = vec2(3.0, 4.0);  
  
mat2 N = mat2(x, y);          // matrices are assigned in column major order  
  
mat2 K = mat2(1.0,0.0,1.0,0.0); // all elements are specified
```

/* The declaration and initialization of structures is demonstrated below.

```
*/  
  
struct DirectionalLight  
{  
    vec4 position;  
    vec3 ambient, diffuse, specular;  
};  
  
DirectionalLight dl = DirectionalLight(  
    vec4(0.0, 0.0, -1.0, 0.0),  
    vec3(0.4, 0.4, 0.4),  
    vec3(0.8, 0.8, 0.8),  
    vec3(1.0, 1.0, 1.0));
```

/* In GLSL a few extras are provided to simplify our lives, and make the code a little bit clearer. Accessing a vector can be done using letters as well as standard C selectors.

```
*/  
  
vec4 s = vec4(1.0, 2.0, 3.0, 4.0);
```



Variables in GLSL, part III

```
float x_coordinate = s.x;  
float y_coordinate = s[1];  
  
vec2 both_xy_coordinates = s.xy;  
  
float depth = s.w;
```

- If you are talking about colors then r, g, b, a can be used.
For texture coordinates the available selectors are s, t, p, q.
Notice that by convention, texture coordinates are often referred as s, t, r, q.
However r is already being used as a selector for "red" in RGBA.
Hence there was a need to find a different letter, and the lucky one was p.

Matrix selectors can take one or two arguments, for instance m[0], or m[2][3].
In the first case the first column is selected, whereas in the second a single element is selected.

As for structures the names of the elements of the structure can be used as in C,
so assuming the structures described above the following line of code could be written:

- ```
dl.ambient = vec3(0.5, 0.0, 0.0);
```



## Variable qualifiers

- **const** – the declaration is of a compile time constant;
- **attribute** – global variables that may change per vertex, that are passed from the OpenGL application to vertex shaders (this qualifier can only be used in vertex shaders for which such a variable is read-only);
- **uniform** – global variables that may change per primitive (may not be set inside glBegin/glEnd), that are passed from the OpenGL application to the shaders (this qualifier can be used in both vertex and fragment shaders; for the shaders such variables are read-only);
- **varying** – used for interpolated data between a vertex shader and a fragment shader (available for writing in the vertex shader, and read-only in a fragment shader).



## Variable qualifiers

- **const** – the declaration is of a compile time constant;
- **attribute** – global variables that may change per vertex, that are passed from the OpenGL application to vertex shaders (this qualifier can only be used in vertex shaders for which such a variable is read-only);
- **uniform** – global variables that may change per primitive (may not be set inside glBegin/glEnd), that are passed from the OpenGL application to the shaders (this qualifier can be used in both vertex and fragment shaders; for the shaders such variables are read-only);
- **varying** – used for interpolated data between a vertex shader and a fragment shader (available for writing in the vertex shader, and read-only in a fragment shader).



## Variable qualifiers

- **const** – the declaration is of a compile time constant;
- **attribute** – global variables that may change per vertex, that are passed from the OpenGL application to vertex shaders (this qualifier can only be used in vertex shaders for which such a variable is read-only);
- **uniform** – global variables that may change per primitive (may not be set inside glBegin/glEnd), that are passed from the OpenGL application to the shaders (this qualifier can be used in both vertex and fragment shaders; for the shaders such variables are read-only);
- **varying** – used for interpolated data between a vertex shader and a fragment shader (available for writing in the vertex shader, and read-only in a fragment shader).



## Variable qualifiers

- **const** – the declaration is of a compile time constant;
- **attribute** – global variables that may change per vertex, that are passed from the OpenGL application to vertex shaders (this qualifier can only be used in vertex shaders for which such a variable is read-only);
- **uniform** – global variables that may change per primitive (may not be set inside glBegin/glEnd), that are passed from the OpenGL application to the shaders (this qualifier can be used in both vertex and fragment shaders; for the shaders such variables are read-only);
- **varying** – used for interpolated data between a vertex shader and a fragment shader (available for writing in the vertex shader, and read-only in a fragment shader).



# Control flow statements in GLSL

- The available options are pretty much the same as in C. There are conditional statements, like **if-else**, iteration statements like **for**, **while** and **do-while**.
- A few jumps are also defined:

`continue`     `// available in loops, causes a jump to the next iteration of the loop`

`break`        `// available in loops, causes an exit of the loop`

`discard`      `// can only be used in fragment shaders: it causes the termination of the shader`  
`// for the current fragment without writing to the frame buffer, or depth`



# Control flow statements in GLSL

- The available options are pretty much the same as in C. There are conditional statements, like **if-else**, iteration statements like **for**, **while** and **do-while**.
- A few jumps are also defined:

**continue**     // available in loops, causes a jump to the next iteration of the loop

**break**        // available in loops, causes an exit of the loop

**discard**      // can only be used in fragment shaders: it causes the termination of the shader  
                 // for the current fragment without writing to the frame buffer, or depth





## Functions in GLSL

- As in C a shader is structured in functions.
- At least each type of shader must have a main function declared with the following syntax:

```
void main()
{
 /*
 code
 */
}
```

- User defined functions may be defined. As in C a function may have a return value, and should use the **return statement** to pass out its result. A function can be **void** of course. **The return type can have any type, but it cannot be an array.**
- The parameters of a function have the following qualifiers available:

```
in // for input parameters

out // for outputs of the function (the return statement is also an option
 // for sending the result of a function)

inout // for parameters that are both input and output of a function
```

If no qualifier is specified, by default it is considered to be **in**.

- A function can be overloaded as long as the list of parameters is different. Recursion behavior is undefined by specification.



## Functions in GLSL

- As in C a shader is structured in functions.
- At least each type of shader must have a main function declared with the following syntax:

```
void main()
{
 /*
 code
 */
}
```

- User defined functions may be defined. As in C a function may have a return value, and should use the **return statement** to pass out its result. A function can be **void** of course. **The return type can have any type, but it cannot be an array.**
- The parameters of a function have the following qualifiers available:

```
in // for input parameters

out // for outputs of the function (the return statement is also an option
 // for sending the result of a function)

inout // for parameters that are both input and output of a function
```

If no qualifier is specified, by default it is considered to be **in**.

- A function can be overloaded as long as the list of parameters is different. Recursion behavior is undefined by specification.



# Functions in GLSL

- As in C a shader is structured in functions.
- At least each type of shader must have a main function declared with the following syntax:

```
void main()
{
 /*
 code
 */
}
```

- User defined functions may be defined. As in C a function may have a return value, and should use the **return statement** to pass out its result. A function can be **void** of course. **The return type can have any type, but it cannot be an array.**
- The parameters of a function have the following qualifiers available:

```
in // for input parameters

out // for outputs of the function (the return statement is also an option
 // for sending the result of a function)

inout // for parameters that are both input and output of a function
```

If no qualifier is specified, by default it is considered to be **in**.

- A function can be overloaded as long as the list of parameters is different. Recursion behavior is undefined by specification.



## Functions in GLSL

- As in C a shader is structured in functions.
- At least each type of shader must have a main function declared with the following syntax:

```
void main()
{
 /*
 code
 */
}
```

- User defined functions may be defined. As in C a function may have a return value, and should use the **return statement** to pass out its result. A function can be **void** of course. **The return type can have any type, but it cannot be an array.**
- The parameters of a function have the following qualifiers available:

```
in // for input parameters

out // for outputs of the function (the return statement is also an option
 // for sending the result of a function)

inout // for parameters that are both input and output of a function
```

If no qualifier is specified, by default it is considered to be **in**.

- A function can be overloaded as long as the list of parameters is different. Recursion behavior is undefined by specification.



## Functions in GLSL

- As in C a shader is structured in functions.
- At least each type of shader must have a main function declared with the following syntax:

```
void main()
{
 /*
 code
 */
}
```

- User defined functions may be defined. As in C a function may have a return value, and should use the **return statement** to pass out its result. A function can be **void** of course. **The return type can have any type, but it cannot be an array.**
- The parameters of a function have the following qualifiers available:

```
in // for input parameters

out // for outputs of the function (the return statement is also an option
 // for sending the result of a function)

inout // for parameters that are both input and output of a function
```

If no qualifier is specified, by default it is considered to be **in**.

- A function can be overloaded as long as the list of parameters is different. Recursion behavior is undefined by specification.



# Two sided lighting

Vertex shader: `two_sided_lighting.vert`

```
1 /*
2 It is assumed that the OpenGL 2.0+ application provides:
3 * projection and model view matrices;
4 * several light sources using light indices GL_LIGHT0, GL_LIGHT1,..., GL_LIGHT7;
5 * materials for front and back faces; and
6 * a normal vector for each vertex.
7 */
8
9 varying vec3 normal;
10 varying vec3 vertex;
11
12 void main()
13 {
14 // calculate and normalize the normal vector
15 normal = normalize(gl_NormalMatrix * gl_Normal);
16
17 // transform the vertex position to eye space
18 vertex = vec3(gl_ModelViewMatrix * gl_Vertex);
19
20 gl_Position = ftransform();
21 }
```



# Two sided lighting, part I

Fragment shader: `two_sided_lighting.frag`

```
1 varying vec3 normal;
2 varying vec3 vertex;
3
4 const vec4 AMBIENT_BLACK = vec4(0.0, 0.0, 0.0, 1.0);
5 const vec4 DEFAULT_BLACK = vec4(0.0, 0.0, 0.0, 0.0);
6
7 // i denotes the index of a light source.
8 bool IsLightEnabled(in int i)
9 {
10 bool enabled = true;
11
12 // If all the colors of the Light are set to BLACK then we know we do not need to bother
13 // doing a lighting calculation on it.
14 if ((gl_LightSource[i].ambient == AMBIENT_BLACK) &&
15 (gl_LightSource[i].diffuse == DEFAULT_BLACK) &&
16 (gl_LightSource[i].specular == DEFAULT_BLACK))
17 enabled = false;
18
19 return (enabled);
20 }
21
22 // distance is measured from current vertex to the ith light source.
23 float CalculateAttenuation(in int i, in float distance)
24 {
25 return (1.0 / (gl_LightSource[i].constantAttenuation +
26 gl_LightSource[i].linearAttenuation * distance +
27 gl_LightSource[i].quadraticAttenuation * distance * distance));
28 }
29
30 // N denotes the unit varying normal vector.
31 void DirectionalLight(in int i, in vec3 N, in float shininess,
32 inout vec4 ambient, inout vec4 diffuse, inout vec4 specular)
33 {
34 vec3 L = normalize(gl_LightSource[i].position.xyz);
35 }
```



## Two sided lighting, part II

Fragment shader: `two_sided_lighting.frag`

```
36 float N_dot_L = dot(N, L);
37
38 if (N_dot_L > 0.0)
39 {
40 vec3 H = gl_LightSource[i].halfVector.xyz;
41
42 float pf = pow(max(dot(N,H), 0.0), shininess);
43
44 diffuse += gl_LightSource[i].diffuse * N_dot_L;
45 specular += gl_LightSource[i].specular * pf;
46 }
47
48 ambient += gl_LightSource[i].ambient;
49 }
50
51 // N denotes the unit varying normal vector, while V corresponds to the varying vertex position.
52 void PointLight(in int i, in vec3 N, in vec3 V, in float shininess,
53 inout vec4 ambient, inout vec4 diffuse, inout vec4 specular)
54 {
55 vec3 D = gl_LightSource[i].position.xyz - V;
56 vec3 L = normalize(D);
57
58 float distance = length(D);
59 float attenuation = CalculateAttenuation(i, distance);
60
61 float N_dot_L = dot(N,L);
62
63 if (N_dot_L > 0.0)
64 {
65 vec3 E = normalize(-V);
66 vec3 R = reflect(-L, N);
67
68 float pf = pow(max(dot(R,E), 0.0), shininess);
69
70 diffuse += gl_LightSource[i].diffuse * attenuation * N_dot_L;
```





## Two sided lighting, part III

Fragment shader: `two_sided_lighting.frag`

```
71 specular += gl_LightSource[i].specular * attenuation * pf;
72 }
73
74 ambient += gl_LightSource[i].ambient * attenuation;
75 }
76
77 // N denotes the unit varying normal vector, while V corresponds to the varying vertex position.
78 void Spotlight(in int i, in vec3 N, in vec3 V, in float shininess,
79 inout vec4 ambient, inout vec4 diffuse, inout vec4 specular)
80 {
81 vec3 D = gl_LightSource[i].position.xyz - V;
82 vec3 L = normalize(D);
83
84 float distance = length(D);
85 float attenuation = CalculateAttenuation(i, distance);
86
87 float N_dot_L = dot(N,L);
88
89 if (N_dot_L > 0.0)
90 {
91 float spot_effect = dot(normalize(gl_LightSource[i].spotDirection), -L);
92
93 if (spot_effect > gl_LightSource[i].spotCosCutoff)
94 {
95 attenuation *= pow(spot_effect, gl_LightSource[i].spotExponent);
96
97 vec3 E = normalize(-V);
98 vec3 R = reflect(-L, N);
99
100 float pf = pow(max(dot(R,E), 0.0), shininess);
101
102 diffuse += gl_LightSource[i].diffuse * attenuation * N_dot_L;
103 specular += gl_LightSource[i].specular * attenuation * pf;
104 }
105 }
```



## Two sided lighting, part IV

Fragment shader: `two_sided_lighting.frag`

```
106
107 ambient += gl_LightSource[i].ambient * attenuation;
108 }
109
110 // N denotes the unit varying normal vector, while V corresponds to the varying vertex position.
111 void CalculateLighting(in int number_of_light_sources, in vec3 N, in vec3 V, in float shininess,
112 inout vec4 ambient, inout vec4 diffuse, inout vec4 specular)
113 {
114 // Just loop through each light, and if its enabled add
115 // its contributions to the color of the pixel.
116 for (int i = 0; i < number_of_light_sources; i++)
117 {
118 if (IsLightEnabled(i))
119 {
120 if (gl_LightSource[i].position.w == 0.0)
121 DirectionalLight(i, N, shininess, ambient, diffuse, specular);
122 else if (gl_LightSource[i].spotCutoff == 180.0)
123 PointLight(i, N, V, shininess, ambient, diffuse, specular);
124 else
125 Spotlight(i, N, V, shininess, ambient, diffuse, specular);
126 }
127 }
128 }
129
130 void main()
131 {
132 // Normalize the normal. A varying variable CANNOT be modified by a fragment shader.
133 // So a new variable needs to be created.
134 vec3 n = normalize(normal);
135
136 vec4 ambient, diffuse, specular, color;
137
138 // Initialize the contributions for the front-face-pass over the lights.
139 ambient = vec4(0.0);
140 diffuse = vec4(0.0);
```



## Two sided lighting, part V


Fragment shader: `two_sided_lighting.frag`

```
141 specular = vec4(0.0);
142
143 // In this case the built-in uniform gl_MaxLights is used to denote the number of lights.
144 // A better option may be passing in the number of lights as a uniform or replacing the
145 // current value with a smaller value.
146 CalculateLighting(gl_MaxLights, n, vertex, gl_FrontMaterial.shininess,
147 ambient, diffuse, specular);
148
149 color = gl_FrontLightModelProduct.sceneColor +
150 (ambient * gl_FrontMaterial.ambient) +
151 (diffuse * gl_FrontMaterial.diffuse) +
152 (specular * gl_FrontMaterial.specular);
153
154 // Re-initialize the contributions for the back-face-pass over the lights.
155 ambient = vec4(0.0);
156 diffuse = vec4(0.0);
157 specular = vec4(0.0);
158
159 // Now caculate the back contribution. All that needs to be done is to flip the normal.
160 CalculateLighting(gl_MaxLights, -n, vertex, gl_BackMaterial.shininess,
161 ambient, diffuse, specular);
162
163 color += gl_BackLightModelProduct.sceneColor +
164 (ambient * gl_BackMaterial.ambient) +
165 (diffuse * gl_BackMaterial.diffuse) +
166 (specular * gl_BackMaterial.specular);
167
168 color = clamp(color, 0.0, 1.0);
169
170 gl_FragColor = color;
171 }
```



# Two sided lighting

## Results




**Fig. 1:** Simple color shader.



## Two sided lighting

### Results



**Fig. 2:** A directional light.



## Two sided lighting

### Results




**Fig. 3:** A point light.



## Two sided lighting

### Results




**Fig. 4:** A spotlight.



## Two sided lighting

### Results




**Fig. 5:** The contributions of previous directional and point lights.





## Two sided lighting

### Results




**Fig. 6:** The contributions of previous point and spotlights.



## Two sided lighting

### Results




**Fig. 7:** The contributions of previous directional and spotlights.



## Two sided lighting

### Results




**Fig. 8:** The contributions of previous directional, point, and spotlights.



## Two sided lighting

### Results



**Fig. 9:** The interior (i.e. the set of back faces) of the previous model is also lit up.



# Toon shader

Vertex shader: `toon.vert`

```
1 varying float intensity;
2 varying vec3 normal, light_direction;
3
4 void main()
5 {
6 normal = normalize(gl_NormalMatrix * gl_Normal);
7
8 light_direction = normalize(vec3(gl_LightSource[0].position));
9
10 intensity = dot(light_direction, normal);
11
12 gl_Position = ftransform();
13 }
```



# Toon shader


Fragment shader: `toon.frag`

```
1 uniform vec4 default_outline_color;
2
3 varying float intensity;
4 varying vec3 normal, light_direction;
5
6 void main()
7 {
8 vec4 color = gl_FrontMaterial.ambient;
9 vec3 N = normalize(normal), L = normalize(light_direction);
10 float N_dot_L = max(0.0, dot(N, L));
11
12 if (intensity > 0.95)
13 color += gl_FrontMaterial.diffuse * N_dot_L * 0.95;
14 else if (intensity > 0.85)
15 color += gl_FrontMaterial.diffuse * N_dot_L * 0.85;
16 else if (intensity > 0.75)
17 color += gl_FrontMaterial.diffuse * N_dot_L * 0.75;
18 else if (intensity > 0.65)
19 color += gl_FrontMaterial.diffuse * N_dot_L * 0.65;
20 else if (intensity > 0.55)
21 color += gl_FrontMaterial.diffuse * N_dot_L * 0.55;
22 else if (intensity > 0.45)
23 color += gl_FrontMaterial.diffuse * N_dot_L * 0.45;
24 else
25 {
26 color = default_outline_color;
27 }
28
29 gl_FragColor = color;
30 }
```



## Toon shader

### Results




**Fig. 10:** Toon shader (the default outline color is  $(0.2, 0.125, 0.0, 1.0)$ ; the applied material is MatFBRuby).



## Toon shader

### Results





**Fig. 11:** Toon shader (the default outline color is  $(0.15, 0.0, 0.2, 1.0)$ ); the applied material is MatFBPearl).





## Guide to writing shaders



© Agoston Roth, 2022