

Quote

41260509

PT. Flow Force Indonesia
 Kawasan Industri, Delta Silicon 5, Jl. Kenari 1
 Blok G1, No.23D
 Cikarang Bekasi WEST JAVA 17550
 Indonesia

Date Quoted: 29/06/2026
 Expires: 13/08/2026
 Customer: PT. Flow Force Indonesia
 Payment terms: 100% Upfront before Dispatch
 Delivery: FCA Noordwijkerhout Incoterms®
 2020
 Sales Person: Stan Wijnands
 Handled by: Pallavi H
 E-mail: P.H@dmnwestinghouse.com
 Phone:

Reference: 2451

Line	Part Description	Revision	Quantity	Unit Price	Discount %	Total Price
1	RV BL 200 4TS : BL - Rotary valve Option 1 Commodity Code: 84818090		1 NOS	€ 10,923.00	30.00%	€ 7,646.10
	Packaging Costs			€ 125.00		
		Lead Time 20weeks a.r.o				
2	RV BL 200 2 : BL - Rotary valve Option 2 Commodity Code: 84818090		1 NOS	€ 15,088.00	30.00%	€ 10,561.60
	Packaging Costs			€ 125.00		
		Lead Time 20weeks a.r.o				
Lines Total:						€ 18,207.70
Line Miscellaneous Charges:						€ 250.00
Total Net Including Taxes:						€ 18,457.70

"GENERAL CONDITIONS for the SUPPLY OF MECHANICAL, ELECTRICAL AND ELECTRONIC PRODUCTS" submitted along with Quotation by DMN India Private Limited.

Bank Details
 Bank Name: Axis Bank
 Account No: 920020068358184
 IFSC Code: UTIB0002103
 Branch: Redhills

CIN No.
 U29309TN2020FTC139131
 PAN No. AAICD1095M

TAN No. CHED12479F
 GST No. 33AAICD1095M1ZG
 IEC No. AAICD1095M

Quote Number:	Line:	
41260509	1	Rotary valve DMN
Web Configuration ID	112107	
Description	BL 200 4TS : BL - Rotary valve	
Customer specification		
Product Certification	Europe [CE]	
Product specification		
Product temperature [°C]	45	
Country of destination	Indonesia	
Industry	Other	
Product name	Not in table	
Product name [Free text]	PVC blend powder + 35% calcium carbonate	
Average Bulk Density [kg/m3]	0.0	
Product size		
Flowability		
Abrasive	Very abrasive	
Corrosive		
Sticky	No	
Fluidising	No	
Hygroscopic	No	
System description		
Location	Indoor installation	
Application	Pneumatic conveying	
Valve position		
Capacity [ton/hr]	0.000	
Filling efficiency [%]	0	
Pressure inlet [barg]	0.000	
Pressure outlet [barg]	0.000	
Pressure difference [barg]	0.000	
Ambient temperature Min. [°C]	20	
Ambient temperature Max. [°C]	20	
Conveying air temperature Max. [°C]	30	
Explosive Atmosphere		
Explosive Atmosphere	No	
Hygienic Design		
EC1935/2004	No	
Hygienic Design	No	

Rotary valve specification

Type	BL - Rotary valve
Size	200
Execution	4TS - Abrasion resistant cast iron (Tungsten SED)

Body and Cover

Connection	Round flange DN
Flange hole pattern	Drilled DIN PN10
Coating body and end covers	Bore and end covers internally tungsten carbide coated
Material body and end covers	Cast iron EN-GJL-250
Bearing	Outboard ball bearings sealed for life
Vent holes	Drilled and plugged
Blowing line flange diameter	Ø 80mm
Blowing line counter flange	Counter Flanges mild steel
Earthing lug	Including earthing lug M10 on inlet flange

Rotor

Rotor	9 Adjustable blades - Semi end disc - Mild steel
Capacity at 100% filling [l/rev]	10.50
Coating rotor	Semi end discs and shafts tungsten carbide coated

Blades

Rotor blades	Hardened steel / Hardox 450 replaceable
--------------	---

Seal

Shaft sealing	Air purge with Rameh packing
Air regulator set	Pressure regulator/filterset *FESTO On-Off valve 24VDC (3GD)

Drive

Rotor speed [rpm]	18
Drive execution	Chain Drive
Voltage [V]	230D/400Y 50Hz
Frequency	50Hz/inverter operation 25-50Hz
Protection class [IP]	65
Thermal class [ISO]	F
Drive speed [rpm]	22
Drive	SEW R47DRN80M4/TF IE3 0.75kW PTC M5 180/2 22/27rpm 50/60Hz

Painting

Paint valve	RAL 9006 colour valve DMN system A - Standard C1
Paint drive	RAL 9006 colour drive DMN system A - Standard C1

Packaging

Packaging	Pallet box - Individual packaging
-----------	-----------------------------------

Documentation

Standard language

Base Documents

English

Rotary valve Installation and Safety instructions

Spare part list

Parts list

Operating instruction

CE Declaration of conformity

Inspection report

Quote Number: **Line:**

41260509

2

Rotary valve DMN

Web Configuration ID

112108

Description

BL 200 2 : BL - Rotary valve

Customer specification

Product Certification

Europe [CE]

Product specification

Product temperature [°C]

45

Country of destination

Indonesia

Industry

Other

Product name

Not in table

Product name [Free text]

PVC blend powder + 35% calcium carbonate

Average Bulk Density [kg/m3]

0.0

Product size

Flowability

Abrasive

Very abrasive

Corrosive

Sticky

No

Fluidising

No

Hygroscopic

No

System description

Location

Indoor installation

Application

Pneumatic conveying

Valve position

Capacity [ton/hr]

0.000

Filling efficiency [%]

0

Pressure inlet [barg]

0.000

Pressure outlet [barg]

0.000

Pressure difference [barg]

0.000

Ambient temperature Min. [°C]

20

Ambient temperature Max. [°C]

20

Conveying air temperature Max. [°C]

30

Explosive Atmosphere

Explosive Atmosphere

No

Hygienic Design

EC1935/2004

No

Hygienic Design

No

Rotary valve specification

Type	BL - Rotary valve
Size	200
Execution	2 - Stainless steel

Body and Cover

Connection	Round flange DN
Flange hole pattern	Drilled DIN PN10
Coating body and end covers	Bore and end covers internally tungsten carbide coated
Material body and end covers	Stainless steel 316 (DIN 1.4408)
Bearing	Outboard ball bearings sealed for life
Vent holes	Vent holes drilled including plugs
Blowing line flange diameter	Ø 80mm
Blowing line counter flange	Counter Flanges stainless steel 316L
Earthing lug	Including earthing lug M10 on inlet flange

Rotor

Rotor	9 Adjustable blades - Stainless steel
Capacity at 100% filling [l/rev]	10.50
Coating rotor	Rotor shafts tungsten coated

Blades

Rotor blades	Stainless steel replaceable
Option	Kolsterised C22

Seal

Shaft sealing	Air purge with Teadit 2005 FDA packing
Air regulator set	Pressure regulator/filterset *FESTO On-Off valve 24VDC (3GD)

Drive

Rotor speed [rpm]	18
Drive execution	Chain Drive
Voltage [V]	230D/400Y 50Hz
Frequency	50Hz/inverter operation 25-50Hz
Protection class [IP]	65
Thermal class [ISO]	F
Drive speed [rpm]	22
Drive	SEW R47DRN80M4/TF IE3 0.75kW PTC M5 180/2 22/27rpm 50/60Hz
Stainless steel parts	Motor base plate and Chain guard Stainless steel

Painting

Paint drive	RAL 9006 colour drive DMN system A - Standard C1
-------------	--

Packaging

Packaging	Pallet box - Individual packaging
-----------	-----------------------------------

Documentation

Standard language	English
-------------------	---------

Base Documents

Rotary valve Installation and Safety instructions
Spare part list
Parts list
Operating instruction
CE Declaration of conformity
Inspection report