

[Dashboard](#) / [My courses](#) / [CENG420\(Tripoli-B-214045\) Fall 2022 - 2023](#) / [CENG420 Midterm](#) / [Midterm Exam](#)

Question **1**

Not yet answered

Marked out of 4.00

Select tag that does not include the "multiple" is similar to:

Select one:

- ☒ a. Radio
- ☐ b. textarea
- ☒ c. Checkboxes

[Clear my choice](#)

Question **2**

Not yet answered

Marked out of 4.00

If the encoding value is known, one can insert the corresponding character directly into a web page using the character encoding reference \_\_\_\_.

- ☐ a. &char;
- ☐ b. &copy;
- ☐ c. &nbsp;
- ☒ d. &#code;

[Clear my choice](#)

Question **3**  
Not yet answered  
Marked out of 4.00

Use the correct HTML attribute to show a table like the one in the figure

Name		Age
Hamssa	Hasrouny	100
XYZ	Amine	94

```
<table>  
  <tr> <th colspan="2">Name</th> <th>Age</th> </tr>  
  <tr> <td>Hamssa</td> <td>Hasrouny</td> <td>100</td> </tr>  
  <tr> <td>XYZ</td> <td>Amine</td> <td>94</td> </tr>  
</table>
```

Time left 0:02:43



## Question 4

Not yet answered

Marked out of 8.00

Complete the code such that it validates the inputs on form submit as follows:

1. The name can not be empty and must contain only alphabets
2. The password is at least 8 characters with capital, lowercase and number

If the above restrictions are satisfied, the user will be redirected to the next page, otherwise, the function returns false and an error alert message will be displayed.

```
<body>
```

```
< script
function validate_inputs(){
var name=document.getElementById("
uname").value;
var password=document.getElementById("
upassword").value;
if (name === ""){
alert("Name can't be blank");
return false;
}else if(name.match(/^(?=.{8})(?=.*[a-z])(?=.*[A-Z])/g)){
alert("Name must contain only alphabets");
return false;
} else if (password.match(/8)=null){
alert("password must be at least 8 characters with capital, lowercase and number");
return false;
}
}
</script>
<form action="next.php" innerhtml="return
;" >
Name: <input type="text" id="uname"> <br/>
Password: <input type="password" id="upassword"> <br/>
<input type="submit" value="Submit">
</form>
```



&lt;/body&gt;

Question **5**

Not yet answered

Marked out of 4.00

The output of this code is:

&lt;script&gt;

```
var str="WY WZY W.YZ Y";
```

```
result = str.match(/W.Y/g);
```

```
document.write(result);
```

&lt;/script&gt;

Select one:

- ☐ a. WY,WZY,W.Y
- ☐ b. W.Y
- ☒ c. WZY,W.Y

[Clear my choice](#)Question **6**

Not yet answered

Marked out of 4.00

Identify a text-level element used to mark only text within the document.

- ☐ a. span
- ☒ b. mark
- ☐ c. cite
- ☐ d. div

[Clear my choice](#)

## Question 7

Not yet answered

Marked out of 4.00

Fill in the blanks such that the below Javascript code creates `<span>` that contains the course code and appends it to the paragraph having id "myParag".

`<script>``var myParag= document.  ("myParag");``var myspan= document.  ("  ");``myspan.  = "CENG420";` `myspan.appendChild(text);``myParag.  .(myspan);``</script>`

## Question 8

Not yet answered

Marked out of 4.00

Select the correct JavaScript data type of the following variable:

`var code= 10 + "key";`

Your answer is  **key**

## Question 9

Not yet answered

Marked out of 4.00

Identify an attribute selector that recognizes groups of elements that share a similar characteristic or property.

- ☐ a. list-style-position
- ☒ b. class
- ☐ c. id
- ☐ d. pseudo-element

[Clear my choice](#)

Question **10**

Not yet answered

Marked out of 4.00

**What will be the effect of below mentioned code snippet?**

```
p, strong {background-color: yellow;}
```

Select one:

- ☐ a. None of the mentioned
- ☒ b. Strong have yellow background
- ☐ c. Both p and strong have yellow background
- ☐ d. Strong element within a p element have a yellow background

[Clear my choice](#)Question **11**

Not yet answered

Marked out of 4.00

in HTML, the \_\_\_\_ tag is used as keywords for search engines

Select one:

- ☒ a. meta
- ☐ b. head
- ☐ c. link

[Clear my choice](#)Question **12**

Not yet answered

Marked out of 4.00

Select the correct JavaScript data type of the following variable:

```
var code= Number("10");
```

Your answer is

**Number**

Question **13**

Not yet answered

Marked out of 4.00

The structure for an unordered list is similar to that used with ordered lists except that the list items are grouped within the \_\_\_\_\_ element.

- ☒ a. `ul`
- ☐ b. `ol`
- ☐ c. `li`
- ☐ d. `p`

[Clear my choice](#)Question **14**

Not yet answered

Marked out of 4.00

What is the correct JavaScript syntax to change the font family of an HTML element?

Select one:

- ☐ a. `document.getElementById(id).fontFamily`
- ☐ b. `document.getElementById(id).style.fontfamily`
- ☒ c. `document.getElementById(id).style.fontFamily`
- ☐ d. `document.getElementById(id).fontfamily`

[Clear my choice](#)Question **15**

Not yet answered

Marked out of 4.00

\_\_\_\_\_ contains a generic grouping of elements within a document.

- ☒ a. `<div>`
- ☐ b. `<span>`
- ☐ c. `<dir>`
- ☐ d. `<dd>`

[Clear my choice](#)

## Question 16

Not yet answered

Marked out of 4.00

To access the styles in an external style sheet, use the empty \_\_\_\_ element to link a document to a style sheet.

- ☒ a. <link>
- ☐ b. <head>
- ☐ c. <access>
- ☐ d. <style>

[Clear my choice](#)

## Question 17

Not yet answered

Marked out of 4.00

**When using the shorthand property, the order of the values are**

Select one:

- ☐ a. font-family font-variant font-weight font-size font-style
- ☒ b. font-style font-variant font-weight font-size font-family
- ☐ c. all of the mentioned
- ☐ d. font-variant font-weight font-size font-family font-style

[Clear my choice](#)

## Question 18

Not yet answered

Marked out of 8.00

Complete the missing text:

```
p.one {  
  border- : solid;  
  border- : red;  
  border- : 2px;  
}
```



Question **19**

Not yet answered

Marked out of 4.00

input type Textarea, has rows and cols attribute to specify the size.

Select one:

☐ True

☒ False

Question **20**

Not yet answered

Marked out of 4.00

**Which HTML attribute is used to define inline styles?**

Select one:

☐ a. class

☐ b. font

☐ c. style

☒ d. styles

[Clear my choice](#)

Question **21**

Not yet answered

Marked out of 4.00

`<body onload="myFunction()">` executes myFunction() immediately after a page has been loaded:

Question **22**

Not yet answered

Marked out of 4.00

If you need to display a mathematical equation in your Web document, the Web browser will not interpret '<' and '>' as the beginning and end brackets of an XHTML tag.

Select one:

☐ True

☒ False



Question **23**

Not yet answered

Marked out of 4.00

Which of the following HTML attributes is used to create a single cell that occupies more than one cell from a series of horizontal cells?

- ☐ a. colwidth
- ☐ b. rowwidth
- ☒ c. rowspan
- ☐ d. colspan

[Clear my choice](#)[Client Side Lecture 1 ►](#)