université de BORDEAUX

Automatic tuning of the IO500 benchmark parameters with Bayesian Optimization

M2 Computer Science
Internship Report

Inria Centre at the University of Bordeaux

Supervisors:

September 1, 2026

Contents

1. Introduction **1**
1.1. Objectives of the internship . . . 3
1.2. Contributions . . . 3
1.3. Organisation of the report . . . 3

2. Context of the internship **3**
2.1. Inria and the Inria Centre at the University of Bordeaux . . . 3
2.2. The host team : TADaaM [6] . . . 4
2.3. Scientific and technical environment . . . 4
2.4. Objectives and specifications . . . 5
2.5. Organisation of the work . . . 6

3. Background **7**
3.1. IO500 . . . 7
3.1.1. Motivation and purpose . . . 7
3.1.2. Benchmark structure . . . 7
3.1.3. IO500 workloads . . . 8
3.1.4. Scoring and ranking . . . 8
3.1.5. Execution rules and stonewall . . . 9
3.1.6. Configuration and tuning . . . 10
3.2. IOPS . . . 11
3.2.1. Motivation and purpose . . . 11
3.2.2. IOPS workflow . . . 11
3.2.3. Parameter configuration . . . 12
3.2.4. Search strategies . . . 12
3.2.5. Result management and caching . . . 13
3.3. Bayesian Optimization . . . 13

Bibliography **16**

1. Introduction

High Performance Computing (HPC) systems are used to run large-scale scientific and engineering applications. The applications use many compute resources in parallel and often process large amounts of data. Therefore, an application's performance does not only depend on the computing power of the system, but also on the performance of its storage infrastructure. In many HPC workloads, I/O operations become the bottleneck that limits overall application performance.

Parallel file systems (PFS) such as Lustre [12], BeeGFS [17] and GPFS [11] are commonly used to provide high-performance storage in HPC environments. In a PFS, the storage capacity is exposed as a set of logical units called Object Storage Targets (OSTs). When a file is written, it is split into fixed-size chunks that are sent in parallel to several targets, so that the bandwidth of many storage devices is used at once. This process is known as striping and is illustrated in Figure 1. How many targets a file is spread over, called the stripe count, and how large each chunk is, called the stripe size, are configuration choices rather than fixed properties of the system. Therefore, a PFS exposes configuration parameters that can affect I/O performance. Beyond striping, performance can also depend on the transfer size, the number of processes, or the placement of processes on compute nodes. The best values for these parameters are not necessarily the same for every machine: a configuration that performs well on one system may perform poorly on another one.




Figure 1: Striping in a parallel file system. A file created on a compute node is split into fixed-size chunks, which are written in parallel to storage targets hosted by the storage servers. Here the stripe count is three, so the file is spread over three of the eight available targets.

To evaluate the performance of these systems, we rely on benchmarks. A benchmark is a program designed to stress a specific part of a system under controlled and reproducible conditions, so that

the measurements it produces can be compared across machines and configurations [2]. For I/O, two of the most widely used benchmarks are IOR [14], which measures the bandwidth reached by large parallel read and write operations, and mdtest [15], which measures the rate at which metadata operations such as creating, opening and removing files are performed. A different approach is taken by mini-applications, or miniapps [1], which reproduce the access pattern of a real scientific application in a reduced and self-contained form, and therefore measure performance under a workload closer to production use. Each of these benchmarks characterises one aspect of the system, and none of them alone describes the storage system as a whole.

Thus, the variety of parameters and access patterns makes the evaluation of I/O performance difficult: a benchmark must not only measure the performance of the storage system, but also provide a meaningful way to compare different systems and configurations. For this reason, the HPC community maintains rankings in which every system runs the same benchmarks under a common set of rules, so that the resulting scores can be compared and ordered. The best known of them is the TOP500 [21], which ranks HPC platforms by their computational performance. In the I/O world, the community created the IO500 benchmark suite [9]. IO500 is widely used to evaluate and rank the I/O performance of HPC storage systems, and it combines several workloads, including bandwidth-oriented and metadata-oriented operations, into a single score, which is used to produce the IO500 ranking.

Because IO500 is a ranking, there is a direct incentive for HPC sites to obtain the best possible score. For vendors and system integrators, a high position is a commercial argument, used in marketing material and in procurement discussions. For computing centres, it is a public and comparable demonstration that the machine they operate delivers the capability it was built for, which matters both for the visibility of the centre and for justifying the investment it represents. However, the reported performance of a system does not only depend on its hardware, but also on how the system is configured and how the benchmark is executed. Finding a good configuration is therefore essential to obtain the highest possible score.

However, there is a large number of possible configurations, which makes the tuning of IO500 difficult: a configuration can involve several parameters, and each parameter can have multiple possible values. The combination of these parameters creates a potentially large search space, and finding a good configuration therefore requires evaluating many possible combinations.

Another important difficulty is the cost of an IO500 evaluation. According to the IO500 submission rules [10], each write and create phase must run for at least 300 s. A run that finishes the write phase earlier is considered invalid. This requirement makes a valid IO500 measurement relatively expensive in terms of cluster time: on the target platform, one valid measurement takes approximately 30 min of exclusive cluster time. When several configurations and repetitions are considered, the total cost becomes very large. For instance, in the parameter space considered in this work, approximately 7,840 configurations have to be evaluated. Measuring all of them with three repetitions would require approximately 12 000 h of wall-clock time, which corresponds to more than one year of computation on the target machine. Therefore, An exhaustive search is not practical.

This leads to the main research question of this internship:

> *Can a smarter search method find a near-optimal IO500 configuration using far fewer evaluations, and which search method is most effective for this problem?*

1.1. Objectives of the internship

The objective of this internship is to tune IO500 with a guided search instead of an exhaustive one, and to determine which search method should be used in practice. Bayesian Optimization is the main candidate, but it is a family of methods rather than a single one, so a large part of the work consists in comparing its variants, and comparing them against random and exhaustive search.

The work is carried out with IOPS [13], a benchmark orchestration framework developed in the team. IOPS describes a parametric study in a single YAML file and takes care of generating the runs, submitting them to the cluster scheduler, parsing their output and caching the results. Two of its features matter here: the search strategy is a configuration option, so exhaustive, random and Bayesian searches can be compared without changing anything else; and a study can be replayed from the cache, which is what makes the offline comparison possible.

1.2. Contributions

The main contributions of this work are the following.

- *A cheap ground-truth methodology* to evaluate search strategies for tuning IO500, based on a set of invalid scores that are much cheaper to generate but still allow the strategies to be compared.
- *A systematic comparison of Bayesian Optimization variants*, which identifies the setup that performs best and shows which of its parameters actually matter.
- *A validation campaign* on the cluster, checking that the configurations selected on the cheap proxy remain the best ones under the official IO500 rules.

1.3. Organisation of the report

The remainder of this report is organised as follows. The next section presents the host laboratory and the environment in which the internship took place. The background section then introduces what is needed to read the rest of the report: the IO500 benchmark and its rules, the parameters exposed by parallel file systems, and the principles of Bayesian Optimization. Related work on I/O auto-tuning is reviewed next, followed by a description of the tools, the platform and the experimental setup. The methodology section explains how the ground truth was built and how the search strategies were compared, and the results section reports and analyses the measurements. The report closes with a discussion of the limitations of the study and a conclusion.

2. Context of the internship

2.1. Inria and the Inria Centre at the University of Bordeaux

Inria is the French national research institute for digital science and technology. Its research activities cover a wide range of topics in computer science, applied mathematics, and digital technologies. Research is organised into project teams, which bring together researchers, engineers, PhD students, and other scientific staff around common research topics.

The internship was carried out at the Inria Centre at the University of Bordeaux. The centre is located on the Talence campus and brings together research teams working on different areas of

digital science. Inria currently has 22 project teams associated with the centre, including 20 teams located in Talence and two teams in Pau. The centre brings together more than 470 researchers, engineers, technical staff, and other members of the research and innovation community. These teams are developed in partnership with institutions such as the University of Bordeaux, Bordeaux INP, CNRS, Inserm, INRAE, and other academic and industrial partners [3].

The research activities of the centre cover several areas of digital science. These include high-performance computing and Big Data, machine learning, and digital health. This diversity reflects the different research problems addressed within the centre, ranging from fundamental computer science to applications in science, engineering, and health. For the work presented in this report, the high-performance computing research activities are particularly relevant.

Several project teams at the centre work on high-performance and distributed computing. For example, the STORM, TADaaM, CONCACE, and TOPAL teams are associated with research topics related to high-performance computing, systems, optimisation, and the execution of parallel applications [5]. These teams contribute to a local research environment in which computing performance, system software, and large-scale data management are studied using both theoretical approaches and experiments on real HPC platforms.

2.2. The host team : TADaaM [6]

The internship was carried out within the TADaaM project team at the Inria Centre at the University of Bordeaux. TADaaM works on data management for high-performance computing systems, with a particular interest in the interaction between applications, computing resources, networks, and storage systems. The team studies how data can be managed efficiently at system scale and how the characteristics of the underlying infrastructure affect application performance.

The internship is part of the team's activities related to storage performance characterisation and I/O benchmarking. In particular, the work contributes to the study of how HPC storage systems can be configured and evaluated using the IO500 benchmark suite. The internship also makes use of IOPS, a benchmark orchestration and optimisation framework developed within the team. The framework provides the tools needed to automate benchmark executions, explore different parameter configurations, and collect and analyse their results.

The internship was supervised by Luan Teylo, a researcher working within the TADaaM team. The work was also connected to a broader collaboration around IO500 and HPC I/O performance. Discussions involved Liam Radita, Sara Neuwirth, and Jay Lofstead. These interactions provided feedback on the benchmark configuration, experimental methodology, and interpretation of the results.

The specific role of the internship was therefore to investigate the automated tuning of IO500 configurations. The work focused on the experimental side of this research activity, from running the benchmark on the target platform to evaluating automated search strategies and validating their results.

2.3. Scientific and technical environment

The experiments conducted during the internship were carried out on PlaFRIM, the experimental computing platform used by the Inria research community in Bordeaux. PlaFRIM provides access

to several types of computing nodes and is designed to support experiments on high-performance computing systems and new hardware technologies [4].

The experiments presented in this report were conducted on the `bora` nodes, which consist of 44 nodes, from `bora001` to `bora044`. Each node is equipped with two 18-core Intel Xeon Gold 6240 processors, providing 36 physical CPU cores per node, and 192 GB of memory. The nodes are connected through a 100 Gbit/s Omni-Path network, as well as a 10 Gbit/s Ethernet network. For the experiments described in this report, the BeeGFS parallel file system is accessed through the 100 Gbit/s Omni-Path network [4].

The use of a dedicated and homogeneous set of nodes is important for the experiments carried out in this work. Since the objective is to compare different IO500 configurations, changes in the measured performance should primarily result from the parameters being studied rather than from differences between compute nodes. [4].

The experiments were managed using SLURM, the workload manager used on PlaFRIM. SLURM was used to request computing resources and to execute benchmark experiments on the selected nodes. Depending on the experiment, jobs could therefore be allocated with a specified number of nodes and resources. This was particularly important for the internship because the number of compute nodes and processes is itself part of the parameter space explored when tuning IO500.

The storage system used for the experiments is BeeGFS, a parallel file system designed to provide high-performance access to shared storage. The benchmark data and results were stored on the BeeGFS file system provided by PlaFRIM. In addition to BeeGFS, the `bora` nodes provide a local 1 TB disk mounted under `/tmp`. The experiments described in this report, however, focus on the performance of the parallel storage system rather than the local disks [4].

The software environment consisted of Linux together with the tools required to build and execute the benchmarks. Python 3.10 was used for the development and execution of the scripts associated with the experiments. OpenMPI was used as the MPI implementation required by the parallel benchmark workloads. The main research tools were IO500, used to evaluate the I/O performance of the system, and IOPS, used to automate the execution and exploration of different benchmark configurations.

The development process was split between the PlaFRIM environment and a local development machine. The source code, scripts, and experimental configurations were managed using Git and GitLab. This allowed the development work and experimental results to be kept under version control while the computationally intensive benchmark executions were performed on the cluster.

2.4. Objectives and specifications

The main objective of the internship was to tune the IO500 benchmark on the PlaFRIM `bora` cluster and determine whether automated search strategies could find good configurations with fewer evaluations than an exhaustive search.

From the beginning, the main elements of the study were fixed: IO500 was used as the benchmark, PlaFRIM `bora` as the target platform, and IOPS as the framework for running the experiments. Bayesian Optimization (BO) was selected as the main search strategy, with random search and exhaustive search used for comparison.

The first stage of the internship focused on the exhaustive search. The objective was to explore the parameter space and obtain measurements that could later be used to compare the different search strategies. Each configuration was also evaluated several times to account for the variability of HPC measurements.

The study then focused on comparing the different search strategies under a limited number of evaluations. In particular, the objective was to determine whether BO could find configurations close to the best configurations found by exhaustive search while requiring significantly fewer evaluations.

As the internship progressed, the scope was extended to the development of IOPS. A plugin for running IO500 experiments was added to IOPS, together with an example YAML configuration describing the benchmark and the parameters explored during the study. This made it possible to run the IO500 experiments directly through IOPS and provided a reproducible configuration for the experiments.

The IOPS documentation was also updated to describe the new functionality and its usage.

The search component of IOPS was also extended with an implementation of the Tree-structured Parzen Estimator (TPE). At this stage, the method had been implemented but had not yet been evaluated on the IO500 experiments. Other optimisation methods, such as Iterated Racing (irace) and Covariance Matrix Adaptation Evolution Strategy (CMA-ES), were also considered as possible extensions.

These additional tasks emerged as the project evolved and extended the initial scope of the internship.

2.5. Organisation of the work

The internship took place from 14 April to 16 September. The work was organised progressively, starting with the study of the existing tools and the experimental environment, followed by the experimental campaigns and the development work.

The work was supervised by Luan Teylo through a weekly meeting of approximately 30 minutes. These meetings were used to review the progress of the work, discuss experimental results, and define the next tasks. Notes and follow-up tasks were recorded using the Inria Notes platform. Mattermost was also used for communication.

The work was managed using Git and GitLab. A personal repository was used to keep track of the work carried out during the internship, while the IOPS team repository was used for contributions to the existing IOPS project. This allowed the development work and experimental scripts to be versioned throughout the internship.

The internship also included a meeting with Liam Radita, Sara Neuwirth, and Jay Lofstead as part of the broader collaboration around the IO500 work.

3. Background

3.1. IO500

3.1.1. Motivation and purpose

IO500 is a benchmark suite designed to evaluate the I/O performance of storage systems used in High Performance Computing (HPC). It was created to provide a common and reproducible way of measuring storage performance across different systems and configurations [7].

Rather than measuring a single aspect of I/O performance, IO500 combines several workloads that represent different types of storage operations. The results can then be used both to characterise a system and to compare it with other systems through the public IO500 ranking [9].

In this work, IO500 is used as the objective to optimise. The following subsections describe how the suite is organised, which workloads it uses, how its score is computed, and which execution rules and configuration parameters are relevant to the experiments.

3.1.2. Benchmark structure

IO500 is a benchmark suite rather than a single benchmark program. It combines several workloads that evaluate different aspects of I/O performance. The suite provides a common framework for running these workloads and collecting their results under the same experimental conditions [7].

The benchmark is organised into a sequence of tests. Each test runs a specific workload on the storage system and produces a performance measurement. These measurements are kept separately because they represent different aspects of I/O performance. For example, a workload may focus on the amount of data transferred per second, while another may measure the rate of file-system metadata operations.

The workloads are executed using a set of parameters that describe how the benchmark should use the available computing and storage resources. These parameters can include the number of compute nodes, the number of processes, and file-system settings. The same workload can therefore produce different results depending on the configuration used for the run.

After the individual workloads have been executed, their results are combined to produce the overall IO500 score. The score provides a single value that can be used to compare different storage systems or different configurations of the same system. The individual results are also important because they make it possible to identify which aspects of I/O performance contribute to the final score.

IO500 also defines common rules for submitting results to the public ranking. A submission contains not only the measured performance but also information about the system and the configuration used during the experiment [10]. This makes the results more reproducible and allows the conditions of different submissions to be compared.

The suite is used to produce several public lists, including the Production and Research lists. These lists group results according to the conditions under which the systems were evaluated [9]. The following subsection describes the main workloads included in IO500 and the type of I/O operations measured by each of them.

3.1.3. IO500 workloads

IO500 combines several workloads in order to evaluate different aspects of storage performance. The current mandatory benchmark includes `ior-easy`, `ior-hard`, `mdtest-easy`, `mdtest-hard`, and `find` [7, 10]. The workloads are based on IOR, mdtest, and pfind, which are included with the IO500 software.

The IOR workloads focus on data transfer performance. They measure how quickly data can be written to and read from the storage system. The `ior-easy` workload uses a relatively regular access pattern, while `ior-hard` uses a more demanding pattern. These two workloads therefore provide complementary measurements of bandwidth performance.

The mdtest workloads focus on metadata operations. Instead of measuring the amount of data transferred, they measure operations such as creating, stat-ing, reading, and deleting files. The `mdtest-easy` and `mdtest-hard` workloads use different configurations to exercise the metadata system under different conditions.

The `find` workload measures the performance of searching for files and directories. This operation is different from the operations performed by IOR and mdtest because it involves searching through the file-system namespace.

The benchmark therefore combines workloads that stress different parts of the storage system. IOR mainly contributes to the bandwidth measurement, while mdtest and find provide information about metadata and namespace performance. The individual results are kept separately and are then used to compute the final IO500 score [7].

Table 1 summarises the main workloads used in this work.

Table 1: Main IO500 workloads used in this work.

Workload	Main tool	Main aspect measured
`ior-easy`	IOR	Sequential I/O bandwidth
`ior-hard`	IOR	More demanding I/O pattern
`mdtest-easy`	mdtest	Metadata performance
`mdtest-hard`	mdtest	Metadata performance
`find`	pfind	File-system search

The next subsection explains how these individual measurements are combined into the IO500 score and how this score is used for ranking systems.

3.1.4. Scoring and ranking

Each IO500 workload produces an individual performance result. These results use different units depending on the type of operation. For example, IOR measures bandwidth, while metadata and search workloads measure the rate of file-system operations.

Since these results are not directly comparable, IO500 converts them into scores and combines them to obtain an overall score. The scores of the different workloads are combined using a geometric mean. For a set of n workload scores $s_1, s_2, \ldots, s_n$, the combined score is computed as

$$S = \left(\prod_{i=1}^{n} s_i \right)^{1/n} . \tag{3.1}$$

The use of the geometric mean gives importance to all workloads. A low score in one workload can therefore reduce the overall score even if the other workloads perform well. This makes it difficult to obtain a high overall score by optimising only one aspect of I/O performance.

The IO500 workloads cover different aspects of storage performance, including bandwidth, metadata operations, and file-system search. Their individual results are combined according to the scoring rules defined by IO500 [10]. The resulting score provides a single value that can be used to compare different systems and configurations.

These scores are then used to build the IO500 ranking. A higher score corresponds to a better position in the ranking, allowing storage systems to be compared under common benchmark and execution rules [9]. The configuration used for the benchmark is therefore an important part of the reported performance.

In this internship, the IO500 score is used as the objective value of the optimisation problem. Each configuration evaluated by IOPS produces a score, and the different search strategies aim to find configurations that maximise this value.

3.1.5. Execution rules and stonewall

IO500 defines several rules for running the benchmark. These rules are important because they make it possible to compare results obtained on different systems. In particular, the benchmark requires some workloads to run for a minimum amount of time.

For an official IO500 submission, the stonewall timer is set to 300 s. This means that the create and write phases must run for at least 300 seconds. If a phase finishes before this time, the run is marked as invalid [10].

The stonewall timer also gives the benchmark enough time to measure the performance of the storage system. Without this minimum time, a short execution could give a result that does not represent the normal performance of the system.

This rule is important for this internship because one IO500 evaluation can take a significant amount of cluster time. When many configurations have to be tested, running every configuration with the official rules would therefore be very expensive.

During the first experiments, we used a shorter stonewall time and small workloads. The goal was to check that IO500 was correctly installed and configured, and to estimate the execution time of a benchmark run. These tests were not valid IO500 submissions because they did not follow the official execution time requirements.

For example, one of the first tests was run with very small workload parameters. The benchmark finished the write phases before the required time and reported the result as invalid. An example of this execution is shown in Figure 2.

```
IO500 version io500-isc26_v2-26-g02091cf254d8 (standard)
[RESULT]       ior-easy-write        1.393679 GiB/s : time 14.363 seconds [INVALID]
[RESULT]    mdtest-easy-write        0.004657 kIOPS : time 4.230 seconds [INVALID]
[      ]            timestamp        0.000000 kIOPS : time 0.001 seconds
[RESULT]       ior-hard-write        0.062207 GiB/s : time 0.027 seconds [INVALID]
[RESULT]    mdtest-hard-write        0.411183 kIOPS : time 1.025 seconds [INVALID]
[RESULT]                 find        9.638051 kIOPS : time 0.004 seconds [INVALID]
[RESULT]        ior-easy-read        2.162208 GiB/s : time 9.263 seconds
[RESULT]     mdtest-easy-stat        8.068038 kIOPS : time 1.008 seconds
[RESULT]        ior-hard-read        0.311229 GiB/s : time 0.009 seconds
[RESULT]     mdtest-hard-stat        2.995320 kIOPS : time 1.008 seconds
[RESULT]   mdtest-easy-delete        3.453049 kIOPS : time 1.010 seconds
[RESULT]     mdtest-hard-read        1.113940 kIOPS : time 1.012 seconds
[RESULT]   mdtest-hard-delete        2.372919 kIOPS : time 1.008 seconds
[      ]  ior-rnd4K-easy-read        0.074871 GiB/s : time 300.007 seconds
[SCORE ] Bandwidth 0.491468 GiB/s : IOPS 1.191814 kiops : TOTAL 0.765335 [INVALID]
```

Figure 2: Example of an invalid IO500 run using a shortened workload. The test was used to verify the benchmark configuration and estimate its execution time.

These short runs were useful for testing the experimental setup. They are also used later in this work as a cheaper way to evaluate many configurations.

3.1.6. Configuration and tuning

The performance obtained by IO500 depends not only on the storage hardware, but also on how the benchmark uses the available resources. Several parameters can therefore be changed between two executions.

At the compute level, the configuration can include the number of compute nodes and the number of processes used by the benchmark. The placement of processes can also affect the communication between the compute nodes and the storage system.

The file system configuration provides additional parameters. For example, the number of storage targets used by a file and the way data is distributed across these targets can affect I/O performance. Other parameters, such as transfer size and block size, can also influence the measured performance.

These parameters are not independent. A configuration that performs well with a small number of processes may not provide the same performance when more processes or nodes are used. Similarly, changing a file-system parameter can have a different effect depending on the number of clients accessing the storage system.

The result is a multi-dimensional configuration space in which each combination of parameter values corresponds to a possible IO500 execution. In this internship, this configuration space is explored using IOPS and different search strategies.

The exhaustive search described later in this report evaluates the configurations in the selected parameter space and provides a reference for the other search strategies. Bayesian Optimization and random search can then be evaluated according to how quickly they find high-scoring configurations.

3.2. IOPS

3.2.1. Motivation and purpose

The previous section showed that tuning IO500 can require a large number of benchmark evaluations. Each evaluation can take a significant amount of cluster time, making manual testing and exhaustive search difficult in practice.

To automate this process, the internship uses IOPS [13]. IOPS is a framework developed within the TADaaM team to run parameter studies on HPC systems. It can generate benchmark runs, submit them to the cluster, collect their results, and use these results to guide a search.

This makes IOPS suitable for the IO500 tuning problem. Instead of manually changing the parameters and launching each benchmark, the parameters and their possible values can be described in an IOPS configuration file. The search strategy can then select which configuration should be evaluated next.

In this internship, IOPS is used as the common framework for comparing different search strategies. This allows exhaustive search, random search, and Bayesian Optimization to use the same benchmark and experimental environment. The main difference between the experiments is therefore the way in which the next configuration is selected.

IOPS also stores the results of the experiments. This is particularly useful for this study because IO500 evaluations are expensive. Once a configuration has been evaluated, its result can be reused without running the benchmark again. This feature is later used to perform part of the comparison offline.

3.2.2. IOPS workflow

An IOPS experiment starts with a configuration file that describes the parameters to be tested and the benchmark to be executed. From this configuration, IOPS generates the different parameter combinations that will be evaluated.

For each evaluation, IOPS prepares the benchmark command with the selected parameters and submits the job to the HPC cluster. The cluster scheduler then executes the benchmark on the allocated resources. Once the execution is finished, IOPS collects the output and extracts the performance result.

The result is associated with the parameters used for the corresponding run. It can then be used by the search strategy to select the next configuration to evaluate. The process is repeated until the search budget is reached or all configurations have been evaluated.

IOPS also provides a cache for the results. When a configuration has already been evaluated, its result can be retrieved from the cache instead of running the benchmark again. This is particularly useful for IO500, where a single valid evaluation can require a significant amount of cluster time.

The general workflow used in this internship can therefore be summarised as follows:

$$\textit{Configuration} \rightarrow \textit{Search} \rightarrow \textit{Job submission} \rightarrow \textit{IO500} \rightarrow \textit{Result} \rightarrow \textit{Cache} \rightarrow \textit{Next configuration}$$

This workflow allows the benchmark execution and the search strategy to remain separate. The same IO500 experiment can therefore be used with different search strategies without changing the

rest of the experimental setup.

3.2.3. Parameter configuration

IOPS uses a YAML configuration file to describe an experiment. The file contains the parameters to explore, the values that can be used for each parameter, and the commands needed to run the benchmark. This makes the experimental setup explicit and allows the same study to be reproduced later.

For the IO500 experiments, the configuration file describes the parameters that can affect the benchmark performance. For example, the number of compute nodes, the number of processes per node, and storage-related parameters can be included in the study. Each possible value is specified in the YAML file, and IOPS uses these values to generate the configurations to evaluate.

A simplified example of the configuration used for this work is shown below:

```yaml
benchmark:
  name: io500

parameters:
  nodes:
    values: [1, 2, 4]
  processes_per_node:
    values: [1, 2, 4, 8]
```

For each combination of parameter values, IOPS creates an experiment and runs IO500 with the corresponding configuration. The resulting IO500 score is then associated with the parameter combination.

The YAML configuration defines the benchmark and the parameter space to explore, while the search strategy determines how configurations are selected. Therefore, the same parameter space can be explored using different strategies available in IOPS, such as exhaustive search, random search, or Bayesian Optimization.

During the internship, an example IO500 YAML configuration was also created as part of the work. This configuration provides a reproducible description of the experiment and can be reused to run IO500 through IOPS.

3.2.4. Search strategies

IOPS supports several search strategies for exploring a parameter space. The search strategy determines which configuration is selected at each step of an experiment.

The simplest approach is exhaustive search. It evaluates all possible parameter combinations and provides the best result within the defined search space. However, the number of configurations can quickly become too large. In this internship, exhaustive search was first used as a reference for the other strategies.

Random search selects configurations randomly from the parameter space. It does not use the results of previous evaluations to select the next configuration. It is therefore simple to use and provides a

useful baseline for comparison.

Bayesian Optimization (BO) is the main search strategy investigated in this internship. It uses the results of previous evaluations to guide the selection of new configurations. However, BO is not a single fixed method. Its behaviour depends on several choices, such as the surrogate model, the acquisition function, the exploration parameters, the number of initial evaluations, and the total search budget.

These parameters can have a significant effect on the quality of the search. For example, the surrogate model determines how the results of previous evaluations are represented, while the acquisition function controls how new configurations are selected. The exploration parameters also influence the balance between testing promising configurations and exploring less tested areas of the parameter space.

In this internship, different BO configurations were therefore evaluated rather than treating Bayesian Optimization as a single method. The objective was to determine which combination of parameters performs best for the IO500 tuning problem under a limited number of evaluations.

The search component of IOPS was also extended during the internship with additional optimization methods. The Tree-structured Parzen Estimator (TPE) was implemented as an additional search strategy. Iterated Racing (irace) and Covariance Matrix Adaptation Evolution Strategy (CMA-ES) were also considered as possible extensions.

All these strategies can use the same IOPS experiment and parameter space.

3.2.5. Result management and caching

IOPS stores the result of each experiment together with the parameters used for that experiment. This allows the results to be kept and reused after the benchmark execution.

This feature is particularly useful for this internship because IO500 evaluations are expensive. Once a configuration has been evaluated, it does not need to be run again if its result is already available.

The results used in this work are stored in an SQLite database. Each entry associates a parameter configuration with its corresponding benchmark result. The database therefore provides a persistent record of the experiments performed during the study.

The cache also makes it possible to replay an experiment without using the cluster. For example, IOPS can use the previously stored results in cache-only mode instead of submitting new benchmark jobs. This was used to compare search strategies offline using the same set of IO500 measurements.

This separation between benchmark execution and result analysis is important for the experimental study. Expensive measurements only need to be performed once, while different search strategies can be evaluated later using the stored results.

3.3. Bayesian Optimization

Bayesian Optimization (BO) is a search method designed for problems where evaluating a configuration is expensive. This makes it suitable for the IO500 tuning problem, since each configuration requires running the benchmark on an HPC system and can therefore consume a

significant amount of cluster time. The main idea of BO is to use the results of previous evaluations to decide which configuration should be evaluated next.

Let the configuration of a benchmark be represented by a vector of parameters x, and let $f(x)$ be the performance obtained by running IO500 with this configuration. The objective is to find a configuration that maximises $f(x)$. In a large search space, evaluating every possible configuration may be too expensive. BO instead tries to find a good configuration with a limited number of evaluations.

BO starts with a small number of initial configurations. These configurations are evaluated using the real objective function, in our case the IO500 benchmark. The obtained results form the initial set of observations. BO then builds a model, called a *surrogate model*, from these observations. This model provides an approximation of the relationship between the configuration parameters and the expected performance.

The surrogate model is used because evaluating the real objective function is expensive, while evaluating the model is much cheaper. The model can therefore be used to estimate which parts of the search space are promising before running another IO500 experiment.

After building the surrogate model, BO uses an *acquisition function* to select the next configuration to evaluate. The acquisition function uses the information provided by the model to decide where the next evaluation should be performed. It can favour configurations that are expected to provide a high score, but it can also favour configurations where the model is uncertain.

The general workflow of Bayesian Optimization is illustrated in Figure 3.




Figure 3: General workflow of Bayesian Optimization for IO500 tuning.

This creates a balance between *exploitation* and *exploration*. Exploitation means testing configurations that are expected to perform well according to the current model. Exploration means testing less certain configurations in order to obtain new information about the search space. Finding a good balance between these two behaviours is important because focusing only on exploitation can cause the search to remain in a local region, while excessive exploration can waste evaluations on configurations that are unlikely to perform well.

The process is then repeated. The selected configuration is evaluated with IO500, its measured score is added to the observations, and the surrogate model is updated. A new configuration is then selected using the updated model. In this way, each expensive evaluation provides information that can be used to improve the following choices.

An important point is that Bayesian Optimization is not a single fixed algorithm. Different surrogate models and acquisition functions can be used, and their parameters can change the behaviour of the search. In this work, we consider Gaussian Processes (GP), Random Forests (RF), and Extra-Trees (ET) as surrogate models. We also consider Expected Improvement (EI), Probability of Improvement (PI), and Lower Confidence Bound (LCB) as acquisition functions.

Other parameters also affect the search, such as the number of initial evaluations and the parameters controlling exploration. The total number of evaluations, or search budget, is another important factor because it determines how many expensive IO500 runs can be performed.

For this reason, the objective of the study is not simply to determine whether Bayesian Optimization works. We also want to determine which combination of BO choices is the most effective for the IO500 tuning problem. The different configurations are evaluated under the same experimental conditions and with a limited number of evaluations. Their performance can then be compared with the exhaustive and random search strategies described previously.

Bibliography

References

[1] Michael A. Heroux, Douglas W. Doerfler, Paul S. Crozier, James M. Willenbring, H. Carter Edwards, Alan Williams, Mahesh Rajan, Eric R. Keiter, Heidi K. Thornquist, and Robert W. Numrich. Improving performance via mini-applications. Technical Report SAND2009-5574, Sandia National Laboratories, 2009. VERIFY: author list and report number.

[2] Torsten Hoefler and Roberto Belli. Scientific benchmarking of parallel computing systems: Twelve ways to tell the masses when reporting performance results. In *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis (SC)*, 2015. VERIFY: article number / pages.

[3] Inria. Inria centre at the university of bordeaux. `https://www.inria.fr/en/inria-centre-university-bordeaux`. Accessed: 2026-08-24.

[4] Inria. Plafrim – cluster of inria of bordeaux. `https://plafrim-users.gitlabpages.inria.fr/doc/`. Accessed: 2026-08-24.

[5] Inria. The project-teams – distributed and high performance computing. `https://www.inria.fr/en/list-of-project-teams`. Accessed: 2026-08-24.

[6] Inria. Tadaam – topology-aware system-scale data management for high-performance computing. `https://www.inria.fr/en/tadaam`. Accessed: 2026-08-24.

[7] IO500 Foundation. Io500 – about. `https://io500.org/about`. Accessed: 2026-08-27.

[8] IO500 Foundation. Io500 – running. `https://io500.org/running`. Accessed: 2026-08-27.

[9] IO500 Foundation. The IO500 list. `https://io500.org/`, 2026. Accessed: September 1, 2026.

[10] IO500 Foundation. IO500 submission rules. `https://io500.org/rules/submission`, 2026. Accessed: September 1, 2026.

[11] Frank Schmuck and Roger Haskin. GPFS: A shared-disk file system for large computing clusters. In *Proceedings of the 1st USENIX Conference on File and Storage Technologies (FAST)*, pages 231–244, 2002. VERIFY: page numbers.

[12] Philip Schwan. Lustre: Building a file system for 1000-node clusters. In *Proceedings of the 2003 Linux Symposium*, 2003. VERIFY: page numbers.

[13] TADaaM, Inria. IOPS: Integrated orchestration for parametric studies. `https://iops-benchmark.com`, 2026. Source repository: `https://gitlab.inria.fr/hpc_io/iops`. Accessed: September 1, 2026.

[14] The IOR contributors. IOR and mdtest: Parallel filesystem I/O benchmarks. `https://github.com/hpc/ior`, 2026. Accessed: September 1, 2026.

[15] The IOR contributors. mdtest: Metadata benchmark for parallel file systems. `https://github.com/hpc/ior`, 2026. Distributed with the IOR suite. Accessed: September 1, 2026.

[16] The scikit-optimize contributors. scikit-optimize: Sequential model-based optimization in Python. https://scikit-optimize.github.io/, 2026. Version TO-COMPLETE.

[17] ThinkParQ GmbH. BeeGFS: The parallel cluster file system. https://www.beegfs.io/, 2026. Accessed: September 1, 2026.

[18] TO-COMPLETE. To-complete: 2022 I/O performance study. https://inria.hal.science/hal-03753813/, 2022.

[19] TO-COMPLETE. To-complete: IO500 tuning on CLAIX23. In *IEEE International Conference on Cluster Computing Workshops (CLUSTER Workshops)*, 2025.

[20] TO-COMPLETE. To-complete: IO500 benchmark reference paper, 2026.

[21] TOP500.org. The TOP500 list. https://www.top500.org/, 2026. Accessed: September 1, 2026.