

API NAME (you don't need it)	HTTP METHOD	PATH	STATUS CODE	DESCRIPTION (if needed)
getAdmin	GET	/api/insight/v1/admin	NO STATUS	Return a list of all admins (without the password which is equal to null)
updateAdmin	PUT	/api/insight/v1/admin/update	200 (OK)	If it returns 200 that means it is updated. Hint: password is not updated with this api. Your request should be sent as a (RequestBody) that means you must check the database to choose the same fields name.
updateAdminPassword	PUT	/api/insight/v1/admin/update/password	200 (OK) 201 (NOT OK)	You must send a RequestBody with the two fields email and the new password (as they are written in the db). If email exists, it will update the password and return 200. If not, it will return 201
addAdmin	POST	/api/insight/v1/admin/add	200 (OK) 201 (NOT OK)	It will check if the new added admin does not exist before by checking the email (Primary key). If the email is not used before, it will create it and return 200. if it is used, it will return 201. Also, it is a RequestBody.
deleteAdmin	DELETE	/api/insight/v1/admin/delete/{email}	200 (OK) 201 (NOT OK)	If the email does exist, it will delete the admin and return 200, and 201 otherwise. {email} in the PATH must be replaced by the email of the admin you need to delete.
login	POST	/api/insight/v1/admin/login	200 (OK) 201 (NOT OK)	It will check for the email and password if both are correct then return 200. If one of them is not correct, then return 201. (RequestBody)
getAboutus	GET	/api/insight/v1/aboutus	NO STATUS	Return the aboutus text

updateAboutus	PUT	/api/insight/v1/aboutus/update	200	200 means updated successfully. (RequestBody)
getCommittee	GET	/api/insight/v1/committee	NO STATUS	Return list of the committee
updateCommittee	PUT	/api/insight/v1/committee/update	200	Return 200 if updated successfully. (RequestBody)
addCommittee	POST	/api/insight/v1/committee/add	200	RequestBody
deleteCommittee	DELETE	/api/insight/v1/committee/delete/{id}	200	Provide the id in the path
getSubcommittee	GET	/api/insight/v1/subcommittee	NO STATUS	Return list of the subcommittee
updateSubcommittee	PUT	/api/insight/v1/subcommittee/update	200	Return 200 if updated successfully. (RequestBody)
addSubcommittee	POST	/api/insight/v1/subcommittee/add	200	RequestBody
deleteSubcommittee	DELETE	/api/insight/v1/subcommittee/delete/{id}	200	Provide the id in the path
getProgram	GET	/api/insight/v1/program	NO STATUS	Return list of the programs
updateProgram	PUT	/api/insight/v1/program/update	200	Return 200 if updated successfully. (RequestBody)
addProgram	POST	/api/insight/v1/program/add	200	RequestBody
deleteProram	DELETE	/api/insight/v1/program/delete/{id}	200	Provide the id in the path
getFutureevent	GET	/api/insight/v1/futureevent	NO STATUS	Return list of the future events
updateFutureevent	PUT	/api/insight/v1/futureevent/update	200	Return 200 if updated successfully. (RequestBody)
addFutureevent	POST	/api/insight/v1/futureevent/add	200	RequestBody
deleteFutureevent	DELETE	/api/insight/v1/futureevent/delete/{id}	200	Provide the id in the path
getPreviousevent	GET	/api/insight/v1/previousevent	NO STATUS	Return list of the previous events
updatePreviousevent	PUT	/api/insight/v1/previousevent/update	200	Return 200 if updated successfully. (RequestBody)
addPreviousevent	POST	/api/insight/v1/previousevent/add	200	RequestBody
deletePreviousevent	DELETE	/api/insight/v1/previousevent/delete/{id}	200	Provide the id in the path
getContactinfo	GET	/api/insight/v1/contactinfo	NO STATUS	Return the contact info (location, phone, ...)
updateContactinfo	PUT	/api/insight/v1/contactinfo/update	200	RequestBody
getFaqs	GET	/api/insight/v1/faq	NO STATUS	Return list of the faqs
updateFaq	PUT	/api/insight/v1/faq/update	200	Return 200 if updated successfully. (RequestBody)
addFaq	POST	/api/insight/v1/faq/add	200	RequestBody
deleteFaq	DELETE	/api/insight/v1/faq/delete/{id}	200	Provide the id in the path

getGoals	GET	/api/insight/v1/goal	NO STATUS	Return list of the goals
updateGoal	PUT	/api/insight/v1/goal/update	200	Return 200 if updated successfully. (RequestBody)
addGoal	POST	/api/insight/v1/goal/add	200	RequestBody
deleteGoal	DELETE	/api/insight/v1/goal/delete/{id}	200	Provide the id in the path
getBlogs	GET	/api/insight/v1/blog	NO STATUS	Return list of the blogs
updateBlog	PUT	/api/insight/v1/blog/update	200	Return 200 if updated successfully. (RequestBody)
addBlog	POST	/api/insight/v1/blog/add	200	RequestBody
deleteBlog	DELETE	/api/insight/v1/blog/delete/{id}	200	Provide the id in the path

HINT:

RequestBody example:

In the db, goal table has the following columns (idgoal, goaltitle, goalayah).

When you need to send the RequestBody, the idea is that the data to be sent in the body request should be in json format and the name should match those in the db. Example:

```
{
  "goaltitle" : "first goal",
  "goalayah": "first ayah"
}
```

idgoal should not be added because it is AUTO incremental, the db will generated.