

Problem C. Simple Text Editor

OS Linux

Implement a simple text editor. The editor initially contains an empty string, S . Perform Q operations of the following 4 types:

1. $append(W)$ - Append string W to the end of S .
2. $delete(k)$ - Delete the last k characters of S .
3. $print(k)$ - Print the k^{th} character of S .
4. $undo()$ - Undo the last (not previously undone) operation of type 1 or 2, reverting S to the state it was in prior to that operation.

Example

$S = 'abcde'$

$ops = ['1 fg', '3 6', '2 5', '4', '3 7', '4', '3 4']$

operation

index	S	ops[index]	explanation
-----	-----	-----	-----
0	abcde	1 fg	append fg
1	abcdefg	3 6	print the 6th letter - f
2	abcdefg	2 5	delete the last 5 letters
3	ab	4	undo the last operation, index 2
4	abcdefg	3 7	print the 7th character - g
5	abcdefg	4	undo the last operation, index 4
6	abcde	3 4	print the 4th character - d

The results should be printed as:

1		f
2		g
3		d

Input Format

The first line contains an integer, Q , denoting the number of operations.

Each line i of the Q subsequent lines (where $0 \leq i < Q$) defines an operation to be performed. Each operation starts with a single integer, t (where $t \in \{1, 2, 3, 4\}$), denoting a type of operation as defined in the *Problem Statement* above. If the operation requires an argument, t is

followed by its space-separated argument. For example, if $t = 1$ and $W = \text{"abcd"}$, line i will be **1 abcd**.

Constraints

- $1 \leq Q \leq 10^6$
- $1 \leq k \leq |S|$
- The sum of the lengths of all W in the input $\leq 10^6$.
- The sum of k over all delete operations $\leq 2 \cdot 10^6$.
- All input characters are lowercase English letters.
- It is guaranteed that the sequence of operations given as input is possible to perform.

Output Format

Each operation of type **3** must print the k^{th} character on a new line.

Input		Output
STDIN	Function	c y a
-----	-----	
8	$Q = 8$	
1 abc	$ops[0] = '1\ abc'$	
3 3	$ops[1] = '3\ 3'$	
2 3	...	
1 xy		
3 2		
4		
4		
3 1		

Explanation

Initially, S is empty. The following sequence of 8 operations are described below:

1. $S = ""$. We append abc to S , so $S = \text{"abc"}$.
2. Print the 3^{rd} character on a new line. Currently, the 3^{rd} character is **c**.
3. Delete the last 3 characters in $S(abc)$, so $S = ""$.
4. Append xy to S , so $S = \text{"xy"}$.
5. Print the 2^{nd} character on a new line. Currently, the 2^{nd} character is **y**.
6. Undo the last update to S , making S empty again (i.e., $S = ""$).
7. Undo the next to last update to S (the deletion of the last 3 characters), making $S = \text{"abc"}$.
8. Print the 1^{st} character on a new line. Currently, the 1^{st} character is **a**.