

Option:
PTFE-RING=TR
(corrosion barrier)

PIPE BODY


	Imperial	Metric
Nominal OD	1.900 in.	48,30 mm
Nominal ID	1.500 in.	38,10 mm
Nominal Wall	0.200 in.	5,08 mm
Drift Diameter	1.406 in.	35,71 mm
Tensile Yield Strength	117,000 lb	521 kN
Internal Yield Pressure	20,260 psi	1.397 bar
Collapse Pressure	20,720 psi	1.429 bar

CONNECTION PROPERTIES

Connection Type: *Integral*

	Imperial	Metric
Nominal OD	2.162 in.	54,91 mm
Nominal ID	1.440 in.	36,58 mm
Make-up Loss Length	2.230 in.	56,60 mm
	<i>Efficiency</i>	
Tensile Yield Strength	117,000 lb 100 %	521 kN
Compression Strength	93,600 lb 80 %	416 kN
Internal Yield Pressure	20,260 psi 100 %	1.397 bar
Collapse Pressure	20,720 psi 100 %	1.429 bar

FIELD MAKE-UP TORQUE



	Imperial	Metric
Min.	800 ft-lb	1085 Nm
Opt.	900 ft-lb	1220 Nm
Max.	1000 ft-lb	1360 Nm

