Milestone 3

Studiando

Names:

- 1-Omnia Karem Mahfouz | 21010299
- 2-Ibrahim Mohamed Elsayed | 21010023
- 3-Mohamed Mohamed Abdel-Moniem | 21011213
- 4-Mohamed Hassan Kabari | 21011115
- 5-Mohamed Mohamed Ibrahim | 21011211
- 6-Omar Hani Bishr | 21010891

O Introduction:

Overview and purpose of the application:

Students often grapple with the challenge of managing multiple resources in their daily lives, leading to issues of abstraction. Our website is designed to alleviate these challenges, providing a seamless and userfriendly experience to enhance students' daily lives.

Goals and objectives:

The goal of this project is to create a user-friendly website that combines an Al-powered search engine, Google Drive integration, an announcements section, text and voice chat features, and a collaborative to-do list. The website aims to improve communication and productivity for teams, whether they are students or professionals in various settings.

Target audience or users:

Our website is specially for **students**.

O Installation Guide:

• Instructions for installation:


- 1- Download the project folder and extract it.
- 2- Make sure you have downloaded Vue.js.
- 3- Open the *Studiando* folder using visual studio code, then open the terminal of the IDE, and write "npm install" in the terminal.
- 4- Write "npm i serve" then "npm run serve" in the terminal to run the project.

O User Manual:

- How-to guides or tutorials describing the flows:
 - Please use this link to go to a How-To-Use video that will answer all your questions. https://youtu.be/sisjwQmRoyY
 - Main page should be run on local host 8080 and user page and User page should be run on local host 8081.

O Architecture Overview:

- High-level architecture diagram:
- Components, modules, or layers and their interactions:



O API documentation:

Base URL: https://textchat-159f4-default-rtdb.firebaseio.com

Endpoint 1

Create new Notifications Admin sends a new notification to users

URL: "/chats/notifications.json"

Method: "Post" Parameters:

• Index: id of the notification

• date: date of the notification

• message: content of the notification

• name: name of the sender (the admin)

Status Codes

• 201 Created: Data successfully created.

• 400 Bad Request: Invalid request parameters.

• 500 Internal Server Error: Server error.

Endpoint 2

Receive all Notifications Users receive notifications from admin

URL: "/chats/notifications.json"

Method: "Get"

Parameters:

• notifications: array of notifications

Status Codes

• 200 OK: Successful request.

• 400 Bad Request: Invalid request parameters.

• 404 Not Found: Data not found.

Create new message in a specific channel Users sends a new message in a channel by his own selection

URL: "/chats/channels/\${this.currentChannel}.json"

Method: "Post" Parameters:

• Index: id of the notification

date: date of the notification

• message: content of the notification

• name: name of the sender (the admin)

this.currentChannel: the selected channel

Status Codes

• 201 Created: Data successfully created.

• 400 Bad Request: Invalid request parameters.

• 500 Internal Server Error: Server error.

Endpoint 4

Receive all Channels

Users receive Channels which have been created before

URL: "/chats/channels.json"

Method: "Get"

Parameters:

• channels: array of channels

Status Codes

• 200 OK: Successful request.

• 400 Bad Request: Invalid request parameters.

• 404 Not Found: Data not found.

Create a new message in a specific private channel chat Users sends a new message in a channel which contains 2 members only

URL: "/chats/private/\${this.privateChat}.json"

Method: "Post"

Parameters:

Index: id of the notification

date: date of the notification

• message: content of the notification

• name: name of the sender (the admin)

• this.privateChat: the selected private chat

Status Codes

• 201 Created: Data successfully created.

• 400 Bad Request: Invalid request parameters.

• 500 Internal Server Error: Server error.

Endpoint 6

Receive all messages in a private chat

URL: "/chats/private/\${this.privateChat}.json"

Method: "Get"

Parameters:

messages: array of messages

this.privateChat: the selected private chat

Status Codes

• 200 OK: Successful request.

• 400 Bad Request: Invalid request parameters.

• 404 Not Found: Data not found.

Receive all messages in a Channel

URL: "/chats/private/\${this.currentChannel }.json"

Method: "Get"

Parameters:

• messages: array of messages

• this.currentChannel: the selected channel

Status Codes

• 200 OK: Successful request.

• 400 Bad Request: Invalid request parameters.

• 404 Not Found: Data not found.

• 500 Internal Server Error: Server error.

Endpoint 8

Receive all private Chats URL: "/chats/private.json"

Method: "Get"

Parameters:

• messages: array of all private chats

Status Codes

• 200 OK: Successful request.

• 400 Bad Request: Invalid request parameters.

• 404 Not Found: Data not found.

Receive all users in the system

URL: "/users.json" Method: "Get"

Parameters:

• users: array of all private chats

Status Codes

• 200 OK: Successful request.

• 400 Bad Request: Invalid request parameters.

• 404 Not Found: Data not found.

• 500 Internal Server Error: Server error.

Endpoint 10

Sign in or sign up URL: "/users.json" Method: "Post"

Parameters:

fName: first name of the userlName: last name of the user

o userName: user name of the user

o password: password

o email: user email

o dateOfBirth: user birth of birth

o gender: user gender

Status Codes

• 201 Created: Data successfully created.

• 400 Bad Request: Invalid request parameters.

Delete a user in the system

URL: "/users/ \${ourMessage}.json"

Method: "Delete"

Parameters:

• ourMessage: id of the user to be delete

Status Codes

• 204 No Content: User successfully deleted.

• 404 Not Found: User with the provided ID not found.