

Rajalakshmi Engineering College

Name: Mohamed Yahya A
Email: 240701325@rajalakshmi.edu.in
Roll no: 240701325
Phone: 9600561844
Branch: REC
Department: CSE - Section 9
Batch: 2028
Degree: B.E - CSE

Scan to verify results



2024_28_III_OOPS Using Java Lab

REC_2028_OOPS using Java_Week 8_CY

Attempt : 1
Total Mark : 40
Marks Obtained : 40

Section 1 : Coding

1. Problem Statement

In an online shopping cart system, users can apply coupon codes during checkout to avail of discounts. However, to ensure the validity and security of coupon codes, the system enforces specific rules for their format. Your task is to implement a Java program named CouponCodeValidator that takes user input for a coupon code and validates it according to the specified rules.

Rules for Valid Coupon Code:

The coupon code must consist of exactly 10 characters. The coupon code must contain at least one alphabet (uppercase or lowercase) and at least one digit (0-9). Special characters are not allowed in the coupon code.

Implement a custom exception, InvalidCouponException, to handle cases where the entered coupon code does not meet the specified criteria.

Input Format

The input consists of a string s, representing the coupon code.

Output Format

The output is displayed in the following format:

If the entered coupon code meets the specified criteria, the program outputs

"Coupon code applied successfully!"

If the entered coupon code has less than or more than 10 characters it outputs

"Error: Invalid coupon code length. It must be exactly 10 characters."

If the entered coupon code contains only numeric or only alphabets it outputs

"Error: Invalid coupon code format. It must contain at least one alphabet and one digit."

If the entered coupon code contains special characters it outputs

"Error: Coupon code should not contain special characters."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: ABCD123456

Output: Coupon code applied successfully!

Answer

```
import java.util.Scanner;
```

```
class InvalidCouponException extends Exception {  
    public InvalidCouponException(String message) {  
        super(message);  
    }  
}
```

```
class CouponCodeValidator {  
    public static void main(String[] args) {  
        Scanner scanner = new Scanner(System.in);  
        try {  
            String couponCode = scanner.nextLine();  
            validateCouponCode(couponCode);  
            System.out.println("Coupon code applied successfully!");  
        } catch (InvalidCouponException e) {  
            System.out.println("Error: " + e.getMessage());  
        } finally {  
            scanner.close();  
        }  
    }  
  
    private static void validateCouponCode(String couponCode) throws  
    InvalidCouponException {  
  
        if (containsSpecialCharacter(couponCode)) {  
            throw new InvalidCouponException("Coupon code should not contain  
special characters.");  
        }  
  
        if (!couponCode.matches("^(?=.*[a-zA-Z])(?=.*[\\d])[a-zA-Z0-9]{10}$")) {  
            if (couponCode.length() != 10) {  
                throw new InvalidCouponException("Invalid coupon code length. It must  
be exactly 10 characters.");  
            } else {  
                throw new InvalidCouponException("Invalid coupon code format. It  
must contain at least one alphabet and one digit.");  
            }  
        }  
    }  
  
    private static boolean containsSpecialCharacter(String str) {  
  
        return str.matches(".*[^a-zA-Z0-9].*");  
    }  
}
```

Status : Correct

Marks : 10/10

2. Problem Statement

Faustus is managing his bank account and wants to create a program to update his account balance based on certain conditions. However, he needs to handle specific scenarios related to invalid inputs and insufficient balances. Faustus wants to update his account balance. He inputs the current balance and the amount to be updated.

The initial account balance should be positive. If Faustus enters a negative initial balance, the program should throw an `InvalidAmountException` with the message "Invalid amount. Please enter a positive initial balance." If the amount to be updated is negative, the program should check if the subtraction results in a negative balance. If so, it should throw an `InsufficientBalanceException` with the message "Insufficient balance." If the amount to be updated is positive, it should be added to the current balance, and the new balance should be printed.

Implement a custom exception, `InvalidAmountException`, and `InsufficientBalanceException`, to manage his bank account.

Input Format

The first line of input consists of a double value 'd', representing the initial account balance.

The second line of input consists of a double value 'd1', representing the amount to be updated.

Output Format

The output is displayed in the following format:

If the validation passes, print

"Account balance updated successfully! New balance: {new_balance}"

where {new_balance} is the updated account balance.

If the initial bank amount is negative it displays

"Error: Invalid amount. Please enter a positive initial balance."

If the updated amount exceeds the initial account balance in withdrawal it displays

"Error: Insufficient balance."

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1000

500

Output: Account balance updated successfully! New balance: 1500.0

Answer

```
import java.util.Scanner;
class BalanceUpdater {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        try {
            double currentBalance = scanner.nextDouble();
            if (currentBalance < 0) {
                throw new InvalidAmountException("Invalid amount. Please enter a
positive initial balance.");
            }
            double updateAmount = scanner.nextDouble();
            updateBalance(currentBalance, updateAmount);
            System.out.println("Account balance updated successfully! New balance:
" + (currentBalance + updateAmount));
        } catch (InvalidAmountException | InsufficientBalanceException |
java.util.InputMismatchException e) {
            System.out.println("Error: " + e.getMessage());
        } finally {
            scanner.close();
        }
    }

    private static void updateBalance(double currentBalance, double
updateAmount)
        throws InvalidAmountException, InsufficientBalanceException {
        if (updateAmount < 0) {
```

```

        if (currentBalance + updateAmount < 0) {
            throw new InsufficientBalanceException("Insufficient balance.");
        }
    } else {
        currentBalance += updateAmount;
    }
}
class InvalidAmountException extends Exception {
    public InvalidAmountException(String message) {
        super(message);
    }
}
class InsufficientBalanceException extends Exception {
    public InsufficientBalanceException(String message) {
        super(message);
    }
}

```

Status : Correct

Marks : 10/10

3. Problem Statement

Hemanth is designing a banking system for XYZ Bank. The system should allow customers to perform deposit, withdrawal, and balance inquiry operations. Implement exception handling for scenarios involving invalid transaction amounts or insufficient funds.

Create two custom exception classes, InvalidAmountException and InsufficientFundsException, both extending the Exception class. Throw an InvalidAmountException with a message if the deposit amount is less than or equal to zero. Throw an InsufficientFundsException if the withdrawal amount is greater than the available balance. Deduct the withdrawal amount from the balance if the withdrawal is successful.

Assist Hemanth in designing the program.

Input Format

The first line of input consists of a double value B, representing the initial balance.

The second line consists of a double value D, representing the deposit amount.

The third line consists of a double value W, representing the withdrawal amount.

Output Format

If the withdrawal is successful, print the amount withdrawn and the current balance, rounded off to one decimal place.

If an `InvalidAmountException` occurs, print "Error: [D] is not valid".

If an `InsufficientFundsException` occurs, print "Error: Insufficient funds".

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 1050.1

270.2

150.3

Output: Amount Withdrawn: 150.3

Current Balance: 1170.0

Answer

```
import java.util.Scanner;

class InvalidAmountException extends Exception {
    public InvalidAmountException(String message) {
        super(message);
    }
}

class InsufficientFundsException extends Exception {
    public InsufficientFundsException(String message) {
        super(message);
    }
}

class HDFCBank {
    private double balance;
```

```
public static void main(String[] args) {
    HDFCBank hdfcBank = new HDFCBank();
    hdfcBank.processTransactions();
}

public void processTransactions() {
    Scanner scanner = new Scanner(System.in);

    try {
        balance = scanner.nextDouble();
        double depositAmount = scanner.nextDouble();
        deposit(depositAmount);

        double withdrawAmount = scanner.nextDouble();
        double withdrawnAmount = withdraw(withdrawAmount);

        System.out.printf("Amount Withdrawn: %.1f\n", withdrawnAmount);
        balanceEnquiry();
    } catch (InvalidAmountException | InsufficientFundsException e) {
        System.out.println("Error: " + e.getMessage());
    } finally {
        scanner.close();
    }
}

public void deposit(double amount) throws InvalidAmountException {
    if (amount <= 0) {
        throw new InvalidAmountException(amount + " is not valid");
    }
    balance = balance + amount;
}

public double withdraw(double amount) throws InsufficientFundsException {
    if (balance < amount) {
        throw new InsufficientFundsException("Insufficient funds");
    }
    balance = balance - amount;
    return amount;
}

public void balanceEnquiry() {
```

```
        System.out.printf("Current Balance: %.1f\n" ,balance);  
    }  
}
```

Status : Correct

Marks : 10/10

4. Problem Statement

Tim was tasked with creating a user profile system that validates the user's date of birth input. The system should throw a custom exception, `InvalidDateOfBirthException`, if the date is not in the specified format "dd-mm-yyyy" or if it represents an invalid calendar date.

The main method takes user input, validates the date of birth, and prints whether it is valid or not.

Input Format

The input consists of a string, representing the date of birth of the user.

Output Format

The output displays one of the following results:

If the entered date of birth is valid according to the specified format, the program prints:

"[Date] is a valid date of birth"

If the entered date of birth is not valid according to the specified format, the program prints:

"Invalid date: [Date]"

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 01-01-2000

Output: 01-01-2000 is a valid date of birth

Answer

```
import java.text.ParseException;
import java.text.SimpleDateFormat;
import java.util.Date;
import java.util.Scanner;
class InvalidDateOfBirthException extends Exception {
    public InvalidDateOfBirthException(String message) {
        super(message);
    }
}
class UserProfileSystem {
    public static void main(String[] args) {
        Scanner scanner = new Scanner(System.in);
        String userInput = "";
        try {
            userInput = scanner.nextLine();
            validateDateOfBirth(userInput);
            System.out.println(userInput + " is a valid date of birth");
        } catch (InvalidDateOfBirthException e) {
            System.out.println(e.getMessage() + ": " + userInput);
        } finally {
            scanner.close();
        }
    }
    private static void validateDateOfBirth(String userInput) throws
    InvalidDateOfBirthException {
        SimpleDateFormat dateFormat = new SimpleDateFormat("dd-MM-yyyy");
        dateFormat.setLenient(false);
        try {
            Date dob = dateFormat.parse(userInput);
        } catch (ParseException e) {
            throw new InvalidDateOfBirthException("Invalid date");
        }
    }
}
```

Status : Correct

Marks : 10/10