```
Session  Actions  Edit  View  Help
Traceback (most recent call last):
  File "/home/projectcsx/payload-framework/main.py", line 7, in <module>
    rot13_payload = encode(payload)
  File "/home/projectcsx/payload-framework/encoder/rot13_encoder.py", line 7, in encode
    if char.ilower():
       ^^^^^^^^^^^
AttributeError: 'str' object has no attribute 'ilower'. Did you mean: 'islower'?

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano encoder/rot13_encoder.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
ROT13 payload: pzq.rkr /p jubnzv


Traceback (most recent call last):
  File "/home/projectcsx/payload-framework/main.py", line 10, in <module>
    if detect(rot13_encoded):
              ^^^^^^^^^^^^^
NameError: name 'rot13_encoded' is not defined

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
ROT13 payload: pzq.rkr /p jubnzv


rot13 Payload: Not DETECTED

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$
```

Session Actions Edit View Help

```
.
├── detection
│   ├── __pycache__
│   │   └── signature_detector.cpython-313.pyc
│   └── signature_detector.py
├── encoder
│   ├── base64_encoder.py
│   ├── __pycache__
│   │   ├── base64_encoder.cpython-313.pyc
│   │   ├── rot13_encoder.cpython-313.pyc
│   │   └── xor_encoder.cpython-313.pyc
│   ├── rot12_encoder.py
│   ├── rot13_encoder.py
│   └── xor_encoder.py
├── main.py
├── obfuscator
│   └── string_obfuscation.py
├── payloads
│   └── sample_payload.txt
├── reports
│   └── results.txt
└── screenshots

9 directories, 13 files

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano obfuscator/string_obfuscator.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Obfuscated payload: c_m_d_._e_x_e_ _/_c_ _w_h_o_a_m_i_
_
_
obfuscated Payload: Not DETECTED

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$
```

```
Session  Actions  Edit  View  Help
    for i in range(len(payload)):
IndentationError: unexpected indent

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ sed -i 's/t\/    /g' encoder/xor_encoder.py
sed: -e expression #1, char 11: unterminated `s' command

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ ^[[200~sed -i 's/\t/    /g' encoder/xor_encoder.py
zsh: bad pattern: ^[[200~sed

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ sed -i 's/\t/    /g' encoder/xor_encoder.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano encoder/xor_encoder.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Xor Encoded Payload:\
                    ELE

y
xor Payload: Not DETECTED

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$
```

```
Session  Actions  Edit  View  Help
┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Original Payload: DETECTED

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano encoder/base64_encoder.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Traceback (most recent call last):
  File "/home/projectcsx/payload-framework/main.py", line 9, in <module>
    print ("Encoded Payload:", encode_payload)
                               ^^^^^^^^^^^^^^
NameError: name 'encode_payload' is not defined. Did you mean: 'encoded_payload'?

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Encoded Payload: Y21kLmV4ZSAvYyB3aG9hbWkKCg==
base64  Payload: Not DETECTED

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$
```

Session Actions Edit View Help

GNU nano 8.6 main.py

```python
from encoder.base64_encoder import encode
from detection.signature_detector import detect

with open("payloads/sample_payload.txt", "r") as f:
    payload = f.read()

encoded_payload = encode(payload)

print ("Encoded Payload:", encode_payload)

if detect(encoded_payload):
    print("base64  Payload: DETECTED")
else:
    print("base64  Payload: Not DETECTED")
```

[Read 14 lines]

^G Help	^O Write Out	^F Where Is	^K Cut	^T Execute	^C Location	M-U Undo	M-A Set Mark	M-] To Bracket
^X Exit	^R Read File	^\ Replace	^U Paste	^J Justify	^/ Go To Line	M-E Redo	M-6 Copy	^B Where Was

```
Session  Actions  Edit  View  Help
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Traceback (most recent call last):
  File "/home/projectcsx/payload-framework/main.py", line 1, in <module>
    from detection.signature_detector import detect
  File "/home/projectcsx/payload-framework/detection/signature_detector.py", line 5
        if sig in payload.lower():
    ^
TabError: inconsistent use of tabs and spaces in indentation

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano detection/signature_detector.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Traceback (most recent call last):
  File "/home/projectcsx/payload-framework/main.py", line 1, in <module>
    from detection.signature_detector import detect
  File "/home/projectcsx/payload-framework/detection/signature_detector.py", line 2
    signatures = ["cmd", "powershell", "exec", "shell"]
    ^^^^^^^^^^
IndentationError: expected an indented block after function definition on line 1

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano detection/signature_detector.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Original Payload: DETECTED

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$
```

```
Session  Actions  Edit  View  Help

7 directories, 1 file

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano payloads/sample_payload.txt

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ tree
.
├── detection
├── encoder
├── main.py
├── obfuscation
├── payloads
│   └── sample_payload.txt
├── reports
└── screenshots

7 directories, 2 files

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ detection/signature_detector.py
zsh: no such file or directory: detection/signature_detector.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano detection/signature_detector.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano detection/signature_detector.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ nano main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ python3 main.py
Traceback (most recent call last):
  File "/home/projectcsx/payload-framework/main.py", line 1, in <module>
    from detection.signature_detector import detect
  File "/home/projectcsx/payload-framework/detection/signature_detector.py", line 5
        if sig in payload.lower():
    ^
TabError: inconsistent use of tabs and spaces in indentation

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$
```

Session Actions Edit View Help

```
  GNU nano 8.6                                   detection/signature_detector.py
def detect(payload):
    signatures = ["cmd", "powershell", "exec", "shell"]

    for sig in signatures:
        if sig in payload.lower():
            return True
    return False
```

[Read 7 lines]

^G Help	^O Write Out	^F Where Is	^K Cut	^T Execute	^C Location	M-U Undo	M-A Set Mark	M-] To Bracket
^X Exit	^R Read File	^\ Replace	^U Paste	^J Justify	^/ Go To Line	M-E Redo	M-6 Copy	^B Where Was

projectcsx@kali: ~/payload-framework

Session Actions Edit View Help

```
┌──(projectcsx㉿kali)-[~]
└─$ mkdir payload-framework

┌──(projectcsx㉿kali)-[~]
└─$ cd payload-framework

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ mkdir payload encoder obfuscation detection screenshots reports

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$ touch main.py

┌──(projectcsx㉿kali)-[~/payload-framework]
└─$
```