The journal’s API

Every route the journal’s server answers, what it takes, what it returns, and whether anything calls it. **29 routes**: 19 in `journal/src/routes/journal.js` (mounted at `/api/journal`), 5 in `journal/src/addons/accounts.js`, 5 in `journal/server.js`. Static files come from `journal/public/`.

Every route sits behind the desk’s login (`src/auth`, the same `td_auth` cookie as every program). Bodies are JSON, up to 10 MB.

“Caller” says what uses the route today: **page** (`journal.html`), **add-on** (`addons.js`), or **none**.

Trades

Method	Path	Takes	Returns	Caller
GET	`/api/journal/trades`	optional query: `from`, `to` (dates), `account`, `setup_id`, `direction`, `status`, `ticker`	every matching trade, newest date and entry time first	page (no filters)
GET	`/api/journal/trades/:id`		the trade with `context`, `technical` and `conditions`; 404 if missing	none
POST	`/api/journal/trades`	`date, ticker, direction, shares, entry_price, entry_time` (required); `exit_price, exit_time, sl, tp, commission, setup_id, notes, account, context`	`{ ok, id }`; 400 when a required field is missing	none
PATCH	`/api/journal/trades/:id`	any of `exit_price, exit_time, sl, tp, setup_id, notes, status`	`{ ok }`; 404 if missing	page (`setup_id` only)
DELETE	`/api/journal/trades/:id`		`{ ok }`; also deletes its snapshots, conditions and grading card	page

The rules for each are in IMPORT.md.

Import

Method	Path	Takes	Returns	Caller
POST	`/api/journal/import`	`{ csv, account? }`	`{ ok, imported, total, trades, bridged: { mirrored, skipped, failed } }`; 400 with `{ ok: false, error }` when the file is refused or the parser throws	page

The formats and the pairing: IMPORT.md.

Technicals and conditions

Method	Path	Takes	Returns	Caller
POST	`/api/journal/trades/:id/compute`		`{ ok, technicalSnapshot, outcomes }`, after fetching bars and evaluating the setup's template; 500 with the reason on failure	none
POST	`/api/journal/compute-all`		`{ ok, queued }` at once; the work runs in the background, 300 ms apart, errors swallowed	none
POST	`/api/journal/reevaluate-conditions`		`{ ok, evaluated }`: closed, tagged trades with a snapshot, no bar fetch	page (**Re-eval Conditions**)
POST	`/api/journal/trades/:id/context`	the context fields: `regime, regimeLabel, secBias, broadResolved, shortTerm, midTerm, longTerm, secScore, sector, industry, scanner_score, scanner_confidence`	`{ ok }` (replaces the trade's context snapshot)	none
GET	`/api/journal/templates`		every setup template, conditions parsed	none
PUT	`/api/journal/templates/:setupId`	`{ conditions, min_grade_trades?, min_condition_trades? }`	`{ ok }` (creates or replaces)	none

What each computes: ANALYSIS.md.

Analysis

Method	Path	Takes	Returns	Caller
GET	`/api/journal/analysis/metrics`	`from, to, account, setup_id`	the server's metrics (ANALYSIS.md)	none
GET	`/api/journal/analysis/calendar`	`from, to` (the account is ignored)	`[{ date, pnl, n }]` per date	none
POST	`/api/journal/analysis/backfill-to-grading`		`{ ok, considered, mirrored, skipped, failed }`; safe to repeat	none

The code points readers of the grading data to `/api/trading/grading/summary` and `/api/trading/grading/setup/:id`. **Those routes do not exist** in the journal.

Notes and fees

Method	Path	Takes	Returns	Caller
GET	`/api/journal/notes/:date`		`{ date, note, updated_at }`, or an empty note	none
PUT	`/api/journal/notes/:date`	`{ note }`	`{ ok }`	none
GET	`/api/journal/fees`		every fee profile, rules parsed	none
PUT	`/api/journal/fees/:account`	`{ rules, mode? }` (`replace` by default)	`{ ok }`. The rules are stored, never applied	none

Alpaca accounts

Method	Path	Takes	Returns	Caller
GET	`/api/journal/accounts`		`{ ok, accounts }`: no secrets, key id shortened, with `lastRun`	add-on
POST	`/api/journal/accounts`	new: `name, keyId, secret, paper, everyMinutes, days, enabled`. Edit: `id` plus any of those (keys both or neither)	`{ ok, account }` or `{ ok: false, error }` (always status 200)	add-on (add, pause/resume)
DELETE	`/api/journal/accounts/:id`		`{ ok }`; the account's trades stay	add-on
POST	`/api/journal/accounts/:id/test`		`{ ok, number, status, paper }` or `{ ok: false, error }`	add-on
POST	`/api/journal/accounts/:id/fetch`		the run: `{ ok, at, fills, trades, added, updated, error }`	add-on

The rules: ACCOUNTS.md.

Shared and the page

Method	Path	Returns	Caller
GET	`/api/trading/setups`	every row of `trading_setups`, `config` parsed; `[]` on any error	page
GET	`/api/tools`	`{ ok, tools, apps }` from `tools.config.json`; never fails (an error gives empty lists)	the app bar
GET	`/deskbar.css`	the app bar's rules cut from `public/desk.css`, `no-cache`	the page
GET	`/desk.js`	`public/desk.js` from the repo, `no-cache`	the page
GET	`/`	`journal.html`	the browser
GET	`/addons.js`, other files	static files from `journal/public/` (`/` itself is the route above)	the page

In summary

Of the 29 routes, the page, its add-on and the app bar use 15. One trade with its snapshots, hand entry, technicals, context, templates, notes, fees, the server’s metrics and calendar, and the grading backfill (14 routes) have no caller. A rebuild should start from what the page needs, and give each route either a screen or a job that calls it.