qp: charts, strategies, backtests, alerts

Above: ARCHITECTURE.md §4.4.

Talks to:

- the front door (`/quant/`);
- the shared record: registers, market states and facts, as of a day;
- the data sources: bars;
- the desk: its scheduler starts each alert cycle;
- the journal: the chart of a trade, and backtests exported as trades;
- its own files.

---

1. What it is

qp is the chart and backtest program of the desk, written in Python (FastAPI, `quant-platform/chart/server.py`, port 8765). It is the best-built part of the old desk, and its library, engine and backtest carry over almost unchanged.

Job	The question it answers
Chart	what does this stock look like, with indicators I can trust?
Build	can I describe this setup as rules, by clicking?
Backtest	if I had traded these rules on the stocks my tools found, on the days they found them, what would have happened, honestly?
Alert	is one of my saved strategies firing now on today's lists?
Print	let me review a day's (or a list's) charts, with the numbers behind them

What it owns:


- strategies and their versions;
- backtests and their trades;
- the alert history;
- the library's approvals.

What it never does:

- compute a card fact or a market fact;
- keep a timer of its own;
- place an order: it alerts only.

---

2. The diagram



3. Its parts

Part	Job	Detail
the page	one page: chart, tools rail, indicators, the ⚡ strategy drawer (evaluate, test any rule, the signal funnel), the register browser, the backtest, alerts, print sheets	CHART.md
the library	the 71 verified primitives: the only market math anywhere in qp, each approved against TradingView	LIBRARY.md
the strategy engine	the strategy grammar, 14 operators, timing and groups; entries and exits; the risk block; the four fill models; the exit plan and the one order function	STRATEGIES.md
the backtest	the same evaluation as the preview, day by day over a universe as frozen that day; the honesty rules; settings and filters; accounting; the report and exports	BACKTEST.md
signal alerts	every saved strategy on today's lists, one cycle each time the desk starts it; one alert per strategy, symbol and bar; history kept; the cycle's new signals returned to the desk, which pushes them to the phone	SIGNAL-ALERTS.md
bar feeds and cache	the feeds (Alpaca, Polygon, Yahoo, the hybrid), warm-up, the bar cache and its limits, the borrow check	FEEDS.md

The working rule of the page: never trust a piece you have not seen. Plot it, test it, then compose it.

4. What changes from today

Change	Why	Detail
One fill model for preview, backtest and alerts. Alerts evaluate with the strategy's own fill (default `desk`)	an alert and a backtest of the same strategy must take the same bar (Q-N9)	SIGNAL-ALERTS.md
Registers, market states and facts are read as of a day from the shared record	today they are read over HTTP from each tool's port, and a stopped tool needed the archive program	BACKTEST.md
No O'Neil computation	the research worker owns it. While qp was down, every ticker first seen had a blank CANSLIM reading, and a photo then froze the blanks	RESEARCH-WORKER.md
No timer of its own	the desk's scheduler starts each alert cycle and records it, so a cycle that fails or does not run alerts	JOBS.md
Alert history kept	a restart never repeats an alert, and alerts can be reviewed	SIGNAL-ALERTS.md
Signals on the phone	today a signal reaches only an open page (a sound and a browser notification). The desk pushes each new one to its own ntfy topic; qp holds no push key	ALERTS.md §3.6
Shared bars per cycle	one fetch per symbol per cycle, shared by every strategy	FEEDS.md
The CANSLIM gate on the page	it is in the API only today (Q-N4); letters that cannot be rebuilt for a day are refused before the run	BACKTEST.md
`breakeven_after_target` simulated, or refused on save	it is reported and never simulated today (Q-N7)	STRATEGIES.md
Strategy versions	saving a strategy creates a version; a backtest records the versions it ran. The versions live in qp's own file	STRATEGIES.md
No per-route feed defaults	some routes default to Polygon, not the desk's default (Q-N6)	FEEDS.md

5. Contracts

It owns (qp's file, `~/.qp/platform.db`)	Key
`strategies`, `strategy_versions` (versions: to build)	id; id, version
`backtests`, `backtest_trades`	id
`alert_seen`, `alert_history`	strategy, symbol, bar
the library's approvals	`approvals/approvals.json`, in git

It reads	From
bars	the data sources, through its feeds (FEEDS.md)
R1, the shortlist, R3, as of a day	the shared record (today: each tool's port; built but off: the desk's `/db/<tool>`)

It reads	From
market states, CANSLIM facts, as of a day	the shared record

Routes, behind `/quant/`	
the legacy routes carry over	53 routes and the live WebSocket (legacy/qp/API.md). The register routes read the shared record, and the alert routes read the stored history
`POST /api/alerts/cycle` (to build)	one alert cycle, started by the desk's scheduler; answers with the signals new in that cycle

6. When it fails

Event	What happens
qp is down	the desk is unaffected. Each alert cycle the scheduler starts fails, is recorded and alerts. Charts and backtests wait for qp to restart
a feed fails or returns nothing	the chart and the backtest say which feed and for which symbols; the backtest's coverage line counts the empty feeds
the shared record is down	backtests that need registers or facts say so and do not run; charts still work
one strategy or symbol fails in an alert cycle	the cycle goes on with the others; the error is in the cycle's record

7. Built on

The old desk: the whole of legacy/qp/:

- LIBRARY and CATALOG, with the library's code in library/;
- STRATEGIES and BACKTEST;
- ALERTS-AND-PRINTS and PAGE;
- DATA-FEEDS;
- SCALPS, SCALPS_SPEC and PINE;
- OPERATIONS and DATA-MODEL.

What failed there:

ID	Fault	Prevented by
Q-N9	alerts use the `close` fill and backtests `desk`, so an alert can fire on a different bar	one fill model
Q-N7	`breakeven_after_target` is reported, never simulated	simulated, or refused on save
Q-N4	the CANSLIM gate has no control on the page	a control, reading facts as of the day
Q-N6	some routes default to Polygon	no per-route defaults
Q-N5	the nightly O'Neil chain lives in qp, on a hand-installed timer	moved to the research worker, started by the desk
—	registers are read over HTTP from every tool's port	read from the shared record
—	a qp restart took 3 min 20 s	fixed on 2026-10-06; one supervisor

ID	Fault	Prevented by
—	alert repeats were held in memory	alert history stored (built, step 12)
—	each strategy-symbol pair fetched its own bars every cycle	shared bars per cycle
Q-N1–Q-N3, Q-N8, Q-N10	out-of-date help text	help generated from the definitions

The full list: legacy/qp/KNOWN-ISSUES.md.

---

8. Status

Part	Status
the library, engine, backtest, page, print sheets	**built** (legacy, kept)
alerts on each strategy's own fill model; alert history kept	**built, live** (step 12)
registers from the shared record	**built, off** (`quantRegistersMode`). Today qp reads each tool's port
facts and market states as of a day	**to build** (step D)
alert cycles started by the desk's scheduler, their new signals pushed to the phone	**to build** (step C). Today qp runs its own watcher thread, and signals reach only an open page
the O'Neil chain out of qp	**built** in the research worker, in shadow; the chain still runs from qp's timer until step C
strategy versions; the CANSLIM control; `breakeven_after_target`	**to build**
a re-run of past backtests against the shared record, compared	**to do**, before step D