qp API

Every route qp answers on `:8765`: 53 HTTP routes and one WebSocket, from `quant-platform/chart/server.py`. Every route needs the desk's `td_auth` cookie, except calls from the box itself.

Parameters are query strings unless marked *body* (JSON). Dates are `YYYY-MM-DD`; `register` is `R1` or `Shortlist`, optionally with a tool (`s3:R1`) or all tools merged (`*:R1`).

Page and platform

Method	Path	Parameters	Answer
GET	`/`	—	the page (never cached)
GET	`/api/health`	—	build, primitives, feeds with credentials, default feed
GET	`/api/tools`	—	the desk's programs, for the app bar
POST	`/api/settings/default-feed`	*body* `{feed}`	sets the default feed (DATA-FEEDS.md)
GET	`/api/primitives`	—	every primitive with its parameters, outputs and approval (LIBRARY.md)
GET	`/api/oplog`	`limit` (200), `op`, `day`, `summary`	the operations log, newest first

Chart

Method	Path	Parameters	Answer
GET	`/api/chart`	`symbol` (SPY), `tf` (5m), `days` (5), `feed` (polygon), `view` (all | regular), `overlays` (JSON list of indicators), `asof`	candles and every indicator series
WS	`/ws/live`	the client sends its chart request once	the newest bar and each indicator's newest value, on an interval

Screener registers

Method	Path	Parameters	Answer
GET	`/api/screener/health`	—	registers, options, whether the tools answer
GET	`/api/screener/sources`	`reload`	every configured tool and whether it is up, plus the picker options
GET	`/api/screener/dates`	`register`	the days that register holds; names any tool that did not answer
GET	`/api/screener/register`	`register`, `date` (latest)	compact cards for that day

Strategies

Method	Path	Parameters	Answer
GET	`/api/strategies`	—	every saved strategy
POST	`/api/strategies`	*body* a strategy	create or update
GET	`/api/strategies/{sid}`	—	the exact stored JSON, with its derived exit protocol
POST	`/api/strategies/{sid}/tools`	*body* `{tools}`	assign tools only, without rewriting the strategy
DELETE	`/api/strategies/{sid}`	—	delete
POST	`/api/strategy/evaluate`	*body* `{strategy, symbol, tf, days, feed, view, asof, fill, rules}`	trades, markers, stop and target lines, entry/exit true now, preview stats
POST	`/api/strategy/test`	*body* `{node, symbol, tf, …}`	every bar where one rule or group holds
GET	`/api/strategy/explain`	`name`, `symbol`, `day`, `tf` (1m), `feed` (polygon)	the signal funnel: each entry step’s true-bar count
GET	`/api/strategy/explain_scan`	`name`, `day`, `tf`, `feed`, `register`	the funnel over a whole register day, closest first

Backtests

Method	Path	Parameters	Answer
POST	`/api/backtest`	*body* the run spec (BACKTEST.md)	`{ok, id}` at once; refused while another runs
GET	`/api/backtest/{bid}`	`trades` (1)	status, progress, summary, trades
GET	`/api/backtests`	`brief`	every run, newest first
POST	`/api/backtest/{bid}/stop`	—	stop at the next symbol; a row nothing is running is marked interrupted
GET	`/api/backtest/{bid}/report`	—	the HTML report
GET	`/api/backtest/{bid}/stats.json`	—	every statistic
GET	`/api/backtest/{bid}/csv`	—	every trade with its register card flattened as `ctx_*` columns
GET	`/api/backtest/{bid}/journal.csv`	—	one row per trade
DELETE	`/api/backtest/{bid}`	—	delete the run and its trades

Alerts

Method	Path	Parameters	Answer
POST	`/api/alerts/start`	`interval` (s)	start the watcher (ALERTS-AND-PRINTS.md)
POST	`/api/alerts/stop`	—	stop
GET	`/api/alerts/status`	—	state, what it watches, errors
GET	`/api/alerts/recent`	`since_ts`	alerts newer than a time

Print sheets and exports

Method	Path	Parameters	Answer
GET	`/api/r1/print`	`start`, `end` or `day`, `tf` (1m), `feed`, `overlays`, `register`, `days_before` (1), `days_after` (0), `cols`	HTML: one chart per ticker per day (150 at most)
GET	`/api/r1/swing`	as above, `tf` (1d), `lookback` (252)	HTML: the swing sheet
GET	`/api/r1/swing.csv`	as `/swing`	CSV, with `phase` and `pct_from_found`
GET	`/api/r1/csv`	as `/print`	CSV: one row per bar, a column per indicator
GET	`/api/r1/cards.csv`	`start`, `end` or `day`, `register`	CSV: every frozen card column
POST	`/api/pairs/parse`	*body* `{pairs}`	how a pasted list will be read
GET	`/api/pairs/print`	`pairs`, `tf` (5m), `feed`, `overlays`, `register`, `days_before` (1), `days_after` (1), `cols`, `height`, `trades`	HTML for a list of `symbol, date` pairs
GET	`/api/pairs/csv`	as `/pairs/print`	CSV

O’Neil / CANSLIM

Read by the screener tools’ Market tab and cards (CANSLIM.md).

Method	Path	Parameters	Answer
GET	`/api/oneil/market`	`refresh`, `days` (500), `feed` (yahoo)	the market model (M)
GET	`/api/oneil/groups`	`refresh`	group ranks and rank-in-group (L)
GET	`/api/oneil/fundamentals`	`symbols`, `refresh`, `cached_only`	the C and A tables from EDGAR
GET	`/api/oneil/13f`	`refresh`	institutional holders and their direction (I)
GET	`/api/oneil/base`	`symbols`, `feed` (yahoo)	the base on a weekly chart
GET	`/api/oneil/ratings`	`symbols`, `feed`, `index` (^GSPC)	up/down volume, accumulation/distribution, RS line, divergence
GET	`/api/oneil/stock`	`symbols`, `feed`	what each stock did on the live distribution days

Data checks and the cache

Method	Path	Parameters	Answer
GET	`/api/datacheck`	`symbol` (SPY)	every source judged (DATACHECK.md)
GET	`/api/feedcheck`	`symbol`	which feeds actually returned data
GET	`/api/cache`	—	bar cache size and free disk
POST	`/api/cache/clear`	*body* `{older_than_days?}`	delete cached bars
POST	`/api/cache/sweep`	—	trim to the limit now