qp: charts, strategies and backtests

The second program on the desk. It charts any stock with indicators that have been verified against TradingView, lets you build trading rules by clicking, backtests them on **the stocks the screener tools actually found, on the days they found them**, watches today's lists for live signals, and builds the O'Neil/CANSLIM data the screener cards and Market tab show.


Process	`qp` under pm2, FastAPI (`quant-platform/chart/server.py`), port **8765**
Page	one page: chart, tools rail, strategy drawer, backtest, register browser, alerts, print sheets
Its data	`~/.qp/platform.db` (strategies, backtests), `~/.qp-cache/` (bars, CANSLIM caches)
Reads	the screener tools' registers, over HTTP
Writes for the tools	`data/oneil-*.json`, `data/industry-map.json` (the nightly chain)

Read in this order

#	Document	Answers
1	LIBRARY.md	the verified indicator library: the one rule, definition, verification, deviations from Pine
2	CATALOG.md	every primitive: inputs, outputs, parameters (generated)
3	PAGE.md	everything on the page
4	STRATEGIES.md	the strategy grammar, how rules become trades, fill models, the exit plan and the order
5	BACKTEST.md	the backtest: universe, honesty rules, every setting, accounting, the report
6	DATA-FEEDS.md	the bar feeds, warm-up, the cache and its limits, the borrow check
7	ALERTS-AND-PRINTS.md	the live signal watcher and the print sheets
8	CANSLIM.md	the O’Neil method as built: M, C, A, N, S, L, I, the RS rating, groups
9	SCALPS.md, SCALPS_SPEC.md	the five SMB scalps, and how each is built in the grammar
10	PINE.md	the three ready strategies as TradingView Pine scripts (pine/)
11	OPERATIONS.md	the process, restarts, the nightly CANSLIM job, environment
12	DATA-MODEL.md	every table, file and cache, and what survives what
13	API.md	every route
14	SCRIPTS.md	the helper scripts and the test suite
15	KNOWN-ISSUES.md	open findings, and what was fixed

The library’s code is in library/.

How qp fits with the screener tools



The code, file by file (`quant-platform/`)

File	Does
`qp/registry.py`, `qp/primitives/*`	the library (LIBRARY.md)
`chart/server.py`	the FastAPI app: every route, start-up
`chart/strategy.py`	the strategy engine: operands, rules, groups, trade pairing, fill models
`chart/exit_protocol.py`	the declared exit plan: legs, stops, runner
`chart/order_plan.py`	one function from a trade to broker orders: sizing, caps, legs, cents
`chart/backtest.py`	day-by-day replay, filters, ranking, accounting blocks
`chart/report.py`	the backtest report and statistics
`chart/rank_sweep.py`	which ranking metric suits a strategy
`chart/parity.py`	is the saved strategy the one a backtest ran
`chart/store.py`	the database: strategies, backtests, seeds, JSON copies
`chart/data_manager.py`	bars from the loaders, warm-up, the live tail
`chart/screener.py`	reading the tools' registers over HTTP, multi-source
`chart/alerts.py`	the live signal watcher
`chart/datacheck.py`	judging every source's data (DATACHECK.md)
`chart/oplog.py`	the operations log
`chart/auth.py`	the desk login, for qp and its WebSocket
`chart/oneil.py`, `relstrength.py`, `sic.py`, `groups.py`, `edgar.py`, `f13.py`, `base.py`, `ratings.py`, `canslim.py`	the CANSLIM chain (CANSLIM.md)
`chart/static/index.html`	the page
`chart/seeds/*.json`	the bundled strategies

File	Does
`tools/compare_server.py`, `tools/data/*`	the verification page and the bar loaders
`deploy/run_*.py`, `deploy/qp-*.service`, `qp-daily.timer`	the nightly chain and one-off jobs

Rules a rebuild must keep

The math

1. **One implementation of every indicator**, in one registry, used by the chart, the engine, the backtest and the alerts (LIBRARY.md).
2. **Nothing is trusted until verified** against TradingView, with a recorded approval; the catalogue is generated, never hand-written.
3. **NaN means "not known yet"**, never zero; any missing operand makes a rule false.

The strategy 4. **One evaluator**: the preview, the backtest and live signals call the same function (STRATEGIES.md). 5. **The exit is declared**, leg by leg, every leg with its own stop, fractions summing to exactly 1. 6. **The order is one pure function**; the backtest books exactly those orders.

The backtest 7. **As of the day**, on the universe as frozen that day; only trades entered that day count (BACKTEST.md). 8. **The honest fill by default** (decision at the close, fill at the next open, levels from the decision), explicit and never silently replaced. 9. **No trade before the scanner found the stock.** 10. **Costs, borrow and capital limits are modelled**, and everything excluded is counted and shown. 11. **A run keeps a frozen copy of what it ran**; numbers always state their basis (dollars or unit %) and their sample's adequacy.

The data 12. **A feed is judged by what it returns, not by whether a key exists** (DATA-FEEDS.md). 13. **Caches have limits tied to free disk.** 14. **qp is the only writer of the O'Neil files**, rebuilt every night by one job that never stops on one failed step (OPERATIONS.md). 15. **One supervisor**: pm2 only, never systemd as well.

What not to copy

- the alerts' `close` fill, which differs from the backtest's (Q-N9);
- options the engine reports but does not simulate (`breakeven_after_target`, Q-N7);
- the text that still describes the removed trading module (Q-N3, Q-N10);
- the open items in KNOWN-ISSUES.md.