From today’s desk to the new one

Trunk section: §10 From today’s desk to this one.

How to get from the desk that runs today to the design, **without a rewrite and without stopping the desk**. Each step ships on its own, keeps the desk working, is checked against the old desk before the old part is switched off, and can be undone.

Built on: the earlier rebuild draft, the legacy known issues (screeners, qp, journal), and the “how the rebuild is proven” section of every design leaf.

---

1. The rules of the migration

1. **The old desk keeps running** until the new part has matched it for a set period (a week, unless stated).
2. **Compare, then switch.** Every step has a parity check against the old desk; differences are explained (a fixed fault) or fixed.
3. **One step at a time**, each a pull request through CI.
4. **Reversible.** Each step says how to go back.
5. **The research record is sacred.** No R1, R3 or shortlist row of any tool, running or archived, is lost; every import is checked by row counts.

---

2. The steps

#	Step	Domain(s)	Changes	Parity check	Undo	Risk
1	**CI**	platform	every test (Jest, qp `run_all`) runs on every pull request; red blocks a merge	a failing test blocks	remove the workflow	none
2	**One front door**	platform	Cloudflare Tunnel or Caddy with TLS; the same login; every other port closed	outside port scan shows only 443; every page works through the door	reopen the ports	low · needs a domain
3	**Checks on save**	tools	capture vs windows; `r1 < A < B`; tested selectivity; fix D-S9 (move T6's photo after 11:30, or its window earlier) and D-S10 (startup repairs)	T6's current setting refused	revert	low
4	**Trading calendar and real instants**	platform, journal, registers	one calendar; UTC instants; fixes D-J8, D-J10, D-J12 in the current journal and qp's chart link	a June morning trade's bars and marks land right	revert	low
5	**The database and the fact store**	platform, sources, card	Postgres (or SQLite, one writer per file); the adapters; tools read short interest, borrow and news from the shared facts	cards from old and new paths compared field by field for a week; calls per ticker fall to one	tools read their own fetches again	medium
6	**The market engine**	market	one market state per scan for every tool; hot state persisted; the sector map completed	regimes, stages and scores equal the old tools' for a week (before the corrections)	tools compute their own again	low–medium
7	**The research**	research data	the O'Neil chain leaves qp; facts	facts equal qp's files for a week;	cards read qp's files	medium

#	Step	Domain(s)	Changes	Parity check	Undo	Risk
	worker		with dates; cards and the Market tab read facts	with qp stopped, cards and the tab unchanged	again	
8	**One scheduler**	platform	every job as a row with run history and alerts; the systemd timer and pm2 cron retired	jobs run side by side for a week with identical results; a missed run alerts	the old schedulers again	medium
9	**Tools as rows**	tools, card, registers	one discovery engine for every tool; tool cards; R1 photos in the database; the archive retired; the benchmark (T9) restarted	per tool, R1 compared row by row for a week before its old process stops	per tool: restart the old process	the largest · per tool
10	**Learning rebuilt**	learning	the new model and the direction-aware scorecard; scorer processes retired	walk-forward reports; the scorecard reproduces legacy numbers for bullish screeners	the old scorecard	medium
11	**The journal rebuilt**	journal	one pairing engine; fills, stops, fees; new parsers; snapshots from the fact store	every import case that failed now passes; legacy Alpaca trades re-derived and compared	the old journal (its database is kept)	medium
12	**Quant on the database**	quant	registers and facts read as of a day from the database; one fill model for alerts; alert history	past backtests re-run with identical trades; alert bars equal backtest bars	read over HTTP again	medium
13	**Backup and one-command restore**	platform	verified nightly dumps, Parquet, models; `desk restore`; monthly rehearsal	three monthly rehearsals pass before the old backup is retired	the old backup keeps running until then	medium

#	Step	Domain(s)	Changes	Parity check	Undo	Risk
14	**One web shell**	platform	one origin, one app bar, phone first, ⓘ on every label	every page reachable from the bar	—	low

Steps 1–4 are safe on their own and fix the known faults with the highest cost. Steps 5–8 remove most duplicated work and risk. Step 9 is where the per-tool memory cost goes away.

---

3. Importing the old data

Done once, at step 9 for each tool (step 11 for the journal, step 12 for qp), following the map in DATA-MODEL.md §4:

Source	Into	Check
each tool's `r1_frozen`, `r3a`, `r3b`, `shortlist`, `screeners`, `settings`, `scheduler_jobs` (running and archived tools)	`r1_photos`, `r3_outcomes`, `shortlist`, `screeners` + version 1, `settings`, `jobs`	row counts per tool, register and day; a sample of rows compared field by field
`r4a_train` / `r4b_train` uploads	`r4_uploads`	row counts
each tool's `r2_market_snapshots`	`market_states` (old days)	row counts
`data/oneil-*.json`, `industry-map.json`	`facts` as of their dates	counts per family
`~/.qp/platform.db`	`strategies`, `strategy_versions`, `backtests`, `backtest_trades`	counts; a re-run of a sample of backtests
`data/journal/journal.db`	`accounts`, `fills`, `trades`, `setups`, `day_notes`	counts; Alpaca trades re-derived and compared

Old rows that lack something the new schema records (screener versions, a market state id, an O'Neil status frozen at the time) are imported with that field marked **unknown**, never guessed.

---

4. What stays exactly as it is

- The research method: one photo a day per tool, entries A and B, outcomes in ATR, the 1.3 good-move line, the benchmark, the mirrors.

- Every card field, every Market-tab section, every source and its fallback order: their home changes, their content does not.
- Each tool’s results, model and history isolated from every other.
- “A label, never a filter” for every shared fact.
- The O’Neil method as built; quant’s verified library and engine.
- The one password and the nightly backup to R2, until their replacements have proven themselves.

---

5. Decisions needed before starting

From the trunk (§11): where it runs, Postgres or SQLite, a domain name, how far to go, and which push service to use. Step 3 also needs one decision of its own: **T6’s photo**. Either move the photo after 11:30 (and its entries with it), or open its window earlier.