Registers: the research record

Trunk section: §6.6 Registers.

Talks to: the Card (§6.3), whose cards and tool cards the photo freezes; Tools and screeners (§6.2), for capture and entry times and screener versions; the Market (§6.4), whose history R2 reads; Sources (§6.1), for the outcome bars; Learning (§6.7), which trains and judges on R4; Quant (§6.8), which backtests over R1; Platform (§6.10), which backs the registers up and exports them.

Built on: REGISTERS (every register and column), METHODOLOGY (the photo, the entries, the measure), DATA-MODEL, and the code in `src/warehouse/registers.js`, `src/sideH/capture.js`, `src/scheduler.js`, `src/db/index.js`, `scripts/backup-r2.js`.

Contents

1. What the registers are for
2. The legacy registers in full
3. What failed
4. The new design
5. Contracts
6. How the rebuild is proven


---

1. What the registers are for

They turn a day of screening into data that can be judged, learned from and backtested, without look-ahead:

Register	Question it answers
R0	what is on screen right now?
R1	what did each card look like at the tool's photo minute?
R2	what was the market doing around the photo?
R3A / R3B	from entry A / B, how far did each photographed card run, each way, in ATR?
R4A / R4B	the photo and its outcome, side by side: one example per card per day
Shortlist	what did the trader (or the auto-rule) pick?

Every register exists **per tool**: tools are separate experiments.



---

2. The legacy registers in full

Register	Written	Trigger	Table	One row per
R0	continuously	every scan and refresh	memory + `r0_checkpoint`	ticker, today
R1	the tool's capture minute	scheduler `R1 Capture HH:MM`	`r1_frozen`	ticker, date
R2	09:26, 09:31 ... 10:01	scheduler	`r2_market_snapshots`	slot, date
R3A / R3B	16:05	`R3 EOD Capture`	`r3a` / `r3b`	ticker, date
R4A / R4B	read time, and copied at 16:05	R3 capture	`r4a_train` / `r4b_train`	ticker, date
Shortlist	each star; the auto-rule	☆, auto-rule	`shortlist`	date (a list)

2.1 R0: the live list

Every card of today, live and stale, in the process's memory, checkpointed to the database after each scan, reloaded on a same-day restart, cleared at midnight. Exported with R1's columns plus `liveNow` and `lastUpdated`.

2.2 R1: the photo

At the capture minute, `captureR1` takes **every R0 row of today**, live or stale, and stores each row's **complete JSON**. A re-capture replaces the day. Exported columns:

Group	Columns	Source
Identity	`ticker`, `date`, `capturedAt`	—
State at the photo	`inShortlist`, `_score`, `bias`	R0
Price	`price`, `prevClose`, `open`, `change`, `gapPct`, `vwap`	quote, derived
Moving averages	`sma5`, `ema9`, `ema13`, `ema20`, `ema50`	quote
Volatility, volume	`rvol`, `atr`, `adrPct`, `dayHigh`, `dayLow`	quote, derived
Ranges	week, month, quarter, year high / low / position; `allTimeHigh`	quote, derived
Size	`mcap`, `floatShares`	quote
Short interest	`shortFloat`, `daysToCover`, `shortBasis`, `shortAsOf`	FINRA / Yahoo / Nasdaq
Pre-market	`pmHigh`, `pmLow`, `pmRange`, `pmAdrRatio`	quote, derived
Classification	`sector`, `industry`, `screenerKeys`, `themes`	quote, desk
Market context	`regime`, `regimeLabel`, `longTerm`, `midTerm`, `shortTerm`, `broadResolved`, `secBias`, `secScore`, `secHot`	market
Relations (27)	`vsEma9 … vsPmLow`, `distEma9 … distPmLow`, `maStack`, `maStackScore`, `monthQuarter`, `pmAdrBand`, `dayRangePos`, `aboveAllMas`, `belowAllMas`	derived
CANSLIM (31)	`csEpsChg`, `csSalesChg`, `csQuarter`, `csAccelerating`, `csBeats`, `csGrowth3yr`, `csStability`, `csRoe`, `csBaseWeeks`, `csBaseDepth`, `csPivot`, `csPctToPivot`, `csBaseScore`, `csHandle`, `csUdRatio`, `csAdLetter`, `csRsLineTell`, `csGroup`, `csGroupLevel`, `csGroupRank`, `csGroupOf`, `csRsInGroup`, `csGroupMembers`, `csFunds`, `csFundsChg`, `csFundsDir`, `csMarket`, `csDdChecked`, `csDdHeld`, `csDdAvgRel`, `csDdVerdict`	qp
Catalyst	`catalyst` (label)	news
Cross-tool	`shortlistedElsewhere`	unified shortlist
Timing	`foundMinsFromOpen` (earliest match, minutes from 09:30; negative pre-market)	R0 `seenAt`

Frozen in the JSON but not exported: `shortSrc`, `shortTrend`, `shortable`, `easyToBorrow`, `regSho`, `regShoDay`, `move2hPct`, `trend6mPct`, the full catalyst, news, `seenAt`, `autoBias`, `_changeFromOpen`.

2.3 R2: market snapshots

Eight slots, 09:26 to 10:01, each the whole market snapshot as JSON; skipped when no scan has built one yet.

Group	Columns
When	`date`, `slot`, `capturedAt`
SPY	close, change, week change, SMA 5/20/50/200, Bollinger upper/lower
QQQ	close, change, week change, SMA 5/20/50/200
IWM, DIA, VIX	close, change (and week change for IWM, VIX)
Desk read	`regime`, `regimeLabel`, `shortBias`, `shortScore`, `midStage`, `longBias`, counts of bullish / bearish sectors, `breakouts` (up to 5 symbols up > 3 % on > 2× volume)
O'Neil	`oneilStatus`, `oneilAsOf`, `oneilDistributionDays`, `oneilSessionsSinceFtd`, `oneilFtdDate` (read at export: D-D3)
Per sector (15)	bias, score, change, hot

2.4 R3A / R3B: outcomes

At 16:05, for every ticker in today's R1:

1. 1-minute bars for the day from **Yahoo**, then **Alpaca** for tickers Yahoo returned empty; daily bars from Yahoo, else Alpaca; batches of 100.
2. **ATR14** from daily bars **strictly before today**.
3. **Entry** = the **open** of the bar at the entry minute; no bar at that minute = no row (logged `missing HH:MM bar`).
4. From the entry bar to the close: `hh` = highest high, `ll` = lowest low.
5. `upR = (hh − entry) / ATR14`, `downR = (entry − ll) / ATR14`, both positive.
6. The **opening range** 09:30–09:35 high and low.

Columns: `date`, `ticker`, `entryPrice{A,B}`, `hh{A,B}`, `ll{A,B}`, `atr14`, `upR_{A,B}`, `downR_{A,B}`, `capturedAt`; `or_high`, `or_low` stored but not exported (D-D4). Worked example: entry $10, high $12.50, low $9.40, ATR $1 → upR 2.5, downR 0.6.

2.5 R4A / R4B: training rows

R1 joined to R3A (or R3B) on ticker. Read live, and at 16:05 the rows with an outcome are copied into `r4a_train` / `r4b_train` for training and for Analysis export and upload. R1's `price`

is called `price936` whatever the capture time (P-1). **Narrower than R1:** no CANSLIM columns, no week, quarter or year ranges, no `allTimeHigh`, `daysToCover`, `shortBasis`, `shortAsOf` (D-D2).

2.6 Shortlist

One row per date holding a list of items: `ticker`, `tvSymbol`, `addedAt`, `method` (`manual` or `auto`), `price`, `change`, `sector`, `score` at that moment, `exported`, `exportedAt` (copied to TradingView from the Shortlist tab).

- **Auto-rule:** one minute before the photo, the top `shortlistTopN` (5) cards with a score of at least `shortlistMinScore` (70) are added, once a day. With the scorer off, it adds nothing (D-D1).
- **Unified list:** each change is published to `data/shortlist-all.json`; other tools show `★ also T2`; `inShortlist` stays this tool's own.

2.7 Reading them

A tool's **Warehouse** tab (pick a date and a register; CSV or JSON); `GET /api/warehouse/available-dates?register=R1` and `GET /api/warehouse/<REG>/<date>`; qp over localhost for charts, R1 sheets and backtests; **Cloudflare R2** nightly CSVs per tool × register × day under `analysis/`; archived tools through the archive process, read-only.

---

3. What failed

ID	Fault	Root cause	Prevented by
D-D2	R4 narrower than R1	R4 is a copied table with its own column list	R4 is a view over R1 and R3
D-D3	an old R2 day shows today's O'Neil status	read at export	R2 reads the market history, which holds M as it was
D-D4	the opening range is stored but not exported	a hand-kept export list	exports generated from the schema
P-1	`price936` whatever the capture time	a historical name	the photo's price is `price`; the legacy name is kept only in legacy exports
D-S9	T6's photo taken before its screener can find anything	no check	checked on save (TOOLS-AND-SCREENERS.md §8.3)
D-D1	the auto-rule adds nothing	no scores	scores applied in-process (LEARNING.md)
—	empty `cs*` columns frozen while qp restarts	CANSLIM fetched from qp per scan	facts read from the fact store
—	R0 lost on restart until the checkpoint reload; hot-sector and live state in memory	memory state	tool cards are rows
—	outcomes on weekday arithmetic; a missing bar silently drops a ticker (logged only)	no trading calendar; reasons not stored	the trading calendar; a reason row for every ticker not measured
—	uploaded external rows mixed into training and verdicts	one table for both	uploads stored apart and labelled
—	registers spread over one SQLite file per tool, read by qp over HTTP from each tool's port	per-tool processes	one database; quant reads directly

4. The new design

4.1 R0 is the tool cards

There is no separate live register: R0 is the day's **tool cards** joined to the shared cards (CARD.md §5.1). They are rows, so a restart loses nothing, and they are kept after the day closes.

4.2 R1: the photo

At each tool's capture minute (from the tool row), the register job writes, for every tool card of the day (live or stale):

Column	Contents
`tool`, `day`, `ticker`	key
`captured_at`	the instant
`card`	the whole card as JSON: every fact family with its value, status, source and `known_at`
`tool_card`	the whole tool card: screener keys **with versions and first-match times**, first seen, live, star, manual bias, score (with model version, sample, confidence)
`market_state_id`	the market state the card carried
`capture_version`	the version of the photo's definition

Nothing is left out, so any column can be added to an export later without losing a day. A re-capture of the same day replaces it and is logged.

4.3 R2: a view of the market history

R2 is generated from the market states of the trading day nearest to each slot (09:26, 09:31 … 10:01), and carries the O'Neil status **as it was** in that state (MARKET.md §5.2). Its columns are those of §2.3.

4.4 R3: outcomes on the trading calendar

At 16:05 on each trading day (half days: 15 minutes after their close), for every R1 row of every tool:

Step	Rule
bars	1-minute and daily bars through the bar adapters (Yahoo, then Alpaca), stored once per ticker per day and shared by every tool
ATR14	from the 14 sessions before the day, on the trading calendar
entries	the open of the bar at each of the tool's entry minutes
hh, ll, upR, downR	as §2.4
opening range	09:30–09:35 high and low
result	`ok`, or a **reason** (`no bar at 09:37`, `no daily history`, `halted`), stored as a row

R3 is one table with an `entry` column (`A`, `B`), so a third entry can be added without a new table.

4.5 R4: a view

`R4 = R1 ⋈ R3` on tool, day, ticker, entry. Every R1 column is available, CANSLIM, ranges and all. A model or scorecard selects the columns it uses; the view never drifts. **Uploaded rows** (examples from outside the tool) live in their own table, are labelled by source, and are excluded from verdicts unless explicitly included.

4.6 Shortlist

Table	Key	Columns
`shortlist`	tool, day, ticker	`added_at`, `method` (manual, auto), the card's price, change, sector and score at that moment, `exported_at`

The unified view is a query over every tool's shortlist (no shared file). The auto-rule runs one minute before each tool's photo, from scores that now exist.

4.7 Exports

Generated from the schema, never from a hand-kept column list:

Export	Format	Where
a register for a tool and day	CSV or JSON	the Warehouse tab, the API
the nightly analysis set	Parquet (and CSV for compatibility)	R2 bucket, `analysis/<tool>/<register>/<day>`
the legacy CSV layout (with `price936`)	CSV	on request, for old notebooks

5. Contracts

Owns

Table / view	Key
`r1_photos`	tool, day, ticker
`r2_slots` (view)	tool, day, slot
`r3_outcomes`	tool, day, ticker, entry
`r4` (view)	tool, day, ticker, entry
`r4_uploads`	tool, day, ticker, entry, source
`shortlist`	tool, day, ticker
`bars_day`	ticker, day (shared outcome bars)

Reads

From	What
tools and screeners	capture minute, entries, screener versions
card	cards and tool cards
market	market states
sources	bars

Read by

Domain	What
learning	R4 per tool
quant	R1 per tool and day (backtest universes), R3 (outcomes)
platform	exports and backups

Routes (desk-web)

Route	Returns
`GET /api/tools/:tool/registers/:reg/dates`	the days a register has
`GET /api/tools/:tool/registers/:reg/:day?format=csv|json`	the register
`POST /api/tools/:tool/shortlist/:ticker`, `DELETE …`	star, unstar
`GET /api/shortlist?day=`	every tool’s shortlist

---

6. How the rebuild is proven

1. **R1 parity.** For a week, each tool’s new R1 is compared column by column with the old tool’s `r1_frozen` (exported columns and frozen JSON).
2. **R3 parity.** For the same week, upR and downR match the old R3 to the cent, except where the trading calendar or a stored reason explains it.
3. **R4 completeness.** Every R1 column is present in R4.
4. **Old history imported.** Every legacy tool database (running and archived) is imported into the new tables; row counts per tool, register and day match.
5. **Legacy exports.** The legacy CSV layout regenerated from the new tables is byte-identical for a sample of past days.