



Top highlighted


What is Entropy and why Information gain matter in Decision Trees?



Nasir Islam Sujan

Follow

Jun 29, 2018 · 5 min read



According to [Wikipedia](#), **Entropy** refers to disorder or uncertainty.

Definition: **Entropy** is the measures of **impurity, disorder** or **uncertainty** in a bunch of examples.

What an Entropy basically does?

Entropy controls how a Decision Tree decides to **split** the data. It actually effects how a **Decision Tree** draws its boundaries.

The Equation of Entropy:

$$\text{Entropy} = - \sum p(X) \log p(X)$$

here $p(x)$ is a fraction of examples in a given class

Equation of Entropy

...

What is Information gain and why it is matter in Decision Tree?

Definition: Information gain (IG) measures how much “information” a feature gives us about the class.

Why it matter ?

- **Information gain** is the main key that is used by **Decision Tree Algorithms** to construct a Decision Tree.
- **Decision Trees** algorithm will always tries to maximize **Information gain**.
- An **attribute** with highest **Information gain** will tested/split first.

The Equation of Information gain:

$$\text{Information gain} = \text{entropy (parent)} - [\text{weightes average}] * \text{entropy (children)}$$

Equation of Information gain

. . .

To understand Entropy and Information gain, lets draw a simple table with some features and labels.

This example taken from [Udacity](#) (Introduction to Machine Learning) course

Here in this `table`,

- `Grade`, `Bumpiness` and `Speed Limit` are the features and **`Speed`** is label.
- Total four observation.

. . .

First, lets work with `Grade` feature

In the `Grade` column there are four values and correspond that values there are four labels.

Lets consider all the labels as a parent `node`.

```
SSFF => parent node
```

So, what is the entropy of this parent node ?

Lets find out,

firstly we need to find out the *fraction of examples* that are present in the parent node. There are 2 types (*slow and fast*) of example present in the parent node, and parent node contains total 4 examples.

1. $P(\text{slow}) \Rightarrow$ fraction of slow examples in parent node
2. $P(\text{fast}) \Rightarrow$ fraction of fast examples in parent node

lets find out $P(\text{slow})$,

$p(\text{slow}) = \text{no. of slow examples in parent node} / \text{total number of examples}$

$$p_{\text{slow}} = \frac{2}{4} = 0.5$$

fraction of $P(\text{slow})$ examples

Similarly the fraction of fast examples $P(\text{fast})$ will be,

$$p_{\text{fast}} = \frac{2}{4} = 0.5$$

fraction of $P(\text{fast})$ examples

So, the **entropy** of parent node:

$$\text{Entropy}_{\text{parent}} = - \sum P_{\text{slow}} \log_2(P_{\text{slow}}) + P_{\text{fast}} \log_2(P_{\text{fast}})$$

entropy of parent node

$$\begin{aligned} \text{Entropy}(\text{parent}) &= - \{0.5 \log_2(0.5) + 0.5 \log_2(0.5)\} \\ &= - \{-0.5 + (-0.5)\} \\ &= 1 \end{aligned}$$

So the *entropy* of parent node is 1.


. . .

Now, lets explore how a **Decision Tree Algorithm** construct a **Decision Tree** based on **Information gain**

First lets check whether the parent node split by `Grade` or not.

If the **Information gain** from `Grade` feature is greater than all other features then the parent node can be split by `Grade`.

To find out **Information gain of** `Grade` feature, we need to virtually split the parent node by `Grade` feature.



Now, we need to find out the entropy both of this child nodes.

Entropy of the right side child node (F) is 0 , *because all of the examples in this node belongs to the same class.*

Lets find out **Entropy** of the left side node SSF :

In this node SSF there are two type of examples present, so we need to find out the ***fraction of slow and fast example*** separately for this node.

```

P(slow) = 2/3 = 0.667
P(fast) = 1/3 = 0.334
  
```

So,

```

Entropy(SSF) = - {0.667 log2(0.667) + 0.334 log2(0.334)}
              = - {-0.38 + (-0.52)}
              = 0.9
  
```

we can also find out the *Entropy* by using `scipy` library.

Now, we need to find out `Entropy(children)` with weighted average.

```

Total number of examples in parent node: 4
"      "      "      "      "      left child node: 3
"      "      "      "      "      right child node: 1
  
```

Formula of Entropy(children) with weighted avg. :

```

[Weighted avg]Entropy(children) =
(no. of examples in left child node) / (total no. of examples in
parent node) * (entropy of left node)
+
(no. of examples in right child node) / (total no. of examples in
parent node) * (entropy of right node)
  
```

$$[weighted_{avg}](children) = \frac{3}{4} * 0.9 + \frac{1}{4} * 0$$

Entropy(children) with weighted avg. is = **0.675**

So,

$$\text{Information gain} = \text{entropy}(\text{parent}) - [\text{weighted average}] * \text{entropy}(\text{children})$$


Equation of Information gain

$$\begin{aligned} \text{Information gain(Grade)} &= 1 - 0.675 \\ &= 0.325 \end{aligned}$$

Information gain from `Grade` feature is 0.325 .

Decision Tree Algorithm choose the highest Information gain to *split/construct* a **Decision Tree**. So we need to check all the feature in order to split the Tree.

Information gain from `Bumpiness`



The **entropy** of left and right child nodes are same because they contains same classes.

entropy(bumpy) and **entropy(smooth)** both equals to 1 .

So, **entropy (children)** with weighted avg. for `Bumpiness` :

$$\begin{aligned} [\text{weighted avg.}] \text{entropy}(\text{children}) &= 2/4 * 1 + 2/4 * 1 \\ &= 1 \end{aligned}$$

Hence,


$$\begin{aligned} \text{Information gain(Bumpiness)} &= 1 - 1 \\ &= 0 \end{aligned}$$

Till now we have to **Information gain**:

$$\begin{aligned} \text{IG(Grade)} &\Rightarrow 0.325 \\ \text{IG(Bumpiness)} &\Rightarrow 0 \end{aligned}$$

. . .

Information gain from `SpeedLimit`



The **entropy** of left side child node will be 0, because all of the examples in this node belongs to the same class.

Similarly, **entropy** of right side node is 0.

Hence, **Entropy(children)** with weighted avg. for SpeedLimit :

```
[weighted avg.] entropy(children) = 2/4 * 0 + 2/4 * 0
                                   = 0
```

So, **Information gain** from SpeedLimit :


```
Information gain(SpeedLimit) = 1 - 0
                             = 1
```

Final Information gain from all the features:

```
IG(Grade) => 0.325
IG(Bumpiness) => 0
IG(SpeedLimit) => 1
```

As we know that, **Decision Tree Algorithm** construct **Decision Tree** based on features that have highest **Information gain**

So, here we can see that SpeedLimit has highest **Information gain**. So the final **Decision Tree** for this datasets will be look like this:



Coinmonks

Machine Learning

Data Science

Decision Tree

Entropy

Information Gain



813 claps

Applause from you and 156 others



WRITTEN BY

Nasir Islam Sujan

Follow

Research Assistant | Machine Learning Practitioner | ASP.NET, C# developer | UI/UX designer.



Coinmonks

Following

Coinmonks is a technology-focused publication embracing decentralize technologies. We are Non-profit and education is our core value. Learn, Build and thrive. Our other project—<https://coinmonks.com>, <https://cryptofi.co>, <https://coincodetap.com>

See responses (8)

More From Medium

More from Coinmonks

Bitcoin's bull run: This is what's different compared to 2017



Lucien Lecarme in Coinmonks

Jun 24 · 8 min read ★



908



More from Coinmonks

Whitepaper Deep Dive— Move: Facebook Libra Blockchain's New Programming Language



李婷婷 Lee Ting Ting in Coinmonks

Jun 19 · 11 min read ★



1.6K



More from Coinmonks

Bitcoin: Welcome to Bitfinex's Second Tether Bubble



cryptomarketrisk in Coinmonks

Jun 28 · 5 min read ★



407

