

# Broken Stadium VLAN

Network / Cisco Packet Tracer / Troubleshooting - Medium - Author: oxFelouja

|               |                               |
|---------------|-------------------------------|
| Challenge     | Broken Stadium VLAN           |
| Category      | Network / Cisco Packet Tracer |
| Level         | Medium                        |
| File provided | broken_stadium_vlan.pka       |
| Flag format   | CSCC{}                        |

## Scenario

During the CSCC Olympics final ceremony, the scoreboard server became unreachable. You received a Packet Tracer activity file containing the stadium network in a broken state.

Your mission is to troubleshoot the network, restore connectivity, open the scoreboard web page, and submit the flag.

## Objective

From Admin-PC, access the scoreboard server:

```
http://192.168.30.10
```

The flag is displayed on the web page after the network is fixed.

## Addressing Table

| Device            | Interface | IP Address    | Mask          | Gateway      |
|-------------------|-----------|---------------|---------------|--------------|
| Admin-PC          | Fa0       | 192.168.10.10 | 255.255.255.0 | 192.168.10.1 |
| Athlete-PC        | Fa0       | 192.168.20.10 | 255.255.255.0 | 192.168.20.1 |
| Scoreboard-Server | Fa0       | 192.168.30.10 | 255.255.255.0 | Check it     |
| R1                | G0/0.10   | 192.168.10.1  | 255.255.255.0 | -            |
| R1                | G0/0.20   | 192.168.20.1  | 255.255.255.0 | -            |
| R1                | G0/0.30   | 192.168.30.1  | 255.255.255.0 | -            |

## VLANs

| VLAN | Name       | Network         |
|------|------------|-----------------|
| 10   | ADMIN      | 192.168.10.0/24 |
| 20   | ATHLETES   | 192.168.20.0/24 |
| 30   | SCOREBOARD | 192.168.30.0/24 |

## Rules

- Do not change IP networks unless necessary.
- Do not delete devices from the Packet Tracer file.
- Do not edit the HTTP page manually.
- You may use CLI commands and Packet Tracer simulation tools.

## What to investigate

- VLAN membership on switch ports.
- Trunk configuration between the switch and router.
- Router-on-a-stick subinterfaces.
- Default gateway configuration on end devices.
- End-to-end connectivity from Admin-PC to Scoreboard-Server.

## Useful commands

```
show vlan brief
show interfaces trunk
show running-config
show ip interface brief
ping 192.168.30.10
```

## Success condition

The challenge is solved when Admin-PC can open:

```
http://192.168.30.10
```

Submit only the flag shown on the scoreboard page.

## Submission format

```
CSCC{...}
```

## Note for participants

The problem is not solved by guessing the flag. You must restore the network path to the scoreboard server.