

C:\Documents and Settings\user>route print

Interface List

0x1 MS TCP Loopback interface
0x2 ...50 fe 9c 09 4f 00 Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:

Network	Destination	Netmask	Gateway	Interface	Metric
	50.0.0.0	255.0.0.0	50.0.0.10	50.0.0.10	10
	50.0.0.10	255.255.255.255	127.0.0.1	127.0.0.1	10
50.255.255.255	255.255.255.255		50.0.0.10	50.0.0.10	10
	127.0.0.0	255.0.0.0	127.0.0.1	127.0.0.1	1
	224.0.0.0	240.0.0.0	50.0.0.10	50.0.0.10	10
255.255.255.255	255.255.255.255		50.0.0.10	50.0.0.10	1

Persistent Routes:

None

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:

Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss).

C:\Documents and Settings\user>

224.0.0.0	255.0.0.0	50.0.0.10	127.0.0.1	10
255.255.255.255	240.0.0.0	50.0.0.1	50.0.0.10	10
	255.255.255.255	127.0.0.1	50.0.0.10	10
		50.0.0.10	127.0.0.1	1
		50.0.0.10	50.0.0.10	1
		50.0.0.10	50.0.0.10	10
			50.0.0.10	1

Persistent Routes:
None

C:\Documents and Settings\user>ping 60.0.0.10

Pinging 60.0.0.10 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 60.0.0.10:

Packets: Sent = 4, Received = 0, Lost = 4 (100% loss).

C:\Documents and Settings\user>_

```
network connections
C:\WINDOWS\system32\cmd.exe
Minimum = 1ms, Maximum = 2ms, Average = 1ms
C:\Documents and Settings\user>route print
=====
Interface List
0x1 ..... MS TCP Loopback interface
0x2 ...50 86 5f 09 50 00 ..... Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport
=====
Active Routes:
Network Destination    Netmask          Gateway          Interface        Metric
0.0.0.0                0.0.0.0          60.0.0.1        60.0.0.10       10
60.0.0.0              255.255.255.255  60.0.0.10      60.0.0.10       10
60.0.0.10            255.255.255.255  127.0.0.1      127.0.0.1       10
127.0.0.0            255.255.255.255  60.0.0.10      127.0.0.1       10
127.0.0.1            255.255.255.255  60.0.0.10      127.0.0.1       1
255.255.255.255      255.255.255.255  60.0.0.10      60.0.0.10       10
Default Gateway:      60.0.0.1        60.0.0.10      60.0.0.10       1
Persistent Routes:
None
=====
C:\Documents and Settings\user>
```

Connection	Source	Subnet mask	Default gateway	Received
Other Places				
Control Panel				
		255.0.0.0		
		60.0.0.0		

Network Tasks

- Create a new connection
- Set up a home or office network
- Change Windows Firewall settings
- Disable this device
- Repair this connection
- Rename this connection
- View status of this connection
- Change settings for this connection

Other Places

- Control Panel
- My Network Places
- My Documents
- My Computer

Details

Local Area Connection
LAN or High-Speed Internet

General | Advanced

Internet Protocol (TCP/IP) Properties

General

You can get IP settings assigned automatically if your network supports this capability. Otherwise, you need to ask your network administrator for the appropriate IP settings.

☐ Obtain an IP address automatically

☒ Use the following IP address:

IP address:

60 . 0 . 0 . 10

Subnet mask:

255 . 0 . 0 . 0

Default gateway:

60 . 0 . 0 . 1

☐ Obtain DNS server address automatically

☒ Use the following DNS server addresses:

Preferred DNS server:

Alternate DNS server:

Advanced...

OK

Cancel

Connected
00:29:05
1.0 Gbps

Received

25

```
ping 60.0.0.10 and Settings\user>ping 60.0.0.10
Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 60.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
C:\Documents and Settings\user>ping 60.0.0.10
Pinging 60.0.0.10 with 32 bytes of data:
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127
Reply from 60.0.0.10: bytes=32 time=1ms TTL=127

Ping statistics for 60.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 1ms, Average = 1ms
C:\Documents and Settings\user>
```

Start | 

Statistics for 60.0.0.10:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 1ms, Average = 1ms

C:\Documents and Settings\user>route print

Interface List

0x1 MS TCP Loopback interface
0x2 ...50 fe 9c 09 4f 00 Intel(R) PRO/1000 MT Network Connection - Packet Scheduler Miniport

Active Routes:

Network Destination	Netmask	Gateway	Interface	Metric
0.0.0.0	0.0.0.0	50.0.0.1	50.0.0.10	10
50.0.0.0	255.0.0.0	50.0.0.10	50.0.0.10	10
50.0.0.10	255.255.255.255	127.0.0.1	127.0.0.1	10
50.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	10
127.0.0.0	255.0.0.0	127.0.0.1	127.0.0.1	1
224.0.0.0	240.0.0.0	50.0.0.10	50.0.0.10	10
255.255.255.255	255.255.255.255	50.0.0.10	50.0.0.10	1

Default Gateway:

Persistent Routes:

None

C:\Documents and Settings\user>_

General

You can get IP settings assigned automatically if your network supports this capability. Otherwise, you need to ask your network administrator for the appropriate IP settings.

☐ Obtain an IP address automatically

☒ Use the following IP address:

IP address:

50 0 0 10

Subnet mask:

255 0 0 0

Default gateway:

50 0 0 1

☐ Obtain DNS server address automatically

☒ Use the following DNS server addresses:

Preferred DNS server:

Alternate DNS server:

Advanced

OK

Cancel

```
255.255.255.255 255.255.255.255 60.0.0.10
127.0.0.0 255.255.255.255 127.0.0.1
224.0.0.0 255.0.0.0 60.0.0.10
255.255.255.255 240.0.0.0 127.0.0.1
255.255.255.255 255.255.255.255 60.0.0.10
60.0.0.10 60.0.0.10 1
60.0.0.10 60.0.0.10 1
60.0.0.10 60.0.0.10 1
```

Persistent Routes:
None

C:\Documents and Settings\user>ping 50.0.0.10
Pinging 50.0.0.10 with 32 bytes of data:

```
Reply from 50.0.0.10: bytes=32 time=2ms TTL=127
Reply from 50.0.0.10: bytes=32 time<1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=1ms TTL=127
Reply from 50.0.0.10: bytes=32 time=2ms TTL=127
```

Ping statistics for 50.0.0.10:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-I...

Old Java ASDM