

ES Next


Lec 1

Nourhan Saeed

TODAY'S AGENDA

- ECMAScript HISTORY
- VARIABLES DECLARATION
- RESET PARAMETERS / SPREAD OPERATOR
- DESTRUCTURING (ARRAY / OBJECT)
- ARROW FUNCTION

HISTORY OF ECMAScript



A new version of Ecma is released every year and so on

The TC39 Process



STAGE 0

Ideas (Straw Man)



STAGE 1

Formal Proposal



STAGE 2

Draft



STAGE 3

Candidate



STAGE 4

Finished

Variable **Declarations**

ES6 provides two new ways of declaring variables: `let` and `const`, which mostly replace the ES5 way of declaring variables, `var`.

let

`let` works similarly to `var`, but the variable it declares is block-scoped, it only exists within the current block. `var` is function-scoped.

const

`const` works like `let`, but the variable you declare must be immediately initialized, with a value that can't be changed afterwards


Rest Parameters

- Rest parameter must come at the **end** of the parameters list
- Rest parameter must be with **function signature** only

Spread Operators


- **Easier in concatenating arrays**
- **Deep copying arrays and objects**
- **Can call function with array of params**

Destructuring



- **Allow us to extract values from array or object**
- **Can be used to swap values without temp**
- **Can skip values**
- **Can be used in the function parameters as well**

Default Parameters



- **ES6** make it possible to assign default parameters to functions to get a value instead of undefined
- Must come at the end of the params list

Arrow Function

One of JavaScript's most difficult topics, the **this** keyword, allow us to refer to the **object** that executes a method.

Its **value** is determined by where the **function is called** that uses **this**

Even after defining 'this' to work a certain way it can still change at any point in your program

Arrow Function

Rules to help determine the value of 'this':

- When you create an object using the new keyword with a constructor function/class this will refer to the **new object** inside the function.
- Using bind call, or apply will **override** the value inside a function, and you can **hardcode** its value for **this**.
- If a function is called on an object as a method, **this** will refer to the **object that is calling it**.

Arrow Function


Rules to help determine the value of 'this':

- If a function is executed without any of the three previous criteria being applied, **this** will refer to the **global object**, which is **window** in the browser.
- If you are using **strict mode**, this will be **undefined**.
- Arrow function ignore all the above rules, and the value of **this** is determined by the **scope** enclosed by the arrow function

Arrow Function

This

When it is inside of an object's method — the function's owner is the object. Thus the 'this' keyword is bound to the object. Yet when it is inside of a function, either stand alone or within another method, it will always refer to the window/global object.



THANK YOU

ANY QUESTIONS ?



LAB

In the JS file, you will find a web designer object.




01

Change 'Your name' placholder to your name



02

Write a `getAge()` function that takes the years alive array as destructure and return your age, save the value you return in const called 'age'



LAB



03

Divide the web designer skills into 2 variables `designSkills` and `developmentSkills`



04

Uncomment the `newSkills` array and merge the `developmentSkills` array with `newSkills` array in a new array `'updatedDevSkills'`

Contact me 😎



FeedBack: <https://forms.gle/pbiG8YPCQRPgsrdZA>

Phone: 01271888031