

# Standardizing Data

PREPROCESSING FOR MACHINE LEARNING IN PYTHON



**Sarah Guido**  
Senior Data Scientist

# What is standardization?

- Scikit-learn models assume normally distributed data
- Log normalization and feature scaling in this course
- Applied to continuous numerical data

# When to standardize: models

- Model in linear space
- Dataset features have high variance
- Dataset features are continuous and on different scales
- Linearity assumptions

# Let's practice!

PREPROCESSING FOR MACHINE LEARNING IN PYTHON

# Log normalization

PREPROCESSING FOR MACHINE LEARNING IN PYTHON



**Sarah Guido**  
Senior Data Scientist

# What is log normalization?

- Applies log transformation
- Natural log using the constant  $e$  (2.718)
- Captures relative changes, the magnitude of change, and keeps everything in the positive space

Number	Log
30	3.4
300	5.7
3000	8

# Log normalization in Python

```
print(df)
```

```
   col1  col2
0  1.00   3.0
1  1.20  45.5
2  0.75  28.0
3  1.60 100.0
```

```
print(df.var())
```

```
col1    0.128958
col2   1691.729167
dtype: float64
```

```
import numpy as np
df["log_2"] = np.log(df["col2"])
print(df)
```

```
   col1  col2  log_2
0  1.00   3.0  1.098612
1  1.20  45.5  3.817712
2  0.75  28.0  3.332205
3  1.60 100.0  4.605170
```

```
print(np.var(df[["col1", "log_2"]]))
```

```
col1    0.096719
log_2    1.697165
dtype: float64
```

# Let's practice!

PREPROCESSING FOR MACHINE LEARNING IN PYTHON



# Scaling data

PREPROCESSING FOR MACHINE LEARNING IN PYTHON



**Sarah Guido**  
Senior Data Scientist

# What is feature scaling?

- Features on different scales
- Model with linear characteristics
- Center features around 0 and transform to unit variance
- Transforms to approximately normal distribution

# How to scale data

```
print(df)
```

```
   col1  col2  col3
0  1.00  48.0  100.0
1  1.20  45.5  101.3
2  0.75  46.2  103.5
3  1.60  50.0  104.0
```

```
print(df.var())
```

```
col1    0.128958
col2    4.055833
col3    3.526667
dtype: float64
```

# How to scale data

```
from sklearn.preprocessing import StandardScaler
scaler = StandardScaler()
df_scaled = pd.DataFrame(scaler.fit_transform(df),
                          columns=df.columns)
```

```
print(df_scaled)
```

```
      col1      col2      col3
0 -0.442127  0.329683 -1.352726
1  0.200967 -1.103723 -0.553388
2 -1.245995 -0.702369  0.799338
3  1.487156  1.476409  1.106776
```

```
print(df.var())
```

```
col1    1.333333
col2    1.333333
col3    1.333333
dtype: float64
```

# Let's practice!

PREPROCESSING FOR MACHINE LEARNING IN PYTHON

# Standardized data and modeling

PREPROCESSING FOR MACHINE LEARNING IN PYTHON



**Sarah Guido**  
Senior Data Scientist

# K-nearest neighbors

```
from sklearn.model_selection import train_test_split
from sklearn.neighbors import KNeighborsClassifier
```

```
# Preprocessing first
X_train, X_test, y_train, y_test = train_test_split(X, y)
```

```
knn = KNeighborsClassifier()
knn.fit(X_train, y_train)
```

```
knn.score(X_test, y_test)
```

# Let's practice!

PREPROCESSING FOR MACHINE LEARNING IN PYTHON