

1. Overview

A relational database designed to manage user productivity through structured entities including tasks, meetings, notes, and progress tracking.

The system ensures clear ownership, scalability, and efficient querying for real-world applications.

2. Core Features

- Task management with deadlines and status tracking
- Meeting scheduling with participants
- Notes storage for unstructured data
- Progress tracking for measurable metrics
- User-centric data ownership

3. Core Entities

- **Users** → system identity
- **Tasks** → actionable items
- **Meetings** → scheduled events
- **Meeting Participants** → multi-attendee support
- **Notes** → free text data
- **Progress** → tracked metrics

3.1 Users

Stores user identity and ownership of all resources.

Attribute	Type	Description	Constraints
id	SERIAL	Unique identifier for each user	Primary Key
name	VARCHAR(50)	User's name	NOT NULL
email	VARCHAR(50)	User's email address	NOT NULL, UNIQUE

3.2 Tasks Table

The tasks table stores actionable items assigned to users.

Attribute	Type	Description	Constraints
id	SERIAL	Unique task identifier	Primary Key
title	VARCHAR(50)	Short task description	NOT NULL
deadline	TIMESTAMPTZ	Due date and time	NOT NULL
status	ENUM{ 'pending', 'in_progress', 'completed' }	Task state (e.g., pending, completed)	Default: 'pending'
user_id	INT	Reference to task owner	Foreign Key → users(id), NOT NULL

3.3 Meetings Table

The meetings table stores scheduled events.

Attribute	Type	Description	Constraints
id	SERIAL	Unique meeting identifier	Primary Key
title	VARCHAR(50)	Meeting title	NOT NULL
scheduled_at	TIMESTAMPTZ	Meeting state (scheduled, done, etc.)	NOT NULL, UNIQUE
status	ENUM{ 'scheduled ', 'completed ', 'canceled ' }	Meeting state (scheduled, completed, etc.)	Default: 'scheduled'
location	VARCHAR(50)	Meeting location	Optional
user_id	INT	Owner of meeting	Foreign Key → users(id), NOT NULL

3.4 Meeting Participants Table

This table stores participants linked to meetings.

Attribute	Type	Description	Constraints
id	SERIAL	Unique identifier	Primary Key
name	VARCHAR(50)	Participant name	NOT NULL
meeting_id	VARCHAR(50)	Associated meeting	Foreign Key → meetings(id), NOT NULL

3.5 Notes Table

The notes table stores unstructured user content.

Attribute	Type	Description	Constraints
id	SERIAL	Unique note identifier	Primary Key
title	VARCHAR(50)	Note title	NOT NULL
description	TEXT	Full note content	NOT NULL
user_id	INT	Owner of note	Foreign Key → users(id), NOT NULL

3.6 Progress Table

The progress table tracks user metrics over time.

Attribute	Type	Description	Constraints
id	SERIAL	Unique progress identifier	Primary Key
title	VARCHAR(50)	progress title	NOT NULL
logged_at	TIMESTAMPTZ	Time of record	Default: CURRENT_TIMESTAMP
status	ENUM{ 'not_started', 'in_progress', 'completed' }	progress state (not_started, completed, etc.)	Default: 'not_started'
field	VARCHAR(30)	Category of metric	Optional
value	INT	Recorded value	Optional
user_id	INT	Owner of record	Foreign Key → users(id), NOT NULL

Notes:

- All **id** fields are auto-incremented primary keys.
- All **user_id** fields enforce ownership and data isolation.
- Foreign keys use **ON DELETE CASCADE** to maintain integrity.
- Timestamp fields default to current time for automatic tracking

Additional Column to all tables:

- **created_at** → when the row is first inserted Default: CURRENT_TIMESTAMP
- **updated_at** → when the row is last modified Default: CURRENT_TIMESTAMP