


Labo Routage



ping depuis PC1 vers PC2

```
root@PC-1-T:~# ping 172.16.20.12
PING 172.16.20.12 (172.16.20.12) 56(84) bytes of data.
64 bytes from 172.16.20.12: icmp_seq=1 ttl=63 time=1.57 ms
64 bytes from 172.16.20.12: icmp_seq=2 ttl=63 time=1.59 ms
64 bytes from 172.16.20.12: icmp_seq=3 ttl=63 time=1.57 ms
64 bytes from 172.16.20.12: icmp_seq=4 ttl=63 time=1.48 ms
64 bytes from 172.16.20.12: icmp_seq=5 ttl=63 time=1.44 ms
64 bytes from 172.16.20.12: icmp_seq=6 ttl=63 time=1.08 ms
64 bytes from 172.16.20.12: icmp_seq=7 ttl=63 time=1.46 ms
64 bytes from 172.16.20.12: icmp_seq=8 ttl=63 time=1.17 ms
64 bytes from 172.16.20.12: icmp_seq=9 ttl=63 time=1.39 ms
64 bytes from 172.16.20.12: icmp_seq=10 ttl=63 time=1.63 ms
64 bytes from 172.16.20.12: icmp_seq=11 ttl=63 time=1.42 ms
64 bytes from 172.16.20.12: icmp_seq=12 ttl=63 time=1.35 ms
64 bytes from 172.16.20.12: icmp_seq=13 ttl=63 time=1.49 ms
64 bytes from 172.16.20.12: icmp_seq=14 ttl=63 time=1.50 ms
^C
--- 172.16.20.12 ping statistics ---
14 packets transmitted, 14 received, 0% packet loss, time 13020ms
rtt min/avg/max/mdev = 1.088/1.443/1.630/0.152 ms
root@PC-1-T:~# |
```

ping depuis PC1 vers PC3

```
root@PC-1-T:~# ping 172.16.30.13
PING 172.16.30.13 (172.16.30.13) 56(84) bytes of data.
64 bytes from 172.16.30.13: icmp_seq=1 ttl=63 time=1.51 ms
64 bytes from 172.16.30.13: icmp_seq=2 ttl=63 time=1.56 ms
64 bytes from 172.16.30.13: icmp_seq=3 ttl=63 time=1.53 ms
64 bytes from 172.16.30.13: icmp_seq=4 ttl=63 time=1.60 ms
64 bytes from 172.16.30.13: icmp_seq=5 ttl=63 time=1.10 ms
64 bytes from 172.16.30.13: icmp_seq=6 ttl=63 time=1.45 ms
^C
--- 172.16.30.13 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5007ms
rtt min/avg/max/mdev = 1.102/1.462/1.606/0.170 ms
root@PC-1-T:~# |
```

ping depuis PC1 vers S1

```
root@PC-1-T:~# ping 172.16.30.11
PING 172.16.30.11 (172.16.30.11) 56(84) bytes of data.
64 bytes from 172.16.30.11: icmp_seq=2 ttl=255 time=1.34 ms
64 bytes from 172.16.30.11: icmp_seq=3 ttl=255 time=1.56 ms
64 bytes from 172.16.30.11: icmp_seq=4 ttl=255 time=1.40 ms
64 bytes from 172.16.30.11: icmp_seq=5 ttl=255 time=1.47 ms
64 bytes from 172.16.30.11: icmp_seq=6 ttl=255 time=1.33 ms
64 bytes from 172.16.30.11: icmp_seq=7 ttl=255 time=1.34 ms
64 bytes from 172.16.30.11: icmp_seq=8 ttl=255 time=1.54 ms
^C
--- 172.16.30.11 ping statistics ---
8 packets transmitted, 7 received, 12% packet loss, time 7010ms
rtt min/avg/max/mdev = 1.333/1.430/1.563/0.092 ms
root@PC-1-T:~# |
```

ping depuis PC1 vers S2 :

```
root@PC-1-T:~# ping 172.16.30.12
PING 172.16.30.12 (172.16.30.12) 56(84) bytes of data.
64 bytes from 172.16.30.12: icmp_seq=1 ttl=254 time=2.21 ms
64 bytes from 172.16.30.12: icmp_seq=2 ttl=254 time=2.19 ms
64 bytes from 172.16.30.12: icmp_seq=3 ttl=254 time=2.11 ms
64 bytes from 172.16.30.12: icmp_seq=4 ttl=254 time=2.10 ms
64 bytes from 172.16.30.12: icmp_seq=5 ttl=254 time=2.17 ms
^C
--- 172.16.30.12 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4005ms
rtt min/avg/max/mdev = 2.100/2.159/2.214/0.067 ms
root@PC-1-T:~# |
```

ping depuis PC1 vers R1

```
root@PC-1-T:~# ping 172.16.10.2
PING 172.16.10.2 (172.16.10.2) 56(84) bytes of data.
64 bytes from 172.16.10.2: icmp_seq=1 ttl=255 time=0.881 ms
64 bytes from 172.16.10.2: icmp_seq=2 ttl=255 time=1.16 ms
64 bytes from 172.16.10.2: icmp_seq=3 ttl=255 time=1.21 ms
64 bytes from 172.16.10.2: icmp_seq=4 ttl=255 time=0.982 ms
^C
--- 172.16.10.2 ping statistics ---
4 packets transmitted, 4 received, 0% packet loss, time 3004ms
rtt min/avg/max/mdev = 0.881/1.060/1.216/0.139 ms
root@PC-1-T:~# |
```

ping depuis PC1 vers R2

```
root@PC-1-T:~# ping 172.16.10.3
PING 172.16.10.3 (172.16.10.3) 56(84) bytes of data.
64 bytes from 172.16.10.3: icmp_seq=1 ttl=255 time=1.26 ms
64 bytes from 172.16.10.3: icmp_seq=2 ttl=255 time=1.73 ms
64 bytes from 172.16.10.3: icmp_seq=3 ttl=255 time=0.975 ms
64 bytes from 172.16.10.3: icmp_seq=4 ttl=255 time=1.17 ms
64 bytes from 172.16.10.3: icmp_seq=5 ttl=255 time=1.03 ms
64 bytes from 172.16.10.3: icmp_seq=6 ttl=255 time=1.13 ms
^C
--- 172.16.10.3 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5006ms
rtt min/avg/max/mdev = 0.975/1.218/1.731/0.251 ms
root@PC-1-T:~# |
```

ping depuis PC1 vers R3

```
root@PC-1-T:~# ping 209.165.200.225
PING 209.165.200.225 (209.165.200.225) 56(84) bytes of data.
64 bytes from 209.165.200.225: icmp_seq=1 ttl=254 time=1.39 ms
64 bytes from 209.165.200.225: icmp_seq=2 ttl=254 time=1.72 ms
64 bytes from 209.165.200.225: icmp_seq=3 ttl=254 time=1.82 ms
64 bytes from 209.165.200.225: icmp_seq=4 ttl=254 time=1.69 ms
64 bytes from 209.165.200.225: icmp_seq=5 ttl=254 time=1.73 ms
^C
--- 209.165.200.225 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4007ms
rtt min/avg/max/mdev = 1.398/1.675/1.828/0.148 ms
root@PC-1-T:~# |
```

ping depuis PC1 vers la passerelle virtuelle

```
root@PC-1-T:~# ping 172.16.10.1
PING 172.16.10.1 (172.16.10.1) 56(84) bytes of data.
64 bytes from 172.16.10.1: icmp_seq=1 ttl=255 time=1.39 ms
64 bytes from 172.16.10.1: icmp_seq=2 ttl=255 time=1.50 ms
64 bytes from 172.16.10.1: icmp_seq=3 ttl=255 time=1.50 ms
64 bytes from 172.16.10.1: icmp_seq=4 ttl=255 time=1.47 ms
64 bytes from 172.16.10.1: icmp_seq=5 ttl=255 time=1.73 ms
64 bytes from 172.16.10.1: icmp_seq=6 ttl=255 time=1.64 ms
^C
--- 172.16.10.1 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5007ms
rtt min/avg/max/mdev = 1.399/1.543/1.738/0.123 ms
root@PC-1-T:~# |
```

ping depuis PC2 vers PC1

```
root@PC-2-T:~# ping 172.16.10.11
PING 172.16.10.11 (172.16.10.11) 56(84) bytes of data.
64 bytes from 172.16.10.11: icmp_seq=1 ttl=63 time=1.45 ms
64 bytes from 172.16.10.11: icmp_seq=2 ttl=63 time=1.58 ms
64 bytes from 172.16.10.11: icmp_seq=3 ttl=63 time=1.23 ms
64 bytes from 172.16.10.11: icmp_seq=4 ttl=63 time=1.40 ms
64 bytes from 172.16.10.11: icmp_seq=5 ttl=63 time=1.19 ms
^C
--- 172.16.10.11 ping statistics ---
5 packets transmitted, 5 received, 0% packet loss, time 4006ms
rtt min/avg/max/mdev = 1.199/1.375/1.581/0.144 ms
root@PC-2-T:~# |
```

ping depuis PC2 vers PC3

```
root@PC-2-T:~# ping 172.16.30.13
PING 172.16.30.13 (172.16.30.13) 56(84) bytes of data.
64 bytes from 172.16.30.13: icmp_seq=1 ttl=63 time=1.60 ms
64 bytes from 172.16.30.13: icmp_seq=2 ttl=63 time=1.07 ms
64 bytes from 172.16.30.13: icmp_seq=3 ttl=63 time=1.44 ms
64 bytes from 172.16.30.13: icmp_seq=4 ttl=63 time=1.44 ms
64 bytes from 172.16.30.13: icmp_seq=5 ttl=63 time=1.26 ms
64 bytes from 172.16.30.13: icmp_seq=6 ttl=63 time=1.22 ms
64 bytes from 172.16.30.13: icmp_seq=7 ttl=63 time=1.72 ms
^C
--- 172.16.30.13 ping statistics ---
7 packets transmitted, 7 received, 0% packet loss, time 6008ms
rtt min/avg/max/mdev = 1.077/1.397/1.723/0.210 ms
root@PC-2-T:~# |
```

ping depuis PC2 vers S1

```
root@PC-2-T:~# ping 172.16.30.11
PING 172.16.30.11 (172.16.30.11) 56(84) bytes of data.
64 bytes from 172.16.30.11: icmp_seq=3 ttl=254 time=1.64 ms
64 bytes from 172.16.30.11: icmp_seq=4 ttl=254 time=1.47 ms
64 bytes from 172.16.30.11: icmp_seq=5 ttl=254 time=1.38 ms
64 bytes from 172.16.30.11: icmp_seq=6 ttl=254 time=1.55 ms
64 bytes from 172.16.30.11: icmp_seq=7 ttl=254 time=1.48 ms
64 bytes from 172.16.30.11: icmp_seq=8 ttl=254 time=2.09 ms
64 bytes from 172.16.30.11: icmp_seq=9 ttl=254 time=1.63 ms
^C
--- 172.16.30.11 ping statistics ---
9 packets transmitted, 7 received, 22% packet loss, time 8049ms
rtt min/avg/max/mdev = 1.389/1.611/2.099/0.218 ms
root@PC-2-T:~# |
```

ping depuis PC2 vers S2

```
root@PC-2-T:~# ping 172.16.30.12
PING 172.16.30.12 (172.16.30.12) 56(84) bytes of data.
64 bytes from 172.16.30.12: icmp_seq=1 ttl=254 time=2.09 ms
64 bytes from 172.16.30.12: icmp_seq=2 ttl=254 time=2.29 ms
64 bytes from 172.16.30.12: icmp_seq=3 ttl=254 time=2.47 ms
64 bytes from 172.16.30.12: icmp_seq=4 ttl=254 time=2.51 ms
64 bytes from 172.16.30.12: icmp_seq=5 ttl=254 time=2.34 ms
64 bytes from 172.16.30.12: icmp_seq=6 ttl=254 time=2.19 ms
^C
--- 172.16.30.12 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5006ms
rtt min/avg/max/mdev = 2.099/2.320/2.514/0.150 ms
root@PC-2-T:~# |
```

ping depuis PC2 vers la passerelle virtuelle

```
root@PC-2-T:~# ping 172.16.20.1
PING 172.16.20.1 (172.16.20.1) 56(84) bytes of data.
64 bytes from 172.16.20.1: icmp_seq=1 ttl=255 time=1.24 ms
64 bytes from 172.16.20.1: icmp_seq=2 ttl=255 time=14.8 ms
64 bytes from 172.16.20.1: icmp_seq=3 ttl=255 time=1.38 ms
64 bytes from 172.16.20.1: icmp_seq=4 ttl=255 time=1.64 ms
64 bytes from 172.16.20.1: icmp_seq=5 ttl=255 time=1.57 ms
64 bytes from 172.16.20.1: icmp_seq=6 ttl=255 time=1.70 ms
^C
--- 172.16.20.1 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5008ms
rtt min/avg/max/mdev = 1.240/3.729/14.832/4.968 ms
root@PC-2-T:~# |
```

ping depuis PC2 vers R1

```
root@PC-2-T:~# ping 172.16.20.2
PING 172.16.20.2 (172.16.20.2) 56(84) bytes of data.
64 bytes from 172.16.20.2: icmp_seq=1 ttl=255 time=1.03 ms
64 bytes from 172.16.20.2: icmp_seq=2 ttl=255 time=1.28 ms
64 bytes from 172.16.20.2: icmp_seq=3 ttl=255 time=1.31 ms
64 bytes from 172.16.20.2: icmp_seq=4 ttl=255 time=1.12 ms
64 bytes from 172.16.20.2: icmp_seq=5 ttl=255 time=1.14 ms
64 bytes from 172.16.20.2: icmp_seq=6 ttl=255 time=1.06 ms
64 bytes from 172.16.20.2: icmp_seq=7 ttl=255 time=1.20 ms
64 bytes from 172.16.20.2: icmp_seq=8 ttl=255 time=1.14 ms
^C
--- 172.16.20.2 ping statistics ---
8 packets transmitted, 8 received, 0% packet loss, time 7009ms
rtt min/avg/max/mdev = 1.034/1.163/1.311/0.100 ms
root@PC-2-T:~#
```

ping depuis PC2 vers R2

```
root@PC-2-T:~# ping 172.16.20.3
PING 172.16.20.3 (172.16.20.3) 56(84) bytes of data.
64 bytes from 172.16.20.3: icmp_seq=1 ttl=255 time=1.05 ms
64 bytes from 172.16.20.3: icmp_seq=2 ttl=255 time=1.34 ms
64 bytes from 172.16.20.3: icmp_seq=3 ttl=255 time=1.43 ms
64 bytes from 172.16.20.3: icmp_seq=4 ttl=255 time=1.17 ms
64 bytes from 172.16.20.3: icmp_seq=5 ttl=255 time=1.29 ms
64 bytes from 172.16.20.3: icmp_seq=6 ttl=255 time=1.23 ms
^C
--- 172.16.20.3 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5006ms
rtt min/avg/max/mdev = 1.051/1.254/1.431/0.123 ms
root@PC-2-T:~# |
```


ping depuis PC2 vers R3

```
root@PC-2-T:~# ping 209.165.200.225
PING 209.165.200.225 (209.165.200.225) 56(84) bytes of data.
64 bytes from 209.165.200.225: icmp_seq=1 ttl=254 time=1.91 ms
64 bytes from 209.165.200.225: icmp_seq=2 ttl=254 time=1.74 ms
64 bytes from 209.165.200.225: icmp_seq=3 ttl=254 time=1.83 ms
64 bytes from 209.165.200.225: icmp_seq=4 ttl=254 time=1.66 ms
64 bytes from 209.165.200.225: icmp_seq=5 ttl=254 time=1.68 ms
64 bytes from 209.165.200.225: icmp_seq=6 ttl=254 time=1.66 ms
^C
--- 209.165.200.225 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5009ms
rtt min/avg/max/mdev = 1.660/1.751/1.918/0.101 ms
root@PC-2-T:~# |
```

ping depuis PC3 vers PC1

```
root@PC-3-T:~# ping 172.16.10.11
PING 172.16.10.11 (172.16.10.11) 56(84) bytes of data.
64 bytes from 172.16.10.11: icmp_seq=1 ttl=63 time=1.58 ms
64 bytes from 172.16.10.11: icmp_seq=2 ttl=63 time=1.40 ms
64 bytes from 172.16.10.11: icmp_seq=3 ttl=63 time=1.52 ms
64 bytes from 172.16.10.11: icmp_seq=4 ttl=63 time=1.37 ms
64 bytes from 172.16.10.11: icmp_seq=5 ttl=63 time=1.31 ms
64 bytes from 172.16.10.11: icmp_seq=6 ttl=63 time=1.39 ms
64 bytes from 172.16.10.11: icmp_seq=7 ttl=63 time=1.25 ms
^C
--- 172.16.10.11 ping statistics ---
7 packets transmitted, 7 received, 0% packet loss, time 6009ms
rtt min/avg/max/mdev = 1.250/1.406/1.585/0.116 ms
root@PC-3-T:~# |
```


ping depuis PC3 vers PC2

```
root@PC-3-T:~# ping 172.16.20.12
PING 172.16.20.12 (172.16.20.12) 56(84) bytes of data.
64 bytes from 172.16.20.12: icmp_seq=1 ttl=63 time=1.03 ms
64 bytes from 172.16.20.12: icmp_seq=2 ttl=63 time=1.75 ms
64 bytes from 172.16.20.12: icmp_seq=3 ttl=63 time=1.53 ms
64 bytes from 172.16.20.12: icmp_seq=4 ttl=63 time=1.47 ms
64 bytes from 172.16.20.12: icmp_seq=5 ttl=63 time=1.47 ms
64 bytes from 172.16.20.12: icmp_seq=6 ttl=63 time=1.18 ms
^C
--- 172.16.20.12 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5007ms
rtt min/avg/max/mdev = 1.032/1.408/1.754/0.239 ms
root@PC-3-T:~# |
```

ping depuis PC3 vers s1

```
root@PC-3-T:~# ping 172.16.30.11
PING 172.16.30.11 (172.16.30.11) 56(84) bytes of data.
64 bytes from 172.16.30.11: icmp_seq=1 ttl=255 time=0.946 ms
64 bytes from 172.16.30.11: icmp_seq=2 ttl=255 time=1.24 ms
64 bytes from 172.16.30.11: icmp_seq=3 ttl=255 time=1.23 ms
64 bytes from 172.16.30.11: icmp_seq=4 ttl=255 time=1.34 ms
64 bytes from 172.16.30.11: icmp_seq=5 ttl=255 time=0.995 ms
64 bytes from 172.16.30.11: icmp_seq=6 ttl=255 time=1.35 ms
^C
--- 172.16.30.11 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5006ms
rtt min/avg/max/mdev = 0.946/1.186/1.359/0.163 ms
root@PC-3-T:~# |
```

ping depuis PC3 vers s2

```
root@PC-3-T:~# ping 172.16.30.12
PING 172.16.30.12 (172.16.30.12) 56(84) bytes of data.
64 bytes from 172.16.30.12: icmp_seq=2 ttl=255 time=2.15 ms
64 bytes from 172.16.30.12: icmp_seq=3 ttl=255 time=2.12 ms
64 bytes from 172.16.30.12: icmp_seq=4 ttl=255 time=2.18 ms
64 bytes from 172.16.30.12: icmp_seq=5 ttl=255 time=2.08 ms
64 bytes from 172.16.30.12: icmp_seq=6 ttl=255 time=1.98 ms
64 bytes from 172.16.30.12: icmp_seq=7 ttl=255 time=1.89 ms
64 bytes from 172.16.30.12: icmp_seq=8 ttl=255 time=1.94 ms
^C
--- 172.16.30.12 ping statistics ---
8 packets transmitted, 7 received, 12% packet loss, time 7038ms
rtt min/avg/max/mdev = 1.893/2.052/2.183/0.115 ms
root@PC-3-T:~# |
```

ping depuis PC3 vers R1

```
root@PC-3-T:~# ping 172.16.30.2
PING 172.16.30.2 (172.16.30.2) 56(84) bytes of data.
64 bytes from 172.16.30.2: icmp_seq=1 ttl=255 time=1.58 ms
64 bytes from 172.16.30.2: icmp_seq=2 ttl=255 time=1.11 ms
64 bytes from 172.16.30.2: icmp_seq=3 ttl=255 time=1.17 ms
64 bytes from 172.16.30.2: icmp_seq=4 ttl=255 time=1.19 ms
64 bytes from 172.16.30.2: icmp_seq=5 ttl=255 time=1.28 ms
64 bytes from 172.16.30.2: icmp_seq=6 ttl=255 time=1.19 ms
64 bytes from 172.16.30.2: icmp_seq=7 ttl=255 time=1.28 ms
^C
--- 172.16.30.2 ping statistics ---
7 packets transmitted, 7 received, 0% packet loss, time 6008ms
rtt min/avg/max/mdev = 1.117/1.262/1.587/0.149 ms
root@PC-3-T:~# |
```

ping depuis PC3 vers R2

```
root@PC-3-T:~# ping 172.16.30.3
PING 172.16.30.3 (172.16.30.3) 56(84) bytes of data.
64 bytes from 172.16.30.3: icmp_seq=1 ttl=255 time=1.73 ms
64 bytes from 172.16.30.3: icmp_seq=2 ttl=255 time=1.58 ms
64 bytes from 172.16.30.3: icmp_seq=3 ttl=255 time=1.32 ms
64 bytes from 172.16.30.3: icmp_seq=4 ttl=255 time=1.37 ms
64 bytes from 172.16.30.3: icmp_seq=5 ttl=255 time=1.22 ms
64 bytes from 172.16.30.3: icmp_seq=6 ttl=255 time=1.27 ms
^C
--- 172.16.30.3 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5007ms
rtt min/avg/max/mdev = 1.221/1.417/1.739/0.188 ms
root@PC-3-T:~# |
```

ping depuis PC3 vers R3

```
root@PC-3-T:~# ping 209.165.200.225
PING 209.165.200.225 (209.165.200.225) 56(84) bytes of data.
64 bytes from 209.165.200.225: icmp_seq=1 ttl=254 time=1.37 ms
64 bytes from 209.165.200.225: icmp_seq=2 ttl=254 time=1.41 ms
64 bytes from 209.165.200.225: icmp_seq=3 ttl=254 time=1.48 ms
64 bytes from 209.165.200.225: icmp_seq=4 ttl=254 time=1.62 ms
64 bytes from 209.165.200.225: icmp_seq=5 ttl=254 time=1.86 ms
64 bytes from 209.165.200.225: icmp_seq=6 ttl=254 time=1.54 ms
^C
--- 209.165.200.225 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5008ms
rtt min/avg/max/mdev = 1.372/1.549/1.860/0.164 ms
root@PC-3-T:~# |
```

ping depuis PC3 vers la passerelle virtuelle

```
root@PC-3-T:~# ping 172.16.30.1
PING 172.16.30.1 (172.16.30.1) 56(84) bytes of data.
64 bytes from 172.16.30.1: icmp_seq=1 ttl=255 time=1.34 ms
64 bytes from 172.16.30.1: icmp_seq=2 ttl=255 time=1.34 ms
64 bytes from 172.16.30.1: icmp_seq=3 ttl=255 time=1.73 ms
64 bytes from 172.16.30.1: icmp_seq=4 ttl=255 time=1.44 ms
64 bytes from 172.16.30.1: icmp_seq=5 ttl=255 time=1.44 ms
64 bytes from 172.16.30.1: icmp_seq=6 ttl=255 time=1.58 ms
64 bytes from 172.16.30.1: icmp_seq=7 ttl=255 time=1.50 ms
^C
--- 172.16.30.1 ping statistics ---
7 packets transmitted, 7 received, 0% packet loss, time 6009ms
rtt min/avg/max/mdev = 1.340/1.485/1.739/0.139 ms
root@PC-3-T:~# |
```

show etherchannel summary sur S1 :

```
S1#sh eth sum
Flags:  D - down          P - bundled in port-channel
        I - stand-alone  s - suspended
        H - Hot-standby (LACP only)
        R - Layer3       S - Layer2
        U - in use       f - failed to allocate aggregator

        M - not in use, minimum links not met
        u - unsuitable for bundling
        w - waiting to be aggregated
        d - default port

Number of channel-groups in use: 1
Number of aggregators:          1

Group  Port-channel  Protocol    Ports
-----+-----+-----+-----
1      Po1(SU)           PAgP        Fa0/1(P)   Fa0/2(P)

S1#
```

show etherchannel summary sur S2 :

```
S2#sh eth sum
Flags:  D - down          P - in port-channel
        I - stand-alone  s - suspended
        H - Hot-standby (LACP only)
        R - Layer3       S - Layer2
        u - unsuitable for bundling
        U - in use       f - failed to allocate aggregator
        d - default port

Number of channel-groups in use: 1
Number of aggregators:          1

Group  Port-channel  Protocol    Ports
-----+-----+-----+-----
1      Po1(SU)           PAgP        Fa0/1(Pd)  Fa0/2(P)

S2#
```

show interfaces trunk sur S1 :

```
S1#show interfaces trunk

Port      Mode      Encapsulation  Status        Native vlan
Fa0/5     on        802.1q         trunking      99
Po1       on        802.1q         trunking      99

Port      Vlans allowed on trunk
Fa0/5     1-4094
Po1       1-4094

Port      Vlans allowed and active in management domain
Fa0/5     1,10,20,30,40,90,99-100,200,333,999-1000
Po1       1,10,20,30,40,90,99-100,200,333,999-1000

Port      Vlans in spanning tree forwarding state and not pruned
Fa0/5     1,10,20,30,40,90,99-100,200,333,999-1000
Po1       1,10,20,30,40,90,99-100,200,333,999-1000
S1#
```

show interfaces trunk sur S2 :

```
S2#show interfaces trunk

Port      Mode      Encapsulation  Status        Native vlan
Fa0/5     on        802.1q         trunking      99
Po1       on        802.1q         trunking      99

Port      Vlans allowed on trunk
Fa0/5     1-4094
Po1       1-4094

Port      Vlans allowed and active in management domain
Fa0/5     1,10,20,30,90,99
Po1       1,10,20,30,90,99

Port      Vlans in spanning tree forwarding state and not pruned
Fa0/5     1,10,20,30,90,99
Po1       1,10,20,30,90,99
S2#
```

show vlan brief sur S1 :

```
S1#show vlan brief
```

VLAN	Name	Status	Ports
1	default	active	
10	R&D	active	Fa0/6
20	STAFF	active	
30	MGNT	active	
40	Sales	active	
90	TRASH	active	Fa0/3, Fa0/4, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gi0/1, Gi0/2
99	NATIF	active	
100	team100	active	
200	team200	active	
333	VLAN0333	active	
999	ParkingLot	active	
1000	Native	active	
1002	fddi-default	act/unsup	
1003	token-ring-default	act/unsup	
1004	fddinet-default	act/unsup	
1005	trnet-default	act/unsup	

```
S1#
```

show vlan brief sur S2 :

```
S2#show vlan brief
```

VLAN	Name	Status	Ports
1	default	active	
10	VLAN0010	active	
20	VLAN0020	active	Fa0/24
30	VLAN0030	active	Fa0/18
90	VLAN0090	active	Fa0/3, Fa0/4, Fa0/6, Fa0/7 Fa0/8, Fa0/9, Fa0/10, Fa0/11 Fa0/12, Fa0/13, Fa0/14, Fa0/15 Fa0/16, Fa0/17, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23
99	VLAN0099	active	
1002	fddi-default	act/unsup	
1003	token-ring-default	act/unsup	
1004	fddinet-default	act/unsup	
1005	trnet-default	act/unsup	

```
S2#
```

sh ip int br sur S1 :

```
S1#sh ip int br
Interface      IP-Address      OK? Method Status      Protocol
Vlan1          unassigned      YES unset    administratively down down
Vlan10         unassigned      YES manual  administratively down down
Vlan30         172.16.30.11   YES manual  up          up
FastEthernet0/1 unassigned      YES unset    up          up
FastEthernet0/2 unassigned      YES unset    up          up
FastEthernet0/3 unassigned      YES unset    administratively down down
FastEthernet0/4 unassigned      YES unset    administratively down down
FastEthernet0/5 unassigned      YES unset    up          up
FastEthernet0/6 unassigned      YES unset    up          up
FastEthernet0/7 unassigned      YES unset    administratively down down
FastEthernet0/8 unassigned      YES unset    administratively down down
FastEthernet0/9 unassigned      YES unset    administratively down down
FastEthernet0/10 unassigned      YES unset    administratively down down
FastEthernet0/11 unassigned      YES unset    administratively down down
FastEthernet0/12 unassigned      YES unset    administratively down down
FastEthernet0/13 unassigned      YES unset    administratively down down
FastEthernet0/14 unassigned      YES unset    administratively down down
FastEthernet0/15 unassigned      YES unset    administratively down down
FastEthernet0/16 unassigned      YES unset    administratively down down
FastEthernet0/17 unassigned      YES unset    administratively down down
FastEthernet0/18 unassigned      YES unset    administratively down down
FastEthernet0/19 unassigned      YES unset    administratively down down
FastEthernet0/20 unassigned      YES unset    administratively down down
FastEthernet0/21 unassigned      YES unset    administratively down down
FastEthernet0/22 unassigned      YES unset    administratively down down
FastEthernet0/23 unassigned      YES unset    administratively down down
FastEthernet0/24 unassigned      YES unset    administratively down down
GigabitEthernet0/1 unassigned      YES unset    administratively down down
GigabitEthernet0/2 unassigned      YES unset    administratively down down
Port-channel1  unassigned      YES unset    up          up
S1#
```


sh ip int br sur S2:

```
S2#sh ip int br
Interface IP-Address OK? Method Status Protocol
Vlan1 unassigned YES unset administratively down down
Vlan10 unassigned YES manual administratively down down
Vlan30 172.16.30.12 YES manual up up
FastEthernet0/1 unassigned YES unset up up
FastEthernet0/2 unassigned YES unset up up
FastEthernet0/3 unassigned YES unset administratively down down
FastEthernet0/4 unassigned YES unset administratively down down
FastEthernet0/5 unassigned YES unset up up
FastEthernet0/6 unassigned YES unset administratively down down
FastEthernet0/7 unassigned YES unset administratively down down
FastEthernet0/8 unassigned YES unset administratively down down
FastEthernet0/9 unassigned YES unset administratively down down
FastEthernet0/10 unassigned YES unset administratively down down
FastEthernet0/11 unassigned YES unset administratively down down
FastEthernet0/12 unassigned YES unset administratively down down
FastEthernet0/13 unassigned YES unset administratively down down
FastEthernet0/14 unassigned YES unset administratively down down
FastEthernet0/15 unassigned YES unset administratively down down
FastEthernet0/16 unassigned YES unset administratively down down
FastEthernet0/17 unassigned YES unset administratively down down
FastEthernet0/18 unassigned YES unset up up
FastEthernet0/19 unassigned YES unset administratively down down
FastEthernet0/20 unassigned YES unset administratively down down
FastEthernet0/21 unassigned YES unset administratively down down
FastEthernet0/22 unassigned YES unset administratively down down
FastEthernet0/23 unassigned YES unset administratively down down
FastEthernet0/24 unassigned YES unset up up
Port-channel1 unassigned YES unset up up
S2#
```

ifconfig sur pc1 :

```
root@PC-1-T:~# ifconfig
eth0      Link encap:Ethernet  HWaddr 7e:f5:43:c5:1a:44
          inet addr:172.16.10.11 Bcast:0.0.0.0 Mask:255.255.255.0
          UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
          RX packets:105689 errors:0 dropped:0 overruns:0 frame:0
          TX packets:1017 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:6668986 (6.6 MB) TX bytes:219743 (219.7 KB)

lo        Link encap:Local Loopback
          inet addr:127.0.0.1 Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING MTU:65536 Metric:1
          RX packets:35 errors:0 dropped:0 overruns:0 frame:0
          TX packets:35 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:3808 (3.8 KB) TX bytes:3808 (3.8 KB)

root@PC-1-T:~# |
```

ifconfig sur pc2 :

```
root@PC-2-T:~# ifconfig
eth0      Link encap:Ethernet  HWaddr 2e:37:b3:ea:b8:6e
          inet addr:172.16.20.12 Bcast:0.0.0.0 Mask:255.255.255.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:107931 errors:0 dropped:2 overruns:0 frame:0
          TX packets:2606 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:6869212 (6.8 MB)  TX bytes:254720 (254.7 KB)

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:65536  Metric:1
          RX packets:8 errors:0 dropped:0 overruns:0 frame:0
          TX packets:8 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:668 (668.0 B)  TX bytes:668 (668.0 B)

root@PC-2-T:~# |
```

ifconfig sur pc3 :

```
root@PC-3-T:~# ifconfig
eth0      Link encap:Ethernet  HWaddr ae:1a:c9:cf:85:32
          inet addr:172.16.30.13 Bcast:0.0.0.0 Mask:255.255.255.0
          UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
          RX packets:105934 errors:0 dropped:0 overruns:0 frame:0
          TX packets:626 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:6678290 (6.6 MB)  TX bytes:185216 (185.2 KB)

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:65536  Metric:1
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0
          TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:0 (0.0 B)  TX bytes:0 (0.0 B)

root@PC-3-T:~# |
```

sh ip inter br sur R1

```
R1#sh ip inter br
Interface          IP-Address      OK? Method Status      Protocol
GigabitEthernet0/0/0  unassigned      YES unset    up          up
Gi0/0/0.10         172.16.10.2     YES manual    up          up
Gi0/0/0.20         172.16.20.2     YES manual    up          up
Gi0/0/0.30         172.16.30.2     YES manual    up          up
GigabitEthernet0/0/1  10.10.13.1      YES manual    up          up
GigabitEthernet0/0/2  unassigned      YES unset    administratively down down
GigabitEthernet0      unassigned      YES unset    administratively down down
R1#
```

sh ip route sur R1

```
R1#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is 10.10.13.2 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.13.2
      10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      10.10.13.0/30 is directly connected, GigabitEthernet0/0/1
L      10.10.13.1/32 is directly connected, GigabitEthernet0/0/1
      172.16.0.0/16 is variably subnetted, 6 subnets, 2 masks
C      172.16.10.0/24 is directly connected, GigabitEthernet0/0/0.10
L      172.16.10.2/32 is directly connected, GigabitEthernet0/0/0.10
C      172.16.20.0/24 is directly connected, GigabitEthernet0/0/0.20
L      172.16.20.2/32 is directly connected, GigabitEthernet0/0/0.20
C      172.16.30.0/24 is directly connected, GigabitEthernet0/0/0.30
L      172.16.30.2/32 is directly connected, GigabitEthernet0/0/0.30
R1#
```

sh standby brief sur R1

```

R1#sh standby brief
          P indicates configured to preempt.
          |
Interface  Grp  Pri  P State   Active      Standby      Virtual IP
Gi0/0/0.10 10   110 P Active  local       172.16.10.3  172.16.10.1
Gi0/0/0.20 20   100 Standby  172.16.20.3 local        172.16.20.1
Gi0/0/0.30 30   110 P Active  local       172.16.30.3  172.16.30.1
R1#
```

sh ip inter br sur R2

```

R2#sh ip inter br
          User Name
Interface  IP-Address  OK? Method Status      Protocol
GigabitEthernet0/0/0 unassigned  YES unset  up          up
Gi0/0/0.10 172.16.10.3 YES manual up          up
Gi0/0/0.20 172.16.20.3 YES manual up          up
Gi0/0/0.30 172.16.30.3 YES manual up          up
GigabitEthernet0/0/1 10.10.23.1 YES manual up          up
GigabitEthernet0/0/2 unassigned  YES unset  administratively down down
GigabitEthernet0 unassigned  YES unset  administratively down down
R2#
```

sh ip route sur R2

```

R2#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is 10.10.23.2 to network 0.0.0.0

S* 0.0.0.0/0 [1/0] via 10.10.23.2
   10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C   10.10.23.0/30 is directly connected, GigabitEthernet0/0/1
L   10.10.23.1/32 is directly connected, GigabitEthernet0/0/1
   172.16.0.0/16 is variably subnetted, 6 subnets, 2 masks
C   172.16.10.0/24 is directly connected, GigabitEthernet0/0/0.10
L   172.16.10.3/32 is directly connected, GigabitEthernet0/0/0.10
C   172.16.20.0/24 is directly connected, GigabitEthernet0/0/0.20
L   172.16.20.3/32 is directly connected, GigabitEthernet0/0/0.20
C   172.16.30.0/24 is directly connected, GigabitEthernet0/0/0.30
L   172.16.30.3/32 is directly connected, GigabitEthernet0/0/0.30
R2#
```

sh ip dhcp binding sur R2

c'est R3 qui gère l'attribution des adresses IP pour tout mon réseau, et non R1 ou R2. Alors ce résultat est normal

```
via natto, receive
R2#sh ip dhcp binding
Bindings from all pools not associated with VRF:
IP address      Client-ID/      Lease expiration        Type      State      Interface
                  Hardware address/
                  User name
R2#
```

sh standby brief sur R2

```
R2#sh standby brief
                P indicates configured to preempt.
                |
Interface      Grp  Pri  P  State  Active        Standby        Virtual IP
Gi0/0/0.10    10   100      Standby  172.16.10.2    local          172.16.10.1
Gi0/0/0.20    20   110  P  Active  local          172.16.20.2    172.16.20.1
Gi0/0/0.30    30   100      Standby  172.16.30.2    local          172.16.30.1
R2#
```

sh ip dhcp binding sur R3

```
R3#sh ip dhcp binding
Bindings from all pools not associated with VRF:
IP address      Client-ID/      Lease expiration        Type
                  Hardware address/
                  User name
172.16.10.11     017e.f543.c51a.44    Jan 03 2006 03:08 PM    Automatic
172.16.10.12     01de.f3eb.01fe.57    Jan 04 2006 02:13 PM    Automatic
172.16.20.11     015a.6e68.fd81.00    Jan 03 2006 02:51 PM    Automatic
172.16.20.12     012e.37b3.eab8.6e    Jan 04 2006 01:28 PM    Automatic
172.16.20.13     0152.1533.f0d8.2f    Jan 04 2006 02:13 PM    Automatic
172.16.30.13     01ae.1ac9.cf85.32    Jan 04 2006 01:38 PM    Automatic
172.16.30.14     01ee.4d2c.d9d9.f9    Jan 04 2006 02:13 PM    Automatic
R3#
```

sh ip inter br sur R3

```
R3#sh ip inter br
Interface      IP-Address      OK? Method Status      Protocol
FastEthernet0/0 10.10.13.2      YES manual up          up
FastEthernet0/1 10.10.23.2      YES manual up          up
Serial0/0/0      unassigned      YES unset administratively down down
Serial0/0/1      unassigned      YES unset administratively down down
FastEthernet0/1/0 unassigned      YES unset up          down
FastEthernet0/1/1 unassigned      YES unset up          down
FastEthernet0/1/2 unassigned      YES unset up          down
FastEthernet0/1/3 unassigned      YES unset up          down
Loopback0       209.165.200.225 YES manual up          up
Vlan1           unassigned      YES unset up          down
R3#
```

sh ip interface sur R3 :

```
R3#sh ip interface
FastEthernet0/0 is up, line protocol is up
  Internet address is 10.10.13.2/30
  Broadcast address is 255.255.255.255
  Address determined by setup command
  MTU is 1500 bytes
  Helper address is not set
  Directed broadcast forwarding is disabled
  Outgoing access list is not set
  Inbound access list is not set
  Proxy ARP is enabled
  Local Proxy ARP is disabled
  Security level is default
  Split horizon is enabled
  ICMP redirects are always sent
  ICMP unreachable are always sent
  ICMP mask replies are never sent
  IP fast switching is enabled
  IP fast switching on the same interface is disabled
  IP Flow switching is disabled
  IP CEF switching is enabled
  IP CEF switching turbo vector
  IP multicast fast switching is enabled
  IP multicast distributed fast switching is disabled
  IP route-cache flags are Fast, CEF
  Router Discovery is disabled
  IP output packet accounting is disabled
  IP access violation accounting is disabled
  TCP/IP header compression is disabled
  RTP/IP header compression is disabled
  Policy routing is disabled
  Network address translation is disabled
  BGP Policy Mapping is disabled
  Input features: MCI Check
  WCCP Redirect outbound is disabled
  WCCP Redirect inbound is disabled
  WCCP Redirect exclude is disabled
FastEthernet0/1 is up, line protocol is up

R3#|
```


sh ip route sur R3 :

```
R3#sh ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       + - replicated route, % - next hop override

Gateway of last resort is not set

  10.0.0.0/8 is variably subnetted, 4 subnets, 2 masks
C       10.10.13.0/30 is directly connected, FastEthernet0/0
L       10.10.13.2/32 is directly connected, FastEthernet0/0
C       10.10.23.0/30 is directly connected, FastEthernet0/1
L       10.10.23.2/32 is directly connected, FastEthernet0/1
  172.16.0.0/24 is subnetted, 3 subnets
S       172.16.10.0 [1/0] via 10.10.13.1
S       172.16.20.0 [1/0] via 10.10.23.1
S       172.16.30.0 [1/0] via 10.10.13.1
  209.165.200.0/24 is variably subnetted, 2 subnets, 2 masks
C       209.165.200.224/27 is directly connected, Loopback0
L       209.165.200.225/32 is directly connected, Loopback0
R3#
```

sh ip route | begin Gateway sur R1 :

```
R1#sh ip route | begin Gateway
Gateway of last resort is 10.10.13.2 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.13.2
  10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       10.10.13.0/30 is directly connected, GigabitEthernet0/0/1
L       10.10.13.1/32 is directly connected, GigabitEthernet0/0/1
  172.16.0.0/16 is variably subnetted, 6 subnets, 2 masks
C       172.16.10.0/24 is directly connected, GigabitEthernet0/0/0.10
L       172.16.10.2/32 is directly connected, GigabitEthernet0/0/0.10
C       172.16.20.0/24 is directly connected, GigabitEthernet0/0/0.20
L       172.16.20.2/32 is directly connected, GigabitEthernet0/0/0.20
C       172.16.30.0/24 is directly connected, GigabitEthernet0/0/0.30
L       172.16.30.2/32 is directly connected, GigabitEthernet0/0/0.30
R1#
```

sh ip route | begin Gateway sur R2 :

```
R2#sh ip route | begin Gateway
Gateway of last resort is 10.10.23.2 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.23.2
      10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      10.10.23.0/30 is directly connected, GigabitEthernet0/0/1
L      10.10.23.1/32 is directly connected, GigabitEthernet0/0/1
      172.16.0.0/16 is variably subnetted, 6 subnets, 2 masks
C      172.16.10.0/24 is directly connected, GigabitEthernet0/0/0.10
L      172.16.10.3/32 is directly connected, GigabitEthernet0/0/0.10
C      172.16.20.0/24 is directly connected, GigabitEthernet0/0/0.20
L      172.16.20.3/32 is directly connected, GigabitEthernet0/0/0.20
C      172.16.30.0/24 is directly connected, GigabitEthernet0/0/0.30
L      172.16.30.3/32 is directly connected, GigabitEthernet0/0/0.30
R2#
```

sh ip route | begin Gateway sur R3 :

```
R3#sh ip route | begin Gateway
Gateway of last resort is not set

      10.0.0.0/8 is variably subnetted, 4 subnets, 2 masks
C      10.10.13.0/30 is directly connected, FastEthernet0/0
L      10.10.13.2/32 is directly connected, FastEthernet0/0
C      10.10.23.0/30 is directly connected, FastEthernet0/1
L      10.10.23.2/32 is directly connected, FastEthernet0/1
      172.16.0.0/24 is subnetted, 3 subnets
S      172.16.10.0 [1/0] via 10.10.13.1
S      172.16.20.0 [1/0] via 10.10.23.1
S      172.16.30.0 [1/0] via 10.10.13.1
      209.165.200.0/24 is variably subnetted, 2 subnets, 2 masks
C      209.165.200.224/27 is directly connected, Loopback0
L      209.165.200.225/32 is directly connected, Loopback0
R3#
```

sh ipv6 route | begin C sur R1 :

```
R1#sh ipv6 route | begin C
Codes: C - Connected, L - Local, S - Static, U - Per-user Static route
       B - BGP, R - RIP, H - NHRP, I1 - ISIS L1
       I2 - ISIS L2, IA - ISIS interarea, IS - ISIS summary, D - EIGRP
       EX - EIGRP external, ND - ND Default, NDp - ND Prefix, DCE - Destination
       NDr - Redirect, RL - RPL, O - OSPF Intra, OI - OSPF Inter
       OE1 - OSPF ext 1, OE2 - OSPF ext 2, ON1 - OSPF NSSA ext 1
       ON2 - OSPF NSSA ext 2, a - Application
L   FF00::/8 [0/0]
    via Null0, receive
```

sh ip route static sur R1 :

```
R1#sh ip route static
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is 10.10.13.2 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.13.2
R1#
```

sh ip route static sur R2 :

```
R2#sh ip route static
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is 10.10.23.2 to network 0.0.0.0

S*    0.0.0.0/0 [1/0] via 10.10.23.2
R2#
```

sh ip route static sur R3 :

```
R3#sh ip route static
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       + - replicated route, % - next hop override

Gateway of last resort is not set

      172.16.0.0/24 is subnetted, 3 subnets
S       172.16.10.0 [1/0] via 10.10.13.1
S       172.16.20.0 [1/0] via 10.10.23.1
S       172.16.30.0 [1/0] via 10.10.13.1
R3#|
```

traceroute 172.16.10.1 depuis pc1 :

```
root@PC-1-T:~# traceroute 172.16.10.1
traceroute to 172.16.10.1 (172.16.10.1), 30 hops max, 60 byte packets
 1  172.16.10.2 (172.16.10.2)  5.622 ms * *
root@PC-1-T:~#
```

traceroute 209.165.200.225 depuis pc1 :

```
root@PC-1-T:~# traceroute 209.165.200.225
traceroute to 209.165.200.225 (209.165.200.225), 30 hops max, 60 byte packets
 1  172.16.10.2 (172.16.10.2)  1.349 ms  1.321 ms  1.464 ms
 2  10.10.13.2 (10.10.13.2)  2.945 ms * *
root@PC-1-T:~#
```

traceroute 172.16.20.3 depuis pc1 :

```
root@PC-1-T:~# traceroute 172.16.20.3
traceroute to 172.16.20.3 (172.16.20.3), 30 hops max, 60 byte packets
 1  172.16.10.2 (172.16.10.2)  0.791 ms  0.778 ms  0.779 ms
 2  172.16.20.3 (172.16.20.3)  1.350 ms * *
root@PC-1-T:~# |
```

ping depuis PC1 vers la passerelle virtuelle avant enlever le câble

```
root@PC-1-T:~# ping 172.16.10.1
PING 172.16.10.1 (172.16.10.1) 56(84) bytes of data.
64 bytes from 172.16.10.1: icmp_seq=1 ttl=255 time=1.33 ms
64 bytes from 172.16.10.1: icmp_seq=2 ttl=255 time=1.15 ms
64 bytes from 172.16.10.1: icmp_seq=3 ttl=255 time=1.44 ms
64 bytes from 172.16.10.1: icmp_seq=4 ttl=255 time=1.31 ms
64 bytes from 172.16.10.1: icmp_seq=5 ttl=255 time=1.56 ms
64 bytes from 172.16.10.1: icmp_seq=6 ttl=255 time=1.76 ms
64 bytes from 172.16.10.1: icmp_seq=7 ttl=255 time=1.60 ms
64 bytes from 172.16.10.1: icmp_seq=8 ttl=255 time=1.43 ms
64 bytes from 172.16.10.1: icmp_seq=9 ttl=255 time=1.40 ms
64 bytes from 172.16.10.1: icmp_seq=10 ttl=255 time=1.50 ms
64 bytes from 172.16.10.1: icmp_seq=11 ttl=255 time=1.36 ms
```

ping depuis PC1 vers la passerelle virtuelle avant et après enlever le câble

```
root@PC-1-T:~# ping 172.16.10.1
PING 172.16.10.1 (172.16.10.1) 56(84) bytes of data.
64 bytes from 172.16.10.1: icmp_seq=1 ttl=255 time=1.33 ms
64 bytes from 172.16.10.1: icmp_seq=2 ttl=255 time=1.15 ms
64 bytes from 172.16.10.1: icmp_seq=3 ttl=255 time=1.44 ms
64 bytes from 172.16.10.1: icmp_seq=4 ttl=255 time=1.31 ms
64 bytes from 172.16.10.1: icmp_seq=5 ttl=255 time=1.56 ms
64 bytes from 172.16.10.1: icmp_seq=6 ttl=255 time=1.76 ms
64 bytes from 172.16.10.1: icmp_seq=7 ttl=255 time=1.60 ms
64 bytes from 172.16.10.1: icmp_seq=8 ttl=255 time=1.43 ms
64 bytes from 172.16.10.1: icmp_seq=9 ttl=255 time=1.40 ms
64 bytes from 172.16.10.1: icmp_seq=10 ttl=255 time=1.50 ms
64 bytes from 172.16.10.1: icmp_seq=11 ttl=255 time=1.36 ms
64 bytes from 172.16.10.1: icmp_seq=22 ttl=255 time=1.41 ms
64 bytes from 172.16.10.1: icmp_seq=23 ttl=255 time=1.48 ms
64 bytes from 172.16.10.1: icmp_seq=24 ttl=255 time=1.56 ms
64 bytes from 172.16.10.1: icmp_seq=25 ttl=255 time=1.66 ms
64 bytes from 172.16.10.1: icmp_seq=26 ttl=255 time=1.55 ms
64 bytes from 172.16.10.1: icmp_seq=27 ttl=255 time=1.47 ms
64 bytes from 172.16.10.1: icmp_seq=28 ttl=255 time=1.66 ms
64 bytes from 172.16.10.1: icmp_seq=29 ttl=255 time=1.65 ms
64 bytes from 172.16.10.1: icmp_seq=30 ttl=255 time=1.63 ms
64 bytes from 172.16.10.1: icmp_seq=31 ttl=255 time=1.65 ms
64 bytes from 172.16.10.1: icmp_seq=32 ttl=255 time=1.49 ms
64 bytes from 172.16.10.1: icmp_seq=33 ttl=255 time=1.62 ms
64 bytes from 172.16.10.1: icmp_seq=34 ttl=255 time=1.65 ms
64 bytes from 172.16.10.1: icmp_seq=35 ttl=255 time=1.47 ms
64 bytes from 172.16.10.1: icmp_seq=36 ttl=255 time=1.51 ms
64 bytes from 172.16.10.1: icmp_seq=37 ttl=255 time=1.66 ms
64 bytes from 172.16.10.1: icmp_seq=38 ttl=255 time=1.56 ms
64 bytes from 172.16.10.1: icmp_seq=39 ttl=255 time=1.48 ms
64 bytes from 172.16.10.1: icmp_seq=40 ttl=255 time=1.52 ms
64 bytes from 172.16.10.1: icmp_seq=41 ttl=255 time=1.50 ms
64 bytes from 172.16.10.1: icmp_seq=42 ttl=255 time=1.79 ms
64 bytes from 172.16.10.1: icmp_seq=43 ttl=255 time=1.59 ms
64 bytes from 172.16.10.1: icmp_seq=44 ttl=255 time=1.62 ms
64 bytes from 172.16.10.1: icmp_seq=45 ttl=255 time=1.39 ms
64 bytes from 172.16.10.1: icmp_seq=46 ttl=255 time=1.69 ms
64 bytes from 172.16.10.1: icmp_seq=47 ttl=255 time=1.80 ms
64 bytes from 172.16.10.1: icmp_seq=48 ttl=255 time=1.41 ms
^C
--- 172.16.10.1 ping statistics ---
48 packets transmitted, 38 received, 20% packet loss, time 47300ms
rtt min/avg/max/mdev = 1.154/1.539/1.808/0.143 ms
root@PC-1-T:~# |
```

traceroute 172.16.10.1 sur pc1 qui passe par R2 après reconnecter le câble

```
root@PC-1-T:~# traceroute 172.16.10.1
traceroute to 172.16.10.1 (172.16.10.1), 30 hops max, 60 byte packets
 1  172.16.10.2 (172.16.10.2)  1.547 ms * *
root@PC-1-T:~# |
```