

Regional Infrastructure Condition Assessment — Full Technical Report

Prepared by Office of Infrastructure Planning

Section 1: Findings

Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Reservoir storage across the district ended the water year at 78 percent of capacity. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates.

Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Reservoir storage across the district ended the water year at 78 percent of capacity. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates.

Reservoir storage across the district ended the water year at 78 percent of capacity. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Reservoir storage across the district ended the water year at 78 percent of capacity. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points.

Reservoir storage across the district ended the water year at 78 percent of capacity. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Reservoir storage across the district ended the water year at 78 percent of capacity. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points.

Reservoir storage across the district ended the water year at 78 percent of capacity. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates.

Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates.

Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Lead service

line replacement reached 2,300 households, ahead of the consent decree schedule. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain.

Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule.

Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Reservoir storage across the district ended the water year at 78 percent of capacity. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration.

Section 2: Analysis

Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Reservoir storage across the district ended the water year at 78 percent of capacity. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain.

The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Reservoir storage across the district ended the water year at 78 percent of capacity. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain.

Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance.

Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. Reservoir storage across the district ended the water year at 78 percent of capacity. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule.

Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. Water quality sampling met all federal and state standards at 99.7 percent of

monitoring points. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain.

Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance.

The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Reservoir storage across the district ended the water year at 78 percent of capacity. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Reservoir storage across the district ended the water year at 78 percent of capacity.

The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. Reservoir storage across the district ended the water year at 78 percent of capacity.

Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates.

Section 3: Methodology

Reservoir storage across the district ended the water year at 78 percent of capacity. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Reservoir storage across the district ended the water year at 78 percent of capacity. Reservoir storage across the district ended the water year at 78 percent of capacity. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration.

The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Reservoir storage across the district ended the water year at 78 percent of capacity. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points.

Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Drought contingency triggers were not activated this year, though long-range forecasts remain

uncertain. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points.

The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates.

Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Reservoir storage across the district ended the water year at 78 percent of capacity. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Reservoir storage across the district ended the water year at 78 percent of capacity.

Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Reservoir storage across the district ended the water year at 78 percent of capacity. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration.

Reservoir storage across the district ended the water year at 78 percent of capacity. Drought contingency triggers were not activated this year, though long-range forecasts remain uncertain. Reservoir storage across the district ended the water year at 78 percent of capacity. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Reservoir storage across the district ended the water year at 78 percent of capacity.

Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points. Groundwater extraction declined 12 percent following implementation of the sustainable yield ordinance. Reservoir storage across the district ended the water year at 78 percent of capacity. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Water quality sampling met all federal and state standards at 99.7 percent of monitoring points.

Reservoir storage across the district ended the water year at 78 percent of capacity. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule. Reservoir storage across the district ended the water year at 78 percent of capacity. The treatment plant expansion added 40 million gallons per day of capacity with membrane filtration. Per-capita residential consumption fell to 82 gallons per day, driven by turf replacement rebates. Lead service line replacement reached 2,300 households, ahead of the consent decree schedule.

Section 4: Regional Detail

The drip tray and its grate are dishwasher safe; the portafilter basket is not. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The drip tray and its grate are dishwasher safe; the portafilter basket is not. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Warranty coverage excludes damage caused by third-party descaling agents. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Descale the machine every two months in hard water areas using the supplied citric solution. The drip tray and its grate are dishwasher safe; the portafilter basket is not. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler.

The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Warranty coverage excludes damage caused by third-party descaling agents. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Preheat the group head by flushing hot water for three seconds before locking in the portafilter.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The drip tray and its grate are dishwasher safe; the portafilter basket is not. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The drip tray and its grate are dishwasher safe; the portafilter basket is not.

Descale the machine every two months in hard water areas using the supplied citric solution. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Descale the machine every two months in hard water areas using the supplied citric solution. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Warranty coverage excludes damage caused by third-party descaling agents.

If the pump runs but no water flows, check that the reservoir valve is seated correctly. Descale the machine every two months in hard water areas using the supplied citric solution. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Descale the machine every two months in hard water areas using the supplied citric solution. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Warranty coverage excludes damage caused by third-party descaling agents.

Descale the machine every two months in hard water areas using the supplied citric solution. The drip tray and its grate are dishwasher safe; the portafilter basket is not. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

Section 5: Appendix

Allow the optical tube thirty minutes to reach ambient temperature before observing. Firmware updates for the hand controller are distributed through the vendor website. Store the corrector plate with the dust cover fitted and desiccant in the case. Store the corrector plate with the dust cover fitted and desiccant in the case. Store the corrector plate with the dust cover fitted and desiccant in the case. Allow the optical tube thirty minutes to reach ambient temperature before observing.

Never point the telescope at the sun without a certified full-aperture solar filter. The equatorial mount requires polar alignment within one degree for accurate tracking. Collimate the primary mirror before each session using the supplied laser tool. Firmware updates for the hand controller are distributed through the vendor website. Allow the optical tube thirty minutes to reach ambient temperature before observing. Collimate the primary mirror before each session using the supplied laser tool.

Collimate the primary mirror before each session using the supplied laser tool. Store the corrector plate with the dust cover fitted and desiccant in the case. Store the corrector plate with the dust cover fitted and desiccant in the case. The equatorial mount requires polar alignment within one degree for accurate tracking. Never point the telescope at the sun without a certified full-aperture solar filter. Allow the optical tube thirty minutes to reach ambient temperature before observing.

Collimate the primary mirror before each session using the supplied laser tool. Collimate the primary mirror before each session using the supplied laser tool. Store the corrector plate with the dust cover fitted and desiccant in the case. Firmware updates for the hand controller are distributed through the vendor website. Never point the telescope at the sun without a certified full-aperture solar filter. Firmware updates for the hand controller are distributed through the vendor website.

Balance the tube in both axes before engaging the motor drives. Store the corrector plate with the dust cover fitted and desiccant in the case. The equatorial mount requires polar alignment within one degree for accurate tracking. Balance the tube in both axes before engaging the motor drives. Allow the optical tube thirty minutes to reach ambient temperature before observing. Store the corrector plate with the dust cover fitted and desiccant in the case.

The equatorial mount requires polar alignment within one degree for accurate tracking. Collimate the primary mirror before each session using the supplied laser tool. Never point the telescope at the sun without a certified full-aperture solar filter. Allow the optical tube thirty minutes to reach ambient temperature before observing. Allow the optical tube thirty minutes to reach ambient temperature before observing. The equatorial mount requires polar alignment within one degree for accurate tracking.

Never point the telescope at the sun without a certified full-aperture solar filter. Collimate the primary mirror before each session using the supplied laser tool. The equatorial mount requires polar alignment within one degree for accurate tracking. The equatorial mount requires polar alignment within one degree for accurate tracking. The equatorial mount requires polar alignment within one degree for accurate tracking. Balance the tube in both axes before engaging the motor drives.

The equatorial mount requires polar alignment within one degree for accurate tracking. Allow the optical tube thirty minutes to reach ambient temperature before observing. Collimate the primary mirror before each session using the supplied laser tool. The equatorial mount requires polar alignment within one degree for accurate tracking. Allow the optical tube thirty minutes to reach ambient temperature before observing. The equatorial mount requires polar alignment within one degree for accurate tracking.

Allow the optical tube thirty minutes to reach ambient temperature before observing. Collimate the primary mirror before each session using the supplied laser tool. The equatorial mount requires polar alignment within one degree for accurate tracking. Never point the telescope at the sun without a certified full-aperture solar filter. Collimate the primary mirror before each session using the supplied

laser tool. Never point the telescope at the sun without a certified full-aperture solar filter.

Section 6: Findings

The drip tray and its grate are dishwasher safe; the portafilter basket is not. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Warranty coverage excludes damage caused by third-party descaling agents.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Warranty coverage excludes damage caused by third-party descaling agents. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

Descal the machine every two months in hard water areas using the supplied citric solution. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Descal the machine every two months in hard water areas using the supplied citric solution. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler.

The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The drip tray and its grate are dishwasher safe; the portafilter basket is not. The drip tray and its grate are dishwasher safe; the portafilter basket is not.

Warranty coverage excludes damage caused by third-party descaling agents. Warranty coverage excludes damage caused by third-party descaling agents. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. If the pump runs but no water flows, check that the reservoir valve is seated correctly. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Warranty coverage excludes damage caused by third-party descaling agents.

The drip tray and its grate are dishwasher safe; the portafilter basket is not. Descal the machine every two months in hard water areas using the supplied citric solution. Warranty coverage excludes damage caused by third-party descaling agents. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Descal the machine every two months in hard water areas using the supplied citric solution.

Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The drip tray and its grate are dishwasher safe; the portafilter basket is not. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Warranty coverage excludes damage caused by third-party descaling agents. Warranty coverage excludes damage caused by third-party descaling agents. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The drip tray and its grate are dishwasher safe; the portafilter basket is not. If the pump runs but no water flows, check that the reservoir valve is seated

correctly.

Descale the machine every two months in hard water areas using the supplied citric solution. If the pump runs but no water flows, check that the reservoir valve is seated correctly. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Warranty coverage excludes damage caused by third-party descaling agents. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

Section 7: Analysis

Monitoring transects were surveyed twice yearly at fixed depth contours. Restoration nurseries propagated 18,000 coral fragments across the study sites. Restoration nurseries propagated 18,000 coral fragments across the study sites. Monitoring transects were surveyed twice yearly at fixed depth contours. Monitoring transects were surveyed twice yearly at fixed depth contours. Monitoring transects were surveyed twice yearly at fixed depth contours.

Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Monitoring transects were surveyed twice yearly at fixed depth contours. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Restoration nurseries propagated 18,000 coral fragments across the study sites. Monitoring transects were surveyed twice yearly at fixed depth contours. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits.

Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Reef fish biomass on protected reefs was 2.4 times higher than on adjacent fished reefs. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae.

Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Reef fish biomass on protected reefs was 2.4 times higher than on adjacent fished reefs. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Larval connectivity models suggest recovery depends on upstream source reefs remaining healthy. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Ocean acidification reduces calcification rates in most reef-building species studied.

Monitoring transects were surveyed twice yearly at fixed depth contours. Ocean acidification reduces calcification rates in most reef-building species studied. Restoration nurseries propagated 18,000 coral fragments across the study sites. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae.

Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Restoration nurseries propagated 18,000 coral fragments across the study sites. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Reef fish biomass on protected reefs was 2.4 times higher than on adjacent fished reefs. Ocean acidification reduces calcification rates in most reef-building species studied. Larval connectivity models suggest recovery depends on upstream source reefs remaining healthy.

Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Ocean acidification reduces calcification rates in most reef-building species studied. Monitoring transects were surveyed twice yearly at fixed depth contours. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Restoration nurseries propagated 18,000 coral fragments across the study sites.

Restoration nurseries propagated 18,000 coral fragments across the study sites. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Restoration nurseries propagated 18,000 coral fragments across the study sites. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Herbivorous fish control macroalgae that would otherwise outcompete coral recruits.

Herbivorous fish control macroalgae that would otherwise outcompete coral recruits. Ocean acidification reduces calcification rates in most reef-building species studied. Larval connectivity models suggest recovery depends on upstream source reefs remaining healthy. Monitoring transects were surveyed twice yearly at fixed depth contours. Bleaching occurs when thermal stress causes corals to expel their symbiotic algae. Monitoring transects were surveyed twice yearly at fixed depth contours.

Section 8: Methodology

Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Warranty coverage excludes damage caused by third-party descaling agents. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. If the pump runs but no water flows, check that the reservoir valve is seated correctly.

If the pump runs but no water flows, check that the reservoir valve is seated correctly. Descale the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution. Warranty coverage excludes damage caused by third-party descaling agents. Descale the machine every two months in hard water areas using the supplied citric solution. Preheat the group head by flushing hot water for three seconds before locking in the portafilter.

Descale the machine every two months in hard water areas using the supplied citric solution. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Warranty coverage excludes damage caused by third-party descaling agents. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The drip tray and its grate are dishwasher safe; the portafilter basket is not.

If the pump runs but no water flows, check that the reservoir valve is seated correctly. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. If the pump runs but no water flows, check that the reservoir valve is seated correctly. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler.

The drip tray and its grate are dishwasher safe; the portafilter basket is not. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Descale the machine every two months in hard water areas using the supplied citric solution. Preheat the group head by flushing hot water for three seconds before locking in the portafilter.

Descale the machine every two months in hard water areas using the supplied citric solution. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

If the pump runs but no water flows, check that the reservoir valve is seated correctly. Descale the machine every two months in hard water areas using the supplied citric solution. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The drip tray and its grate are dishwasher safe; the portafilter basket is not. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler.

Descale the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution. Warranty coverage excludes damage caused by third-party descaling agents. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The drip tray and its grate are dishwasher safe; the portafilter basket is not.

Section 9: Regional Detail

Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures.

The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. The auditor issued an unmodified opinion with no material weaknesses identified. The rainy day reserve was drawn once during the year to cover storm response costs. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures. Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures.

Pension contributions rose to 28 percent of covered payroll under the updated actuarial assumptions. Pension contributions rose to 28 percent of covered payroll under the updated actuarial assumptions. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. The rainy day reserve was drawn once during the year to cover storm response costs. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. Pension contributions rose to 28 percent of covered payroll under the updated actuarial assumptions.

Capital outlay totaled 142 million dollars, concentrated in roads, parks, and facility renewal. The rainy day reserve was drawn once during the year to cover storm response costs. Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. Pension contributions rose to 28 percent of covered payroll under the updated actuarial assumptions. The rainy day reserve was drawn once during the year to cover storm response costs.

The auditor issued an unmodified opinion with no material weaknesses identified. Capital outlay totaled 142 million dollars, concentrated in roads, parks, and facility renewal. The rainy day reserve was drawn once during the year to cover storm response costs. Sales tax receipts grew 4.2 percent, outpacing the

adopted budget forecast by a full point. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. Capital outlay totaled 142 million dollars, concentrated in roads, parks, and facility renewal.

Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. Pension contributions rose to 28 percent of covered payroll under the updated actuarial assumptions. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures.

Pension contributions rose to 28 percent of covered payroll under the updated actuarial assumptions. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures. Capital outlay totaled 142 million dollars, concentrated in roads, parks, and facility renewal. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures.

Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. Capital outlay totaled 142 million dollars, concentrated in roads, parks, and facility renewal. Pension contributions rose to 28 percent of covered payroll under the updated actuarial assumptions. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures. Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. Debt service remains below the ten percent policy ceiling at 6.8 percent of governmental expenditures.

Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. The auditor issued an unmodified opinion with no material weaknesses identified. Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point. The general fund closed the fiscal year with an unassigned balance equal to 17 percent of expenditures. Sales tax receipts grew 4.2 percent, outpacing the adopted budget forecast by a full point.

Section 10: Appendix

Firmware updates for the hand controller are distributed through the vendor website. Never point the telescope at the sun without a certified full-aperture solar filter. Collimate the primary mirror before each session using the supplied laser tool. Allow the optical tube thirty minutes to reach ambient temperature before observing. Store the corrector plate with the dust cover fitted and desiccant in the case. Collimate the primary mirror before each session using the supplied laser tool.

Store the corrector plate with the dust cover fitted and desiccant in the case. The equatorial mount requires polar alignment within one degree for accurate tracking. The equatorial mount requires polar alignment within one degree for accurate tracking. The equatorial mount requires polar alignment within one degree for accurate tracking. Collimate the primary mirror before each session using the supplied laser tool. Never point the telescope at the sun without a certified full-aperture solar filter.

Never point the telescope at the sun without a certified full-aperture solar filter. Firmware updates for the hand controller are distributed through the vendor website. Balance the tube in both axes before engaging the motor drives. Collimate the primary mirror before each session using the supplied laser tool. The equatorial mount requires polar alignment within one degree for accurate tracking. Never point the telescope at the sun without a certified full-aperture solar filter.

Firmware updates for the hand controller are distributed through the vendor website. The equatorial mount requires polar alignment within one degree for accurate tracking. Firmware updates for the hand

controller are distributed through the vendor website. Collimate the primary mirror before each session using the supplied laser tool. The equatorial mount requires polar alignment within one degree for accurate tracking. Collimate the primary mirror before each session using the supplied laser tool.

Collimate the primary mirror before each session using the supplied laser tool. Firmware updates for the hand controller are distributed through the vendor website. Store the corrector plate with the dust cover fitted and desiccant in the case. The equatorial mount requires polar alignment within one degree for accurate tracking. Store the corrector plate with the dust cover fitted and desiccant in the case. Allow the optical tube thirty minutes to reach ambient temperature before observing.

Allow the optical tube thirty minutes to reach ambient temperature before observing. The equatorial mount requires polar alignment within one degree for accurate tracking. Never point the telescope at the sun without a certified full-aperture solar filter. Balance the tube in both axes before engaging the motor drives. The equatorial mount requires polar alignment within one degree for accurate tracking. Allow the optical tube thirty minutes to reach ambient temperature before observing.

Firmware updates for the hand controller are distributed through the vendor website. The equatorial mount requires polar alignment within one degree for accurate tracking. Firmware updates for the hand controller are distributed through the vendor website. Never point the telescope at the sun without a certified full-aperture solar filter. Collimate the primary mirror before each session using the supplied laser tool. Firmware updates for the hand controller are distributed through the vendor website.

Firmware updates for the hand controller are distributed through the vendor website. Store the corrector plate with the dust cover fitted and desiccant in the case. Never point the telescope at the sun without a certified full-aperture solar filter. Balance the tube in both axes before engaging the motor drives. Balance the tube in both axes before engaging the motor drives. Allow the optical tube thirty minutes to reach ambient temperature before observing.

Store the corrector plate with the dust cover fitted and desiccant in the case. Collimate the primary mirror before each session using the supplied laser tool. Collimate the primary mirror before each session using the supplied laser tool. Store the corrector plate with the dust cover fitted and desiccant in the case. Never point the telescope at the sun without a certified full-aperture solar filter. Never point the telescope at the sun without a certified full-aperture solar filter.

Section 11: Findings

Hospital readmission rates for heart failure fell to 18 percent following the care transition program. Public health laboratories processed 62,000 specimens with a median turnaround of 26 hours. The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters. Overdose deaths declined 9 percent, the first decrease recorded in six years. Influenza vaccination coverage among adults 65 and older reached 71 percent this season. Community health workers completed 15,000 home visits under the maternal health initiative.

Emergency department visits for respiratory illness peaked in the second week of January. Emergency department visits for respiratory illness peaked in the second week of January. Overdose deaths declined 9 percent, the first decrease recorded in six years. Overdose deaths declined 9 percent, the first decrease recorded in six years. The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters. The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters.

The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters. The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters. Hospital readmission rates for heart failure fell to 18 percent following the care transition program. Hospital readmission rates for heart failure fell to 18 percent following the care transition program. Hospital readmission rates for heart failure fell to 18 percent following the care transition program. The

county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters.

Overdose deaths declined 9 percent, the first decrease recorded in six years. Hospital readmission rates for heart failure fell to 18 percent following the care transition program. Emergency department visits for respiratory illness peaked in the second week of January. The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters. Overdose deaths declined 9 percent, the first decrease recorded in six years. Community health workers completed 15,000 home visits under the maternal health initiative.

Hospital readmission rates for heart failure fell to 18 percent following the care transition program. Overdose deaths declined 9 percent, the first decrease recorded in six years. Influenza vaccination coverage among adults 65 and older reached 71 percent this season. Emergency department visits for respiratory illness peaked in the second week of January. Hospital readmission rates for heart failure fell to 18 percent following the care transition program. Emergency department visits for respiratory illness peaked in the second week of January.

Influenza vaccination coverage among adults 65 and older reached 71 percent this season. Emergency department visits for respiratory illness peaked in the second week of January. Community health workers completed 15,000 home visits under the maternal health initiative. Public health laboratories processed 62,000 specimens with a median turnaround of 26 hours. Overdose deaths declined 9 percent, the first decrease recorded in six years. Community health workers completed 15,000 home visits under the maternal health initiative.

Emergency department visits for respiratory illness peaked in the second week of January. Overdose deaths declined 9 percent, the first decrease recorded in six years. The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters. Public health laboratories processed 62,000 specimens with a median turnaround of 26 hours. Overdose deaths declined 9 percent, the first decrease recorded in six years. Overdose deaths declined 9 percent, the first decrease recorded in six years.

Emergency department visits for respiratory illness peaked in the second week of January. Community health workers completed 15,000 home visits under the maternal health initiative. Emergency department visits for respiratory illness peaked in the second week of January. Emergency department visits for respiratory illness peaked in the second week of January. Influenza vaccination coverage among adults 65 and older reached 71 percent this season. Emergency department visits for respiratory illness peaked in the second week of January.

The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters. Community health workers completed 15,000 home visits under the maternal health initiative. Influenza vaccination coverage among adults 65 and older reached 71 percent this season. The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters. Emergency department visits for respiratory illness peaked in the second week of January. The county expanded mobile clinic service to twelve rural sites, delivering 8,400 patient encounters.

Section 12: Analysis

Warranty coverage excludes damage caused by third-party descaling agents. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Warranty coverage excludes damage caused by third-party descaling agents.

Descale the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution. If the pump runs but

no water flows, check that the reservoir valve is seated correctly. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

Descale the machine every two months in hard water areas using the supplied citric solution. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Warranty coverage excludes damage caused by third-party descaling agents. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Descale the machine every two months in hard water areas using the supplied citric solution.

The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. The drip tray and its grate are dishwasher safe; the portafilter basket is not. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The drip tray and its grate are dishwasher safe; the portafilter basket is not.

The drip tray and its grate are dishwasher safe; the portafilter basket is not. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Warranty coverage excludes damage caused by third-party descaling agents. Warranty coverage excludes damage caused by third-party descaling agents. Warranty coverage excludes damage caused by third-party descaling agents. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Descale the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution. If the pump runs but no water flows, check that the reservoir valve is seated correctly.

Descale the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Warranty coverage excludes damage caused by third-party descaling agents. Warranty coverage excludes damage caused by third-party descaling agents. Warranty coverage excludes damage caused by third-party descaling agents.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Descale the machine every two months in hard water areas using the supplied citric solution. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Warranty coverage excludes damage caused by third-party descaling agents.

Warranty coverage excludes damage caused by third-party descaling agents. Descale the machine every two months in hard water areas using the supplied citric solution. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Descale the machine every two months in hard water areas using the supplied citric solution. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Preheat the group head by flushing hot water for three seconds before locking in the portafilter.

Section 13: Methodology

Refrigerated retardation overnight deepens flavor and makes scoring easier. High-extraction flour ferments faster than white flour and needs less starter. Refrigerated retardation overnight deepens flavor and makes scoring easier. Bake covered at 250 degrees Celsius for twenty minutes, then uncovered for twenty more. Bake covered at 250 degrees Celsius for twenty minutes, then uncovered for twenty more. Bulk fermentation is complete when the dough has risen roughly fifty percent and holds an indentation.

Refrigerated retardation overnight deepens flavor and makes scoring easier. A mature starter should double within six hours of feeding at room temperature. Bulk fermentation is complete when the dough has risen roughly fifty percent and holds an indentation. Bulk fermentation is complete when the dough has risen roughly fifty percent and holds an indentation. Bulk fermentation is complete when the dough has risen roughly fifty percent and holds an indentation. High-extraction flour ferments faster than white flour and needs less starter.

A dutch oven traps steam during the first phase of the bake, improving oven spring. A mature starter should double within six hours of feeding at room temperature. Refrigerated retardation overnight deepens flavor and makes scoring easier. A dutch oven traps steam during the first phase of the bake, improving oven spring. A dutch oven traps steam during the first phase of the bake, improving oven spring. A dutch oven traps steam during the first phase of the bake, improving oven spring.

Refrigerated retardation overnight deepens flavor and makes scoring easier. Refrigerated retardation overnight deepens flavor and makes scoring easier. Bake covered at 250 degrees Celsius for twenty minutes, then uncovered for twenty more. A mature starter should double within six hours of feeding at room temperature. High-extraction flour ferments faster than white flour and needs less starter. Refrigerated retardation overnight deepens flavor and makes scoring easier.

A mature starter should double within six hours of feeding at room temperature. A mature starter should double within six hours of feeding at room temperature. Refrigerated retardation overnight deepens flavor and makes scoring easier. Bulk fermentation is complete when the dough has risen roughly fifty percent and holds an indentation. Bulk fermentation is complete when the dough has risen roughly fifty percent and holds an indentation. High-extraction flour ferments faster than white flour and needs less starter.

A mature starter should double within six hours of feeding at room temperature. A dutch oven traps steam during the first phase of the bake, improving oven spring. A dutch oven traps steam during the first phase of the bake, improving oven spring. Autolyse the flour and water for one hour before incorporating salt and starter. Bulk fermentation is complete when the dough has risen roughly fifty percent and holds an indentation. A dutch oven traps steam during the first phase of the bake, improving oven spring.

Autolyse the flour and water for one hour before incorporating salt and starter. High-extraction flour ferments faster than white flour and needs less starter. A dutch oven traps steam during the first phase of the bake, improving oven spring. Bake covered at 250 degrees Celsius for twenty minutes, then uncovered for twenty more. A dutch oven traps steam during the first phase of the bake, improving oven spring. Refrigerated retardation overnight deepens flavor and makes scoring easier.

A mature starter should double within six hours of feeding at room temperature. A mature starter should double within six hours of feeding at room temperature. A mature starter should double within six hours of feeding at room temperature. Autolyse the flour and water for one hour before incorporating salt and starter. High-extraction flour ferments faster than white flour and needs less starter. High-extraction flour ferments faster than white flour and needs less starter.

Bulk fermentation is complete when the dough has risen roughly fifty percent and holds an indentation. Bake covered at 250 degrees Celsius for twenty minutes, then uncovered for twenty more. Autolyse the flour and water for one hour before incorporating salt and starter. Bulk fermentation is complete when

the dough has risen roughly fifty percent and holds an indentation. Refrigerated retardation overnight deepens flavor and makes scoring easier. High-extraction flour ferments faster than white flour and needs less starter.

Section 14: Regional Detail

Ridership on the metropolitan bus network recovered to 87 percent of pre-pandemic levels during the fiscal year. On-time performance for heavy rail averaged 91 percent, up two points year over year. Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax. Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax.

Accessibility upgrades added elevators at four stations under the systemwide accessibility program. The capital program remains constrained by escalating construction costs and a projected funding gap in the out-years. The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. On-time performance for heavy rail averaged 91 percent, up two points year over year. The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third.

On-time performance for heavy rail averaged 91 percent, up two points year over year. The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third. Ridership on the metropolitan bus network recovered to 87 percent of pre-pandemic levels during the fiscal year. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. Accessibility upgrades added elevators at four stations under the systemwide accessibility program. Accessibility upgrades added elevators at four stations under the systemwide accessibility program.

Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax. Ridership on the metropolitan bus network recovered to 87 percent of pre-pandemic levels during the fiscal year. Ridership on the metropolitan bus network recovered to 87 percent of pre-pandemic levels during the fiscal year. The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. Accessibility upgrades added elevators at four stations under the systemwide accessibility program.

Accessibility upgrades added elevators at four stations under the systemwide accessibility program. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. Ridership on the metropolitan bus network recovered to 87 percent of pre-pandemic levels during the fiscal year. Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax. The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third. Accessibility upgrades added elevators at four stations under the systemwide accessibility program.

Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax. The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. Ridership on the metropolitan bus network recovered to 87 percent of pre-pandemic levels during the fiscal year. Accessibility upgrades added elevators at four stations under the systemwide accessibility program.

Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax. Accessibility upgrades added elevators at four stations under the systemwide accessibility program. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax. Accessibility upgrades added elevators at four stations under the systemwide accessibility program. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots.

The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third. Ridership on the metropolitan bus network recovered to 87 percent of pre-pandemic levels during the fiscal year. The capital program remains constrained by escalating construction costs and a projected funding gap in the out-years. Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax. Accessibility upgrades added elevators at four stations under the systemwide accessibility program. The capital program remains constrained by escalating construction costs and a projected funding gap in the out-years.

On-time performance for heavy rail averaged 91 percent, up two points year over year. Ridership on the metropolitan bus network recovered to 87 percent of pre-pandemic levels during the fiscal year. The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third. Electric bus procurement continued with 42 vehicles delivered and charging infrastructure installed at two depots. The agency completed track renewal on 14 miles of the Blue Line, reducing slow zones by a third. Fare revenue covered 31 percent of operating expenses, with the remainder funded by the regional sales tax.