

EM-500 Semi-Automatic Espresso Machine — User Manual

Prepared by Aurora Appliances

Getting Started

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Preheat the group head by flushing hot water for three seconds before locking in the portafilter.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Preheat the group head by flushing hot water for three seconds before locking in the portafilter.

Daily Operation

The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Warranty coverage excludes damage caused by third-party descaling agents.

Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The drip tray and its grate are dishwasher safe; the portafilter basket is not. Descale the machine every two months in hard water areas using the supplied citric solution. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. If the pump runs but no water flows, check that the reservoir valve is seated correctly.

The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. The drip tray and its grate are dishwasher safe; the portafilter basket is not. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Descale the machine every two months in hard water areas using the supplied citric solution.

Maintenance and Descaling

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Warranty coverage excludes damage caused by third-party descaling agents. Descale the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution.

Descal the machine every two months in hard water areas using the supplied citric solution. Descale the machine every two months in hard water areas using the supplied citric solution. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. If the pump runs but no water flows, check that the reservoir valve is seated correctly. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler.

Troubleshooting

Descale the machine every two months in hard water areas using the supplied citric solution. Warranty coverage excludes damage caused by third-party descaling agents. If the pump runs but no water flows, check that the reservoir valve is seated correctly. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The drip tray and its grate are dishwasher safe; the portafilter basket is not.

Preheat the group head by flushing hot water for three seconds before locking in the portafilter. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds. The drip tray and its grate are dishwasher safe; the portafilter basket is not. The steam wand must be purged before and after texturing milk to prevent milk residue in the boiler. Grind size should be adjusted so a double shot extracts in 25 to 30 seconds.