

Astra 130 Newtonian Reflector — Assembly and Operating Manual

Prepared by Meridian Optics

Assembly

Store the corrector plate with the dust cover fitted and desiccant in the case. Balance the tube in both axes before engaging the motor drives. Collimate the primary mirror before each session using the supplied laser tool. Firmware updates for the hand controller are distributed through the vendor website. Balance the tube in both axes before engaging the motor drives.

The equatorial mount requires polar alignment within one degree for accurate tracking. Store the corrector plate with the dust cover fitted and desiccant in the case. Firmware updates for the hand controller are distributed through the vendor website. Collimate the primary mirror before each session using the supplied laser tool. Store the corrector plate with the dust cover fitted and desiccant in the case.

Alignment and Setup

Firmware updates for the hand controller are distributed through the vendor website. The equatorial mount requires polar alignment within one degree for accurate tracking. Balance the tube in both axes before engaging the motor drives. The equatorial mount requires polar alignment within one degree for accurate tracking. Allow the optical tube thirty minutes to reach ambient temperature before observing.

The equatorial mount requires polar alignment within one degree for accurate tracking. Firmware updates for the hand controller are distributed through the vendor website. Allow the optical tube thirty minutes to reach ambient temperature before observing. Balance the tube in both axes before engaging the motor drives. Balance the tube in both axes before engaging the motor drives.

Firmware updates for the hand controller are distributed through the vendor website. Balance the tube in both axes before engaging the motor drives. The equatorial mount requires polar alignment within one degree for accurate tracking. Store the corrector plate with the dust cover fitted and desiccant in the case. Allow the optical tube thirty minutes to reach ambient temperature before observing.

Care and Storage

Balance the tube in both axes before engaging the motor drives. Firmware updates for the hand controller are distributed through the vendor website. Firmware updates for the hand controller are distributed through the vendor website. Firmware updates for the hand controller are distributed through the vendor website. Firmware updates for the hand controller are distributed through the vendor website.

Allow the optical tube thirty minutes to reach ambient temperature before observing. Firmware updates for the hand controller are distributed through the vendor website. Allow the optical tube thirty minutes to reach ambient temperature before observing. Firmware updates for the hand controller are distributed through the vendor website. Never point the telescope at the sun without a certified full-aperture solar filter.