

Numerical Methods Runtime Table

Mohamed Emary

Mohamed Abdelfattah

Abdelfattah Zakaria

Shrouk Elsayed

Dalia Abdallah

Sara Reda

November 2, 2023

1 Equations

We have used the same 25 equations with each method and run each method (Bisection, False Position, and Hybrid) 500 times for each problem and then we have calculated the average time. We have also calculated the number of iterations each method have taken for each problem.

We have also used the same tolerance for each method which is 10^{-14}

These are the equations that we have used with each method:

1.1 Our Equations

In these equations we have tried to use different types of functions and intervals to test our methods.

Table 1: Our Equations Table

No	Equation	Equation Code	Interval
<i>P1</i>	$f(x) = x^3 + 4x^2 - 10 = 0$	<code>x**3 + 4*x**2 - 10</code>	[0, 4]
<i>P2</i>	$f(x) = x^2 - 4$	<code>x**2 - 4</code>	[0, 4]
<i>P3</i>	$f(x) = e^x - 2$	<code>math.exp(x) - 2</code>	[0, 2]
<i>P4</i>	$f(x) = \sin(x)$	<code>math.sin(x)</code>	[2, 6]
<i>P5</i>	$f(x) = x^3 - 6x^2 + 11x - 6$	<code>x**3 - 6*x**2 + 11*x - 6</code>	[1, 2.5]
<i>P6</i>	$f(x) = x^2 + 3x + 2$	<code>x**2 + 3*x + 2</code>	[-2.5, -1.5]
<i>P7</i>	$f(x) = \cos(x) - x$	<code>math.cos(x) - x</code>	[0, 1]
<i>P8</i>	$f(x) = 2^x - 8$	<code>2**x - 8</code>	[2, 4]
<i>P9</i>	$f(x) = \tan(x)$	<code>math.tan(x)</code>	[-1, 1]
<i>P10</i>	$f(x) = x^4 - 8x^3 + 18x^2 - 9x + 1$	<code>x**4 - 8*x**3 + 18*x**2 - 9*x + 1</code>	[2, 4]

1.2 Equations From Paper

We got these equations from [this paper](#) and we have used the same intervals too.

Table 2: Equations From Paper Table

No	Equation	Equation Code	Interval	Reference
P11	$f(x) = x^2 - 3$	<code>x**2 - 3</code>	[1,2]	Harder [18]
P12	$f(x) = x^2 - 5$	<code>x**2 - 5</code>	[2,7]	Srivastava[9]
P13	$f(x) = x^2 - 10$	<code>x**2 - 10</code>	[3,4]	Harder [18]
P14	$f(x) = x^2 - x - 2$	<code>x**2 - x - 2</code>	[1,4]	Moazzam [10]
P15	$f(x) = x^2 + 2x - 7$	<code>x**2 + 2*x - 7</code>	[1,3]	Nayak[11]
P16	$f(x) = x^3 - 2$	<code>x**3 - 2</code>	[0,2]	Harder [18]
P17	$f(x) = xe^x - 7$	<code>x * math.exp(x) - 7</code>	[0,2]	Callhoun [19]
P18	$f(x) = x - \cos(x)$	<code>x - math.cos(x)</code>	[0,1]	Ehiwario [6]
P19	$f(x) = x \sin(x) - 1$	<code>x * math.sin(x) - 1</code>	[0,2]	Mathews [20]
P20	$f(x) = x \cos(x) + 1$	<code>x * math.cos(x) + 1</code>	[-2,4]	Esfandiari [21]
P21	$f(x) = x^{10} - 1$	<code>x**10 - 1</code>	[0,1.3]	Chapra [17]
P22	$f(x) = x^2 + e^{x/2} - 5$	<code>x**2 + (2.71828**(x/2)) - 5</code>	[1,2]	Esfandiari [21]
P23	$f(x) = \sin(x) \sinh(x) + 1$	<code>math.sin(x) * math.sinh(x) + 1</code>	[3,4]	Esfandiari [21]
P24	$f(x) = e^x - 3x - 2$	<code>(2.71828**x) - 3*x - 2</code>	[2,3]	Hoffman [22]
P25	$f(x) = \sin(x) - x^2$	<code>math.sin(x) - x**2</code>	[0.5,1]	Chapra[17]

2 Results

These are the results we got with each method. We have run each method 500 times on each equation and took the average time to get the highest accuracy possible.

2.1 False Position

These are the results we got with False Position method:

Table 3: False Position Table

Problem	False Position Algorithm					
	Iter	Avg CPU Time	Approximate Root	Function Value	Lower Bound	Upper Bound
<i>P1</i>	80	0.000229008	1.3652300134140964	-7.11E-15	1.3652300134140964	4
<i>P2</i>	33	4.399728775024414e-05	1.9999999999999978	-8.88E-15	1.9999999999999978	4
<i>P3</i>	51	5.6000232696533204e-05	0.6931471805599422	-6.22E-15	0.6931471805599422	2
<i>P4</i>	8	6.000041961669922e-06	3.141592653589793	1.2246467991473532e-16	3.141592653589793	3.1415926535899232
<i>P5</i>	2	0	1	0	1	2.5
<i>P6</i>	31	4.800844192504883e-05	-2	-5.33E-15	-2.5	-2
<i>P7</i>	12	1.101541519165039e-05	0.7390851332151551	9.2148511043888e-15	0.7390851332151551	1
<i>P8</i>	30	4.401159286499024e-05	2.9999999999999987	-7.11E-15	2.9999999999999987	4
<i>P9</i>	2	1.991748809814453e-06	0	0	0	1
<i>P10</i>	13	4.0007591247558594e-05	3.1117486563092474	0	3.1117486563092474	3.1117486563092482
<i>P11</i>	14	1.7997264862060548e-05	1.732050807568876	-4.00E-15	1.732050807568876	2
<i>P12</i>	50	6.600427627563476e-05	2.2360679774997876	-9.77E-15	2.2360679774997876	7
<i>P13</i>	17	2.2464752197265626e-05	3.162277660168379	-1.78E-15	3.162277660168379	4
<i>P14</i>	38	5.301380157470703e-05	1.9999999999999971	-8.66E-15	1.9999999999999971	4
<i>P15</i>	21	3.1998634338378904e-05	1.8284271247461896	-2.66E-15	1.8284271247461896	3
<i>P16</i>	41	5.600643157958984e-05	1.2599210498948719	-6.22E-15	1.2599210498948719	2
<i>P17</i>	30	3.40123176574707e-05	1.5243452049841437	-7.99E-15	1.5243452049841437	2
<i>P18</i>	12	1.2005805969238282e-05	0.7390851332151551	-9.21E-15	0.7390851332151551	1
<i>P19</i>	7	7.99846649169922e-06	1.1141571408719306	8.881784197001252e-16	1.0997501702946164	1.1141571408719306
<i>P20</i>	13	1.1332988739013672e-05	2.0739328090912146	7.771561172376096e-16	2.0739328090912146	2.5157197710146586
<i>P21</i>	139	0.000183961	0.9999999999999991	-8.88E-15	0.9999999999999991	1.3
<i>P22</i>	16	3.3281803131103514e-05	1.6490135532979475	-1.78E-15	1.6490135532979475	2
<i>P23</i>	45	7.994651794433594e-05	3.2215883990939416	6.328271240363392e-15	3.2215883990939416	4
<i>P24</i>	45	6.818151473999023e-05	2.1253934262332246	-9.77E-15	2.1253934262332246	3
<i>P25</i>	17	2.703714370727539e-05	0.8767262153950554	7.882583474838611e-15	0.8767262153950554	1

2.2 Bisection Method

These are the results we got with Bisection method:

Table 4: Bisection Table

Problem	Bisection Algorithm					
	Iter	Avg CPU Time	Approximate Root	Function Value	Lower Bound	Upper Bound
P1	50	7.303380966186524e-05	1.3652300134140951	-2.84E-14	1.3652300134140916	1.3652300134140987
P2	1	0	2	0	0	4
P3	49	4.200363159179687e-05	0.6931471805599436	-3.33E-15	0.6931471805599401	0.6931471805599472
P4	50	3.406333923339844e-05	3.141592653589793	1.2246467991473532e-16	3.1415926535897896	3.1415926535897967
P5	48	7.496118545532227e-05	2.0000000000000018	0	1.9999999999999964	2.0000000000000007
P6	1	1.9011497497558594e-06	-2	0	-2.5	-1.5
P7	48	3.201484680175781e-05	0.7390851332151591	2.55351295663786e-15	0.7390851332151556	0.7390851332151627
P8	1	1.9893646240234374e-06	3	0	2	4
P9	1	1.991748809814453e-06	0	0	-1	1
P10	49	9.199857711791992e-05	3.111748656309249	1.0658141036401503e-14	3.1117486563092456	3.1117486563092527
P11	48	4.000377655029297e-05	1.7320508075688785	4.440892098500626e-15	1.732050807568875	1.732050807568882
P12	50	3.901958465576172e-05	2.2360679774997854	-1.95E-14	2.236067977499781	2.236067977
P13	48	3.7988662719726566e-05	3.1622776601683817	1.5987211554602254e-14	3.162277660168378	3.1622776601683853
P14	50	4.400014877319336e-05	1.9999999999999991	-2.66E-15	1.9999999999999964	2.00000000000000018
P15	49	5.607509613037109e-05	1.828427124746188	-1.15E-14	1.8284271247461845	1.8284271247461916
P16	49	3.8086414337158205e-05	1.2599210498948743	5.329070518200751e-15	1.2599210498948707	1.2599210498948779
P17	49	3.905820846557617e-05	1.5243452049841473	3.375077994860476e-14	1.5243452049841437	1.5243452049841508
P18	48	2.9998779296875e-05	0.7390851332151591	-2.55E-15	0.7390851332151556	0.7390851332151627
P19	49	0.000136974	1.114157140871928	-3.00E-15	1.1141571408719244	1.1141571408719315
P20	51	5.606412887573242e-05	2.0739328090912155	-1.33E-15	2.073932809091213	2.073932809091218
P21	48	4.004716873168945e-05	1.0000000000000001	1.1102230246251565e-14	0.9999999999999966	1.0000000000000058
P22	44	5.988311767578125e-05	1.649013553297948	0	1.6490135532978911	1.6490135532980048
P23	48	6.889772415161133e-05	3.2215883990939425	-5.55E-15	3.221588399093939	3.221588399093946
P24	48	4.5994281768798825e-05	2.1253934262332272	5.329070518200751e-15	2.1253934262332237	2.125393426233231
P25	47	6.799602508544923e-05	0.8767262153950632	-8.88E-16	0.8767262153950597	0.8767262153950668

2.3 Hybrid Method

These are the results we got with hybrid method:

Table 5: Hybrid Table

Problem	Hybrid Algorithm (Bisection & False Position)					
	Iter	Avg CPU Time	Approximate Root	Function Value	Lower Bound	Upper Bound
<i>P1</i>	10	3.6006927490234375e-05	1.3652300134140964	-7.11E-15	1.365230013413779	1.3675001980274413
<i>P2</i>	1	1.9969940185546874e-06	2	0	0	4
<i>P3</i>	10	1.399993896484375e-05	0.6931471805599453	0	0.6931471805599334	0.695162706
<i>P4</i>	6	1.006174087524414e-05	3.141592653589793	1.2246467991473532e-16	3.1415903579556947	3.141592653604888
<i>P5</i>	1	3.940105438232422e-06	1	0	1	2.5
<i>P6</i>	1	1.9888877868652345e-06	-2	0	-2.5	-1.5
<i>P7</i>	8	1.1938095092773438e-05	0.7390851332151606	1.1102230246251565e-16	0.739085133	0.7422270732175922
<i>P8</i>	1	2.0036697387695312e-06	3	0	2	4
<i>P9</i>	1	2.0928382873535157e-06	0	0	-1	1
<i>P10</i>	8	2.4066925048828126e-05	3.1117486563092474	0	3.1085379927858856	3.1117486563092536
<i>P11</i>	8	1.7096519470214843e-05	1.7320508075688772	-4.44E-16	1.7320508075688001	1.7350578402209837
<i>P12</i>	10	1.4061450958251953e-05	2.236067977499789	-3.55E-15	2.236067977499364	2.243929153983615
<i>P13</i>	8	1.393747329711914e-05	3.1622776601683795	1.7763568394002505e-15	3.16227766	3.1672187190124017
<i>P14</i>	2	2.0089149475097657e-06	2	0	1.5	2.5
<i>P15</i>	5	8.056163787841797e-06	1.828427125	0	1.8284271247430004	1.8284271247493797
<i>P16</i>	9	1.2000083923339844e-05	1.2599210498948723	-4.00E-15	1.259921049893984	1.2611286403176987
<i>P17</i>	11	1.3935565948486329e-05	1.5243452049841444	0	1.5243452049841386	1.526033337108763
<i>P18</i>	8	1.0064601898193359e-05	0.7390851332151606	-1.11E-16	0.739085133	0.7422270732175922
<i>P19</i>	6	8.002758026123047e-06	1.1141571408719302	2.220446049250313e-16	1.1132427327642702	1.1141571408719768
<i>P20</i>	10	1.5938282012939452e-05	2.073932809091215	-2.22E-16	2.0739328090911866	2.078935003337393
<i>P21</i>	12	1.6058921813964842e-05	0.9999999999999999	-1.11E-15	0.9999999999999305	1.000343363282986
<i>P22</i>	8	2.393531799316406e-05	1.6490135532979473	-3.55E-15	1.6490135532974015	1.6531560376633945
<i>P23</i>	9	1.7997264862060548e-05	3.221588399093942	3.3306690738754696e-16	3.2215883990939242	3.2224168881395068
<i>P24</i>	9	1.2019157409667969e-05	2.125393426233225	-7.11E-15	2.1253934262325003	2.1275213330097245
<i>P25</i>	7	1.1998653411865234e-05	0.8767262153950581	4.773959005888173e-15	0.8767262153886713	0.8772684454348731

As we see from the table above the hybrid method tend to be faster and take much less iterations than both Bisection and False Position methods.