



Symmetric Difference ★

44/115 challenges solved

Rank: 65352 | Points: 595



Your Symmetric Difference submission got 10.00 points.

مشاركة

Tweet

[Try the next challenge](#) | [Try a Random Challenge](#)

Problem

Submissions

Leaderboard

Editorial

Objective

Today, we're learning about a new data type: sets.

Concept

If the inputs are given on one line separated by a character (the delimiter), use `split()` to get the separate values in the form of a list. The delimiter is space (ascii 32) by default. To specify that comma is the delimiter, use `string.split(',')`. For this challenge, and in general on HackerRank, space will be the delimiter.

Usage:

```
>> a = raw_input()
5 4 3 2
>> lis = a.split()
>> print (lis)
['5', '4', '3', '2']
```

If the list values are all integer types, use the `map()` method to convert all the strings to integers.

```
>> newlis = list(map(int, lis))
>> print (newlis)
[5, 4, 3, 2]
```

Sets are an unordered collection of unique values. A single set contains values of any immutable data type.

CREATING SETS

```
>> myset = {1, 2} # Directly assigning values to a set
>> myset = set() # Initializing a set
>> myset = set(['a', 'b']) # Creating a set from a list
>> myset
{'a', 'b'}
```

MODIFYING SETS

Using the `add()` function:

```
>> myset.add('c')
>> myset
{'a', 'c', 'b'}
>> myset.add('a') # As 'a' already exists in the set, nothing happens
>> myset.add((5, 4))
>> myset
{'a', 'c', 'b', (5, 4)}
```

Using the update() function:

```
>> myset.update([1, 2, 3, 4]) # update() only works for iterable objects
>> myset
{'a', 1, 'c', 'b', 4, 2, (5, 4), 3}
>> myset.update({1, 7, 8})
>> myset
{'a', 1, 'c', 'b', 4, 7, 8, 2, (5, 4), 3}
>> myset.update({1, 6}, [5, 13])
>> myset
{'a', 1, 'c', 'b', 4, 5, 6, 7, 8, 2, (5, 4), 13, 3}
```

REMOVING ITEMS

Both the discard() and remove() functions take a single value as an argument and removes that value from the set. If that value is not present, discard() does nothing, but remove() will raise a KeyError exception.

```
>> myset.discard(10)
>> myset
{'a', 1, 'c', 'b', 4, 5, 7, 8, 2, 12, (5, 4), 13, 11, 3}
>> myset.remove(13)
>> myset
{'a', 1, 'c', 'b', 4, 5, 7, 8, 2, 12, (5, 4), 11, 3}
```

COMMON SET OPERATIONS Using union(), intersection() and difference() functions.

```
>> a = {2, 4, 5, 9}
>> b = {2, 4, 11, 12}
>> a.union(b) # Values which exist in a or b
{2, 4, 5, 9, 11, 12}
>> a.intersection(b) # Values which exist in a and b
{2, 4}
>> a.difference(b) # Values which exist in a but not in b
{9, 5}
```

The union() and intersection() functions are symmetric methods:

```
>> a.union(b) == b.union(a)
True
>> a.intersection(b) == b.intersection(a)
True
>> a.difference(b) == b.difference(a)
False
```

These [other built-in data structures in Python](#) are also useful.

Task

Given **2** sets of integers, ***M*** and ***N***, print their symmetric difference in ascending order. The term symmetric difference indicates those values that exist in either ***M*** or ***N*** but do not exist in both.

Input Format

The first line of input contains an integer, ***M***.

The second line contains ***M*** space-separated integers.

The third line contains an integer, ***N***.

The fourth line contains ***N*** space-separated integers.

Output Format

Output the symmetric difference integers in ascending order, one per line.

Sample Input

STDIN	Function
4	set a size M = 4
2 4 5 9	a = {2, 4, 5, 9}
4	set b size N = 4
2 4 11 12	b = {2, 4, 11, 12}

Sample Output

5
9
11
12

Change Theme Language Python 3



```
1 n=int(input())
2 s1=set(map(int,input().split()))
3 m=int(input())
4 s2=set(map(int,input().split()))
5 s=s1.difference(s2)
6 s.update(s2.difference(s1))
7 for i in sorted(s):
8     print(i)
```

Line: 8 Col: 13

Upload Code as File

☐ Test against custom input

Run Code

Submit Code

You have earned 10.00 points!

44/115 challenges solved.

38%



Congratulations



Earn a certificate in Python

Congratulations

You solved this challenge. Would you like to challenge your friends?

Next Challenge

Kudos on your progress! Take the HackerRank Skills Certification test and enrich your profile

Get Certified

Test case 0

Test case 1

Test case 2

Test case 3

Test case 4

Test case 5

Test case 6

Compiler Message

Success

Input (stdin)

Download

```
1 4
2 2 4 5 9
3 4
4 2 4 11 12
```

Expected Output

Download

```
1 5
2 9
3 11
```