



ETHERCHANNEL

SW1

```
SW1#
SW1#conf t
Enter configuration commands, one per line. End with CNTL/Z.
SW1(config)#int range e0/0 , e0/1
SW1(config-if-range)#channel-group 1 mode desirable
Creating a port-channel interface Port-channel 1
```

SW1

```
Number of channel-groups in use: 1
Number of aggregators:          1

Group  Port-channel  Protocol    Ports
-----+-----+-----+-----
1       Po1 (SD)          PAgP        Et0/0 (I)  Et0/1 (I)
```

SW1

```
SW1#show spanning-tree

VLAN0001
  Spanning tree enabled protocol ieee
  Root ID    Priority    32769
             Address     aabb.cc00.0100
             This bridge is the root
             Hello Time  2 sec    Max Age 20 sec    Forward Delay 15 sec

  Bridge ID  Priority    32769 (priority 32768 sys-id-ext 1)
             Address     aabb.cc00.0100
             Hello Time  2 sec    Max Age 20 sec    Forward Delay 15 sec
             Aging Time  300 sec

Interface             Role Sts Cost          Prio.Nbr Type
-----+-----+-----+-----+-----+-----
Po1                    Desg FWD 56           128.65 P2p
```

```
SW2
SW2#conf t
Enter configuration commands, one per line. End with CNTL/Z.
SW2(config)#int range e0/0 , e0/1
SW2(config-if-range)#channel-group 1 mode auto
Creating a port-channel interface Port-channel 1
```

```
SW2
Number of channel-groups in use: 1
Number of aggregators: 1

Group  Port-channel  Protocol  Ports
-----+-----+-----+-----
1      Po1(SU)          PAgP      Et0/0(P)  Et0/1(P)
```

```
SW2
SW2(config)#do show spanning-tree

VLAN0001
  Spanning tree enabled protocol ieee
  Root ID    Priority    32769
             Address    aabb.cc00.0100
             Cost        56
             Port        65 (Port-channel1)
             Hello Time   2 sec  Max Age 20 sec  Forward Delay 15 sec

  Bridge ID  Priority    32769  (priority 32768 sys-id-ext 1)
             Address    aabb.cc00.0200
             Hello Time   2 sec  Max Age 20 sec  Forward Delay 15 sec
             Aging Time   300 sec

Interface                Role Sts Cost      Prio.Nbr Type
-----
Po1                      Root FWD 56        128.65 P2p
```